

Use of Mako to aid book writing

Hans Petter Langtangen^{1,2}

¹Center for Biomedical Computing, Simula Research Laboratory

²Department of Informatics, University of Oslo

Jun 24, 2015

Contents

1	Use of variables	1
1.1	How to speak about “this chapter”	1
2	How to make several variants of the text	2
3	Mako’s Python functions	3
3.1	Basics of Mako functions	4
3.2	How to treat multiple programming languages in the same text .	5

This document describes the work flow and how we can utilize many nice DocOnce features when writing chapters for a future, potential book project.

1 Use of variables

Mako is the preprocessor that is always run prior to translating DocOnce documents into a specific format. It means that your DocOnce source is actually a computer program where you can use variables and functions.

Writing chapters that can both live their individual lives and be part of a book faces some challenges for which we have some nice solutions in the coming sections.

1.1 How to speak about “this chapter”

In a book you will often need the phrase “this chapter”, but this is inappropriate if the chapter is a stand-alone document. Then you would rather say “this document”. Similarly, “this book” must read “this document” in a stand-alone chapter. We have resolved this issue by introducing Mako variables `CHAPTER`, `BOOK`, and `APPENDIX` such that you write

In this `${BOOK}`, the convention is to use boldface for vectors.

For this to work, you need to define `CHAPTER`, `BOOK`, and `APPENDIX` as variables on the command line as part of the `doconce format` command:

Terminal

```
Terminal> doconce format pdflatex ch2 --latex_code_style=pyg \  
          CHAPTER=document BOOK=document APPENDIX=document
```

When the book is compiled, you do

Terminal

```
Terminal> doconce format pdflatex ch2 --latex_code_style=pyg \  
          CHAPTER=chapter BOOK=chapter APPENDIX=appendix
```

The `make*.sh` files found in `doc/src/chapter/` and `doc/src/book` make proper definitions of `CHAPTER`, `BOOK`, and `APPENDIX`.

2 How to make several variants of the text

Sometimes you want to write some text slightly differently if the chapter is a stand-alone document compared to the case when it is part of a book. Mako if tests are ideal for this. Suppose you introduce a Mako variable `ALONE` that is true/defined if the chapter is a stand-alone document and false/undefined if part of a book. Then you can simply write

```
In this  
% if ALONE:  
rather small  
% else:  
large  
% endif  
${BOOK}
```

Running `doconce format` with the option `-DALONE` will turn `ALONE` to true and the output is typically

```
In this rather small document
```

while for a book we skip `-DALONE` as argument to `doconce format`, which makes `ALONE` undefined, and we get the output

```
In this large book
```

Mako variables can be defined/undefined (boolean variables) or be standard strings:

```
% if SOME_STRING_VARIABLE in ('value1', 'value2'):  
some running text  
% endif
```

```

...

% if not SOME_BOOLEAN_VARIABLE:
some other running text
% else:
yet more different text
% endif

```

With Mako variables, you can easily comment out large portions of text by testing on some variable you do not intend to define:

```

% if EXTRA:
This is
text that
will never
appear in the
output.
% endif

```

Also, it is straightforward to write more than one version of a chapter. For example, you may want to produce a version of a chapter that is tailored to a specific course, while you for general publishing on the Internet want a more general version, and maybe a third version when the chapter is included in a book for the international market. All this is easily done by if tests on appropriately defined Mako variables

```

% if COURSE == 'IT1713':
# Specific text for a course IT1713
...
% elif COURSE == 'IT1713b':
# Specific text for a the special IT1713b variant of the course
...
% elif COURSE == 'general':
# General text when the chapter is a stand-alone document
...
% elif COURSE == 'book1':
# Text when course is a part of a particular book
...
% elif COURSE == 'book2':
# Text when course is a part of another book
...
% endif

```

3 Mako's Python functions

The if tests above are fine to handle larger portions of text. What if you need to have four versions of just one word or very short text? A Mako function, defined as a standard Python function, is then more appropriate.

3.1 Basics of Mako functions

Here is a definition of a suitable Mako function, which must be defined inside `<%` and `%>` tags, using standard Python code:

```
<%
def chversion(text_IT1413, text_IT1713b, text_general,
              text_book1, text_book2):
    if COURSE == 'IT1713':
        return text_IT1413
    elif COURSE == 'IT1713b':
        return text_IT1413b
    elif COURSE == 'general':
        return text_general
    elif COURSE == 'book1':
        return text_book1
    elif COURSE == 'book2':
        return text_book2
    else:
        return 'XXX WRONG value of COURSE: %s' % COURSE
%>
```

In the running text you can call `chversion` with five arguments, corresponding to the desired text in the five cases, and when `doconce format` is run, the value of `COURSE` determines which of the five cases that is used. Here is an example on DocOnce text with a function call to `chversion`:

```
It is extremely important to define the term *cure* accurately.
Here we mean ${chversion('handle', 'handle',
'resolve', 'treat', 'resolve')}.

```

You can easily use long multi-line strings as arguments, e.g.,

```
... ${chversion("""
Here comes
a multi-line
string""",
'short string',
'another short string',
""4th
multi-line
string""",
'5th string'')}
...

```

There are two types of Mako functions.

One type resembles Python functions, as demonstrated above. The other type employs a slightly different syntax and is exemplified in the file

`doc/src/chapters/index_files.do.txt`^a. We refer to the Mako syntax documentation^b for more information.

^ahttp://tinyurl.com/kukz8pt/index_files-do.txt

^b<http://docs.makotemplates.org/en/latest/syntax.html>

3.2 How to treat multiple programming languages in the same text

With these ideas, it becomes straightforward to write a book that has its program examples in multiple languages. Introduce `CODE` as the name of the language and use if tests for larger portions of code and text, and Mako functions for shorter inline texts, to handle text that depends on the value of `CODE`. The author has successfully co-written such a book¹ [1] for mathematical programming with either Python or Matlab - the version is set when running `doconce format`.

Here is an example of text, in the style of the mention book, where there are small differences depending on the programming language:

```
The following #{CODE} function 'sampler' does the job
(see the file "#{src('sampler')}"):
"https://github.com/myuser/myproject/src/#{src('sampler')}"):

#{copyfile('sampler')}

Note that in #{CODE}, arrays start at index #{text2('0', '1')}.
Array slices like #{verb2('vec[2:8]', 'vec(2:7)')}
go from the first index (here '2') up to
#{text2('*but not including* the upper limit (here '8')',
'(including) the upper limit (here '7')')}.
% if CODE == 'Python':
Also note that the file 'sampler.py' is a module, meaning
that we can call all the file's functions from other programs,
including 'sampler_vec'.
% elif CODE == 'Matlab':
Also note that only the 'sampler' function can be called
from other Matlab programs. If we want the alternative
implementation in function 'sampler_vec' to be reused
by other programs, this function has to reside in a file
'sampler_vec.py'.
% endif
```

Here we have made use of a few Mako functions to easily choose between a Python or Matlab relevant text:

- `src` for picking a filename with the right extension (`.py` or `.m`)
- `copyfile` for constructing the right `@@@CODE` line for a Python or Matlab source code file

¹<http://hplgit.github.io/Programming-for-Computations/pub/p4c/index.html>

- `text2` for picking the first (Python) or second (Matlab) argument
- `verb2` for picking the first (Python) or second (Matlab) argument typeset in inline verbatim font

The exact Mako code appears below.

```
<%
def src(filestem, url=None, verb=True):
    """Return filestem plus .m or .py."""
    if CODE == "Python":
        filename = filestem + '.py'
    else:
        filename = filestem + '.m'
    if verb:
        filename = '%s' % filename
    if url is not None:
        # Make link to the file at github
        pass
    return filename

def copyfile(filestem, from_=None, to_=None):
    """Return @@@CODE line for copying a Python/Matlab file."""
    r = "@@CODE "
    if CODE == "Python":
        r += "py-src/" + filestem + '.py'
    else:
        r += "m-src/" + filestem + '.m'
    if from_ is not None:
        r += ' fromto: ' + from_ + '@'
    if to_ is not None:
        r += to_
    return r

def verb2(py_expr, m_expr):
    """Return py_expr or m_expr in verbatim depending on CODE."""
    if CODE == "Python":
        expr = py_expr
    else:
        expr = m_expr
    expr = '%s' % expr
    return expr

def text2(py_expr, m_expr):
    """Return py_expr or m_expr depending on CODE."""
    if CODE == "Python":
        expr = py_expr
    else:
        expr = m_expr
    return expr
```

```
%>
```

Compiling the document with

Terminal

```
Terminal> doconce format plain mydoc CODE=Python \  
--latex_code_style=pyg
```

results in the output

```
The following Python function \Verb!sampler! does the job  
(see the file  
\href{{https://github.com/myuser/myproject/src/'sampler.py'}}{\nolinkurl{sampler.py}}\footnote{\texttt{http:  
  
\begin{minted}[escapeinside=,fontsize=\fontsize{9pt}{9pt},linenos=false,  
baselinestretch=1.0,fontfamily=tt,xleftmargin=2mm]{python}  
"""Sampler module."""  
  
def sampler(...):  
    ...  
\end{minted}  
  
Note that in Python, arrays start at index 0.  
Array slices like \Verb!vec[2:8]!  
go from the first index (here \Verb!2!) up to  
\emph{but not including} the upper limit (here \Verb!8!).  
Also note that the file \Verb!sampler.py! is a module, meaning  
that we can call all the file's functions from other programs,  
including \Verb!sampler_vec!.
```

Switching to CODE=Matlab gives

```
The following Matlab function \Verb!sampler! does the job  
(see the file  
\href{{https://github.com/myuser/myproject/src/'sampler.m'}}{\nolinkurl{sampler.m}}\footnote{\texttt{https:  
  
\begin{minted}[escapeinside=,fontsize=\fontsize{9pt}{9pt},linenos=false,  
baselinestretch=1.0,fontfamily=tt,xleftmargin=2mm]{matlab}  
% Sampler code  
  
function samples = sampler(...):  
    ...  
\end{minted}  
  
Note that in Matlab, arrays start at index 1.  
Array slices like \Verb!vec(2:7)!  
go from the first index (here \Verb!2!) up to  
(including) the upper limit (here \Verb!7!).  
Also note that only the \Verb!sampler! function can be called  
from other Matlab programs. If we want the alternative  
implementation in function \Verb!sampler_vec! to be reused
```

```
by other programs, this function has to reside in a file
\Verb!sampler_vec.py!.
```

Another example. The manual contains a useful example² on how to use Mako to implement the nomenclature functionality in the L^AT_EX package `nomenc1`.

References

- [1] S. Linge and H. P. Langtangen. *Programming for Computations*. 2015.

²http://hplgit.github.io/doconce/doc/pub/manual/_manual024.html#manual:mako:nomenclature

Index

APPENDIX, 1

BOOK, 1

boolean in mako, 2

CHAPTER, 1

functions in mako, 3

if tests in mako, 2

mako

- boolean, 2

- functions, 3

- if tests, 2

- variables, 1

variables in mako, 1