
How to Use DocOnce to Write Books

Hans Petter Langtangen^{1,2}

¹Center for Biomedical Computing, Simula Research Laboratory

²Department of Informatics, University of Oslo

Mar 29, 2015

Preface

The purpose of this “book” is to demonstrate a minimalistic setup for making books in the DocOnce format. The setup contains several useful features:

1. Chapters can exist as stand-alone documents in different formats like HTML, Sphinx, and LaTeX-based PDF.
2. Chapters are flexibly assembled into a traditional LaTeX-based book in PDF format for a traditional publisher.
3. The book and the individual chapter documents may have different layouts.
4. Active use of preprocessors like Preprocess and Mako makes it easy to have different versions of the chapters (e.g., a version of a chapter document tailored to the special needs in a specific course at a specific institution).
5. Study guides or slides can easily be developed from the running text and stored along with the chapters.
6. Slides can be compiled to a variety of forms: HTML5 reveal.js, deck.js, Markdown Remark, solarized HTML colors, and classic L^AT_EX Beamer.

These features have the great advantage that a book can evolve from small documents, thereby making the barrier for book writing much smaller. Also, several appealing ebook formats can be produced, both for the book and the individual chapter documents.

Implementation of point 1 and 2 is not trivial and requires some rules that might not feel natural at first sight in the setup. However, the suggested setup works for large-scale books, including the 900-page Springer book “A Primer on Scientific Programming with Python” [3]. Individual chapters of this book, e.g. [1], can be examined online in various ebook formats.

To use this setup, you should have some basic knowledge of DocOnce, including how to compile documents, how to use newcommands in L^AT_EX,

how to use Mako functions, and how to deal with a bibliography, as these features are used in the setup. Some familiarity with basic Bash programming is necessary since there are many Bash scripts lying around in the directory structure to ease the compilation of DocOnce documents.

March 2015

Hans Petter Langtangen

Contents

1	Directory and file structure	1
1.1	Directory structure	1
1.2	Newcommands	2
1.3	Assembling different pieces to a book	3
1.3.1	Organization of a chapter	3
1.3.2	Figures and source code	4
1.3.3	Assembly of chapters to a book	4
1.3.4	HTML/Sphinx versions of the book	7
1.4	Tools	7
1.4.1	Making a new chapter	7
1.4.2	Compiling the chapter	8
1.4.3	About figures when publishing HTML	9
1.4.4	Compiling the book	10
1.5	Cross-referencing across chapters	10
1.5.1	Syntax of generalized cross-references	11
1.6	Study guides and slides	11
1.6.1	Slide directory	11
1.6.2	Generating slides from running text	12
1.6.3	Compiling slides	13
1.6.4	IPython/Jupyter notebooks	14
1.7	Writing in private repository while publishing in public	15
1.8	Special features for teaching material	17
1.8.1	Admonitions	18
1.8.2	Simple box	18
1.8.3	Interactive code	18
1.8.4	Exercises	18
1.8.5	Quote	19
1.8.6	Quiz	19
1.8.7	What about a video lecture?	20

A Use of Mako to aid book writing	21
References	23
Index	25

This chapter describes the file structure of book projects. The setup can of course be used for proceedings and theses as well.

1.1 Directory structure

We shall outline a directory structure that can be effective when assembling different DocOnce documents into a book:

```
doc
  src
    chapters
      ch2
        fig-ch2
        src-ch2
        mov-ch2
        exer-ch2
    book
  pub
    chapters
    book
  web
```

The root directory for all documentation is called `doc`, with two subdirectories: `src` for all the DocOnce source code, and `pub` for compiled (published) documents in various formats. A third subdirectory, `web`, is often present as an entry point for the web pages on GitHub. This directory typically contains the autogenerated `index.html` and additional style files on GitHub. The `index.html` file should have links to published documents in `../pub`.

Under `doc/src` we may have a directory `chapters` for the individual chapters and a directory `book` for the assembly into a book. One may also think of more than one book directory if a set of documents (chapters)

naturally leads to multiple books. All chapters can then be put in the `chapters` directory.

Each chapter has a short *nickname*, say `ch2` for simplicity for Chapter 2 (a more descriptive name related to the content is obviously much better!). Figures are placed in subdirectory `fig-ch2` and computer code in subdirectory `src-ch2`. These two latter directories may have subdirectories if desired. We may also include a directory `mov-ch2` for video files, `exer-ch2` for answers to exercises, etc.

Under `book`, we typically have a document `book.do.txt` for the complete book. This is a file with a lot of `#include "...do.txt"` statements for the Preprocess preprocessor for including the files for the various chapters, see Section 1.3 for details. Additional files in the `book` directory include make files for compiling the book, scripts for packing the book for publishing, perhaps an errata document, etc.

1.2 Newcommands

Files with names `newcommands*.tex` are by DocOnce treated as files with definition of newcommands for \LaTeX mathematics. These files must reside in the same directory as the DocOnce source files. However, for a book project, it is common to have one newcommands file shared by all chapters. This file is placed in `doc/src/chapters/newcommands.p.tex` and copied to a specific chapter by the make script for that chapter. The extension of the file is `.p.tex`, indicating that the file has to be *preprocessed* by `preprocess` prior to being copied. The reason is that one occasionally wants the definitions of the newcommands to depend on the output format (standard \LaTeX or MathJax). For example, subscripts in `mbox` font look best with `footnotesize` font in plain \LaTeX , while the larger `small` font is more appropriate for MathJax. We can then put the following definitions in `newcommands.p.tex`:

```
% #if FORMAT in ("latex", "pdflatex")
% Use footnotesize in subscripts
\newcommand{\subsc}[2]{#1_{\mbox{\footnotesize #2}}}
% #else
% In MathJax, a different construction is used
\newcommand{\subsc}[2]{#1_{\small\mbox{#2}}}
% #endif
```

The make script will then run `preprocess` on this file, typically

```
preprocess -DFORMAT=pdflatex ../newcommands.p.tex > newcommands.tex
# or
preprocess -DFORMAT=html ../newcommands.p.tex > newcommands.tex
```


DocOnce newcommands are for mathematics only!

Note that newcommands in DocOnce context are only used for mathematics, rendered by \LaTeX or MathJax. Newcommands for other \LaTeX constructions (such as section or boxes) should not be used in the DocOnce source code as these are confined to the \LaTeX format. Use instead Mako functions.

1.3 Assembling different pieces to a book

Many smaller writings in the DocOnce format can be assembled into a single, large document such as a book or thesis. The recipe for doing this appears below.

1.3.1 Organization of a chapter

Suppose one chapter) of the book has the nickname `ch2` and may hold all text or just include text in other DocOnce files, e.g., `part1.do.txt`, `part2.do.txt`, and `part3.do.txt`. In this latter case, `ch2.do.txt` has the simple content

```
# #include "part1.do.txt"
# #include "part2.do.txt"
# #include "part3.do.txt"
```

Note that the `ch2.do.txt` file contains just plain text without any `TITLE`, `AUTHOR`, or `DATE` lines and without any table of contents (TOC) and bibliography (BIBITEM). This property makes `ch2.do.txt` suitable for being including in other documents like a book. However, to compile `ch2.do.txt` to a stand-alone document, we normally want a title, an author, a date, and perhaps a table of contents. We also want a bibliography if any of the included files has `cite` tags. To this end, we create a wrapper file, say `main_ch2.do.txt`¹, with the content

```
TITLE: Some chapter title
AUTHOR: A. Name Email:somename@someplace.net at Institute One
AUTHOR: A. Two at Institute One & Institute Two
```

¹

The prefix `main_` is inspired by the main program in computer program: those statements make a program run, like `main_ch2.do.txt` defines the surroundings of the “library text” `ch2.do.txt`. We strip off `main_` when publishing the files in `doc/pub`.

```

DATE: today

TOC: on

# Externaldocuments: ../ch3/main_ch3, ../ch4/main_ch4

# #include "ch2.do.txt"

===== References =====

BIBFILE: ../papers.pub

```

Recall that DocOnce relies on the Publish software for handling bibliographies. It is easy to import from `BIBTEX` to Publish and create a database of references (`papers.pub`) to get started (but we recommend to continue working with the Publish database directly and collect new items in the `papers.pub` file as Publish is more flexible than `BIBTEX`).

1.3.2 Figures and source code

As described in Section 1.1, we recommend to put figures and source codes (to be included in the document) in separate directories. Although such directories could have natural names like `fig` and `src`, it will cause trouble if we do not use unique names for these directories, like `fig-ch2` and `src-ch2`. Otherwise, we would need to copy all figures in all pieces into a common `fig` directory for the book and all source code files into a `src` directory. With unique names, figures and source code files can always reside in their original locations, and we can easily reach them through links. This will be described next.

1.3.3 Assembly of chapters to a book

All the files associated with the `ch2` document and chapter reside in the `ch2` directory. A fundamental principle of DocOnce is to have just one copy of the files (“document once!”). To include the `ch2` text in a larger document like a book, we just need to include the `ch2.do.txt` file and a chapter heading. Here is an example of a document `book.do.txt` for a complete book:

```

TITLE: This is a book title
AUTHOR: A. Name Email:somename@someplace.net at Institute One
AUTHOR: A. Two at Institute One & Institute Two
DATE: today

TOC: on

===== Preface =====
label{ch:preface}

# #include "../chapters/preface/preface.do.txt"

```

```

===== Heading of a chapter =====
label{ch:ch2}

# #include "../chapters/ch2/ch2.do.txt"

# Similar inclusion of other chapters

===== Appendix: Heading of an appendix =====
label{ch:somename}

# #include "../chapters/nickname/nickname.do.txt"

===== References =====

BIBFILE: ../papers.pub

```

When running `doconce format` on `book.do.txt`, the entire document is contained in *one* big file² (!). To see exactly what has been included, you can examine the result of running the first preprocessor, `preprocess`, on `book.do.txt`. All the includes are handled by this preprocessor. The result is contained in the file `tmp_preprocess__book.do.txt`, which then contains the entire DocOnce source code of the book. The second preprocessor, `mako`, is thereafter run (if DocOnce detects that it is necessary). The result of that step is available in `tmp_mako__book.do.txt`. It is important to examine this file if there are problems with Mako variables or functions. The `tmp_mako__book.do.txt` file is thereafter translated to the desired output format.

Say we want to produce a \LaTeX document:

Terminal

```
Terminal> doconce format pdflatex book [options]
```

If the DocOnce source contains copying of source code from files in `@@@CODE` constructs, it is important that `doconce` finds the files. For example,

```
@@@CODE src-ch2/myprog.py  fromto: def test1@def test2
```

will try to open the file `src-ch2/myprog.py`. Since this file is actually located in `../ch2/src-ch2/myprog.py`, `pdflatex` will report an error message. A local link to that directory resolves the problem:

Terminal

```
Terminal> ln -s ../chapters/ch2/src-ch2 src-ch2
```

Similarly, the \LaTeX code in `book.tex` for inclusion of a figure may contain

²

A single DocOnce file and consequently a single `.tex` file works out well on today's laptops. A book with 900 pages [3] has been tested!

```
\includegraphics[width=0.9\linewidth]{fig-ch2/fig1.pdf}
```

For this command to work, it is paramount that there is a link `fig-ch2` in the present `book` directory where the `pdflatex` command is run to the directory `../chapters/ch2/fig-ch2` where the figure file `fig1.pdf` is located.

It is recommended to use the function `make_links` in `scripts.py` to automatically set up all convenient links from the `book` directory to the individual chapter directories. Provided the *list of chapter nicknames* at the top of `scripts.py` is correct, you can just run

```
>>> import scripts
>>> scripts.make_links()
```

to automatically set up all links to all `src-*`, `fig-*`, and `mov-*` directories. You need to rerun this `make_links` function after inclusion of a new chapter in the `chapters` tree.

Identify L^AT_EX errors in the original chapter files!

When you run `pdflatex book` and get L^AT_EX errors, you need to see where they are in `book.tex` and use this information to find the appropriate DocOnce source file in some chapter. Usually, there are few errors at the “book level” if each individual chapter has been compiled. To this end, you can use `scripts.py` to automatically compile each chapter separately. The process is stopped as soon as a DocOnce or L^AT_EX error is encountered.

```
>>> import scripts
>>> scripts.compile_chapters()
```

With heavy use of Mako one can get quite strange error messages. Some ask you to rerun the `doconce format` command with `--mako_strict_undefined` to see undefined Mako variables. Make sure you run the `make.sh` script by `bash -x` if the script does not feature the `set -x` command in the top of the file (for displaying a command prior to running it). Copy the complete `doconce format` with the mouse and add the `--mako_strict_undefined` option. Other error messages point to specific lines that Mako struggles with. Go to the file `tmp_mako__book.do.txt` to investigate the line.

1.3.4 HTML/Sphinx versions of the book

It is easy to make a standard HTML version of the `book.do.txt` manuscript, but for large books, Sphinx is usually a better alternative since it supports navigation, searching, and has an index. There is a script `make_rs.sh` that creates a Sphinx version of the book. Actually, it generates two versions

- standard Sphinx book
- RunestoneInteractive³ Sphinx book

1.4 Tools

You can start a new, future, potential book project by simply copying the directory structure of the `setup4book-doconce`⁴ repository on GitHub. Then you can follow the instructions below to start writing and adapting the structure to your project's needs.

1.4.1 Making a new chapter

Under `doc/src/chapters` you find the chapters in this “sample book” as well as a script `doc/chapters/mkdir.sh` that creates a new directory for you with the typical files needed for a new chapter. You can either edit existing chapters, or make a brand new empty chapter by running

Terminal

```
Terminal> sh mkdir.sh mychap
```

This command makes a directory `mychap` for a new chapter with nickname `mychap`. Files from the `template` directory are used to populate `mychap`. You get an empty `mychap.do.txt` where the text is supposed to go, or this file can just include a series of smaller `.do.txt` files, and you get the wrapper file `main_mychap.do.txt` such that you can compile this chapter as a stand-alone document. You also get `make.sh` which calls `../make.sh` with the chapter main document (`main_mychap`) as argument. Optional arguments for running `doconce format pdflatex` can be given to `../make.sh` in `make.sh` if needed (e.g., `-encoding=utf8`⁵).

³

<http://runestoneinteractive.org>

⁴

<https://github.com/hplgit/setup4book-doconce>

1.4.2 Compiling the chapter

PDF. To make a stand-alone document of a chapter, by compiling to L^AT_EX and PDF, we propose the convention to have a `make.sh` in each chapter directory. This `make.sh` can in most cases just call up a common `../make.sh` script,

```
bash -x ../make.sh main_mychap
```

or optionally with some command-line arguments,

```
bash -x ../make.sh main_mychap --encoding=utf-8
```

The `doc/src/chapters/make.sh` script is quite general and may be edited according to your layout preferences of the L^AT_EX documents.

The present `make.sh` script creates two PDF files: one for printing and one for electronic viewing. The difference is that all URLs in the version for printing appear as footnotes (and just hyperlinks with a dark blue color in the electronic version). The two files are named `mychap.pdf` and `mychap-4print.pdf`, respectively, and copied to `doc/pub/mychap/pdf` for publishing.

Remark. The suggested `make.sh` file applies the `--latex_code_style=` option to `doconce format` for specifying the typesetting of blocks of computer code in L^AT_EX. Originally, DocOnce applied the `ptex2tex` program to select such typesetting, but the new method is more flexible and simpler (in that it gives cleaner L^AT_EX code). (With `ptex2tex` one would need a common configuration file `doc/chapters/.ptex2tex.cfg` to be copied by `doc/chapters/make.sh` to the chapter directory prior to running ‘`ptex2tex`.’)

HTML. There is also a script `doc/src/chapters/make_html.sh` for making HTML versions of the chapter. Just call this as

Terminal

```
Terminal> bash ../make_html.sh main_mychap
```

to make HTML versions of the `mychap` chapter.

The current version of `make_html.sh` creates four types of HTML layouts and an `index.html` file with a list of links to these three files: 1) HTML plain Bootstrap style, 2) HTML Bootswatch readable style, 3) plain HTML solarized color style, and 4) Sphinx pyramid style. (Note that the latter document is a true Sphinx document, made by `doconce format sphinx`, and from which one could make other formats too.)

It is easy to go into the `make_html.sh` script and generate other HTML or Sphinx styles.

You need to edit the index file!

The `index.html` file generated by `make_html.sh` is made from the DocOnce source file `index_html_files.do.txt`. This is a file utilizing Mako programming (see appendix A. There is also a similar file, `index_files.do.txt`, listing all the published documents in various formats associated with a complete book projects (to go to `doc/pub/index.html`).

In the `index_html_files.do.txt` file, we define a Mako dictionary `chapters` mapping nicknames to chapter titles. This dict makes it easy to compile `index_html_files.do.txt` with a Mako variable `CHAPTER` set to the chapter nickname and get a tailored `index.html` file for the HTML versions of that chapter. Similarly, `index_files.do.txt` also has a `chapters` dict and an associated `published` list with all the nicknames of the chapters that we want to list in the overview of the entire book project (all sufficiently finished chapters).

The `index_files.do.txt` file gives a table of contents of all documents, so you will normally compile this manually now and then as

Terminal

```
Terminal> doconce format html index_files --html_style=bootstrap \
          --html_links_in_new_window --html_bootstrap_navbar=off
```

and publish it in `doc/pub/index.html`.

Cleaning Files. The `make*.sh` files generate a lot of files that can easily be regenerated and that are normally removed from the chapter directories. The script `sh ../clean.sh` can be run in any chapter directory to clean up redundant files.

1.4.3 About figures when publishing HTML

There will be `` type of tags in HTML code produced by DocOnce, so it is very important to ensure that the *published* `.html` files have access to a subdirectory `fig-ch2`. Normally, one needs to copy `fig-ch2` from the `ch2` chapter source directory to some publishing directory that stores all the files necessary for accessing the entire HTML document on the web.

1.4.4 Compiling the book

Go to `doc/src/book` and run `make.sh` to compile the book. This requires that `book.do.txt` performs the right include of chapters, table of contents, and bibliography.

There are many other tools in `doc/src/book` too, e.g., the mentioned library of handy scripts in `scripts.py`, and an example on how to pack all files of the entire book projects for publishing with Springer (`pack_Springer.sh`).

The current book layout created by `make.sh` makes use of a (now outdated) Springer T2 style for textbooks (requires the `.cls` and `.sty` files in the `book` directory). Other Springer styles supported by DocOnce are Lecture Notes in Computational Science and Engineering (monographs and proceedings), Lecture Notes in Computer Science (proceedings), and Undergraduate Texts in Physics. Other book styles will require some manual work, either working out a \LaTeX preamble for a special style and use that when compiling `book.do.txt` or actually extending the DocOnce source code.

1.5 Cross-referencing across chapters

A fundamental problem when writing a book *and* stand-alone chapters arises with cross-referencing. In a book file it makes sense to refer to an equation in any chapter, say (4.23), while in a stand-alone chapter references to equations or sections in other stand-alone documents will not work. That is, \LaTeX has a native mechanism for this, the `xr` package, where one can register a set of `.aux` files for other \LaTeX documents and refer directly to these labels and get them right. It is then possible to write something like

```
see (\eqref{sec:results:u:eq}) in \cite{Hansen_2011b}
```

and get it out as

```
see (2.37) in [12]
```

provided our `.tex` file contains `\externaldocument{myother}` and the label `sec:results:u:eq` is defined in `myother.aux`. DocOnce has generalized this feature so it works for non- \LaTeX formats as well. It is called *generalized cross-references*. You can then write such references across chapters and get all labels right whether you produce the entire book or individual chapters.

1.5.1 Syntax of generalized cross-references

Here is an example on a generalized reference to an equation in another chapter:

```
The world's most famous equation is ref[(ref{fake:Emc2})][in
cite{Langtangen_dobook_fake}][
as found in the document "Some document":
"http://hplgit.github.io/setup4book-doconce/doc/pub/fake"
cite{Langtangen_dobook_fake}].
```

This sentence is rendered as follows in the present format (`pdflatex`):

The world's most famous equation is (1)in [2].

More detailed information about generalized cross-references is found in the DocOnce manual⁵. In particular, one has to insert `# Externaldocuments:` commands in all `main_*.do.txt` files that includes files with generalized references.

1.6 Study guides and slides

DocOnce has good support for creating slides from ordinary documents with running text. Rather than speaking about slides, we think of *study guides* where the material is presented in a very condensed, effective, summarizing form for overview, use in lectures, and repetition. The slide format is a good way of writing study guides, but by explicitly thinking of study guides the slide format can be made more effective for self-study when overview and repetition are necessary - with a particular emphasis on gaining understanding.

It is, of course, a very challenging balance between enough information for self-study by reading slides and overwhelmingly much text and information in slides for oral presentations. Text must anyway be minimized all the way on slides, and the reader of a study guide is supposed to also be a reader of the underlying running text in the chapter.

1.6.1 Slide directory

For each DoOnce file in the chapter `ch2` it can be wise to make a corresponding study guide file in the subdirectory `slides-ch2`. For example, `part1.do.txt` has its counterpart with slides in `slides-ch2/part1.do.txt`. Then there is a file `slides_ch2.do.txt` which assembles the parts if `slides-ch2`, typically with a content like

⁵

<http://hplgit.github.io/doconce/doc/pub/manual/html/manual.html#generalized-cross-referencing>

```

TITLE: Study Guide: Some title
AUTHOR: Author Name Email:somename@someplace.net at Institute One
DATE: today

# #ifdef WITH_TOC
!split
TOC: on
# #endif

# #include "lec-ch2/part1.do.txt"

# #include "lec-ch2/part2.do.txt"

# #include "lec-ch2/part3.do.txt"

```

1.6.2 Generating slides from running text

The author has the following work flow for generating slides for a chapter file, say `part1.do.txt`.

1. Copy `part1.do.txt` to `slides-ch2/part1.do.txt`.
2. Make `slides_ch2.do.txt` and include `slides-ch2/part1.do.txt`.
3. Decide on *parts* of the slide collection. Often a part can be a section in the parent `ch2.do.txt` file, but sometimes it can be more natural to have larger parts than sections in the slide collection.
4. Each part in the slide file has a DocOnce section heading with 7 =, while each slide has a DocOnce subsection heading with 5 =.
5. Edit `slides-ch2/part1.do.txt`:
 - One can keep subsection headings from the running text for the most part, but slides need many more subsection headings.
 - Try to let the heading summarize explicitly a conclusion/rule from the slide (the slide table of contents is then a set of conclusions/rules!)
 - Remember a `!split` right above every slide heading!
 - Compile frequently and look at the slides: they become over-full very quickly so there is a constant need for dividing slides into new ones with new headings.
 - Read a paragraph, focus on its main idea and result, and see how it can be condensed to one sentence or a few bullet points. *Making effective slides is the art of condensing the most important information in the text to a eye-catching format.*
 - Do not remove figures without a very good reason. Figures are important!
 - Add new images to live up the presentation. In slides you may think of cartoons or entertaining images that would never be suitable in a chapter/book, but they may help attract attention, communicate ideas, and enhance the memory process.

- Condense every mathematical derivation. Make sure the goal and end result is clear before diving into details.
- Detailed derivations are seldom of interest in a study guide or oral presentation - refer to the underlying running text in the chapter for the details. Focus on ideas and key mathematical steps (if they are important enough).
- Remember that equations are sometimes excellent images for ideas! Complicated equations can therefore be important slide elements although the details will never be addressed.
- It is quite often wise to remove equation numbers in slides. You can automatically remove them by `--denumber_all_equations`, or you can edit the \LaTeX math environment manually. Remember that references to equations numbers must be removed from the slides too!
- Movies are effective in slides. It is still a hassle to get them displayed correctly in PDF files, so using a test on `FORMAT` and writing `MOVIE` for HTML output and just a link in PDF output might be necessary. See the manual⁶ for how to work with movies in DocOnce.

The slides are to fulfill three purposes:

1. reading as a study guide to get overview before reading the full text of chapter,
2. watching as slides during an oral presentation,
3. reading as a study guide to repeat and enforce overview of the material.

It is highly non-trivial to meet all these purposes: limit the information on the slides, make them as visual as *feasible*, make them self contained, and provide the *sufficient* amount of information. Considerable iterations are always needed. Reading the slides as a study guide is easy to accomplish. The slides' properties in live presentations can only be tested by speaking to them (making a rough draft of a video podcast is a very effective way of testing the slides' quality).

1.6.3 Compiling slides

There is a quite general script in `doc/src/chapters/make_slides.sh` for compiling a slide collection defined in a file like `slides_ch2.do.txt`. Just run

```

Terminal
Terminal> bash ../make_slides.sh slides_ch2

```

⁶

<http://hplgit.github.io/doconce/doc/pub/manual/html/manual.html#movies>

from the chapter directory. Note that the script will first spell check the slide files. This is done in the `slides-ch2` directory. Errors are reported in files located in `slides-ch2`. To update the chapter's dictionary for spell checking, you need to do

Terminal

```
Terminal> cp slides-ch2/new_dictionary.txt~ .dict4spell
```

in the `ch2` chapter directory.

Similarly, to look at misspellings, the file `slides-ch2/misspellings.txt~` is the relevant file.

The `make_slides.sh` script compiles a variety of slides:

- First a plain \LaTeX PDF document to catch as many errors in the DocOnce source as early as possible. This document can also be used for compact printing of the contents of the study guide (and the output looks definitely like a study guide and not slides!).
- HTML5 `reveal.js` slides with different colors.
- HTML5 `deck.js` slides. This format is usually inferior to `reveal.js`, but is also very much personal taste.
- \LaTeX Beamer slides. Edit the `theme=red_shadow` line in `make_slides.sh` to control the Beamer theme.
- Remark (Markdown) slides for viewing in a browser.

1.6.4 IPython/Jupyter notebooks

Since DocOnce documents can be translated to IPython/Jupyter notebooks, hereafter just called notebooks, it is tempting to produce a version of the teaching material also in notebook form. This author's experience is that a more traditional book format with running text is not so ideal for a notebook:

- you simply get too much text in a too long notebook,
- the notebook needs more code snippets than what you want to show in a book (or you just want to show fragments while the notebook requires complete code),
- there are many cross-references between equations, sections, figures, and running text that the notebook does not support well.

Instead, making slides from the chapter's text and translating slides to the notebook format is a splendid idea. This requires some tuning, as you want slight differences between classic slides and a notebook. For example, a code snippet that results with a plot should contain the plot in classic slides, while the notebook will automatically produce it when run. This is easily fixed by an if test in Mako, typically `% if FORMAT != 'ipynb':`

followed by a **FIGURE:** line that includes the resulting figure for all formats except the notebook.

Also be aware of the DocOnce *hidden* code environment that can be used to declare code blocks that appear in notebooks (because they are needed) but not in other formats: `!bc pyhid` gives a Python hidden snippet.

Using notebooks as a starting point for a traditional textbook might be a good idea, but will enforce a non-conventional style in the textbook. For example, notebooks should be quite small, leading to similarly small modules in the book. Notebooks use cross-referencing to little extent, and this will be reflected in the textbook too. Notebooks also need more code to run, so one has to accept more code in the textbook. However, there is still a problem for the notebook with defining items for an index, fancy admonitions, and other elements that one would desire in a textbook. More experience is needed to make best practices. Since notebooks can be compiled Markdown, and DocOnce can read basic Markdown input, it is possible to go from the notebook format to DocOnce, but this is not tested.

Remark

More best practices from turning teaching material in books into notebooks are supposed to be collected here in the future.

1.7 Writing in private repository while publishing in public

Sometimes you want to keep ongoing writing in a *private* repository and make only *selected* chapters and/or files publicly visible. In such cases one can set up the book project structure in a private repository, but use a public repository instead of the `doc/pub` directory for publishing selected compiled documents. This is easy: just change the `dest=` line, where the publishing directory is defined, in all `make*.sh` scripts in `doc/src/chapters`. The files will then be copied to this alternative destination.

Often, you want to publish the software associated with the book project, stored in `doc/src/chapter/nickname/src-nickname`, as a part of the public repository. Such files can also easily be copied, say to `src/nickname` in the public repository. However, software files often change names and locations in subdirectories, and then you need to be very careful with updating the Git commands in the public repository every time you do `git add` or `git rm` locally in the private repository. This problem occurs with text files too, but maybe less often, so the

recipe given below applies to all kind of files you want to mirror from a private to a public repository.

We have made a script `rsync_git.py` that can copy files from one repository to another and log files that are removed or deleted and then take the appropriate Git actions. Running

Terminal

```
Terminal> rsync_git.py src-mychap $HOME/repos/pub/mybook/src/mychap
```

will copy all files from `src-mychap` to `$HOME/repos/pub/mybook/src/mychap`, find which files that are new in `src-mychap` and must be added to the destination directory, and which files that are removed in `src-mychap` and should be removed in the destination directory as well. An `rsync` command is run to the physical copy and removal of files, followed by `git add` and `git rm` commands. In this way, you can automatically keep the public repository as a mirror *of parts* of your private repository!⁷

The `rsync_git.py` script is listed below for reference. Note that a file `$HOME/.rsyncexclude` can be made to filter out certain files that you never want to copy (this is always a good idea!).

```
#!/usr/bin/env python
"""
Sync two directory trees with rsync and perform corresponding
git operations (add or rm).
Skip files listed in $HOME/.rsyncexclude.

Usage:  rsync_git.py from-dir to-dir
Example: rsync_git.py src-mychap $HOME/repos/pub/mybook/src/mychap

The from-dir is the source and the to-dir is the destination
(e.g. a public directory where resources are exposed).
The script must be run from a dir within the repo of to-dir.
"""

# Typical rsync output:
"""
sending incremental file list
deleting decay7.py
decay_TULL.py

sent 675 bytes  received 34 bytes  1418.00 bytes/sec
total size is 94788  speedup is 133.69
"""

# Example on $HOME/.rsyncexclude file
"""
.*
.*
*.rsync~
*.a
*.o
*.so
"""
```

7

This functionality should be a part of Git, but no Git expert I have talked to has ever seen use for merging a flexibly defined subset of a repository with another repository. (The current functionality of Git is not capable of working with, e.g., branches that merge with only parts of another branch.)

```

*~
.*~
*.log
*.dvi
*.aux
*.old
tmp_*
.tmp*
*.tar
*.tar.gz
*.tgz
*.pyc
"""

import commands, os, sys

from_ = sys.argv[1]
to_ = sys.argv[2]
cmd = 'rsync -rtDvz -u -e ssh -b ' + \
      '--exclude-from=$HOME/.rsyncexclude ' + \
      '--suffix=rsync~ --delete --force %s/ %s' % (from_, to_)
print cmd
failure, output = commands.getstatusoutput(cmd)
print output

delete = []
add = []
for line in output.splitlines():
    relevant_line = True
    for text in 'sending incremental file list', \
               'sent ', 'total size is':
        if line.startswith(text):
            relevant_line = False
    if relevant_line and line != '':
        if line.startswith('deleting'):
            delete.append(line.split()[1])
        else:
            add.append(line.strip())

print delete
print add

for filename in delete:
    option = '-rf' if os.path.isdir('%s/%s' % (to_, filename)) else '-f'
    cmd = 'git rm %s %s/%s' % (option, to_, filename)
    print cmd
    os.system(cmd)
for filename in add:
    cmd = 'git add %s/%s' % (to_, filename)
    print cmd
    os.system(cmd)

```

1.8 Special features for teaching material

DocOnce offers some special features that can greatly aid development of effective teaching material:

- fancy admonitions
- simple boxes
- interactive code blocks
- hidden code blocks

- exercises
- multiple-choice questions or quizzes
- movies
- quotes

These are briefly exemplified below. If you are mainly interested in how to structure DocOnce-based books, you can safely jump to Section 1.3.

1.8.1 Admonitions

Use admonitions!

Need to notify, warn, summarize, ask a question, give a tip, dive into less important details, or really emphasize a result? DocOnce features special *notice*, *warning*, *summary*, and *question* boxes for called admonitions. These can be typeset in a variety of versions, depending on the output format (check out `doconce format --help` and the many options with `admon` in the name).

1.8.2 Simple box

Put a box around something important:

$$1 + 1 = 2$$

1.8.3 Interactive code

You can step through this code:

```
n = 4
i = 0
while i <= n:
    print i
    i += 1
```

In HTML and Sphinx format this code can be stepped through, while in L^AT_EX one gets a link to a web page with this functionality.

1.8.4 Exercises

Exercise environments

DocOnce supports *exercise subsections*, which are subsections with some extra tagging for exercises. Important features are:

- exercises can be divided into subexercises
- one may specify filename(s) for delivering the answer to an exercise
- one may specify filename(s) for the solution of an exercise
- one may specify a remark (fun facts, comments)
- one or more hints can be given to an exercise or subexercise (can be hidden in certain output formats)
- any exercise or subexercise can have a solution field
- any exercise or subexercise can have an answer field (very condensed solution)
- solutions and answers can be removed from the document at compile time
- exercises can have one of four titles: Exercise, Project, Problem, or Example

1.8.5 Quote

There is also a *quote* environment (invisible box with larger margins).

We're programmers. Programmers are, in their hearts, architects, and the first thing they want to do when they get to a site is to bulldoze the place flat and build something grand. We're not excited by incremental renovation: tinkering, improving, planting flower beds.

There's a subtle reason that programmers always want to throw away the code and start over. The reason is that they think the old code is a mess. And here is the interesting observation: they are probably wrong. The reason that they think the old code is a mess is because of a cardinal, fundamental law of programming: **It's harder to read code than to write it.** This is why code reuse is so hard. This is why everybody on your team has a different function they like to use for splitting strings into arrays of strings. They write their own function because it's easier and more fun than figuring out how the old function works.

Joel Spolsky⁸, 2000

1.8.6 Quiz

Question: How can one typeset a multiple choice question or *quiz* in DocOnce? Recall that a quiz may feature mathematics like

$$F = ma$$

and even nicely typeset computer code:

⁸

<http://www.joelonsoftware.com/articles/fog0000000069.html>

```
def Newtons2nd(m, a):  
    F = m*a  
    return F  
  
print Newtons2nd(1.1, 2.0)
```

A. Cannot be typeset because online quiz tools ignore math and code typesetting.

B. See the DocOnce quiz manual⁹.

C. Read the quiz and the multiple answers out loud and hope for a magic translation to code.

Answer: B.

Solution:

A: Wrong. This is almost true: getkahoot.com has implemented support for DocOnce-generated quizzes with math and code :-)

B: Right. Here you see all capabilities demonstrated.

C: Wrong. Not implemented this year - just had to come up with yet another choice...

1.8.7 What about a video lecture?

<http://youtube.com/PtJrPEIHNJw>

Question

Can you think of applications of the above mentioned features?

⁹

<http://hplgit.github.io/doconce/doc/pub/quiz/quiz.html>

Remark. Documents that contain raw Mako code in verbatim code blocks cannot also be processed by Mako, and this is the case with the `mako` chapter. Since we need Mako for processing the rest of this book document, we are forced to compile the `mako` chapter as a stand-alone document (with the `--no_mako` option) and let this appendix be just a link to the this stand-alone document¹.

¹

http://hplgit.github.io/setup4book-doconce/doc/pub/mako/pdf/main_mako.pdf

References

1. H. P. Langtangen. Loops and lists. <http://hplgit.github.io/primer.html/doc/pub/looplist>.
2. H. P. Langtangen. Some document. <http://hplgit.github.io/setup4book-doconce/doc/pub/fake>.
3. H. P. Langtangen. *A Primer on Scientific Programming With Python*. Texts in Computational Science and Engineering. Springer, fourth edition, 2014.

Index

`'make_slides.sh`, 13

admonitions, 18

assembly (chapters to book), 4

bbox box, 18

chapter

- files, 3
- organization, 3

`clean.sh`, 9

cross-referencing, 10

embedded video in DocOnce, 20

exercises in DocOnce, 18

figure directory, 1, 4

generalized references, 10

interactive code, 18

IPython notebooks, 14

Jupyter notebooks, 14

links to fig/src directories, 5

`make.sh`, 8

`make_html.sh`, 8

mirroring repos, 15

`mkdir.sh`, 7

movie directory, 1, 4

movie in DocOnce, 20

newcommands, 2

nickname, 2

notebooks, 14

private repos, 15

pub directory, 1

pyoptpro interactive code, 18

quiz in DocOnce, 19

ref generalized reference, 11

refch generalized reference, 11

RunestoneInteractive books, 7

scripts module, 6

slides, 11

source code directory, 1, 4

sphinx, 7

study guides, 11

video directory, 1, 4

video in DocOnce, 20