Spotting AI Coding Agents in Git and GitHub

Every known trace, for every agent, plus how to calculate edit velocity. A companion to Agentic Much? (Robbes et al., 2026). Checked against real GitHub data on 24 October 2026.

How to use this

- Agents leave traces in **six places**: commit trailers, the commit author, lines in the commit message, bot accounts, pull requests (branch name, label, body) and files in the repo. Sections 1-6 list them.
- Each table shows the **exact text to match**. Copy it as written: it is case-insensitive for the key (`Co-authored-by` = `Co-Authored-By`), exact for the email.
- The **hits** column is how many public GitHub commits or PRs matched in October 2026. It is approximate (GitHub search matches loosely) and counts commits, not repos. Use it to see which traces matter most.
- Section 7 lists the traps that cause false positives. Section 8 explains edit velocity step by step.

The golden rules

- **Trust the email, not the name.** The email identifies the tool; the name is often the model. `Co-Authored-By: Kimi <noreply@anthropic.com>` is Claude Code running the Kimi model.
- **Match where the agent writes it.** A brand word anywhere in a message is not a signal: “move the cursor” is not Cursor, and a person named Claude is not Claude Code.
- **No trace never means human.** Every trace can be switched off. Over 40% of projects with agent files have no agent trace in any commit (Robbes et al.). Results are always a **lower bound**.
- **Prefer the numeric GitHub id for bots.** Names and emails can be typed by anyone; the number in `198982749+Copilot@users.noreply.github.com` cannot be faked as easily.
- **Separate authoring from reviewing.** AI review bots (CodeRabbit, Copilot review) do not write code.
- **Traces change fast.** Agents rename branches, emails and footers every few months. Re-check yearly.

> **The most reliable traces** (very few false positives, high volume): `noreply@anthropic.com`, `cursoragent@cursor.com`, `198982749+Copilot`, `codex@openai.com`, the bot accounts in Section 4, and branch prefixes `codex/` `copilot/` `cursor/` `claude/` `devin/`.

1. Commit trailers (co-author lines)

A trailer is a line at the end of the commit message, after a blank line. Most agents add themselves as a co-author while the human stays the main author. The five agents your methodology focuses on come first.

Agent	Exact text to match	Notes	Hits
Claude Code	`Co-Authored-By: Claude <noreply@anthropic.com>` `Co-Authored-By: Claude Opus 4.8 <noreply@anthropic.com>`	Name is often the model (Claude Sonnet 4.6, Claude Opus 4.8). Also reused by other tools: the email decides.	8.9M
Copilot (coding agent)	`Co-authored-by: copilot-swe-agent[bot] <198982749+Copilot@users.noreply.github.com>` `Agent-Logs-Url: https://github.com/<owner>/<repo>/sessions/<id>`	Agent-Logs-Url added since March 2026; links the commit to its agent session.	465K 724K
Copilot (VS Code)	`Co-authored-by: Copilot <223556219+Copilot@users.noreply.github.com>`	Added by VS Code's git.addAICoAuthor setting. Weaker: see trap 4 in Section 7.	1.4M
Codex (OpenAI)	`Co-authored-by: Codex <codex@openai.com>`	Codex CLI and cloud.	274K

Cursor	`Co-authored-by: Cursor <cursoragent@cursor.com>`
	`Co-authored-by: Cursor Agent <cursoragent@cursor.com>`
	`Made-with: Cursor`
		Made-with: Cursor is the IDE/CLI agent's trailer; cloud agents use the cursoragent address.	3.4M
			1.5M

Gemini	`Co-authored-by: gemini-code-assist[bot] <176961590+gemini-code-assist[bot]@users.noreply.github.com>`	Appears when a Gemini Code Assist review suggestion is applied. Older names: Gemini 2.5 Pro, Gemini 2.5 Flash.	374K
Aider	`Co-authored-by: aider (<model>) <aider@aider.chat>` `Co-authored-by: aider <noreply@aider.chat>`	Optional (--attribute-co-authored-by). The model is in brackets, e.g. aider (openai/gpt-4o).	131K
Amp (Sourcegraph)	`Co-authored-by: Amp <amp@ampcode.com>` `Amp-Thread-ID: https://ampcode.com/threads/T-<id>`	Both usually together.	124K 138K
Augment Code	`Co-authored-by: Augment <noreply@augmentcode.com>`	Rare.	1.4K
Cline	`Co-Authored-By: Cline <noreply@cline.bot>`	Rare; Cline does not sign by default.	small
Codegen	`Co-authored-by: codegen-sh[bot] <131295404+codegen-sh[bot]@users.noreply.github.com>`		3.4K
Continue	`Co-Authored-By: Continue <noreply@continue.dev>`		2.3K
Crush (Charm)	`Assisted-by: <model> via Crush <crush@charm.land>`	Uses Assisted-by, not Co-authored-by.	17K
Devin	`Co-authored-by: devin-ai-integration[bot] <158243242+devin-ai-integration[bot]@users.noreply.github.com>`	Number sometimes missing from the email.	798K
Factory Droid	`Co-authored-by: factory-droid[bot] <138933559+factory-droid[bot]@users.noreply.github.com>`		132K
Jules (Google)	`Co-authored-by: google-labs-jules[bot] <161369871+google-labs-jules[bot]@users.noreply.github.com>`		264K
Junie (JetBrains)	`Co-authored-by: Junie <junie@jetbrains.com>`		22K
Kiro (AWS)	`Co-authored-by: Kiro Agent <244629292+kiro-agent@users.noreply.github.com>`	Also seen with made-up emails; trust only the noreply form.	14K
Letta Code	`Co-Authored-By: Letta Code <noreply@letta.com>`		18K
Mistral Vibe	`Co-Authored-By: Mistral Vibe <vibe@mistral.ai>`		33K
Ona (ex-Gitpod)	`Co-authored-by: Ona <no-reply@ona.com>`		52K
OpenCode	`Co-authored-by: <model or OpenCode Agent> <noreply@opencode.ai>`	Name is often the model (GLM-5.3-Flash).	93K
OpenHands	`Co-authored-by: openhands <openhands@all-hands.dev>`	Also appears as commit author.	261K
Qwen Code	`Co-authored-by: Qwen-Coder <qwen-coder@alibabacloud.com>`		116K

Agent	Exact text to match	Notes	Hits
TRAE (ByteDance)	`Co-authored-by: TRAE CLI <traecli@bytedance.com>`		16K
Warp	`Co-Authored-By: Warp <agent@warp.dev>`		32K
Windsurf	`Co-authored-by: windsurf-bot[bot] <189301087+windsurf-bot[bot]@users.noreply.github.com>`	Rare.	small
Older / from Robbes et al.	`ChatGPT | hello@sketch.dev (Sketch) | roomote@roocode.com (Roo Code) gru-agent (Gru) | open-swe (Open SWE) | deepsource-autofix (DeepSource)`	Validated in the paper (Oct 2025) but rare in 2026. Kilo Code and Roo Code users mostly type their own emails.	—

Generic AI trailers (no brand, or brand inside)

Trailer	Meaning	Hits
`Assisted-by: AGENT:MODEL`	Linux kernel convention for AI help, e.g. `Assisted-by: Claude Code:claude-opus-4-8`. The agent name comes first.	93K
`AI-Assisted-By: <model> <email>`	Variant seen in the wild, e.g. Gemini.	small
`Generated-by: <tool>`	e.g. `Generated-by: Kiro IDE`. Many human tools use it too; only count it if the tool is an agent.	loose

2. The commit author itself

Some agents commit **as themselves**: the author (or committer) field is the agent. Match the author email exactly; for GitHub bots, the number before the + is the account id.

Agent	Author identity (name <email>)	Notes	Hits
Claude Code	`Claude <noreply@anthropic.com>`	Author or committer. Name may be the model.	21.9M
Cursor	`Cursor Agent <cursoragent@cursor.com>`	Cloud agents always commit as Cursor Agent; the human is the co-author.	2.3M
Copilot	`Copilot <198982749+Copilot@users.noreply.github.com>`	Coding agent; the human who assigned the task is the co-author.	4.4M
Codex	`<any name> <codex@openai.com>`	e.g. “Astra (Codex)”.	640K
Jules	`google-labs-jules[bot] <161369871+google-labs-jules[bot]@users.noreply.github.com>`		1.3M
Devin	`devin-ai-integration[bot] <158243242+devin-ai-integration[bot]@users.noreply.github.com>`		469K
OpenHands	`openhands <openhands@all-hands.dev>`		187K
Aider	`Your Name (aider) <your@email>`	Aider's default: it appends “ (aider)” to the author and committer name. Only the committer name gets it when aider commits files you edited.	—
Codegen	`codegen-sh[bot] <131295404+codegen-sh[bot]@...>`		13K
Sweep	`sweep-ai[bot] <128439645+sweep-ai[bot]@...>`		26K
Factory Droid	`factory-droid[bot] <138933559+factory-droid[bot]@...>`		3.1K
Amazon Q	`amazon-q-developer[bot] <208079219+amazon-q-developer[bot]@...>`		2.2K
Junie	`jetbrains-junie[bot] <201638009+jetbrains-junie[bot]@...>`		1.9K
Roo Code (cloud)	`roomote-roomote[bot] <301996811+roomote-roomote[bot]@...>`		20K
Kiro	`kiro-agent[bot] <245459735+kiro-agent[bot]@...>`		—

3. Lines the agent writes into the message

Footers or links the agent adds to the commit message **and often the PR body too**. (robot emoji) stands for the emoji the agent puts at the start of the line.

Agent	Line to match	Notes	Hits
Claude Code	`(robot emoji) Generated with [Claude Code](https://claude.com/claude-code)`	Older: (https://claude.ai/code). Commits 3.6M; PR bodies 19.5M.	3.6M
Codex	`https://chatgpt.com/codex/tasks/task_e_<id>`	Cloud task link, e.g. “Built by a Codex Cloud task: …”. PR bodies ~2.0M.	50K
Cursor	`Made with [Cursor](https://cursor.com)` `cursor.com/agents | cursor.com/background-agent`	Links in agent PR bodies (“Open in Cursor”). ~1.6M PRs.	1.5M
Copilot	`copilot-workspace.githubnext.com`	Old Copilot Workspace sessions (2024-25).	small
Devin	`https://app.devin.ai/sessions/<id>`	“Link to Devin run”; mostly in PR bodies (340K).	9.5K
Amp	`https://ampcode.com/threads/T-<id>`	Also the Amp-Thread-ID trailer.	138K
Gemini CLI	`(robot emoji) Generated with [Gemini CLI](https://github.com/google-gemini/gemini-cli)`		954

Agent	Line to match	Notes	Hits
OpenCode	`(robot emoji) Generated with [OpenCode](https://opencode.ai)` `Generated with opencode`		50K
Crush	`(heart emoji) Generated with Crush`		46K
Qwen Code	`(robot emoji) Generated with [Qwen Code](https://github.com/QwenLM/qwen-code)`		775
Cline	`(robot emoji) Generated with [Cline](https://cline.bot)`		24
Windsurf	`(robot emoji) Generated with [Windsurf Cascade](https://codeium.com/windsurf)`		6
Cursor (rare)	`(robot emoji) Generated with [Cursor](https://cursor.com)`		533
Aider	`aider: <subject>`	Optional subject prefix (off by default). Match only at the very start of the subject.	—

4. Bot accounts (GitHub logins)

These accounts author commits, open PRs or comment. The id is the number GitHub puts in the bot's noreply email (`<id>+<login>@users.noreply.github.com`). In GitHub's GraphQL API, bot logins come **without** the [bot] suffix.

Agent	Login	Id	What it does
Copilot	`Copilot / copilot-swe-agent[bot]`	`198982749`	Coding agent (commits + PRs). 2.1M PRs.
Copilot (VS Code)	`Copilot`	`223556219`	Co-author added by VS Code, not the agent.
Claude Code	`claude[bot]`	`209825114`	Claude GitHub Action / Claude Code on the web. 68K PRs.
Codex	`chatgpt-codex-connector[bot]` `openai-codex[bot]`	`199175422` `215057067`	Codex cloud on GitHub (reviews, some PRs).
Cursor	`cursor[bot]`	–	Opens cloud-agent PRs (176K) and runs Bugbot reviews.
Gemini	`gemini-code-assist[bot]`	`176961590`	Mostly code review; co-author when suggestions are applied.
Jules	`google-labs-jules[bot]`	`161369871`	Commits + PRs (334K).
Devin	`devin-ai-integration[bot]`	`158243242`	Commits + PRs (313K).
Factory	`factory-droid[bot]`	`138933559`	
Codegen	`codegen-sh[bot]`	`131295404`	
Sweep	`sweep-ai[bot]`	`128439645`	
Amazon Q	`amazon-q-developer[bot]`	`208079219`	
Junie	`jetbrains-junie[bot]`	`201638009`	
Kiro	`kiro-agent[bot]` (user: `kiro-agent`)	`245459735` `244629292`	30K PRs.
Windsurf	`windsurf-bot[bot]`	`189301087`	
Cline (cloud)	`cline-cloud[bot]`	`276134852`	
Roo Code (cloud)	`roomote-roomote[bot]`	`301996811`	
Tembo	`tembo[bot]`	`208362400`	
OpenHands	`openhands-agent` (a user, not [bot])	–	

Not coding agents: exclude these

Type	Logins	Why
AI reviewers	`coderabbitai[bot]`, `sourcery-ai[bot]`, `copilot-pull-request-reviewer[bot]`, `qodo-merge-pro[bot]`, `greptile-apps[bot]` (and `gemini-code-assist[bot]`, `cursor[bot]` when only reviewing)	They review code; they do not write it. Record them separately as “AI review adoption”.
Automation	`dependabot[bot]`, `renovate[bot]`, `github-actions[bot]`, `snyk-bot`, `pre-commit-ci[bot]`, `codecov[bot]`, `allcontributors[bot]`, `mergify[bot]`, `stale[bot]`	Dependency bumps and CI. Robbes et al. filter these out before counting human vs AI commits.

5. Pull requests: branch names and labels

Agent PRs usually come from a branch with a fixed prefix. Match the prefix **at the start** of the branch name only (`docs/copilot` is not a Copilot branch). Hits are from Robbes et al. Table 1 (October 2025), or from GitHub in October 2026 where marked *.

Agent	Branch pattern	Notes	Hits
Codex	`codex/<slug>`	e.g. codex/fix-1701-table-spacing. The prefix can be changed in settings.	2.1M
Copilot	`copilot/<slug>` `copilot/fix-<ids>`		338K
Cursor	`cursor/<slug>-<4 hex>`	e.g. cursor/code-simplification-2c49. Prefix can be changed in the dashboard.	209K
Claude Code	`claude/<slug>-<session id>`	e.g. claude/fix-taskbar-freeze-9fnqS. From Claude Code on the web.	20.7K
Devin	`devin/<unix time>-<slug>`	e.g. devin/1792891125-tile-favicon.	49.8K
Sweep	`sweep/<slug>`		28K
Codegen	`codegen-bot/<slug>`		6.1K
Cline (cloud)	`cline/<id>`	New in 2026.	915 *
Amazon Q	`Q-DEV-issue-<n>-<time>`	Opened by amazon-q-developer[bot].	2.3K *
Jules	`jules-<number>-<hash> or <slug>-<long number>`	No jules/ prefix in 2026; match the bot account instead.	1.5K
Others	`openhands/ gru/ open-swe/ opencode/ goose/ jetbrains_junie`	From Robbes et al.; small.	<1.5K

Labels

Label	Agent	Hits
`codex`	Codex (added by Codex cloud)	4.5M *
`ai-generated`	Unknown agent (generic)	30K *
`amp`	Amp	260
`open-swe`	Langchain Open SWE	677

PR authors and bodies

A PR opened by a bot account from Section 4 is an agent PR. Agent footers from Section 3 also appear in PR bodies, where they are even more common than in commits (Claude Code: 19.5M PR bodies). When a PR is squash-merged, its commit loses the branch name, so carry the PR's label over to the squash commit.

6. Files in the repository

Configuration, rules and guidance files show an agent was **set up** in the repo, not that it wrote a given commit. A path ending in / means any file in that folder. Hits: Robbes et al. Table 1 (Oct 2025).

Agent	Paths	Hits
Claude Code	`CLAUDE.md .claude/ .claudeignore .github/workflows/claude*.yml`	110K + 141K
Copilot	`.github/copilot-instructions.md .github/instructions/ .github/prompts/ .copilotignore .copilot/ .github/workflows/copilot-setup-steps.yml`	45K + 13K
Cursor	`.cursor/ .cursorrules CURSOR.md`	98K + 17K
Codex	`.codex/`	3.3K
Gemini	`GEMINI.md .gemini/`	8.4K + 4.8K
Generic	`AGENTS.md (used by Codex, Copilot, Cursor, Jules, Aider and more)`	37.5K
Kiro	`.kiro/`	42K
Cline	`.clinerules .cline/ memory-bank/ memory_bank/`	27K

Agent	Paths	Hits
Windsurf	`.windsurf/ .windsurfrules`	12.6K
Taskmaster	`.taskmaster/`	14.9K
Amp	`AGENT.md (singular)`	5.9K
Roo Code	`.roo/ .roorules`	6.7K
Trae	`.trae/`	4.4K
Warp / Crush / Qwen	`WARP.md / CRUSH.md / QWEN.md`	3.2K / 382 / —
Junie	`.junie/ (e.g. .junie/guidelines.md)`	2.0K
Kilo Code / OpenCode	`.kilocode/ / .opencode/ opencode.json`	1.8K / 1.6K
SpecKit	`.specify/memory/constitution.md`	1.6K
Augment / Continue	`.augment/ / .continue/`	1.4K / 1.0K
Aider	`.aider.conf.yml .aiderignore`	422
Others	`.openhands/ .goosehints .amazonq/ .factory/ .devin/ .jules/`	small

Tip: the date a file was first added (`git log --diff-filter=A -- CLAUDE.md`) is a good estimate of when the repo adopted that agent.

7. Traps that cause false positives

Trap	What to do
Brand words in normal text	“Fix cursor position”, “claude.md” in a docs path, a login like osman-haider (contains “aider”). Only match the exact trailer, email, login or prefix. This was the main error source when we ran detection on a 185-repo corpus.
Name says one tool, email says another	Co-Authored-By: Kimi = Claude Code with the Kimi model. Many tools let users pick the model, so the name is unreliable.
People typing agent identities by hand	Kilo, Roo Code, Goose and Cascade appear with made-up emails (kilo@example.com). Count only the addresses in Sections 1-2; treat others as “unsure”.
VS Code's Copilot co-author bug	In VS Code 1.117-1.118 (late April to early May 2026) “Co-authored-by: Copilot” (id 223556219) was on by default and was added even to human-written code. Treat that trailer in that window as unreliable.
AGENTS.md is generic	It started with Codex but is now read by dozens of agents. It shows “some agent”, not which one.
CONVENTIONS.md	Aider recommends it, but most projects use it for human conventions. Robbes et al. dropped it; so should you.
Spoofed bot names	We saw “claude[bot]” commits whose email carried github-actions' id (41898282). Check that the id matches Section 4.
Squash merges	A squash commit keeps only the PR's last author, so a human PR can look like Copilot's and vice versa. Use the PR's own label.
Outsider PRs	An agent PR from a stranger (even spam) is not adoption by the project. Count merged agent PRs separately.
Ignored agent files	About 20% of projects with agent files keep them out of git with .gitignore (Robbes et al.). A .gitignore entry like CLAUDE.md is itself a sign.

How good are these rules? Robbes et al. checked about 400 commits, 400 files and 400 PRs by hand: false positives were 0.5-1% (commits 2%, PRs 0.25%), plus about 3% borderline cases. The misses are bigger than the false alarms, so report adoption as a minimum.

8. Edit velocity

Edit velocity catches big changes made in very little time, which is typical of agents. It is a **feature for the classifier**, not proof on its own.

> **edit velocity = (lines added + lines deleted) ÷ seconds since the same author's previous commit**

Step by step

1. **Get every commit with its line counts:** `git log --numstat --format=%H|%ae|%aI|%P`.
2. **Lines changed** = sum of added + deleted over all files. Binary files show "-": count them as 0.
3. **Group by author email** (lowercase), then sort each author's commits by **author date**.
4. **Seconds since previous** = this commit's author date − the same author's previous author date. The author's first commit has no previous one: leave its velocity empty. Skip gaps of 0 or less.
5. **Divide** lines changed by those seconds.
6. **Leave out** commits whose speed means nothing (table below). Keep the number, but don't rank them.
7. **Flag the fastest 5%**: velocity at or above the 95th percentile of the remaining commits.

Worked example (one author, Alice)

Commit	Author date	Added / deleted	Seconds since previous	Velocity (lines/s)	Result
A	10:00:00	+20 / −5	— (first commit)	—	No value
B	10:30:00	+120 / −30	1,800	150 ÷ 1,800 = 0.08	Normal
C	10:31:30	+600 / −0	90	600 ÷ 90 = 6.67	Likely top 5%
D	10:33:00	+2,000 / −0 (package-lock.json)	90	22.2	Left out: lockfile

Commit C added 600 lines 90 seconds after B, far faster than a person types: exactly what the flag is for. Commit D is faster still, but it is a regenerated lockfile, so it is left out.

What to leave out of the ranking

Commit type	How to spot it	Why
Merge commits	2 or more parents	git shows no line counts for them.
Squash merges	The commit GitHub made when squash-merging a PR (title ends with (#N), one parent)	Days of PR work collapsed into one commit.
Mechanical diffs	Only lockfiles changed (package-lock.json, yarn.lock, poetry.lock, Cargo.lock, ...)	Generated, not written.
Bulk reformatting (optional)	e.g. a formatter or license-header run over many files	Huge but not authored. Hard to detect automatically.
Automation bots	dependabot[bot], renovate[bot], ...	Not a person or a coding agent.

Tips and pitfalls

- **Use the author date, not the committer date.** Rebases and squash merges reset the committer date to the merge time.
- **Use timezone-aware dates.** Git dates carry an offset (+02:00); compare them as real times.
- **Tiny gaps blow up.** Two commits 1 second apart give huge values. Consider a minimum gap (e.g. 60 s) or use log(velocity) in the model.
- **Long gaps shrink it.** After a weekend, velocity is near 0; that is fine, it just won't be flagged.
- **Per repo or whole corpus?** The 95th percentile can be calculated per repo (fast for that project) or across the corpus (fast overall). Pick one, write it down, and keep it the same.
- **Agent-authored commits** (author = Copilot, Cursor Agent, ...) form their own "author" group, so their gaps measure the agent's pace, not the human's.

- **Never use the label in the features.** Remove trailers and “Generated with” lines before computing message features, or the model just relearns the label.

Minimal Python

```
import subprocess, collections, datetime as dt
raw = subprocess.run(["git", "log", "--numstat", "--format=@%H|%ae|%aI|%P"],
                     capture_output=True, text=True, encoding="utf-8").stdout
commits, cur = [], None
for line in raw.splitlines():
    if line.startswith("@"):
        sha, email, date, parents = line[1:].split("|")
        cur = dict(sha=sha, email=email.lower(), date=dt.datetime.fromisoformat(date),
                   merge=len(parents.split()) > 1, lines=0)
        commits.append(cur)
    elif line.strip():
        add, dele, _ = line.split("\t", 2)
        cur["lines"] += (int(add) if add.isdigit() else 0) + (int(dele) if dele.isdigit() else 0)
by_author = collections.defaultdict(list)
for c in commits:
    by_author[c["email"]].append(c)
for cs in by_author.values():
    cs.sort(key=lambda c: c["date"])
    for prev, c in zip(cs, cs[1:]):
        gap = (c["date"] - prev["date"]).total_seconds()
        c["velocity"] = c["lines"] / gap if gap > 0 and not c["merge"] else None
```

Sources

- Robbes, Matricon, Degueule, Hora, Zacchiroli. Agentic Much? Adoption of Coding Agents on GitHub. ACM TOSEM, 2026. arXiv:2601.18341. Data: zenodo.org/records/19256968; code: github.com/labri-progress/agent-impact.
- Robbes et al. Promises, Perils, and (Timely) Heuristics for Mining Coding Agent Activity. MSR 2026. arXiv:2601.18345 (Table 1: heuristics and match counts, 20 Oct 2025).
- GitHub commit, PR and code search, run by us on 24 October 2026, for every trace in Sections 1-5 (counts are GitHub's approximate totals).
- Aider documentation, Git integration (aider.chat/docs/git.html): (aider) name suffix, --attribute-co-authored-by, aider: prefix.
- GitHub changelog, 20 March 2026: Trace any Copilot coding agent commit to its session logs (Agent-Logs-Url).
- Cursor forum (staff replies, 2026): cloud agents commit as Cursor Agent, cursor/ branch prefix, Made-with: Cursor trailer.
- Linux kernel documentation, AI Coding Assistants (docs.kernel.org/process/coding-assistants.html): Assisted-by: AGENT_NAME:MODEL_VERSION.
- VS Code git.addAICoAuthor default changes, versions 1.117-1.119 (heise, The Register, VS Code issue 314311), April-May 2026.

Traces change often. These lists were checked on 24 October 2026; re-run the GitHub searches before a new study.