
# Daniel Tilley - C1437041 - Design Document

The dataset for this assignment is based on Airplane crashes. In oracle, the tables are laid out as follows:



## **Designs**

There are 2 design options I am going to implement. The first is just a straight data dump with no formatting and the second will make use of embedding.

### Simple Design:

```
db.createCollection(simpleFormat, {
FlightNumber: <number>,
FlightRoute: <string>,
FlightOperator: <string>,
NumAboardFlight: <number>,
CrashDate: <string>,
CrashTime: <string>,
CrashLocation: <string>,
DeathsInAir: < number>,
DeathsOnGround: <number>,
PlaneType: <string>,
PlaneReg: <string>,
PlaneCNIN: <string>})
Embedded Design: (Uses flight as a first reference)
db.createCollection(embeddedFormat, {
Number: <number>,
Route: <string>,
Operator: <string>,
NumAboard: <number>,
Plane: [{
              Type: <string>,
              PlaneReg: <string>,
              PlaneCNIN: <string>
       }],
Crash: [{
              Date: <string>,
              Time: <string>,
              Location: <string>,
              Deaths: [{
                     InAir: <number>,
                     OnGround: <number>
              }],
       }]
})
```

#### Creates

I have attached two files which have been generated using PL/Sql. One is for the simple layout (simpleLayoutOutput.txt) and the other is for the embedded layout (embeddedLayoutOutput.txt). In both files, you will find the PL/Sql used to generate the file and the creates for mongoDB.

# Queries on simple collection

```
db.simpleFormat.find()
Find certain airline
db.simpleFormat.find({ FlightOperator: "Air France" })
Sort by amount of deaths in air
db.simpleFormat.find().sort( { DeathsInAir: -1 } )
Aggregate function. Sum number of deaths in air and filter by airline
db.simpleFormat.aggregate([
       { $match: { FlightOperator: "Air France" }},
       { $group: { _id: "$ObjectId", DeathsInAir: { $sum: "$DeathsInAir" } } },
])
Update function
db.simpleFormat.update({"FlightNumber": 1},{$set:{"DeathsInAir": 2}})
                          Queries on embedded collection
Find all
db.embeddedFormat.find()
Find certain airline
db.embeddedFormat.find({ Operator: "Military - U.S. Air Force" })
Sort by amount of deaths on ground
db.embeddedFormat.find().sort( { "Crash.Deaths.OnGround": -1 } )
```

Find all

# Aggregate function. Sum number crashes by airline