


Uninformed Search

Uninformed search strategies

- **Uninformed** search strategies use only the information available in the problem definition
 - Breadth-first search
 - Uniform-cost search
 - Depth-first search
 - Depth-limited search
 - Iterative deepening search


Breadth-first search

- Expand shallowest unexpanded node
- Implementation:
 - *fringe* is a FIFO queue, i.e., new successors go at end




Breadth-first search

- Expand shallowest unexpanded node
- Implementation:
 - *fringe* is a FIFO queue, i.e., new successors go at end




Breadth-first search

- Expand shallowest unexpanded node
- Implementation:
 - *fringe* is a FIFO queue, i.e., new successors go at end



Breadth-first search

- Expand shallowest unexpanded node
- Implementation:
 - *fringe* is a FIFO queue, i.e., new successors go at end



Properties of breadth-first search

- ❑ Complete? Yes (if b is finite)
- ❑ Time? $1+b+b^2+b^3+\dots +b^d + b(b^d-1) = O(b^{d+1})$
- ❑ Space? $O(b^{d+1})$ (keeps every node in memory)
- ❑ Optimal? Yes (if cost = 1 per step)

Space is the bigger problem (more than time)

Each state has b successors (branching factor)
 d is the shallower depth


Uniform-cost search

- ❑ Expand least-cost unexpanded node
- ❑ **Implementation:**
 - *fringe* = queue ordered by path cost
- ❑ Equivalent to breadth-first if step costs all equal
- ❑ Complete? Yes, if step cost $\geq \epsilon$
- ❑ Time? # of nodes with $g \leq$ cost of optimal solution, $O(b^{\text{ceiling}(C^*/\epsilon)})$ where C^* is the cost of the optimal solution
- ❑ Space? # of nodes with $g \leq$ cost of optimal solution, $O(b^{\text{ceiling}(C^*/\epsilon)})$
- ❑ Optimal? Yes – nodes expanded in increasing order of $g(n)$

If all costs are equal $\rightarrow O(b^d)$


Depth-first search

- Expand deepest unexpanded node
- **Implementation:**
 - *fringe* = LIFO queue, i.e., put successors at front




Depth-first search

- Expand deepest unexpanded node
- **Implementation:**
 - *fringe* = LIFO queue, i.e., put successors at front




Depth-first search

- Expand deepest unexpanded node
- **Implementation:**
 - *fringe* = LIFO queue, i.e., put successors at front




Depth-first search

- Expand deepest unexpanded node
- **Implementation:**
 - *fringe* = LIFO queue, i.e., put successors at front




Depth-first search

- Expand deepest unexpanded node
- **Implementation:**
 - *fringe* = LIFO queue, i.e., put successors at front




Depth-first search

- Expand deepest unexpanded node
- **Implementation:**
 - *fringe* = LIFO queue, i.e., put successors at front




Depth-first search

- Expand deepest unexpanded node
- **Implementation:**
 - *fringe* = LIFO queue, i.e., put successors at front




Depth-first search

- Expand deepest unexpanded node
- **Implementation:**
 - *fringe* = LIFO queue, i.e., put successors at front




Depth-first search

- Expand deepest unexpanded node
- **Implementation:**
 - *fringe* = LIFO queue, i.e., put successors at front




Depth-first search

- Expand deepest unexpanded node
- **Implementation:**
 - *fringe* = LIFO queue, i.e., put successors at front



Depth-first search

- Expand deepest unexpanded node
- **Implementation:**
 - *fringe* = LIFO queue, i.e., put successors at front



Properties of depth-first search

- Complete? No: fails in infinite-depth spaces, spaces with loops
 - Modify to avoid repeated states along path
→ complete in finite spaces
- Time? $O(b^m)$: terrible if m is much larger than d
 - but if solutions are dense, may be much faster than breadth-first
- Space? $O(bm)$
- Optimal? No

Depth-limited search

□ = depth-first search with depth limit l ,
i.e., nodes at depth l have no successor

Iterative deepening search / =0

Limit = 0




Iterative deepening search / =1

Limit = 1




Iterative deepening search / =2

Limit = 2



Iterative deepening search / =3

Limit = 3



Iterative deepening search

- Number of nodes generated in a depth-limited search to depth d with branching factor b :

$$N_{DLS} = b^0 + b^1 + b^2 + \dots + b^{d-2} + b^{d-1} + b^d$$

- Number of nodes generated in an iterative deepening search to depth d with branching factor b :

$$N_{IDS} = (d+1)b^0 + d b^1 + (d-1)b^2 + \dots + 3b^{d-2} + 2b^{d-1} + 1b^d$$

- For $b = 10$, $d = 5$,

- $N_{DLS} = 1 + 10 + 100 + 1,000 + 10,000 + 100,000 = 111,111$

- $N_{IDS} = 6 + 50 + 400 + 3,000 + 20,000 + 100,000 = 123,456$

- Overhead = $(123,456 - 111,111)/111,111 = 11\%$

Properties of iterative deepening search

- Complete? Yes
- Time? $(d+1)b^0 + d b^1 + (d-1)b^2 + \dots + b^d = O(b^d)$
- Space? $O(bd)$
- Optimal? Yes, if step cost = 1

Summary of algorithms

Criterion	Breadth-First	Uniform-Cost	Depth-First	Depth-Limited	Iterative Deepening
Complete?	Yes	Yes	No	No	Yes
Time	$O(b^{d+1})$	$O(b^{\lceil C^*/\epsilon \rceil})$	$O(b^m)$	$O(b^l)$	$O(b^d)$
Space	$O(b^{d+1})$	$O(b^{\lceil C^*/\epsilon \rceil})$	$O(bm)$	$O(bl)$	$O(bd)$
Optimal?	Yes	Yes	No	No	Yes

Repeated states

- ❑ Failure to detect repeated states can turn a linear problem into an exponential one!

