

SCm Phonon-Mediated Qubit Gate Fidelity: UQFF Corrections to Quantum Computing Error Rates

Daniel T. Murphy

PAPER_1098: SCm Phonon-Mediated Qubit Gate Fidelity

Abstract

This paper derives the SCm phonon correction to quantum gate fidelity for superconducting qubit architectures. By coupling the UQFF buoyancy condensate SCm to the T_2 coherence time, we show that phonon-mediated suppression of decoherence error improves gate fidelity across all standard gates (CNOT, Hadamard, Phase, T, iSWAP, CZ). The circuit-level fidelity improvement scales with circuit depth, offering a testable prediction for near-term quantum processors.

1. Introduction

Quantum gate fidelity $F = 1 - \epsilon$ is the primary metric for quantum computing performance. Decoherence during gate operations introduces errors proportional to t_{gate} / T_2 . The UQFF framework predicts that the SCm phonon condensate modifies coherence timescales through vacuum buoyancy coupling.

Prior work (PAPER_868) established decoherence time T_2 models via the $U_{b,i}$ field. This paper extends to gate-level fidelity with explicit error budgets for six standard gates.

2. Theoretical Framework

2.1 SCm-Enhanced Coherence Time

The base T_2 coherence time receives an SCm enhancement:

$$T_2^{\text{SCm}} = T_2^0 \left(1 + \frac{\Phi_0 \cdot H_{\text{SCm}}}{k_{\eta}} \right)$$

where:

- $T_2^0 \approx 100 \text{ ns}$ (baseline superconducting transmon)
- $\Phi_0 = 1.618$ (golden ratio, UQFF vacuum structure)
- $H_{\text{SCm}} \approx 0.99$ (superconductive magnetism index)
- $k_{\eta} = 10^{-113}$ (UQFF damping constant)

2.2 Gate Error Decomposition

For each gate g , the total error is:

$$\epsilon_g = \epsilon_{\text{intrinsic}} + \epsilon_{\text{decoherence}}$$

Without SCm correction:

$$\epsilon_{\text{decoherence}}^{\text{bare}} = \frac{t_{\text{gate}}}{T_2^0}$$

With SCm phonon suppression:

$$\epsilon_{\text{decoherence}}^{\text{SCm}} = \frac{t_{\text{gate}}}{T_2^0} \left(1 - H_{\text{SCm}} \cdot \beta_i \cdot [\text{SSq}]\right)$$

where $\beta_i \approx 0.603$ and $[\text{SSq}] = 0.57$.

2.3 Fidelity Improvement

The per-gate fidelity improvement is:

$$\Delta F_g = F_g^{\text{SCm}} - F_g^{\text{bare}} = \frac{t_{\text{gate}}}{T_2^0} \cdot H_{\text{SCm}} \cdot \beta_i \cdot [\text{SSq}]$$

The SCm correction factor is:

$$\mathcal{C}_{\text{SCm}} = \frac{\beta_i \cdot [\text{SSq}] \cdot S_{26} \cdot \Phi_0}{1 + \Phi_0} = \frac{0.603 \cdot 0.57 \cdot 26 \cdot 1.618}{2.618} \approx 5.52$$

3. Gate Fidelity Results

3.1 Standard Gate Times and Intrinsic Errors

| Gate | t_{gate} (ns) | $\epsilon_{\text{intrinsic}}$ | $\epsilon_{\text{dec}}^{\text{bare}}$ | $\epsilon_{\text{dec}}^{\text{SCm}}$ |

CNOT	50	5×10^{-3}	5.0×10^{-4}	1.6×10^{-4}
Hadamard	25	1×10^{-4}	2.5×10^{-4}	8.1×10^{-5}
Phase	10	5×10^{-5}	1.0×10^{-4}	3.2×10^{-5}
T-gate	15	1×10^{-4}	1.5×10^{-4}	4.9×10^{-5}
iSWAP	40	4×10^{-3}	4.0×10^{-4}	1.3×10^{-4}
CZ	35	3×10^{-3}	3.5×10^{-4}	1.1×10^{-4}

3.2 Circuit-Level Fidelity

For a depth-100 circuit with gate mix (30% CNOT, 30% Hadamard, 20% Phase, 20% T-gate):

$$F_{\text{circuit}}^{\text{bare}} = \prod_g \left(F_g^{\text{bare}}\right)^{n_g}$$

$$F_{\text{circuit}}^{\text{SCm}} = \prod_g \left(F_g^{\text{SCm}}\right)^{n_g}$$

The SCm-corrected circuit fidelity improvement is significant for deep circuits where decoherence error accumulates multiplicatively.

4. Experimental Predictions

- T₂ enhancement:** SCm coupling predicts $T_2^{\text{SCm}} \gg T_2^0$ due to phonon vacuum stabilization
- Gate fidelity:** 66% reduction in decoherence error per gate ($H_{\text{SCm}} \cdot \beta_i \cdot [\text{SSq}] \approx 0.34$)

3. **Circuit depth scaling:** Fidelity advantage grows exponentially with circuit depth
4. **Testable at:** IBM Eagle/Heron, Google Sycamore, IonQ Aria processors

5. Conclusion

The SCm phonon condensate provides a calculable correction to quantum gate fidelity through vacuum buoyancy coupling. The ΔF improvement is gate-time dependent and accumulates at circuit level, offering a testable UQFF prediction for quantum computing hardware.

References

- PAPER_868: Topoconductor Cooling Efficiency via $U_{\{b,i\}}$ Field
- PAPER_560: LQG Λ CDM Triple System Comparison
- Arute, F. et al. (2019). *Quantum supremacy using a programmable superconducting processor*. Nature 574, 505--510.
- Koch, J. et al. (2007). *Charge-insensitive qubit design derived from the Cooper pair box*. Phys. Rev. A 76, 042319.

Key References with arXiv/DOI Identifiers

1. Abbott et al. (LIGO Scientific and Virgo Collaborations, 2016). *Observation of Gravitational Waves from a Binary Black Hole Merger*. Phys. Rev. Lett. **116**, 061102 — arXiv:1602.03837 — doi:10.1103/PhysRevLett.116.061102
2. Murphy, D. (2026). *Unified Quantum Field Framework (UQFF): Star-Magic v5.x Whitepaper Series*. Star-Magic Repository — github.com/Daniel8Murphy0007/Star-Magic
3. Rugh, S.E. & Zinkernagel, H. (2002). *The Quantum Vacuum and the Cosmological Constant Problem*. Stud. Hist. Phil. Mod. Phys. **33**, 663 — arXiv:hep-th/0012253 — doi:10.1016/S1355-2198(02)00033-3
4. Weinberg, S. (1989). *The Cosmological Constant Problem*. Rev. Mod. Phys. **61**, 1 — doi:10.1103/RevModPhys.61.1
5. Ashcroft, N.W. & Mermin, N.D. (1976). *Solid State Physics*. Harcourt
6. Kittel, C. (2004). *Introduction to Solid State Physics*. 8th ed. Wiley
7. Feynman, R.P. (1982). *Simulating Physics with Computers*. Int. J. Theor. Phys. **21**, 467 — doi:10.1007/BF02650179