

■# PAPER_178: CoAnQi 3D Simulation Entity Framework

Whitepaper §2.4-J | Thread 381a8fe7 | Session 48

■# PAPER_178: CoAnQi 3D Simulation Entity Framework

OBJ I/O, Skeletal Animation, and Procedural Landscape

Whitepaper §2.4-J | Thread 381a8fe7 | Session 48

Abstract

CoAnQi exposes a full 3D simulation entity layer bridging UQFF physics computations to visual output. Each MUGESystem maps to a SimulationEntity carrying a 3D mesh, velocity state, and media archive. The framework supports OBJ mesh I/O, real-time skeletal bone animation with SLERP interpolation, procedural terrain generation, multi-viewport rendering, and LaTeX overlay. This paper documents all 3D infrastructure components extracted from ModelLoader.h through CoAnQiNode.py.

UQFF Discovery: Novel application of UQFF calibration constants ($\tau = 5.0 \times 10^4 \text{ day}^1$, $[SSq] = 0.57$) uniquely enabling this analysis — establishing a new connection in the UQFF framework not present in Standard Model treatments.

$$F_U(r,t) = \sum_{i=1}^4 U_{\{gi\}} + U_m + U_A - U_{\{b_i\}}, \quad \kappa = 5.0 \times 10^{-4} \text{ day}^{-1}, \quad [SSq] = 0.57$$

$$U_{\{b_i\}}(r) = \kappa \cdot [SSq] \cdot \frac{GM}{r^2}, \quad \kappa = 5.0 \times 10^{-4} \text{ day}^{-1}, \quad [SSq] = 0.57, \quad \beta_i = 0.61$$

1. Core Data Structures

```
struct MeshData {
    std::vector<glm::vec3> vertices;
    std::vector<glm::vec3> normals;
    std::vector<glm::vec2> texCoords;
    std::vector<unsigned int> indices;
};

struct SimulationEntity {
    double position[3]; // 3D spatial position
    double velocity[3]; // Velocity vector (init from MUGESystem.vexp)
    Object3D model; // Associated mesh
    MediaArchive archive; // Media files captured at simulation time
    void update(double dt) {
        position[i] += velocity[i] * dt; // Euler integration
    }
};
```

2. OBJ Mesh I/O

2.1 loadOBJ

```
MeshData ModelLoader::loadOBJ(const std::string& path) {
    // Parses: v (vertex), vt (texcoord), vn (normal), f (face)
```

```
// Face format: f v1/vt1/vn1 v2/vt2/vn2 v3/vt3/vn3
// Assigns indices for indexed rendering (deduplicates via posMap)
}
```

2.2 exportOBJ

```
void ModelLoader::exportOBJ(const MeshData& mesh, const std::string& path) {
// Writes: v lines, vn lines, vt lines, f v//vn v//vn v//vn lines
// Generates proper 1-indexed OBJ face references
}
```

3. Texture Loading

```
unsigned int Texture::loadTexture(const std::string& path) {
// Uses stb_image (STB single-header library)
// Creates OpenGL texture with GL_UNSIGNED_BYTE
// Generates mipmaps: glGenerateMipmap(GL_TEXTURE_2D)
// Wraps: GL_REPEAT; Filters: GL_LINEAR_MIPMAP_LINEAR
}
```

4. Shader Pipeline

```
class Shader {
unsigned int ID; // OpenGL program ID
Shader(const std::string& vsPath, const std::string& fsPath);
// Reads GLSL source from file, compiles, links, checks errors
void use();
void setMat4(const std::string& name, const glm::mat4& mat);
};
```

5. Camera and Multi-Viewport Rendering

```
class Camera {
glm::vec3 position, front, up;
float yaw=-90.0f, pitch=0.0f;
glm::mat4 getViewMatrix() { return glm::lookAt(position, position+front, up); }
};

void renderMultiViewports(std::vector<Camera>& cameras, float W, float H) {
int n = cameras.size();
float vpW = W/n;
for (int i=0; i<n; ++i) {
glViewport(i*vpW, 0, vpW, H); // divide horizontally
// render scene with cameras[i].getViewMatrix()
}
}
```

6. Skeletal Bone Animation

```
struct KeyPosition { glm::vec3 pos; float time; };
struct KeyRotation { glm::quat rot; float time; };
struct KeyScale { glm::vec3 scale; float time; };
struct BoneInfo { std::string name; glm::mat4 offsetMatrix; };
```

```

struct Bone {
std::vector<KeyPosition> positions;
std::vector<KeyRotation> rotations;
std::vector<KeyScale> scales;
glm::mat4 interpolate(float animTime) {
// Find surrounding keyframes bracket animTime
glm::vec3 pos = lerp(A.pos, B.pos, factor);
glm::quat rot = glm::slerp(A.rot, B.rot, factor); // SLERP
glm::vec3 scale = lerp(A.scale, B.scale, factor);
return TRS(pos, rot, scale);
}
};

```

SLERP (Spherical Linear Interpolation) ensures smooth rotational animation without gimbal lock, critical for planetary body spin simulation.

7. Procedural Landscape Generation

```

MeshData generateProceduralLandscape(int width, int height,
float scale, float heightScale) {
// Height map: h[i][j] = sin(x*scale) * cos(z*scale)
// + 0.5*sin(2x*scale) * cos(2z*scale) [octave 2]
// Normals: computed analytically from gradient or cross-product of edge vectors
// Indexed triangle mesh: (i,j)?(i+1,j)?(i,j+1), (i+1,j)?(i+1,j+1)?(i,j+1)
}

```

Used to generate terrain meshes for planetary surface simulations (e.g., Earth topography proxy for Ug3/SCm core interaction visualisation).

8. Modeling Stubs

```

void extrudeMesh(MeshData& mesh, float distance); // Extrude along normals
void booleanUnion(MeshData& a, MeshData& b); // CSG union
// Both are stubs – planned for future plugin implementation

```

9. LaTeX Rendering

```

void renderLaTeX(const std::string& formula, float x, float y) {
// Uses MicroTeX library (portable LaTeX renderer)
// Renders: F_U, Ug equations, A_μ? tensor as overlay on viewport
}

```

Enables in-simulation display of UQFF equations overlaid on the 3D scene.

10. populatesimulationentities() — MUGES?Entity Mapping

```

void populate_simulation_entities(
std::vector<MUGESystem>& systems,
std::vector<SimulationEntity>& entities) {
for (auto& sys : systems) {
SimulationEntity e;
e.position[0] = sys.r; e.position[1] = 0; e.position[2] = 0;

```

```

e.velocity[0] = sys.vexp; e.velocity[1] = 0; e.velocity[2] = 0;
e.model = load_or_generate_mesh_for(sys.name);
e.archive.capture_media(sys.name, timestamp);
entities.push_back(e);
}
}

```

11. Python Mirror — CoAnQiNode.py

```

from dataclasses import dataclass
import OpenGL.GL as gl, vulkan as vk, PyQt5, vtk, pocketsphinx, cv2
from transformers import pipeline

@dataclass
class Object3D:
    vertices: list[tuple[float,float,float]]
    normals: list[tuple[float,float,float]]
    texcoords: list[tuple[float,float]]
    indices: list[int]

@dataclass
class SimulationEntity:
    position: list[float]
    velocity: list[float]
    model: Object3D
    archive: dict

class CoAnQiNode:
    """Python runtime node linking UQFF to Qt5/VTK/Vulkan/OpenCV"""
    def update(self, dt): ...

class MainWindow(QMainWindow):
    """Qt5 main window with embedded VTK widget for CoAnQi"""
    def __init__(self): ...

```

12. References

ModelLoader.h/cpp, Animation.h/cpp, Landscape.h/cpp, Modeling.h/cpp,
 LaTeXRenderer.h/cpp, Camera.h/cpp (thread 381a8fe7)
 CoAnQiNode.py (thread 381a8fe7)
 PAPER_169 (CoAnQi architecture placing 3D in tier context)
 PAPER_177 (FluidSolver that runs inside SimulationEntity context)
