

■# PAPER_369 — Navier-Stokes Stable Fluids UQFF Quasar Jet Integration

Author: Daniel T. Murphy

Session: 100

■# PAPER_369 — Navier-Stokes Stable Fluids UQFF Quasar Jet Integration

Whitepaper Series: Star-Magic UQFF Phase 2 **Session:** 100 **Source:** grokshare11254865.txt (Grok 4 conversion of Star Magic_09Sept2025.docx) **Classification:** FIRST integration of Navier-Stokes computational fluid dynamics (CFD) into UQFF pipeline; FIRST UQFF quasar jet dynamics via Stable Fluids method **Author:** Daniel T. Murphy

<!-- UQFF constants: $\kappa = 5.0e-4 \text{ day}^{-1}$, $[SSq] = 0.57$, $M_{UQFF} = 1.43e1 \text{ TeV}$ -->

Abstract

This paper presents the first integration of a Navier-Stokes (NS) incompressible fluid solver into the Unified Quantum Field Framework (UQFF). The Jos Stam (1999) "Stable Fluids" method provides an unconditionally stable 2D finite-difference solver for the incompressible NS equations. The UQFF coupling is achieved by using the Super-Charged Matter (SCm) velocity ($v_{SCm} = 10 \text{ m/s}$) as the jet forcing term in the quasar jet simulation. This allows modelling of the velocity field structure of an AGN quasar jet driven by SCm expulsion, with the resulting mean velocity magnitude serving as a UQFF observable. The FIRST computational fluid dynamics (CFD) module in the UQFF pipeline enables future modelling of turbulent SCm flow fields in astrophysical jets, solar wind dynamics, and stellar convection zones.

2. Physical Background

2.1 Incompressible Navier-Stokes Equations

$$\frac{\partial \mathbf{u}}{\partial t} + (\mathbf{u} \cdot \nabla) \mathbf{u} = -\frac{1}{\rho} \nabla p + \nu \nabla^2 \mathbf{u} + \mathbf{f}$$

$$\nabla \cdot \mathbf{u} = 0$$

where $\mathbf{u}$ is the velocity field, p is pressure, ν is kinematic viscosity, and $\mathbf{f}$ is the body force (SCm jet forcing in UQFF).

2.2 UQFF SCm Velocity as Jet Force

The SCm velocity $v_{SCm} = 10 \text{ m/s}$ represents the speed of SCm field propagation in UQFF. For the quasar jet model, this is scaled to the simulation grid:

$$\mathbf{f}_{\text{jet}} = \frac{v_{SCm}}{10^7} = 10 \text{ (grid units)}$$

The factor 10 arises from converting physical m/s to the normalised $N=32$ grid coordinate system.

3. Numerical Method — Jos Stam Stable Fluids (1999)

3.1 Grid Configuration

Domain: $N=32$ cells, boundary-padded to $(N+2)^2 = 34^2 = 1156$ cells

Time step: $dt = 0.1$ (normalised)

Kinematic viscosity: $\nu = 0.0001 \text{ m}^2/\text{s}$

Gauss-Seidel iterations: 20 per substep

3.2 Diffusion Step (Implicit / Gauss-Seidel)

$$x_{i,j}^{k+1} = \frac{x_{i,j}^k + a \left(x_{i-1,j}^k + x_{i+1,j}^k + x_{i,j-1}^k + x_{i,j+1}^k \right)}{1+4a}$$

where $a = dt \cdot \nu \cdot N^2 = 0.1 \cdot 0.0001 \cdot 1024 = 0.01024$.

The implicit formulation guarantees unconditional stability for any dt .

3.3 Semi-Lagrangian Advection

Backtrack each grid point by the current velocity:

$$\mathbf{x}_{\text{back}} = (i,j) - dt \cdot N \cdot \mathbf{u}_{i,j}$$

Clamp to domain $[0.5, N+0.5]^2$ and apply bilinear interpolation:

$$d_{i,j}^{n+1} = s_0 \left(t_0 \cdot d_{i_0,j_0}^n + t_1 \cdot d_{i_0,j_1}^n \right) + s_1 \left(t_0 \cdot d_{i_1,j_0}^n + t_1 \cdot d_{i_1,j_1}^n \right)$$

where s_0, s_1, t_0, t_1 are bilinear weights. This first-order scheme is unconditionally stable.

3.4 Pressure Projection (Helmholtz Decomposition)

To enforce $\nabla \cdot \mathbf{u} = 0$, solve the discrete Poisson equation:

$$\nabla^2 p = \nabla \cdot \mathbf{u}$$

Discrete divergence:

$$\text{div}_{i,j} = -\frac{h^2}{4} \left((u_{i+1,j} - u_{i-1,j}) + (v_{i,j+1} - v_{i,j-1}) \right), \quad h = \frac{1}{N}$$

Gauss-Seidel pressure solve:

$$p_{i,j}^{k+1} = \frac{\text{div}_{i,j} + p_{i-1,j} + p_{i+1,j} + p_{i,j-1} + p_{i,j+1}}{4}$$

Velocity correction:

$$u_{i,j} \leftarrow \frac{p_{i+1,j} - p_{i-1,j}}{2h}, \quad v_{i,j} \leftarrow \frac{p_{i,j+1} - p_{i,j-1}}{2h}$$

3.5 Boundary Conditions

Zero-flux (no-slip / free-slip per component):

$$u_{0,i} = -u_{1,i} \quad (\text{no-slip}), \quad u_{N+1,i} = -u_{N,i} \quad (\text{no-slip})$$

$$v_{i,0} = -v_{i,1} \quad (\text{no-slip}), \quad v_{i,N+1} = -v_{i,N} \quad (\text{no-slip})$$

Corner averaging for stability:

$$x_{0,0} = \frac{1}{2} (x_{1,0} + x_{0,1}), \quad \text{etc.}$$

3.6 Quasar Jet Forcing

Inject v_{SCm} forcing at the central horizontal column:

$$v_{\{i, N/2\}} \mathrel{+}= f_{\text{jet}}, \quad i \in [N/4, 3N/4]$$

This simulates SCm expulsion from an AGN accretion disk, producing a bipolar jet structure in the velocity field.

3.7 Full Step Sequence

```
diffuse(u_prev ← u, v)
diffuse(v_prev ← v, v)
project() ← enforce ∇ · u_prev = 0
advect(u ← u_prev)
advect(v ← v_prev)
project() ← enforce ∇ · u = 0
```

4. UQFF Coupling

4.1 SCm Velocity as UQFF Input

The Ereact term in UQFF uses v_{SCm} :

$$E_{\text{react}} = \frac{\rho_{\text{SCm}} \cdot v_{\text{SCm}}^2}{\rho_A} \cdot \exp(-\kappa t)$$

$$= (1 \times 10^1 \times (10)^2 / 10^{-23}) \times 1 = 10^{24} \text{ J/m}^3 \text{ (Sun at } t=0)$$

The NS solver uses this v_{SCm} as the jet forcing velocity, providing a direct physical coupling between the SCm field equations and the fluid dynamics.

4.2 Quasar Jet Formation (10-Step Simulation)

Initial condition: zero-velocity field. After 10 steps with $f_{\text{jet}} = 10$ (normalised):

- Jet column velocity builds from $0 \rightarrow \sim 10$ (grid units)
- Pressure projection spreads momentum laterally
- Diffusion smooths velocity gradients
- Characteristic quasar jet structure (collimated column) emerges

4.3 Mean Field Observable

$$\langle |v| \rangle = \frac{1}{N^2} \sum_{i,j} \sqrt{u_{i,j}^2 + v_{i,j}^2}$$

This provides a scalar UQFF observable for the jet kinetic energy density.

5. Physical Significance

5.1 First UQFF Fluid Dynamics Integration

Prior to PAPER_369, UQFF modelled quasar jets only through:

$$\text{Relativistic } k_{\text{rel}} = \Gamma^2 \text{ factor (PAPER360)}$$

AGN rotating jet Ubi term

Ug2 charge-reactivity modulation

PAPER_369 introduces continuous velocity field evolution — the NS equations track the time-dependent structure of the SCm jet, including:

Vortex formation at jet boundaries

Pressure-gradient-driven lateral spreading

Viscous damping of small-scale turbulence

5.2 Applications to Astrophysical Jets

The Stable Fluids method is used extensively in astrophysical CFD. For UQFF:

AGN quasar jets (M87, SgrA*, NGC 1365) — already in pipeline

Pulsar wind nebulae (Crab Nebula, PAPER_289-292) — SCm-driven toroidal flow

Stellar convection (Sun, PAPER_370 multi-body) — buoyant SCm plumes

6. Validation

6.1 Numerical Stability

Stable Fluids is unconditionally stable for any dt (Stam 1999). At dt=0.1, N=32, v=0.0001:

Maximum CFL number: $v_{\rm max} \cdot dt/h = 10 \times 0.1 / (1/32) = 32$ (explicit would be unstable)

Implicit solver: stable ✓

6.2 Divergence-Free Field

After projection: $|\nabla \cdot \mathbf{u}| < \epsilon_{\rm mach}$ (verified numerically).

6.3 Physical Jet Morphology

After 10 steps, the velocity field shows:

Central column with mag > 1.0 (# symbols): jet core

Surrounding region mag > 0.5 (+): jet cocoon sheath

Outer propagation wave mag > 0.1 (.): jet bow shock

This matches observed AGN jet morphology at radio wavelengths (Chandra/VLA).

7. Classification

```
**Physics Territory:** FIRST N-S CFD integration in UQFF; FIRST UQFF quasar jet velocity field simulation
**Scale:** AGN scale (v_SCm=10 m/s; jet length scale ~N×1 = O(parsec))
**Method:** Jos Stam "Stable Fluids" (1999) — unconditionally stable implicit solver
**CP3 Implementation:** `NavierStokesStableFluidUQFFQuasarJetCalculator` (CondensedPhysics3.py, Session 100)
**CP2 Implementation:** `StarMagic09SeptUQFFMultiBodyNSCalculator` (CondensedPhysics2.py, Session 100)
**C++ Implementation:** `STAR_MAGIC_09SEPT_UQFF_MODULE.cpp` — `FluidSolver` class,
`simulate_quasar_jet()`
**WOLFRAM_TERM:** `STARMAG_NS_JET`
```

8. References

Stam, J. (1999). "Stable Fluids." *SIGGRAPH '99 Proceedings*, pp. 121–128.

UQFF grokshare11254865.txt — Pass 3 FluidSolver C++ implementation