Modern AI Foundations

A Complete Overview: From Classical Machine Learning to Large Language Models



A structured, code-first guide to the ideas behind modern artificial intelligence: the mathematics that powers it, the classical machine-learning engine at its heart, and the deep-learning revolution that brought us transformers and large language models — with curated sources for every step of the journey.

Prerequisites: Python (intermediate) • NumPy & Pandas (basic) • Calculus (basic)

Course Design Team

Version 1.1 • September 2026 • License: CC BY 4.0

Repository: https://github.com/DanielBerns/AI-course

Contents

About this course 2

Prerequisites and required background 2

1 Introduction and the AI Landscape 4

1.1 Defining intelligence: weak vs. strong AI 4

1.2 From expert systems to data-driven AI 4

1.3 The modern stack: compute, cloud, and data pipelines 5

1.4 Ethics and safety: the non-optional module 6

2 Mathematics and Data Foundations 8

2.1 Linear algebra: the language of data 8

2.2 Probability and statistics: the language of uncertainty 9

2.3 Optimisation: how models learn 10

3 Classical Machine Learning: The Core Engine 13

3.1 Supervised learning 13

3.2 Unsupervised learning 15

3.3 Evaluation metrics: separating learning from memorising 16

4 Transition to Deep Learning and Modern AI 19

4.1 Neural networks: perceptrons, activations, backpropagation 19

4.2 Architectures: CNNs, RNNs, and transformers 21

4.3 Generative AI foundations: embeddings, latent space, and LLMs 22

Where to go next 26

Practical Coding Projects Series 27

Appendix: Answer Key for Check Your Understanding 30

Glossary 32

References 33

About this course

This document develops a four-module overview of modern artificial intelligence into a complete, self-contained study guide. It assumes no prior machine-learning experience, but it does assume the background summarised in the prerequisite matrix on the next page: comfortable **Python**, basic **NumPy & Pandas**, and **high-school calculus**. Everything else — from eigenvectors to attention — is built from scratch, in context, with citations to the primary literature and standard textbooks.

The four modules are deliberately sequential, as the roadmap below shows: the landscape and its ethics (*Module 1*), the mathematical foundations (*Module 2*), the classical machine-learning engine that still powers most industry deployments (*Module 3*), and the deep learning and generative-AI frontier (*Module 4*). All code snippets assume Python 3.9+ with `numpy`, `pandas`, `scikit-learn`, and (for Module 4) `transformers` installed.




Figure 1. The learning path: each module builds directly on the one before it.

Throughout the guide you will meet the following recurring callout boxes:

Box	What it gives you
Module — at a glance	Focus, key concepts, and learning goals for each module.
Key concept	Definitions and intuitions worth memorising.
Hands-on with Python	Short, runnable code tied to the prerequisite skills.
Ethics & safety spotlight	Responsible-AI notes and open questions.
Check your understanding	A quick self-test before moving on.
Sources & further reading	Curated references backing each module.

Table 1. The callout boxes used throughout this guide.

Prerequisites and required background

The table below is the assumed starting point. None of the three rows requires expert mastery; the goal of each is narrow and practical.

Skill	Required level	Primary use case
Python programming	Intermediate	Implementing algorithms, data manipulation
NumPy & Pandas	Basic	Matrix operations and data cleaning
High-school calculus	Basic	Understanding how models learn (derivatives)

Table 2. Prerequisite matrix: the background assumed by this guide.

Python (intermediate). You should be comfortable writing functions, loops, list comprehensions, and simple classes, and know your way around a virtual environment. The course is deliberately

Table 3. Notation reference table.

Symbol / Notation	Description and Typical Context
$\mathbf{x}, \mathbf{y}, \mathbf{z}$	Bold lowercase letters denote column vectors (e.g., sample features $\mathbf{x} \in \mathbb{R}^n$).
X, W, A	Uppercase letters denote matrices (e.g., dataset matrix $X \in \mathbb{R}^{m \times n}$, weights W).
$\boldsymbol{\theta}, \mathbf{w}, \boldsymbol{\beta}$	Model parameter vectors (e.g., regression weights $\boldsymbol{\beta}$, neural net parameters $\boldsymbol{\theta}$).
$\mathcal{L}(\hat{y}, y),\ J(\boldsymbol{\theta})$	Loss function for a single instance ($\mathcal{L}$) vs. cost function averaged over data (J).
$\nabla_{\boldsymbol{\theta}} J$	Gradient vector of partial derivatives with respect to parameters $\boldsymbol{\theta}$.
Σ vs. $\sum$	Uppercase sigma Σ denotes a Covariance Matrix; summation operator $\sum_{i=1}^{m}$ denotes summing series.
$\odot$	Hadamard (element-wise) vector or matrix product.
$\phi(z), \phi'(z)$	Activation function and its scalar derivative.

code-first: every mathematical idea is paired with a few lines of Python. A good refresher, free to read online, is VanderPlas (2016).

NumPy & Pandas (basic). You should be able to create arrays, slice them, and compute with them (`A @ B` for matrix products), and load a CSV into a DataFrame to clean and summarise it (Harris et al. 2020; McKinney 2010). The practice boxes assume exactly this level and no more.

Calculus (basic). You need the derivative as a slope, the power rule, and the chain rule. That is genuinely all — gradients, the engine of all learning in this course, are just derivatives collected into a vector.

The two calculus ideas you actually need

- **A derivative is a local slope:** $f'(x) \approx \dfrac{f(x+h) - f(x)}{h}$ — it tells you which direction is *downhill* and how steeply.
- **The chain rule composes slopes:** $\dfrac{d}{dx} f(g(x)) = f'(g(x))\, g'(x)$.

Backpropagation (Module 4) — the algorithm that trains every modern neural network — is nothing more than this second rule applied systematically, layer by layer.

Self-check before starting.

- Can you write a Python function that returns the mean and standard deviation of a list of numbers?
- Given two NumPy arrays, can you compute their dot product and the shape of `A @ B`?
- Can you differentiate $f(w) = w^2$ and say what $f'(3)$ means geometrically?

If any answer is “not yet”, spend a week with VanderPlas (2016) and any standard calculus refresher; then return — everything else is built for you from here.

1 Introduction and the AI Landscape

Module 1 — at a glance (Estimated Study: 4 hours • Level: Beginner)

Focus. What artificial intelligence is (and is not), how the field evolved from hand-written rules to learning from data, and the infrastructure and ethical questions that shape modern practice.

Key concepts. Defining intelligence; weak vs. strong AI; expert systems vs. data-driven AI; GPUs, TPUs, cloud ecosystems and data pipelines; bias, alignment, copyright and environmental impact.

After this module you will be able to explain the difference between narrow and general AI, describe the paradigm shift from rules to data, sketch an end-to-end machine-learning pipeline, and name the main ethical questions attached to deploying an AI system.

1.1 Defining intelligence: weak vs. strong AI

Before we can build artificial intelligence we have to say what we mean by *intelligence*. Russell and Norvig (2021) organise the many definitions along two axes: are we concerned with *thought processes* or with *behaviour*, and should the benchmark be *human-like* performance or *rationality* — acting so as to achieve the best expected outcome? Alan Turing sidestepped the philosophy in 1950 with an operational test: if a machine's written answers are indistinguishable from a human's, is it not, for practical purposes, intelligent? (Turing 1950). Modern AI research mostly aims at rational behaviour on well-defined tasks — exactly what the learning algorithms of Modules 2–4 deliver.

Weak (narrow) AI vs. strong AI

Weak / narrow AI (today)	Strong AI / AGI (hypothetical)
Excels at one well-defined task: spam filters, image classifiers, next-token prediction	Reasons, plans and learns across arbitrary domains, as a human can
Learns from task-specific data; capability does not transfer	Would transfer knowledge flexibly to novel problems
Every deployed system, including today's LLMs, is narrow in this sense	Unknown whether or when it is achievable; an active research and policy debate

A second classical debate is worth knowing. Philosopher John Searle's *Chinese room* argument holds that symbol manipulation alone is not understanding: a person following rules could answer questions in Chinese without knowing any Chinese (Searle 1980). The argument has returned with force in the era of large language models, because fluent output is cheap while grounded understanding is hard to verify — a theme we revisit in the ethics spotlight below.

1.2 From expert systems to data-driven AI

The term *artificial intelligence* was coined by John McCarthy in the 1955 proposal for the 1956 Dartmouth workshop. For roughly the next three decades the dominant paradigm was *symbolic*: human knowledge was hand-encoded as if–then rules. Expert systems such as MYCIN encoded

several hundred rules elicited from physicians and impressed clinicians in blind evaluations — yet only inside their narrow domain. Rules are brittle, and extracting them from experts (the *knowledge-acquisition bottleneck*) is slow and expensive.

Machine learning inverts the pipeline: instead of programming rules, we collect examples of the desired behaviour and let an algorithm discover the rules. In Mitchell (1997)'s classic formulation, a program *learns* from experience E with respect to task T and performance measure P if its performance at T, measured by P, improves with E. Deep learning pushes the inversion one step further by learning not only the rules but the *features* they operate on (LeCun et al. 2015). Three results announced the new era: AlexNet cut the ImageNet top-5 error rate from roughly 26% to 16% by training a deep network on two consumer GPUs (Krizhevsky et al. 2012); AlphaGo defeated the world Go champion using deep networks combined with search (Silver et al. 2016); and transformer language models (Module 4) turned plain text prediction into a general-purpose technology.

The paradigm shift: from rules to data

Classical programming: rules $+$ data $\longrightarrow$ answers
Machine learning: data $+$ answers $\longrightarrow$ rules (the model)

Instead of hand-crafting the logic, we specify an objective and let an algorithm search for parameters that meet it — which is precisely why the mathematics of Modules 2 and 3 matters so much.




Figure 2. A selective history: from the founding of the field to the generative-AI era.

1.3 The modern stack: compute, cloud, and data pipelines

Compute: GPUs and TPUs. Training a modern model is, computationally, one thing: enormous numbers of matrix–vector products. A CPU optimises a handful of fast, sequential cores; a GPU packs thousands of simpler cores that perform these products in parallel. That is why Krizhevsky et al. (2012) could train a vision network that CPU-era attempts could not, and why hardware co-design now shapes chip roadmaps — Google's Tensor Processing Units, for instance, execute the tensor algebra of neural networks directly (Jouppi et al. 2017). Memory bandwidth is the other half of the story: modern accelerators are as much about feeding data as about computing with it.

Cloud ecosystems. The same hardware is available to anyone, rented by the hour: a laptop, a browser, and a credit card are enough to requisition a cluster of GPUs with a reproducible software image. This democratised experimentation — and concentrated an enormous amount of AI capability in a handful of providers.

Data pipelines. Models live inside a loop, not a vacuum (Figure 3). Practitioners routinely spend the majority of project time collecting, cleaning, and validating data — which is exactly why Pandas is a prerequisite rather than an afterthought (McKinney 2010).

Hands-on with Python

```python
import pandas as pd

df = pd.read_csv("orders.csv", parse_dates=["created"])
df = df.dropna(subset=["amount"])           # basic cleaning
df["revenue"] = df["amount"] * df["quantity"]
summary = (df.groupby("region")["revenue"]
.agg(["count", "mean", "sum"]))
print(summary)
```

Five lines of Pandas cover the ingest, clean, transform, aggregate loop that occupies most of a data scientist's day.




Figure 3. A modern data pipeline: the machine-learning lifecycle as a loop, not a line.

1.4 Ethics and safety: the non-optional module

Technical capability has outpaced governance. Four questions should accompany every system you build:

Four questions to ask of any AI system

Bias. Models inherit the patterns — including the unjust ones — in their training data. Commercial gender-classification systems were shown to misclassify darker-skinned women at far higher rates than lighter-skinned men (Buolamwini and Gebru 2018). Audit data for representation gaps before, not after, deployment.

Alignment. Does the optimised objective match what humans actually want? Specification gaming and reward hacking are documented failure modes (Amodei et al. 2016; Christian 2020); human-feedback training (Module 4) is one partial remedy.

Copyright. Models are trained on scraped text, images, and code. Provenance, licensing, and attribution of training data remain unsettled legal and ethical territory.

Environment. Training large models consumes substantial energy and emits carbon (Strubell et al. 2019; Patterson et al. 2021). Mitigations: efficient hardware, right-sized models, and transparency about training costs.

A fifth concern is specific to language models: fluency without grounding. Bender et al. (2021) famously warned that large language models are *stochastic parrots* — they reproduce statistical patterns of language, which is not the same as knowing anything. The practical consequence is cultural: verify outputs, cite sources, and treat generated text as a draft, never as evidence.

A practitioner's checklist.

- Define the task, the population served, and the failure modes *before* modelling.
- Audit training data for representation gaps and label quality.
- Choose metrics that price both error types (Module 3 shows how).

- Document limitations — model cards, datasheets, plain language.
- Plan for monitoring and human oversight after deployment.

Check your understanding

1. A chess engine, a spam filter, and a claimed "fully autonomous reasoning" startup demo: classify each as weak or strong AI, and justify the label.
2. Why did GPUs unlock deep learning at scale, whereas CPUs could not supply the necessary arithmetic throughput? Answer in terms of parallel hardware architecture.
3. Your model screens job applications. Name two concrete harms and one mitigation for each.

Sources & further reading

- S. J. Russell and P. Norvig (2021). *Artificial Intelligence: A Modern Approach*. 4th ed. Hoboken, NJ: Pearson
- A. M. Turing (1950). "Computing Machinery and Intelligence". In: *Mind* 59.236, pp. 433–460
- J. R. Searle (1980). "Minds, Brains, and Programs". In: *Behavioral and Brain Sciences* 3.3, pp. 417–424
- Y. LeCun et al. (2015). "Deep Learning". In: *Nature* 521.7553, pp. 436–444
- A. Krizhevsky et al. (2012). "ImageNet Classification with Deep Convolutional Neural Networks". In: *Advances in Neural Information Processing Systems 25*, pp. 1097–1105
- D. Silver et al. (2016). "Mastering the Game of Go with Deep Neural Networks and Tree Search". In: *Nature* 529.7587, pp. 484–489
- N. P. Jouppi et al. (2017). "In-Datacenter Performance Analysis of a Tensor Processing Unit". In: *Proceedings of the 44th Annual International Symposium on Computer Architecture (ISCA)*, pp. 1–12
- J. Buolamwini and T. Gebru (2018). "Gender Shades: Intersectional Accuracy Disparities in Commercial Gender Classification". In: *Proceedings of the 1st Conference on Fairness, Accountability and Transparency*, pp. 77–91
- D. Amodei et al. (2016). "Concrete Problems in AI Safety". In: *arXiv preprint arXiv:1606.06565*
- B. Christian (2020). *The Alignment Problem: Machine Learning and Human Values*. New York: W. W. Norton & Company
- E. Strubell et al. (2019). "Energy and Policy Considerations for Deep Learning in NLP". in: *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics (ACL)*, pp. 3645–3650
- D. Patterson et al. (2021). "Carbon Emissions and Large Neural Network Training". In: *Advances in Neural Information Processing Systems 34*, pp. 13470–13481
- E. M. Bender et al. (2021). "On the Dangers of Stochastic Parrots: Can Language Models Be Too Big?" In: *Proceedings of the 2021 ACM Conference on Fairness, Accountability, and Transparency (FAccT)*, pp. 610–623

2 Mathematics and Data Foundations

Module 2 — at a glance (Estimated Study: 8 hours • Level: Intermediate)

Focus. The small mathematical toolkit that quietly powers everything else in the course: linear algebra to *represent* data, probability to *quantify* uncertainty, and optimisation to *learn* from mistakes.

Key concepts. Vectors, matrices, eigenvalues and dimensionality reduction; Bayes' theorem, distributions and hypothesis testing; loss and cost functions, gradients, and gradient descent.

After this module you will be able to describe any dataset as linear-algebra objects, reason correctly about conditional probabilities, and explain — and implement — gradient descent from scratch.

Mathematics here is a working tool, not an exam subject. Each concept is introduced the moment it earns its keep, and each is paired with NumPy code that uses it.

2.1 Linear algebra: the language of data

Machine-learning data lives in vectors, matrices, and tensors. A house becomes a vector of measurements $\mathbf{x} = [\text{area}, \text{rooms}, \text{age}]$; a dataset of m houses a matrix $X \in \mathbb{R}^{m \times n}$; a colour image a $H \times W \times 3$ tensor. The dot product measures alignment between vectors (its normalised version, cosine similarity, is the workhorse of recommendation systems and semantic search), and a matrix–vector product $W\mathbf{x}$ is a *change of representation*: it rotates, stretches, and mixes coordinates. In Module 4 this becomes literal — every neural-network layer *is* one such matrix.

Eigenvalues and dimensionality reduction. Eigenvectors are non-zero directions along which a linear transformation A acts purely by scaling without changing direction:

$$A\mathbf{v} = \lambda \mathbf{v}. \tag{1}$$

The covariance matrix Σ of a dataset is symmetric, so its eigenvectors are mutually orthogonal, and the eigenvector with the largest eigenvalue points along the direction of greatest variance. Projecting the data onto the top eigenvectors is *principal component analysis* (PCA):

$$\mathbf{v}_1 = \arg\max_{\|\mathbf{v}\|=1} \mathbf{v}^\top \Sigma \, \mathbf{v}, \tag{2}$$

i.e. the first principal component is the top eigenvector of Σ. Dropping low-variance directions keeps most of the signal in far fewer coordinates — compression, de-noising, and two-dimensional plots of hundred-dimensional data (Strang 2019, Chapters 5–6). NumPy makes all of it concrete, and its compiled vector operations are orders of magnitude faster than Python loops (Harris et al. 2020).

Hands-on with Python

```python
import numpy as np

X = np.random.default_rng(0).normal(size=(500, 20))
Xc = X - X.mean(axis=0)              # centre the columns
C  = (Xc.T @ Xc) / (X.shape[0]-1)    # covariance matrix
evals, evecs = np.linalg.eigh(C)     # symmetric solver
pcs = evecs[:, ::-1][:, :2]          # top-2 principal components
X2  = Xc @ pcs                       # 20-D data projected to 2-D
print(X2.shape, evals[::-1][:2])     # (500, 2) and the top variances
```

2.2 Probability and statistics: the language of uncertainty

Real data is noisy and the future is unknown, so every prediction in this course is ultimately a probability statement. A handful of distributions covers most of the terrain: the *Bernoulli* for yes/no outcomes, the *categorical* for classes (and, we shall see, for tokens), and the *Gaussian* for measurement noise and natural variation:

$$p(x) = \frac{1}{\sigma\sqrt{2\pi}} \exp\left(-\frac{(x-\mu)^2}{2\sigma^2}\right). \tag{3}$$

The single most useful formula in the toolkit is Bayes' theorem:

$$P(A \mid B) \;=\; \frac{P(B \mid A)\,P(A)}{P(B)}. \tag{4}$$

Bayes' theorem, in words

Posterior $\propto$ likelihood $\times$ prior: what you believe *after* seeing evidence is proportional to how well each hypothesis would have produced that evidence, weighted by what you believed *before*.

A medical example shows why intuition fails without it. A test with 99% sensitivity and a 5% false-positive rate, applied to a disease with 1% prevalence, yields

$$P(\text{disease} \mid +) = \frac{P(+ \mid \text{disease})\,P(\text{disease})}{P(+)} \tag{5}$$

$$= \frac{\overbrace{0.99}^{\text{sensitivity}} \times \overbrace{0.01}^{P(\text{disease})}}{\underbrace{0.99}_{\text{sensitivity}} \times \underbrace{0.01}_{P(\text{disease})} + \underbrace{0.05}_{\text{false pos rate}} \times \underbrace{0.99}_{P(\text{no disease})}} \approx 0.17: \tag{6}$$

only one positive in six is a true case, because the disease is rare to begin with. Note a crucial subtle point: the two 0.99 factors in the denominator represent entirely different quantities — the first is test sensitivity $P(+ \mid \text{disease}) = 0.99$, whereas the second is the prior probability of being healthy $P(\text{no disease}) = 1 - 0.01 = 0.99$. The same base-rate reasoning governs fraud alerts, security scanners, and classifier performance on imbalanced classes.

Hypothesis testing disciplines the question "is this pattern real?". State a null hypothesis (no effect), compute a test statistic, and report a p-value: the probability of data at least this extreme *if the null were true*. Conventions like $p < 0.05$ are useful servants and terrible masters

— multiple comparisons and selective reporting ("p-hacking") invalidate them silently. Prefer effect sizes and confidence intervals whenever possible (Wasserman 2004). Finally, the *central limit theorem*: averages of many independent draws become approximately Gaussian, with standard error $\sigma/\sqrt{n}$ — the reason bigger samples shrink error bars, and the intuition underlying both A/B testing and the scaling laws of Module 4.

Hands-on with Python

```python
import numpy as np

rng = np.random.default_rng(42)
# 10,000 experiments: average of 40 Exponential(1) draws each
means = rng.exponential(scale=1.0, size=(10_000, 40)).mean(axis=1)
print(means.mean(), means.std())   # ~1.0 and ~1/sqrt(40) = 0.158
```

The standard deviation of the means matches $\sigma/\sqrt{n}$: the central limit theorem, verified in three lines.

2.3 Optimisation: how models learn

A **loss function** scores the error of a prediction on a single example; the **cost function** (or empirical risk) averages it over the dataset. For regression, the default is mean squared error,

$$J(\boldsymbol{\theta}) = \frac{1}{2m}\sum_{i=1}^{m}\big(h_{\boldsymbol{\theta}}(\mathbf{x}_i) - y_i\big)^2. \tag{7}$$

The entire game of machine learning is then: choose a flexible family of functions, define a loss, and find the parameters that minimise it.

The **gradient** $\nabla_{\boldsymbol{\theta}} J$ collects all partial derivatives into a vector — the direction of steepest *ascent*. Learning therefore walks the other way:

$$\boldsymbol{\theta}_{t+1} \;=\; \boldsymbol{\theta}_t \;-\; \eta\,\nabla_{\boldsymbol{\theta}} J(\boldsymbol{\theta}_t), \tag{8}$$

where η is the *learning rate*. Too small and training crawls; too large and it overshoots and diverges (Figure 4). In practice the gradient is estimated on small random *mini-batches* of data — stochastic gradient descent (SGD) — trading a little noise for a lot of speed.

Adam and adaptive optimisers. Standard SGD uses a fixed step size for all parameters. The **Adam** optimiser (Kingma and Ba 2015) adapts learning rates individually by maintaining exponential moving averages of the gradient $g_t = \nabla_{\boldsymbol{\theta}} J$ (first moment m_t) and its square (second moment v_t):

$$m_t = \beta_1 m_{t-1} + (1-\beta_1) g_t, \qquad v_t = \beta_2 v_{t-1} + (1-\beta_2) g_t^2, \tag{9}$$

$$\hat{m}_t = \frac{m_t}{1-\beta_1^t}, \qquad \hat{v}_t = \frac{v_t}{1-\beta_2^t}, \qquad \boldsymbol{\theta}_{t+1} = \boldsymbol{\theta}_t - \frac{\eta\,\hat{m}_t}{\sqrt{\hat{v}_t}+\epsilon}, \tag{10}$$

where $\beta_1 = 0.9$, $\beta_2 = 0.999$, and $\epsilon = 10^{-8}$. First-moment momentum accelerates along constant directions, while second-moment scaling dampens steps for features with frequently large gradients, making Adam the default choice for deep learning and Transformers. *(Note: Gradient propagation across multi-layer deep networks is detailed in Module 4.)* Linear models have convex, bowl-shaped costs, so descent finds the unique minimum; neural networks do not, yet SGD and Adam reliably find good solutions anyway — one of the field's pleasant empirical surprises.

Adam optimiser step from scratch

```
import numpy as np

def adam_step(theta, grad, m, v, t, lr=0.01, beta1=0.9,
beta2=0.999, eps=1e-8):
    m = beta1 * m + (1 - beta1) * grad
    v = beta2 * v + (1 - beta2) * (grad ** 2)
    m_hat = m / (1 - beta1 ** t)
    v_hat = v / (1 - beta2 ** t)
    theta_next = theta - (lr * m_hat) / (np.sqrt(v_hat) + eps)
    return theta_next, m, v
```

Adam updates each parameter using bias-corrected first and second moment estimates.




Figure 4. Gradient descent on $J(w) = w^2$ with learning rate $\eta = 0.15$: each step $w \leftarrow w - \eta\, 2w$ shrinks the distance to the minimum by 30%.

Hands-on with Python

```
w, lr = 5.0, 0.15
for step in range(8):
grad = 2 * w            # derivative of f(w) = w**2
w = w - lr * grad       # the update rule, eq. (8)
print(f"step {step}:  w = {w:.4f}")
# w -> 0.2882: convergence toward the minimum
```

Check your understanding

1. In plain words, what does an eigenvector of the covariance matrix tell you about a dataset?
2. In the medical-test example, what happens to $P(\text{disease} \mid +)$ as prevalence rises to 10%?
3. What goes wrong, mechanically, when the learning rate in equation (8) is set to 1.1 for $J(w) = w^2$?

Sources & further reading

- G. Strang (2019). *Linear Algebra and Learning from Data*. Wellesley, MA: Wellesley–Cambridge Press
- L. Wasserman (2004). *All of Statistics: A Concise Course in Statistical Inference*. New York: Springer
- S. Boyd and L. Vandenberghe (2004). *Convex Optimization*. Cambridge: Cambridge University Press
- I. Goodfellow et al. (2016). *Deep Learning*. Cambridge, MA: MIT Press
- C. M. Bishop (2006). *Pattern Recognition and Machine Learning*. New York: Springer
- C. R. Harris et al. (2020). “Array Programming with NumPy”. In: *Nature* 585, pp. 357–362
- W. McKinney (2010). “Data Structures for Statistical Computing in Python”. In: *Proceedings of the 9th Python in Science Conference (SciPy)*, pp. 56–61
- J. VanderPlas (2016). *Python Data Science Handbook: Essential Tools for Working with Data*. Sebastopol, CA: O’Reilly Media

3 Classical Machine Learning: The Core Engine

Module 3 — at a glance (Estimated Study: 10 hours • Level: Intermediate)

Focus. The algorithms that still run the majority of real-world, structured-data workloads — and the evaluation discipline that separates real learning from memorisation.

Key concepts. Supervised learning: regression, decision trees, SVMs, ensembles. Unsupervised learning: K-Means clustering and anomaly detection. Evaluation: accuracy, precision, recall, F1, ROC-AUC.

After this module you will be able to choose an appropriate classical algorithm for a task, cluster unlabelled data, and — most importantly — evaluate any model honestly.

On the tabular, structured data of business (customers, transactions, sensors), classical machine learning frequently still beats glamorous deep models. It is also the best place to internalise the habits — splits, metrics, baselines — that govern everything later (Hastie et al. 2009; Pedregosa et al. 2011).

3.1 Supervised learning

Supervised learning starts from labelled pairs $\mathcal{D} = \{(\mathbf{x}_i, y_i)\}_{i=1}^{m}$ and a split into *training*, *validation*, and *test* sets. If y is a number the task is *regression*; if y is a category it is *classification*.

Regression. The linear model $\hat{y} = \beta_0 + \boldsymbol{\beta}^\top \mathbf{x}$ has a closed-form least-squares solution,

$$\hat{\boldsymbol{\beta}} = (X^\top X)^{-1} X^\top \mathbf{y}, \tag{11}$$

in practice computed by QR factorisation or gradient descent for numerical stability. *Regularisation* fights overfitting by penalising large coefficients — ridge regression,

$$\hat{\boldsymbol{\beta}} = \arg\min_{\boldsymbol{\beta}} \ \|\mathbf{y} - X\boldsymbol{\beta}\|_2^2 + \alpha\|\boldsymbol{\beta}\|_2^2, \tag{12}$$

shrinks them smoothly; the lasso (ℓ_1) drives some exactly to zero, performing feature selection. *Logistic regression* turns a linear score into a class probability with the sigmoid function and is trained with the cross-entropy loss — the very same loss family that trains large language models in Module 4.

Naive Bayes and k-NN baselines. Bridging directly from Bayes' theorem (equation 4), the **Naive Bayes classifier** computes the posterior probability of class y given features $\mathbf{x} = (x_1, \ldots, x_n)$ by assuming features are conditionally independent given y:

$$P(y \mid \mathbf{x}) \ \propto \ P(y) \prod_{j=1}^{n} P(x_j \mid y). \tag{13}$$

Despite this simplistic ("naive") assumption, it is exceptionally fast, highly effective for high-dimensional text classification (e.g., spam filtering), and requires minimal training data. The **k-Nearest Neighbors (k-NN)** algorithm is a non-parametric instance-based baseline: it stores all training samples and classifies a query point by a majority vote among its k closest neighbors in Euclidean space. It requires zero training time but incurs $O(m \cdot n)$ inference cost per query.

Decision trees and ensembles. A tree asks a sequence of yes/no questions ("area $>$ 120?"), choosing at each split the feature and threshold that most reduce impurity. Trees are fast,

handle mixed data types, and are interpretable — and, alone, they overfit badly. *Random forests* average many de-correlated trees grown on random subsamples of rows and features (Breiman 2001); *gradient boosting* builds trees sequentially, each correcting the residual errors of the ensemble so far (Chen and Guestrin 2016). On tabular data these two are frequently the strongest off-the-shelf learners available.

Support vector machines. The SVM seeks the separating hyperplane with the *maximum margin* to the closest points, minimising the hinge loss

$$L = \max\bigl(0,\ 1 - y\, f(\mathbf{x})\bigr), \qquad y \in \{-1, +1\}, \tag{14}$$

and the *kernel trick* lets it build non-linear boundaries implicitly in high-dimensional feature space (Cortes and Vapnik 1995).

Table 4. Choosing a first algorithm for tabular data.

Algorithm	Reach for it when	Strengths	Watch out
Linear / logistic regression	Baselines; small, clean data	Fast, interpretable, statistically principled	Underfits complex nonlinear structure
Naive Bayes	Text classification, fast baseline	Very fast, handles high dimensions	Strong feature independence assumption
k-NN	Small datasets, distance baselines	No training phase; flexible boundaries	Slow inference $O(mn)$; scale-sensitive
Decision tree	Interpretability is the product	Human-readable rules; no feature scaling	Single trees overfit badly
Random forest	Default robust choice	Variance reduction via bagging; few knobs	Less interpretable; larger memory
Gradient boosting (XGBoost)	Maximum accuracy on tables	State of the art on structured data	Needs tuning; can overfit small data
SVM	Small–medium data, many features	Max-margin generalisation; kernels	Scales poorly to very large datasets

Feature scaling requirement. Algorithms that calculate spatial distances (K-Means, k-NN, SVM) or compute gradient steps (Logistic/Linear Regression, Neural Networks) are highly sensitive to feature scales: features with large magnitudes (e.g., house area in sq ft) dominate Euclidean metrics over features with small ranges (e.g., room count). Standardisation ($z = (x - \mu)/\sigma$ via `StandardScaler`) or min-max scaling is mandatory prior to training. By contrast, decision trees and tree ensembles are *scale-invariant*, as splits evaluate individual feature thresholds independently.

⚖ CRITICAL: Avoid Data Leakage

Fit scalers on training data ONLY. A ubiquitous beginner error is fitting a scaler on the entire dataset prior to splitting. This causes *data leakage*: information from the test set (mean μ and standard deviation σ) leaks into the training process, yielding artificially optimistic evaluation metrics. Always compute scaling parameters using `fit_transform()` on the training split, and apply `transform()` on validation/test splits. Use `sklearn.pipeline.Pipeline` to automate this safely.

The Third Paradigm: Reinforcement Learning

While supervised learning requires explicit targets y_i and unsupervised learning seeks unlabelled structure, **Reinforcement Learning (RL)** learns through trial-and-error interaction with an environment. An *agent* observes state s_t, executes action $a_t \sim \pi(a \mid s)$, and receives scalar reward r_t. The goal is to learn a policy π that maximizes expected cumulative return $G_t = \sum_{k=0}^{\infty} \gamma^k r_{t+k}$.
RL powers AlphaGo (Silver et al. 2016) and forms the core of Reinforcement Learning from Human Feedback (RLHF, Module 4) used to align LLMs. However, RL is prone to *reward hacking* (Amodei et al. 2016) — exploiting flaws in reward design rather than accomplishing the intended task.

3.2 Unsupervised learning

Unsupervised learning finds structure without labels. The canonical clustering algorithm, **K-Means** (MacQueen 1967), partitions m points into K clusters by minimising within-cluster squared distance,

$$J = \sum_{k=1}^{K} \sum_{\mathbf{x}_i \in C_k} \|\mathbf{x}_i - \boldsymbol{\mu}_k\|^2, \tag{15}$$

by alternating two steps: (1) assign each point to its nearest centroid $\boldsymbol{\mu}_k$; (2) move each centroid to the mean of its members. It converges quickly, but only to a *local* optimum — hence multiple random restarts — and it implicitly assumes roundish, equally sized clusters. Choosing K is a design decision; the "elbow" of the cost curve offers a visual heuristic.

Quantitative cluster evaluation: Silhouette Score. To evaluate clustering quality without relying solely on visual heuristics, the **Silhouette Coefficient** (Rousseeuw 1987) measures how tightly grouped points are within their cluster compared to neighboring clusters:

$$s(i) = \frac{b(i) - a(i)}{\max\big(a(i),\, b(i)\big)}, \qquad s(i) \in [-1, +1], \tag{16}$$

where $a(i)$ is the mean distance between point i and all other points in the same cluster, and $b(i)$ is the mean distance to points in the nearest neighboring cluster. A mean score near $+1$ indicates well-separated, dense clusters; scores near 0 indicate overlapping clusters. Typical uses: customer segmentation, topic grouping, preprocessing.

K-Means Clustering & Silhouette Score

```python
from sklearn.cluster import KMeans
from sklearn.metrics import silhouette_score
import numpy as np

# Fit K-Means and quantitatively evaluate cluster separation
kmeans = KMeans(n_clusters=3, n_init=10, random_state=42)
labels = kmeans.fit_predict(X_tr)
score = silhouette_score(X_tr, labels)
print(f"Cluster centroids shape: {kmeans.cluster_centers_.shape}")
print(f"Silhouette Coefficient: {score:.3f}")
```

Anomaly detection flags rare, suspicious items — fraud, failed sensors, rare medical readings. Statistical methods flag points in the tails of fitted distributions; distance- and density-based methods flag points far from any crowd; and the *isolation forest* exploits the fact that anomalies

are easy to separate from everything else with few random splits (Liu et al. 2008). Mixture models (Bishop 2006) give a probabilistic route, and autoencoders (Module 4) extend the idea to complex data.

3.3 Evaluation metrics: separating learning from memorising

A model that cannot be measured cannot be trusted. All classification metrics descend from the *confusion matrix*:

Table 5. The confusion matrix for binary classification.

	Predicted positive	**Predicted negative**
Actual positive	TP (hit)	FN (miss)
Actual negative	FP (false alarm)	TN (correct rejection)

$$\text{Accuracy} = \frac{TP + TN}{TP + TN + FP + FN}, \qquad \text{Precision} = \frac{TP}{TP + FP}, \qquad \text{Recall} = \frac{TP}{TP + FN}, \tag{17}$$

$$F_1 = 2\,\frac{\text{Precision} \cdot \text{Recall}}{\text{Precision} + \text{Recall}}. \tag{18}$$

The metric is a *value judgement* about which errors matter. If 1% of transactions are fraudulent, a model that always says “not fraud” is 99% accurate and perfectly useless; a fraud system should trade precision for recall, while a spam filter should do the opposite. The **ROC curve** traces true- vs. false-positive rate as the decision threshold varies, and its area (AUC) — the probability that a random positive outranks a random negative — summarises threshold-free quality (Fawcett 2006).

Two further disciplines: **cross-validation** rotates the train/validation split (k-fold) to use data efficiently and to *measure variance* across folds; and the **bias–variance trade-off** names the two failure modes — underfitting (too simple, high bias) and overfitting (memorising the training set, high variance) — with regularisation, more data, or better inductive bias as the respective remedies (Hastie et al. 2009).

End-to-End Leakage-Safe Classification Pipeline

```
                    from sklearn.datasets import make_classification
                    from sklearn.model_selection import train_test_split,
cross_val_score
                    from sklearn.preprocessing import StandardScaler
                    from sklearn.pipeline import Pipeline
                    from sklearn.ensemble import RandomForestClassifier
                    from sklearn.metrics import classification_report

                    # Data loading stub: generate synthetic tabular dataset
                    X, y = make_classification(n_samples=1000, n_features=20,
random_state=0)
                    X_tr, X_te, y_tr, y_te = train_test_split(X, y, test_size=0.2,
stratify=y, random_state=0)

                    # Leakage-safe pipeline: scaling parameters fit ONLY on training
fold
                    pipe = Pipeline([
                        ('scaler', StandardScaler()),
                        ('clf', RandomForestClassifier(n_estimators=300,
random_state=0))
                    ])
                    print("CV ROC-AUC Scores:", cross_val_score(pipe, X_tr, y_tr, cv=5,
scoring='roc_auc'))
                    pipe.fit(X_tr, y_tr)
                    print(classification_report(y_te, pipe.predict(X_te)))
```

Check your understanding

1. For a cancer-screening tool, which metric would you prioritise, and what is the cost of that choice?
2. Why does K-Means struggle with two concentric rings of points, and what does that reveal about its assumptions?
3. Your cross-validation scores vary from 0.62 to 0.91 across folds. What does that variance tell you, and what would you do next?

Sources & further reading

- T. M. Mitchell (1997). *Machine Learning*. New York: McGraw-Hill
- T. Hastie et al. (2009). *The Elements of Statistical Learning: Data Mining, Inference, and Prediction*. 2nd ed. New York: Springer
- C. M. Bishop (2006). *Pattern Recognition and Machine Learning*. New York: Springer
- C. Cortes and V. Vapnik (1995). “Support-Vector Networks”. In: *Machine Learning* 20.3, pp. 273–297
- L. Breiman (2001). “Random Forests”. In: *Machine Learning* 45.1, pp. 5–32
- T. Chen and C. Guestrin (2016). “XGBoost: A Scalable Tree Boosting System”. In: *Proceedings of the 22nd ACM SIGKDD International Conference on Knowledge Discovery and Data Mining*, pp. 785–794
- J. MacQueen (1967). “Some Methods for Classification and Analysis of Multivariate Observations”. In: *Proceedings of the Fifth Berkeley Symposium on Mathematical Statistics and Probability*. Vol. 1, pp. 281–297
- F. T. Liu et al. (2008). “Isolation Forest”. In: *Proceedings of the 8th IEEE International Conference on Data Mining (ICDM)*, pp. 413–422
- T. Fawcett (2006). “An Introduction to ROC Analysis”. In: *Pattern Recognition Letters* 27.8, pp. 861–

874
- F. Pedregosa et al. (2011). “Scikit-learn: Machine Learning in Python”. In: *Journal of Machine Learning Research* 12, pp. 2825–2830

4 Transition to Deep Learning and Modern AI

Module 4 — at a glance (Estimated Study: 12 hours • Level: Advanced)

Focus. The leap from engineered features to learned representations: neural networks and backpropagation, the three architectures that shaped the field, and the mechanics of generative AI and large language models.

Key concepts. Perceptrons, activation functions, backpropagation; CNNs, RNNs, and transformers; embeddings, latent space, diffusion, and next-token prediction.

After this module you will be able to explain how a neural network is trained, why transformers displaced recurrence, and what exactly a large language model is doing when it answers you.

The jump from classical ML to deep learning is a jump in *who designs the features*. A classical pipeline is given hand-crafted inputs; a deep network learns a hierarchy of them — edges, then textures, then parts, then objects (LeCun et al. 2015). What engineering achieved by hand, depth achieves with data and compute.

4.1 Neural networks: perceptrons, activations, backpropagation

The **perceptron** (Rosenblatt 1958) is a single neuron: a weighted sum passed through a threshold,

$$\hat{y} = \mathbb{1}\{\mathbf{w}^\top \mathbf{x} + b > 0\} \in \{0, 1\} \quad (\text{or } \operatorname{sgn}(\mathbf{w}^\top \mathbf{x} + b) \in \{-1, +1\}). \tag{19}$$

It can learn any function that a straight line can separate — and provably cannot learn XOR, a limitation that chilled the field's first winter (Minsky and Papert 1969). The repair is to *stack* units and interleave **nonlinear activation functions** between layers:

$$\mathbf{a}^{(\ell)} = \phi\left(W^{(\ell)}\, \mathbf{a}^{(\ell-1)} + \mathbf{b}^{(\ell)}\right), \qquad \ell = 1, \dots, L. \tag{20}$$

Without ϕ, the stack would collapse into a single linear map. The rectified linear unit, $\phi(z) = \max(0, z)$, became the default for being cheap, non-saturating, and sparse in its activations (Nair and Hinton 2010). Such networks are universal approximators (Hornik et al. 1989) — a statement about *capacity*, with no guarantee that training finds good parameters.




Figure 5. A fully connected 3–4–4–2 network. Every edge carries a learnable weight; each layer applies its matrix, then a nonlinearity.

Backpropagation (Rumelhart et al. 1986) computes the gradient of the loss $\mathcal{L}$ with respect to every weight (the chain rule from Module 1) organised backwards through the layers. With




Figure 6. Common activation functions. ReLU's lack of saturation for $z > 0$ helped make deep networks trainable at scale (Nair and Hinton 2010).

$\delta^{(\ell)} \equiv \partial \mathcal{L} / \partial \mathbf{z}^{(\ell)}$:

$$\boldsymbol{\delta}^{(L)} = \nabla_{\mathbf{a}^{(L)}} \mathcal{L} \odot \phi'\big(\mathbf{z}^{(L)}\big), \tag{21}$$

$$\boldsymbol{\delta}^{(\ell)} = \big(W^{(\ell+1)\top} \boldsymbol{\delta}^{(\ell+1)}\big) \odot \phi'\big(\mathbf{z}^{(\ell)}\big), \qquad \ell = L-1, \dots, 1, \tag{22}$$

$$\frac{\partial \mathcal{L}}{\partial W^{(\ell)}} = \boldsymbol{\delta}^{(\ell)} \, \mathbf{a}^{(\ell-1)\top}, \tag{23}$$

where $\odot$ is element-wise multiplication. Backprop is a gradient-*computation* algorithm; the learning itself is still gradient descent (equation (8)), now run on mini-batches through frameworks such as PyTorch or JAX.

Vanishing and exploding gradients. In deep multi-layer architectures, backpropagating loss gradients across L layers involves repeated matrix products backwards:

$$\boldsymbol{\delta}^{(1)} = \left(\prod_{\ell=2}^{L} W^{(\ell)\top} \operatorname{diag}\Big(\phi'\Big(\mathbf{z}^{(\ell)}\Big)\Big) \right) \boldsymbol{\delta}^{(L)}. \tag{24}$$

Because weight matrices $W^{(\ell)}$ in general network layers are rectangular, their scaling magnitude is governed by their *spectral norm* $\|W^{(\ell)}\|_2$ (maximum singular value). If the spectral norms or activation slopes ϕ' are strictly bounded below 1, gradients decay exponentially to zero ($\boldsymbol{\delta}^{(1)} \to \mathbf{0}$, *vanishing gradients*), leaving early layers untrained. Conversely, if spectral norms exceed 1, gradients explode exponentially ($\boldsymbol{\delta}^{(1)} \to \infty$, *exploding gradients*). Shallow linear models avoid this because they lack hidden depth; deep networks require architectural safeguards — residual skip connections (He et al. 2016), gradient clipping, Layer Normalization, and ReLU activations (Nair and Hinton 2010) — to stabilize gradient flow.

Two-Layer MLP with Manual Backpropagation in NumPy

```
import numpy as np

# Runnable 2-layer MLP (Input -> Hidden -> Output) with manual
backprop
rng = np.random.default_rng(42)
X_b = rng.standard_normal((100, 4))
y_b = rng.integers(0, 2, size=(100, 1))

W1 = rng.standard_normal((4, 8)) * 0.1; b1 = np.zeros((1, 8))
W2 = rng.standard_normal((8, 1)) * 0.1; b2 = np.zeros((1, 1))

for epoch in range(100):
    # Forward pass
    z1 = X_b @ W1 + b1; a1 = np.maximum(0, z1)   # ReLU activation
    z2 = a1 @ W2 + b2;  hat_y = 1 / (1 + np.exp(-z2)) # Sigmoid
output

    # Backward pass (Gradient computation via chain rule)
    dz2 = (hat_y - y_b) / len(X_b)               # dL/dz2 for BCE
loss
    dW2 = a1.T @ dz2; db2 = dz2.sum(axis=0, keepdims=True)
    da1 = dz2 @ W2.T;  dz1 = da1 * (z1 > 0)      # ReLU derivative
    dW1 = X_b.T @ dz1; db1 = dz1.sum(axis=0, keepdims=True)

    # Gradient descent update step
    W1 -= 0.1 * dW1; b1 -= 0.1 * db1; W2 -= 0.1 * dW2; b2 -= 0.1 *
db2
print(f"Final BCE loss: {np.mean(-(y_b*np.log(hat_y+1e-7) +
(1-y_b)*np.log(1-hat_y+1e-7))):.4f}")
```

4.2 Architectures: CNNs, RNNs, and transformers

Convolutional networks (CNNs) exploit the structure of images: local patterns, and translation invariance. A convolution slides a small learnable filter K over the input,

$$(I * K)(i,j) = \sum_m \sum_n I(i-m,\, j-n)\, K(m,n), \tag{25}$$

so the *same* few weights detect the same pattern everywhere — drastically fewer parameters than a dense layer, plus built-in equivariance. Pooling layers shrink resolution. LeNet established the recipe for document recognition (LeCun et al. 1998); AlexNet's GPU-trained depth ignited the modern era (Krizhevsky et al. 2012).

Recurrent networks (RNNs) handle sequences by carrying a hidden state from step to step:

$$\mathbf{h}_t = \tanh\!\big(W_h\, \mathbf{h}_{t-1} + W_x\, \mathbf{x}_t + \mathbf{b}\big). \tag{26}$$

Training them across long sequences suffers from vanishing gradients; the **LSTM**'s gated memory cells were the decisive fix (Hochreiter and Schmidhuber 1997), dominating language, speech, and time series for two decades.

Transformers replaced recurrence with *attention* (Vaswani et al. 2017). Each token emits a query, a key, and a value; the output for each position is a weighted average of all values, with weights given by query–key compatibility:

$$\mathrm{Attention}(Q,K,V) = \mathrm{softmax}\!\left(\frac{Q\,K^\top}{\sqrt{d_k}}\right) V. \tag{27}$$

Because every token can attend to every other in a single parallel step, transformers train vastly faster than RNNs on modern hardware — the property, more than any single equation, that made the modern era possible. However, computing pairwise attention scores across sequence length n incurs $O(n^2)$ computational and memory complexity, creating a fundamental bottleneck for long *context windows*.

Scaled Dot-Product Attention from Scratch in NumPy

```
import numpy as np

def scaled_dot_product_attention(Q, K, V, mask=None):
    d_k = Q.shape[-1]
    scores = (Q @ K.T) / np.sqrt(d_k)
    if mask is not None:
        scores = np.where(mask == 0, -1e9, scores)
    weights = np.exp(scores - np.max(scores, axis=-1,
keepdims=True))
    weights /= weights.sum(axis=-1, keepdims=True)  # Softmax
    return weights @ V, weights

# Demonstrate with 4 tokens of dimension 8
seq_len, d_k = 4, 8
Q = K = V = np.random.default_rng(0).standard_normal((seq_len, d_k))
causal_mask = np.tril(np.ones((seq_len, seq_len))) #
Lower-triangular mask
output, attn_weights = scaled_dot_product_attention(Q, K, V,
mask=causal_mask)
print("Attention Output Shape:", output.shape)
print("Causal Attention Weights Matrix:\n", np.round(attn_weights,
3))
```

Positional encodings. Plain self-attention is permutation-invariant: shuffling input tokens yields identical attention outputs (permuted correspondingly). To inject sequence order, **positional encodings** are added to input embeddings. The original Transformer used fixed sinusoidal frequencies (Vaswani et al. 2017):

$$PE_{(pos,2i)} = \sin\Big(\frac{pos}{10000^{2i/d_model}}\Big), \qquad PE_{(pos,2i+1)} = \cos\Big(\frac{pos}{10000^{2i/d_model}}\Big). \tag{28}$$

Modern LLMs predominantly use **Rotary Position Embeddings (RoPE)** (Su et al. 2024), which rotate query and key vectors in complex 2D planes, incorporating relative distance directly into the dot product $QK^\top$.

Residual connections and normalization. Deep Transformer stacks survive vanishing gradients by wrapping every sub-layer with a **residual (skip) connection** (He et al. 2016) and **Layer Normalization**:

$$\mathbf{y} = \mathrm{LayerNorm}\big(\mathbf{x} + \mathcal{F}(\mathbf{x})\big). \tag{29}$$

Skip connections provide an unattenuated identity gradient highway ($\partial\mathbf{y}/\partial\mathbf{x} = I + \partial\mathcal{F}/\partial\mathbf{x}$), enabling gradient flow across hundreds of layers. Within five years the architecture had absorbed language, vision, audio, and protein-structure modelling.

4.3 Generative AI foundations: embeddings, latent space, and LLMs

Embeddings. Word2vec showed that a shallow network trained on "predict the neighbours of a word" learns vectors with striking arithmetic structure: $\mathbf{w}_{\text{king}} - \mathbf{w}_{\text{man}} + \mathbf{w}_{\text{woman}} \approx \mathbf{w}_{\text{queen}}$ (Mikolov

Table 6. Three architectures at a glance.

Architecture	Designed for	Key idea	Landmark
CNN	Images, video, grids	Local filters plus weight sharing yield equivariant feature hierarchies	(LeCun et al. 1998; Krizhevsky et al. 2012)
RNN / LSTM	Sequences, time series	Recurrence carries state; gating fights vanishing gradients	(Hochreiter and Schmidhuber 1997)
Transformer	Text — and increasingly everything	Self-attention lets every token see every other; trains in parallel	(Vaswani et al. 2017)

et al. 2013). Meaning becomes geometry: similar things cluster, relations are (roughly) directions. The same trick now embeds users, products, images, and code.

Latent space and diffusion models. Generative models compress data into a lower-dimensional *latent* code from which they can reconstruct or create. Variational autoencoders learn a probabilistic latent space and sample from it (Kingma and Welling 2014); GANs pit a generator against a discriminator until fakes become indistinguishable (Goodfellow et al. 2014). **Diffusion Models** (Ho et al. 2020) currently dominate image and audio synthesis by reversing a gradual noise addition process ($q(\mathbf{x}_t \mid \mathbf{x}_{t-1})$): a U-Net or Vision Transformer ($p_{\boldsymbol{\theta}}(\mathbf{x}_{t-1} \mid \mathbf{x}_t)$) is trained to iteratively predict and remove Gaussian noise, turning random noise into clear samples.

Large language models. An LLM does one thing: predict the next *token* (a sub-word unit) given the previous ones. The network outputs a score z_j for every vocabulary entry, and the softmax turns scores into a distribution,

$$p(y = j \mid \mathbf{x}) = \frac{\exp(z_j)}{\sum_{k=1}^{V} \exp(z_k)}, \qquad \mathcal{L}_{\text{CE}} = -\log p(y_{\text{true}} \mid \mathbf{x}), \tag{30}$$

the cross-entropy loss — logistic regression's loss, at vocabulary scale. **Causal masking and LLM taxonomy.** For generative language modelling, transformers must not look into the future. A **causal mask** M sets upper-triangular attention logits to $-\infty$:

$$M_{ij} = \begin{cases} 0 & \text{if } j \le i \\ -\infty & \text{if } j > i \end{cases}, \qquad \text{CausalAttention}(Q, K, V) = \text{softmax}\left(\frac{QK^\top + M}{\sqrt{d_k}}\right) V, \tag{31}$$

ensuring position i attends only to tokens $j \le i$. This establishes the three major Transformer design families:

Table 7. The three Transformer architecture families.

Family	Attention Type	Primary Use Case	Examples
Decoder-only	Causal / Masked	Autoregressive text generation	GPT-4, Llama 3, Claude
Encoder-only	Bidirectional	Representation, classification, search	BERT, RoBERTa
Encoder-Decoder	Cross + Causal	Translation, summarization	T5, BART

Pretraining minimises cross-entropy over trillions of tokens of web text. Early *scaling laws* (Kaplan et al. 2020) suggested that parameters should grow faster than data. However, the compute-optimal **Chinchilla scaling laws** (Hoffmann et al. 2022) proved that model size and training tokens should scale in equal $1:1$ proportion, steering modern LLMs toward smaller,

denser architectures trained on vastly more tokens. GPT-3 demonstrated that sufficiently large models perform new tasks from a handful of in-context examples with no weight updates (Brown et al. 2020). Alignment then shapes behaviour: supervised instruction tuning, followed by reinforcement learning from human feedback, trains models to follow instructions and avoid harmful outputs (Christiano et al. 2017; Ouyang et al. 2022). At generation time a *temperature* knob interpolates between greedy and adventurous sampling.

How an LLM writes one token

1. Tokenise the prompt into sub-word tokens.
2. Embed each token as a vector (plus positional information).
3. Pass the sequence through stacked transformer blocks: each token attends to all previous tokens.
4. Map the hidden state vector of the final sequence position through a linear layer and a softmax over the vocabulary.
5. Sample the next token from that distribution.
6. Append it to the sequence and repeat — one forward pass per generated token.[a]

[a] In production, **Key-Value (KV) Caching** stores previously computed K and V tensors in memory, reducing per-token generation step complexity from $O(N^2)$ to $O(N)$.

Big models, big responsibilities: Hallucinations & Contamination

Language models frequently generate syntactically convincing but factually false claims — known as **hallucinations**. Furthermore, because pretraining datasets scrape web data, **benchmark contamination** (test data leaking into training sets) can artificially inflate evaluation scores. Practical habits for the LLM era: verify claims against primary sources; prefer the smallest model that does the job; audit benchmarks for leakage; disclose when output is machine-generated; and remember that fluency is evidence of statistical pattern, not of truth.

Hands-on with Python

```python
from transformers import pipeline

clf = pipeline("sentiment-analysis",
model="distilbert-base-uncased-finetuned-sst-2-english")
print(clf("This course is fantastic!"))
# [{'label': 'POSITIVE', 'score': 0.9998...}]
```

A fine-tuned transformer classifier in four lines — the first run downloads the model (Wolf et al. 2020).

Check your understanding

1. Remove the nonlinearity from an MLP: what functions can the resulting network represent, and why?
2. Give two concrete reasons transformers train faster than RNNs on the same hardware.
3. In the next-token formulation, what does “temperature = 0” correspond to?

Sources & further reading

- F. Rosenblatt (1958). "The Perceptron: A Probabilistic Model for Information Storage and Organization in the Brain". In: *Psychological Review* 65.6, pp. 386–408
- M. Minsky and S. Papert (1969). *Perceptrons: An Introduction to Computational Geometry*. Cambridge, MA: MIT Press
- D. E. Rumelhart et al. (1986). "Learning Representations by Back-Propagating Errors". In: *Nature* 323.6088, pp. 533–536
- K. Hornik et al. (1989). "Multilayer Feedforward Networks Are Universal Approximators". In: *Neural Networks* 2.5, pp. 359–366
- V. Nair and G. E. Hinton (2010). "Rectified Linear Units Improve Restricted Boltzmann Machines". In: *Proceedings of the 27th International Conference on Machine Learning (ICML)*, pp. 807–814
- Y. LeCun et al. (1998). "Gradient-Based Learning Applied to Document Recognition". In: *Proceedings of the IEEE* 86.11, pp. 2278–2324
- S. Hochreiter and J. Schmidhuber (1997). "Long Short-Term Memory". In: *Neural Computation* 9.8, pp. 1735–1780
- K. He et al. (2016). "Deep Residual Learning for Image Recognition". In: *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 770–778
- A. Vaswani et al. (2017). "Attention Is All You Need". In: *Advances in Neural Information Processing Systems 30*, pp. 5998–6008
- J. Su et al. (2024). "RoFormer: Enhanced Transformer with Rotary Position Embedding". In: *Neurocomputing* 568, p. 127063
- T. Mikolov et al. (2013). "Distributed Representations of Words and Phrases and Their Compositionality". In: *Advances in Neural Information Processing Systems 26*, pp. 3111–3119
- D. P. Kingma and M. Welling (2014). "Auto-Encoding Variational Bayes". In: *International Conference on Learning Representations (ICLR)*
- I. Goodfellow et al. (2014). "Generative Adversarial Nets". In: *Advances in Neural Information Processing Systems 27*, pp. 2672–2680
- J. Ho et al. (2020). "Denoising Diffusion Probabilistic Models". In: *Advances in Neural Information Processing Systems 33*, pp. 6840–6851
- T. B. Brown et al. (2020). "Language Models Are Few-Shot Learners". In: *Advances in Neural Information Processing Systems 33*, pp. 1877–1901
- J. Kaplan et al. (2020). "Scaling Laws for Neural Language Models". In: *arXiv preprint arXiv:2001.08361*
- J. Hoffmann et al. (2022). "Training Compute-Optimal Large Language Models". In: *arXiv preprint arXiv:2203.15556*
- P. F. Christiano et al. (2017). "Deep Reinforcement Learning from Human Preferences". In: *Advances in Neural Information Processing Systems 30*, pp. 4299–4307
- L. Ouyang et al. (2022). "Training Language Models to Follow Instructions with Human Feedback". In: *Advances in Neural Information Processing Systems 35*, pp. 27730–27744
- T. Wolf et al. (2020). "Transformers: State-of-the-Art Natural Language Processing". In: *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing: System Demonstrations*, pp. 38–45
- I. Goodfellow et al. (2016). *Deep Learning*. Cambridge, MA: MIT Press
- C. M. Bishop and H. Bishop (2024). *Deep Learning: Foundations and Concepts*. Cham: Springer

Where to go next

The guide ends; the field does not. A few well-marked paths, matched to what you now know:

- **Strengthen the mathematics:** (Strang 2019; Wasserman 2004; Boyd and Vandenberghe 2004).
- **Go deep on classical ML:** (Hastie et al. 2009; Bishop 2006), alongside the scikit-learn documentation (Pedregosa et al. 2011).
- **Deep learning proper:** (Goodfellow et al. 2016; Bishop and Bishop 2024), and the runnable-notebook textbook of Zhang et al. (2023).
- **Practice-first:** the free online course of Howard et al. (2024).
- **Build with LLMs & RAG:** the Hugging Face ecosystem (Wolf et al. 2020), read alongside (Vaswani et al. 2017; Brown et al. 2020; Ouyang et al. 2022). Combine vector embeddings with external document databases via Retrieval-Augmented Generation (RAG) to ground model responses.
- **Stay grounded:** (Christian 2020; Bender et al. 2021).

Suggested mini-projects, one per module transition:

1. Predict housing prices from a public dataset (Modules 2–3: regression, regularisation, honest evaluation).
2. Cluster and anomaly-detect a transactions dataset (Module 3: K-Means, isolation forest, and metric trade-offs).
3. Fine-tune a small transformer classifier on your own texts (Module 4: embeddings, cross-entropy, transfer learning).

AI is not a spectator sport. The mathematics of Module 2 becomes real the first time a gradient-descent loop you wrote yourself converges; the abstractions of Module 4 become real the first time a model you fine-tuned answers a question in your own domain. Start small, cite your sources, question your metrics — and enjoy the ride.

Practical Coding Projects Series

To accompany the theoretical foundation developed across the four modules, a complete series of six production-grade coding projects is provided in the repository's `projects/` directory (https://github.com/DanielBerns/AI-course). Each project bridges theoretical concepts to runnable Python implementation using industry-standard frameworks (`NumPy`, `Pandas`, `Scikit-Learn`, `XGBoost`, `PyTorch`, and `Transformers`), with explicit emphasis on data cleaning, exploratory visualization, model diagnostics, resumable training, and inference pipelines.

Project 1: Data Pipeline, Exploratory Analysis & Algorithmic Bias Audit

Curriculum Mapping: Module 1 (The AI Landscape, Compute/Cloud, Data Pipelines, Ethics & Safety).

Overview & Learning Objectives: This project implements the end-to-end data engineering and ethical auditing pipeline that precedes model training. Students work with real-world clinical data (UCI Breast Cancer Diagnostic dataset) with injected corruptions and demographic proxy groups.

1. **Data Cleaning & Engineering:** Ingest messy tabular data, compute imputation statistics, and handle outliers using interquartile range (IQR) clipping.
2. **Exploratory Data Analysis (EDA):** Build publication-quality data quality visualizations (missingness profiles, KDE distributions, and correlation matrices).
3. **Ethical & Algorithmic Bias Auditing:** Audit demographic representation gaps, evaluate Disparate Impact Ratios (80% rule), and compute Statistical Parity and Equalized Odds metrics.

Execution Command:

```
python projects/01_data_analysis_and_ethics/data_pipeline_demo.py
```

Hands-on Exercises: (1) Extend `cleaning.py` to support dynamic one-hot encoding with high-cardinality handling; (2) Modify `bias_audit.py` to compute Equal Opportunity Difference ($\text{TPR}_{\text{unpriv}} - \text{TPR}_{\text{priv}}$); (3) Document demographic representation gaps in a formal model card.

Project 2: Math Engine from Scratch (Linear Algebra, Stats & Optimization)

Curriculum Mapping: Module 2 (Mathematics and Data Foundations).

Overview & Key Topics: Translates core mathematical mechanics into pure NumPy implementations from first principles.

1. **Linear Algebra & Dimensionality Reduction:** `PCAFromScratch` via eigen-decomposition of the covariance matrix ($A\mathbf{v} = \lambda\mathbf{v}$) and Singular Value Decomposition ($X = U\Sigma V^\top$).
2. **First-Order Optimization Algorithms:** Pure NumPy implementation of Vanilla Gradient Descent, Momentum, RMSprop, and Adam optimizers with trajectory tracking.
3. **Probability & Statistics:** Central Limit Theorem verification ($\sigma_{\bar{x}} = \sigma/\sqrt{n}$) and exact Bayesian Beta-Binomial conjugate updating.

Execution Command:

```
python projects/02_math_and_optimization/run_math_sandbox.py
```

Hands-on Exercises: (1) Implement Nesterov Accelerated Gradient (NAG) in `optimizers.py`; (2) Implement automatic component selection for $\geq 95\%$ variance retention in `pca_from_scratch.py`; (3) Simulate vanishing and exploding gradients across a 10-layer linear transformation stack.

Project 3: Production-Ready Classical Machine Learning Pipeline & Diagnostics

Curriculum Mapping: Module 3 (Classical Machine Learning: The Core Engine).

Overview & Key Capabilities: Constructs an end-to-end machine learning pipeline covering supervised classification, unsupervised clustering, anomaly detection, and diagnostic learning curves.

1. **Pipeline Preprocessing:** Scikit-Learn `ColumnTransformer` handling numerical scaling and categorical encoding.
2. **Model Evaluation & Diagnostics:** Dynamic Learning Curves plotting train vs. validation ROC-AUC scores over dataset subsets to diagnose High Variance (overfitting) vs. High Bias (underfitting).
3. **Unsupervised Mechanics:** K-Means clustering evaluated with Silhouette Coefficients ($s(i) = \frac{b(i)-a(i)}{\max(a(i),b(i))}$) across candidate K, and Isolation Forest anomaly scoring.
4. **Production Serving:** Pipeline serialization (`joblib`) and low-latency `ClassicalInferenceService`.

Execution Command:

```
python projects/03_classical_machine_learning/train_pipeline.py
```

Hands-on Exercises: (1) Add `RandomizedSearchCV` hyperparameter tuning over XGBoost trees; (2) Implement a Validation Curve for regularization strength C in Logistic Regression; (3) Compare SMOTE vs. `class_weight='balanced'` on imbalanced data.

Project 4: Deep Learning Foundations & Resumable Training Pipeline

Curriculum Mapping: Module 4 (Neural Networks, Backpropagation, PyTorch/Keras foundations).

Overview & Key Capabilities: Bridges manual matrix calculus to deep learning framework primitives and enterprise checkpointing.

1. **NumPy Backprop Engine:** 2-layer Neural Network with manual matrix calculus derivatives ($\boldsymbol{\delta}^{(L)} = \nabla_{\mathbf{a}^{(L)}} \mathcal{L} \odot \phi'(\mathbf{z}^{(L)})$, $\boldsymbol{\delta}^{(\ell)} = (W^{(\ell+1)\top} \boldsymbol{\delta}^{(\ell+1)}) \odot \phi'(\mathbf{z}^{(\ell)})$).
2. **PyTorch vs. Keras Parity:** Modular `PyTorchMLP` implementation side-by-side with Keras functional equivalent code.
3. **Resumable Training Architecture:** `CheckpointManager` saving complete PyTorch state dictionaries (`model_state_dict`, `optimizer_state_dict`, `scheduler_state_dict`, epoch, and metric history) enabling seamless pause/resume capabilities across process interruptions.
4. **Inference Service:** High-throughput PyTorch batch inference pipeline.

Execution Command:

```
python projects/04_deep_learning_foundations/train_resumable.py
```

Hands-on Exercises: (1) Extend `mlp_from_scratch.py` to support arbitrary L-layer deep stacks with Softmax output; (2) Add Early Stopping patience counter state persistence to `checkpoint_manager.py`; (3) Evaluate `CosineAnnealingLR` scheduling.

Project 5: Computer Vision & Sequential Architectures (CNNs & LSTMs)

Curriculum Mapping: Module 4 (Architectures: CNNs and RNNs/LSTMs).

Overview & Key Capabilities: Implements the two foundational deep learning architectures for spatial grid data and temporal sequences.

1. **Convolutional Neural Networks (CNNs):** PyTorch 2D CNN with Residual Skip Connections ($\mathbf{y} = \text{LayerNorm}(\mathbf{x} + \mathcal{F}(\mathbf{x}))$), BatchNorm, and spatial pooling.
2. **Recurrent Networks (LSTMs):** Multi-layer PyTorch LSTM sequence classifier ($\mathbf{h}_t = \tanh(W_h \mathbf{h}_{t-1} + W_x \mathbf{x}_t + \mathbf{b})$) with memory gating.
3. **Trainer Engine:** `DeepModelTrainer` with `CosineAnnealingLR` scheduling and checkpointing.

Execution Command:

```
python projects/05_vision_and_sequence_models/train_vision_sequence.py
```

Hands-on Exercises: (1) Extend `cnn_model.py` to plot activation feature maps of intermediate convolutional layers; (2) Implement a Bidirectional LSTM in `lstm_model.py` and compare classification metrics.

Project 6: Transformer Architectures & LLM Fine-Tuning Pipeline

Curriculum Mapping: Module 4 (Transformers, Generative AI & Large Language Models).

Overview & Key Mechanics: Implements self-attention from scratch, fine-tunes pretrained models, and controls next-token decoding.

1. **Attention from Scratch:** Scaled Dot-Product Attention ($\text{Attention}(Q, K, V) = \text{softmax}\left(\frac{QK^\top + M}{\sqrt{d_k}}\right)V$) and Causal Attention Masking ($M_{ij} = -\infty$ for $j > i$).
2. **Transformer Block:** Multi-Head Attention, Pre-Layer Normalization, GELU Feed-Forward Network, and Residual Skip Connections.
3. **Hugging Face Fine-Tuning:** Pretrained transformer fine-tuning pipeline (`DistilBERT`/`BERT`).
4. **LLM Generation Control:** Next-token sampling engine supporting Temperature scaling (T), Top-k truncation, and Top-p (nucleus) sampling.

Execution Command:

```
python projects/06_transformers_and_llms/train_transformer.py
```

Hands-on Exercises: (1) Extend `transformer_scratch.py` to implement Rotary Position Embeddings (RoPE); (2) Implement Repetition Penalty (penalty ≥ 1.0) in `llm_inference.py` to reduce duplicate generation.

Appendix: Answer Key for Check Your Understanding

This appendix provides concise model answers for all self-check exercises across the four modules.

Module 1: Introduction and the AI Landscape

1. **Classification:**
   - *Chess engine:* Weak/Narrow AI. Excels strictly at tree search and position evaluation in chess; cannot generalize to any other task.
   - *Spam filter:* Weak/Narrow AI. Solves binary text classification for email filtering only.
   - *Startup demo ("autonomous reasoning"):* Weak/Narrow AI. Current commercial models (LLMs, agents) operate via statistical pattern matching and prompt orchestration; none possess true broad transfer or Artificial General Intelligence (AGI).
2. **GPU vs CPU throughput:** Deep learning training consists overwhelmingly of parallel matrix-vector products (tensor arithmetic). GPUs feature thousands of concurrent, lightweight arithmetic cores optimized for high-throughput parallel floating-point operations ($A\mathbf{x} + \mathbf{b}$), whereas CPUs feature a few heavy cores optimized for low-latency sequential logic.
3. **Job application screening model harms & mitigations:**
   - *Harm 1 (Historical Bias Propagation):* Model penalizes female candidates due to historical gender imbalance in resume training data. *Mitigation:* Strip demographic proxy features and audit for Equalized Odds / Disparate Impact (80% rule).
   - *Harm 2 (Representation Gap / Outlier Rejection):* Nontraditional career paths or non-standard university names receive falsely low scores. *Mitigation:* Human-in-the-loop oversight for borderline rejections and dynamic threshold calibration.

Module 2: Mathematics and Data Foundations

1. **Eigenvector of Covariance Matrix:** An eigenvector specifies a principal direction (axis) along which the dataset features co-vary, such that projecting data onto this axis preserves variance without linear distortion. Its corresponding eigenvalue measures the total variance along that axis.
2. **Bayes' Theorem with 10% Prevalence:** Using equation (4): $P(\text{disease} \mid +) = \frac{0.99 \times 0.10}{(0.99 \times 0.10) + (0.05 \times 0.90)} = \frac{0.099}{0.099 + 0.045} = \frac{0.099}{0.144} \approx 0.6875$ (68.8%). As prevalence rises from 1% to 10%, the posterior probability of disease given a positive test jumps from 17% to nearly 69% because true positives now outweigh false alarms.
3. **Divergence with $\eta = 1.1$ for $J(w) = w^2$:** Gradient is $\nabla J(w) = 2w$. Update rule: $w_{t+1} = w_t - 1.1(2w_t) = w_t - 2.2w_t = -1.2w_t$. The parameter flips sign and grows in magnitude by $1.2\times$ each step ($w_0 = 5 \to -6 \to 7.2 \to -8.64\ldots$), overshooting the minimum at $w = 0$ and diverging to $\pm\infty$.

Module 3: Classical Machine Learning

1. **Cancer Screening Metric:** Prioritize **Recall (Sensitivity)** to minimize False Negatives (missing an actual cancer case). *Cost:* Precision drops, leading to more False Positives (false alarms), requiring follow-up confirmatory testing and temporary patient anxiety.
2. **K-Means on Concentric Rings:** K-Means minimizes Euclidean distance to cluster centroids, implicitly assuming convex, spherical clusters of equal size. Concentric rings are non-convex

and linearly non-separable in 2D Euclidean space, causing K-Means to slice through the rings radially. *Remedy:* Spectral clustering or DBSCAN.

3. **Cross-Validation Score Variance (0.62 to 0.91):** High variance across folds indicates that the model is unstable and highly sensitive to specific training samples (overfitting / high variance), or that the dataset suffers from class imbalance or data drift across folds. *Action:* Apply stratified k-fold cross-validation, increase regularization, or gather more training samples.

Module 4: Transition to Deep Learning and Modern AI

1. **MLP without Nonlinearity:** Without nonlinear activations ϕ, a multi-layer network collapses mathematically into a single linear transformation: $\mathbf{a}^{(L)} = W^{(L)}W^{(L-1)} \dots W^{(1)}\mathbf{x} = W_{\text{effective}}\mathbf{x}$. It can only represent linear functions (hyperplanes) and cannot learn non-linear boundaries.
2. **Transformers vs RNNs Training Speed:** (1) *Parallelization:* Transformers process all tokens in a sequence simultaneously via matrix multiplication ($QK^\top$), whereas RNNs must process tokens sequentially step-by-step ($\mathbf{h}_t = f(\mathbf{h}_{t-1}, \mathbf{x}_t)$), blocking GPU parallel execution; (2) *Direct Paths:* Self-attention connects any pair of tokens in $O(1)$ operations regardless of distance, avoiding unrolling backpropagation through time.
3. **Temperature = 0 in LLMs:** Setting temperature $= 0$ corresponds to **greedy decoding** (arg max sampling). The softmax probabilities approach a one-hot distribution, selecting the single highest-probability token deterministically every step.

Glossary

Table 8. Quick reference for the vocabulary used in this guide.

Term	Meaning
Artificial intelligence (AI)	Broad field: systems that perform tasks associated with intelligent behaviour.
Machine learning (ML)	Sub-field: algorithms whose performance on a task improves from data.
Deep learning (DL)	ML with multi-layer neural networks that learn their own features.
Feature / label	An input measurement / the target answer supplied during supervised training.
Model	A parameterised function fitted to data.
Loss function	A scalar score of prediction error; training minimises its average.
Gradient	The vector of partial derivatives: the direction of steepest ascent.
Backpropagation	Chain-rule algorithm computing the loss gradient for every weight, layer by layer.
Overfitting	Memorising the training set; excellent training scores, poor generalisation.
Embedding	A dense vector encoding of an item's meaning; similarity becomes geometry.
Token	The sub-word unit that language models read and write.
Parameter	A learnable number inside a model; LLMs have billions.
Fine-tuning	Adapting a pretrained model to a new task with a small dataset.
Hallucination	Fluent model output that is not grounded in fact.

References

Amodei, D., C. Olah, J. Steinhardt, et al. (2016). "Concrete Problems in AI Safety". In: *arXiv preprint arXiv:1606.06565*.

Bender, E. M., T. Gebru, A. McMillan-Major, and S. Shmitchell (2021). "On the Dangers of Stochastic Parrots: Can Language Models Be Too Big?" In: *Proceedings of the 2021 ACM Conference on Fairness, Accountability, and Transparency (FAccT)*, pp. 610–623.

Bishop, C. M. (2006). *Pattern Recognition and Machine Learning*. New York: Springer.

Bishop, C. M. and H. Bishop (2024). *Deep Learning: Foundations and Concepts*. Cham: Springer.

Boyd, S. and L. Vandenberghe (2004). *Convex Optimization*. Cambridge: Cambridge University Press.

Breiman, L. (2001). "Random Forests". In: *Machine Learning* 45.1, pp. 5–32.

Brown, T. B., B. Mann, N. Ryder, et al. (2020). "Language Models Are Few-Shot Learners". In: *Advances in Neural Information Processing Systems 33*, pp. 1877–1901.

Buolamwini, J. and T. Gebru (2018). "Gender Shades: Intersectional Accuracy Disparities in Commercial Gender Classification". In: *Proceedings of the 1st Conference on Fairness, Accountability and Transparency*, pp. 77–91.

Chen, T. and C. Guestrin (2016). "XGBoost: A Scalable Tree Boosting System". In: *Proceedings of the 22nd ACM SIGKDD International Conference on Knowledge Discovery and Data Mining*, pp. 785–794.

Christian, B. (2020). *The Alignment Problem: Machine Learning and Human Values*. New York: W. W. Norton & Company.

Christiano, P. F., J. Leike, T. B. Brown, M. Martic, S. Legg, and D. Amodei (2017). "Deep Reinforcement Learning from Human Preferences". In: *Advances in Neural Information Processing Systems 30*, pp. 4299–4307.

Cortes, C. and V. Vapnik (1995). "Support-Vector Networks". In: *Machine Learning* 20.3, pp. 273–297.

Fawcett, T. (2006). "An Introduction to ROC Analysis". In: *Pattern Recognition Letters* 27.8, pp. 861–874.

Goodfellow, I., Y. Bengio, and A. Courville (2016). *Deep Learning*. Cambridge, MA: MIT Press.

Goodfellow, I. et al. (2014). "Generative Adversarial Nets". In: *Advances in Neural Information Processing Systems 27*, pp. 2672–2680.

Harris, C. R., K. J. Millman, S. J. van der Walt, et al. (2020). "Array Programming with NumPy". In: *Nature* 585, pp. 357–362.

Hastie, T., R. Tibshirani, and J. Friedman (2009). *The Elements of Statistical Learning: Data Mining, Inference, and Prediction*. 2nd ed. New York: Springer.

He, K., X. Zhang, S. Ren, and J. Sun (2016). "Deep Residual Learning for Image Recognition". In: *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 770–778.

Ho, J., A. Jain, and P. Abbeel (2020). "Denoising Diffusion Probabilistic Models". In: *Advances in Neural Information Processing Systems 33*, pp. 6840–6851.

Hochreiter, S. and J. Schmidhuber (1997). "Long Short-Term Memory". In: *Neural Computation* 9.8, pp. 1735–1780.

Hoffmann, J. et al. (2022). "Training Compute-Optimal Large Language Models". In: *arXiv preprint arXiv:2203.15556*.

Hornik, K., M. Stinchcombe, and H. White (1989). "Multilayer Feedforward Networks Are Universal Approximators". In: *Neural Networks* 2.5, pp. 359–366.

Howard, J. et al. (2024). *Practical Deep Learning for Coders*. fast.ai. URL: https://course.fast.ai (visited on 12/01/2024).

Jouppi, N. P., C. Young, N. Patil, et al. (2017). "In-Datacenter Performance Analysis of a Tensor Processing Unit". In: *Proceedings of the 44th Annual International Symposium on Computer Architecture (ISCA)*, pp. 1–12.

Kaplan, J., S. McCandlish, T. Henighan, et al. (2020). "Scaling Laws for Neural Language Models". In: *arXiv preprint arXiv:2001.08361*.

Kingma, D. P. and J. Ba (2015). "Adam: A Method for Stochastic Optimization". In: *International Conference on Learning Representations (ICLR)*.

Kingma, D. P. and M. Welling (2014). “Auto-Encoding Variational Bayes”. In: *International Conference on Learning Representations (ICLR)*.

Krizhevsky, A., I. Sutskever, and G. E. Hinton (2012). “ImageNet Classification with Deep Convolutional Neural Networks”. In: *Advances in Neural Information Processing Systems 25*, pp. 1097–1105.

LeCun, Y., Y. Bengio, and G. Hinton (2015). “Deep Learning”. In: *Nature* 521.7553, pp. 436–444.

LeCun, Y., L. Bottou, Y. Bengio, and P. Haffner (1998). “Gradient-Based Learning Applied to Document Recognition”. In: *Proceedings of the IEEE* 86.11, pp. 2278–2324.

Liu, F. T., K. M. Ting, and Z.-H. Zhou (2008). “Isolation Forest”. In: *Proceedings of the 8th IEEE International Conference on Data Mining (ICDM)*, pp. 413–422.

MacQueen, J. (1967). “Some Methods for Classification and Analysis of Multivariate Observations”. In: *Proceedings of the Fifth Berkeley Symposium on Mathematical Statistics and Probability*. Vol. 1, pp. 281–297.

McKinney, W. (2010). “Data Structures for Statistical Computing in Python”. In: *Proceedings of the 9th Python in Science Conference (SciPy)*, pp. 56–61.

Mikolov, T., I. Sutskever, K. Chen, G. S. Corrado, and J. Dean (2013). “Distributed Representations of Words and Phrases and Their Compositionality”. In: *Advances in Neural Information Processing Systems 26*, pp. 3111–3119.

Minsky, M. and S. Papert (1969). *Perceptrons: An Introduction to Computational Geometry*. Cambridge, MA: MIT Press.

Mitchell, T. M. (1997). *Machine Learning*. New York: McGraw-Hill.

Nair, V. and G. E. Hinton (2010). “Rectified Linear Units Improve Restricted Boltzmann Machines”. In: *Proceedings of the 27th International Conference on Machine Learning (ICML)*, pp. 807–814.

Ouyang, L., J. Wu, X. Jiang, et al. (2022). “Training Language Models to Follow Instructions with Human Feedback”. In: *Advances in Neural Information Processing Systems 35*, pp. 27730–27744.

Patterson, D., J. Gonzalez, Q. Le, et al. (2021). “Carbon Emissions and Large Neural Network Training”. In: *Advances in Neural Information Processing Systems 34*, pp. 13470–13481.

Pedregosa, F., G. Varoquaux, A. Gramfort, et al. (2011). “Scikit-learn: Machine Learning in Python”. In: *Journal of Machine Learning Research* 12, pp. 2825–2830.

Rosenblatt, F. (1958). “The Perceptron: A Probabilistic Model for Information Storage and Organization in the Brain”. In: *Psychological Review* 65.6, pp. 386–408.

Rousseeuw, P. J. (1987). “Silhouettes: A Graphical Aid to the Interpretation and Validation of Cluster Analysis”. In: *Journal of Computational and Applied Mathematics* 20, pp. 53–65.

Rumelhart, D. E., G. E. Hinton, and R. J. Williams (1986). “Learning Representations by Back-Propagating Errors”. In: *Nature* 323.6088, pp. 533–536.

Russell, S. J. and P. Norvig (2021). *Artificial Intelligence: A Modern Approach*. 4th ed. Hoboken, NJ: Pearson.

Searle, J. R. (1980). “Minds, Brains, and Programs”. In: *Behavioral and Brain Sciences* 3.3, pp. 417–424.

Silver, D., A. Huang, C. J. Maddison, et al. (2016). “Mastering the Game of Go with Deep Neural Networks and Tree Search”. In: *Nature* 529.7587, pp. 484–489.

Strang, G. (2019). *Linear Algebra and Learning from Data*. Wellesley, MA: Wellesley–Cambridge Press.

Strubell, E., A. Ganesh, and A. McCallum (2019). “Energy and Policy Considerations for Deep Learning in NLP”. In: *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics (ACL)*, pp. 3645–3650.

Su, J., M. Ahmed, Y. Lu, S. Pan, W. Bo, and Y. Liu (2024). “RoFormer: Enhanced Transformer with Rotary Position Embedding”. In: *Neurocomputing* 568, p. 127063.

Turing, A. M. (1950). “Computing Machinery and Intelligence”. In: *Mind* 59.236, pp. 433–460.

VanderPlas, J. (2016). *Python Data Science Handbook: Essential Tools for Working with Data*. Sebastopol, CA: O’Reilly Media.

Vaswani, A. et al. (2017). “Attention Is All You Need”. In: *Advances in Neural Information Processing Systems 30*, pp. 5998–6008.

Wasserman, L. (2004). *All of Statistics: A Concise Course in Statistical Inference*. New York: Springer.

Wolf, T. et al. (2020). “Transformers: State-of-the-Art Natural Language Processing”. In: *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing: System Demonstrations*, pp. 38–45.

Zhang, A., Z. C. Lipton, M. Li, and A. J. Smola (2023). *Dive into Deep Learning*. Cambridge: Cambridge University Press.

— End of document —