

Package ‘Strategy’

March 9, 2020

Type Package

Title X

Version 1.0

Date 2020-03-09

Author D. Bonnery

Maintainer D. Bonnery <dbonnery@umd.edu>

Description Data

Depends ggplot2,
leaflet,
spatstat,
sf

License GPL (>= 2)

LazyLoad yes

LazyData true

RoxygenNote 7.0.2

R topics documented:

addpiechartclustermarkers	2
closestpointonpolygon	3
closestpointonseg	4
closestpointsontwopolygons	4
closestpointsontwosegments	5
distpointtopoly	6
distpointtoseg	6
distpolytopoly	7
distpolytopoly2	8
distsegmenttopoly	8
distsegmenttosegment	9
dist_areas_f	10
extractpolygonsaslist	10
Generate_Discrete_Time_Epidemic	11

Generate_U	11
neighbourhoods	12
newdist	13
polydistmat	14
polysmalldistmat	15
projpointonseg_a	16
ranges.gap	16
rangesoverlap	17
risktobeinfected	17
risktobeinfectedbydistancetoallinfectedunit	18
risktobeinfectedbydistancetooneinfectedunit	18
segment.intersect	19
test	20
triangleorientation	20
updatedist	21
Index	22

addpiechartclustermarkers

Change leaflet cluster markers to pie charts

Description

Change leaflet cluster markers to pie charts

Usage

addpiechartclustermarkers(map, .data, .colors, group)

Arguments

- map the map to add awesome pie chart cluster markers to
- .data data for the cluster markers
- .colors a vector of colors of at least the same size that nlevels(.data[[group]])
- group the name of a factor variable of .data

Examples

```
data("breweries91",package="leaflet")
breweries91$goodbear<-sample(as.factor(c("terrific","marvelous","culparterretaping")),nrow(breweries91),replac
library(leaflet)
library(dplyr)
leaflet(breweries91) %>%
addTiles() %>%
addAwesomeMarkers()
map<-leaflet(breweries91) %>%addTiles()
addpiechartclustermarkers(map,.data=breweries91,.colors=c("red","green","blue"),group="goodbear")
```

```
leaflet(breweries91) %>%
addTiles() %>%
addpiechartclustermarkers(.data=breweries91,.colors=c("red","green","blue"),group="goodbear")
```

closestpointonpolygon *computes the coordinates of the closest point on the border of a polygon to a point in the plane*

Description

computes the coordinates of the closest point on the border of a polygon to a point in the plane

Usage

```
closestpointonpolygon(p, .poly)
```

Arguments

p	a numeric vector of length 2
.poly	a nx2 numeric matrix, representing a polygon. Each row of the matrix are the coordinates of a vertice of the polygon.

Value

the coordinates of the closest point on the polygon

Examples

```
zz<-function(){
.poly=matrix(sample(0:4,6,rep=T),3,2)[c(1:3,1),]
p<-sample(0:4,2,rep=T)
dd<-distpointtopoly(p,.poly)
plot(rbind(p,.poly),cex=.5,main=paste0("Distance: ", signif(dd,3)),asp=1,xlim=range(s),ylim=range(s),xaxt='n',yaxt='n')
points(.poly,type="l",lwd=2)
cc<-rbind(p,closestpointonpolygon(p,.poly))
points(cc,col="red",cex=2)
points(cc,type="l",lty=3,col="red")
}

par(oma=c(0,0,0,0),mfrow=c(2,2))
set.seed(3);replicate(4,zz())
```

closestpointonseg	<i>computes the coordinates of the closest point on a segment to a point in the plane</i>
-------------------	---

Description

computes the coordinates of the closest point on a segment to a point in the plane

Usage

```
closestpointonseg(p, s)
```

Arguments

p	a numeric vector of length 2
s	a 2x2 numeric matrix, representing a segment. Each row of the matrix are the coordinates of a extreme point of the segment.

Examples

```
zz<-function(p){
  s=matrix(c(0,1,0,0),2,2)
  plot(s,type="l",xlim=c(-.5,1.5),
    xlab="",ylab="",
    xaxt='n',yaxt='n')
  points(x=p[1],y=p[2] ,col="red",cex=.5)
  points(closestpointonseg(p,s)[1],closestpointonseg(p,s)[2],col="red",cex=.5)
  segments(x0 = p[1],y0=p[2],x1=closestpointonseg(p,s)[1],y1=closestpointonseg(p,s)[2],col="red")
  par(mfrow=c(3,3))
  set.seed(1);replicate(9,zz(c(runif(1,-.5,1.5),runif(1,-1,1))))
```

closestpointsonwopolygons	<i>computes the coordinates of the closest point on the border of a polygon to a point in the plane</i>
---------------------------	---

Description

computes the coordinates of the closest point on the border of a polygon to a point in the plane

Usage

```
closestpointsonwopolygons(poly1, poly2)
```

Arguments

poly1	a nx2 numeric matrix, representing a polygon. Each row of the matrix are the coordinates of a vertex of the polygon.
poly2	a nx2 numeric matrix, representing a polygon. Each row of the matrix are the coordinates of a vertex of the polygon.

Value

the coordinates of the closest point on the polygon

Examples

```
zz<-function(){
  poly1=matrix(sample(0:6,6,rep=T),3,2)[c(1:3,1),]
  poly2=matrix(sample(0:6,6,rep=T),3,2)[c(1:3,1),]
  s<-rbind(poly1,poly2)
  dd<-distpolytopoly(poly1,poly2)
  plot(s,cex=.5,main=paste0("Distance: ", signif(dd,3)),asp=1,xlim=range(s),ylim=range(s),xaxt='n',yaxt='n',xlab=
  points(poly1,type="l",lwd=2)
  points(poly2,type="l",lwd=2)
  cc<-closestpointstwowpolygons(poly1,poly2)
  points(cc,col="red",cex=2)
  points(cc,type="l",col="red",lty=3)
}

par(oma=c(0,0,0,0),mfrow=c(2,2))
set.seed(2);replicate(4,zz())
```

closestpointstwowsegments

computes the coordinates of the closest point on a segment to a point in the plane

Description

computes the coordinates of the closest point on a segment to a point in the plane

Usage

```
closestpointstwowsegments(s1, s2)
```

Arguments

s1	a 2x2 numeric matrix, representing a segment. Each row of the matrix are the coordinates of a extreme point of the segment.
s2	a 2x2 numeric matrix, representing a segment. Each row of the matrix are the coordinates of a extreme point of the segment.

distpointtopoly	<i>computes the distance between a point and a polygon</i>
-----------------	--

Description

computes the distance between a point and a polygon

Usage

```
distpointtopoly(p, .poly)
```

Arguments

p	a numeric vector of length 2
.poly	a n x2 numeric matrix, representing a polygon. Each row of the matrix are the coordinates of a vertex of the polygon.

Examples

```
zz<-function(p){
s=matrix(c(0,3,0,0),2,2)
plot(s,type="l",xlim=c(-2,5),ylim=c(-2,2),
xlab="",ylab="",
xaxt='n',yaxt='n')
points(x=p[1],y=p[2],col="red",cex=.5)
points(closestpointonseg(p,s)[1],closestpointonseg(p,s)[2],col="red",cex=.5)
segments(x0 = p[1],y0=p[2],x1=closestpointonseg(p,s)[1],y1=closestpointonseg(p,s)[2],col="red")
text((closestpointonseg(p,s)[1]+p[1])/2,(closestpointonseg(p,s)[2]+p[2])/2,round(distpointtoseg(p,s),2))}
par(mfrow=c(3,3))
set.seed(1);replicate(9,zz(c(sample(-2:3,1),sample(-2:2,1))))
```

distpointtoseg	<i>computes the distance between a point and a segment</i>
----------------	--

Description

computes the distance between a point and a segment

Usage

```
distpointtoseg(p, s)
```

Arguments

p	a numeric vector of length 2
s	a 2x2 numeric matrix, representing a segment. Each row of the matrix are the coordinates of a extreme point of the segment.

Examples

```

zz<-function(p){
s=matrix(c(0,3,0,0),2,2)
plot(s,type="l",xlim=c(-2,5),ylim=c(-2,2),
xlab="",ylab="",
xaxt='n',yaxt='n')
points(x=p[1],y=p[2] ,col="red",cex=.5)
points(closestpointonseg(p,s)[1],closestpointonseg(p,s)[2],col="red",cex=.5)
segments(x0 = p[1],y0=p[2],x1=closestpointonseg(p,s)[1],y1=closestpointonseg(p,s)[2],col="red")
text((closestpointonseg(p,s)[1]+p[1])/2,(closestpointonseg(p,s)[2]+p[2])/2,round(distpointtoseg(p,s),2))}
par(mfrow=c(3,3))
set.seed(1);replicate(9,zz(c(sample(-2:3,1),sample(-2:2,1))))

```

distpolytopoly

*Computes distance between two polygons***Description**

Computes distance between two polygons

Usage

```
distpolytopoly(poly1, poly2)
```

Arguments

poly1	a polygon (a n x 2 numerical matrix)
poly2	a polygon (a n x 2 numerical matrix)

Value

a positive number, the distance between the two polygons

Examples

```

polys=lapply(c(0:1),function(x){
cbind(c(x,x,x+.5,x+.5,x),c(0,1,1,0,0))})
par(mfrow=c(1,1))
plot(do.call(rbind,polys),xlab="",yaxt="n")
for(.poly in polys){segments(x0 = .poly[-5,1],y0 = .poly[-5,2],.poly[-1,1],.poly[-1,2])}
distpolytopoly(polys[[1]],polys[[2]])
polys=lapply(c(1:2),function(x){
cbind(c(-x,-x,x,x,-x),c(-x,x,x,-x,-x))})
par(mfrow=c(1,1))
plot(do.call(rbind,polys),xlab="",yaxt="n")
for(.poly in polys){segments(x0 = .poly[-5,1],y0 = .poly[-5,2],.poly[-1,1],.poly[-1,2])}
distpolytopoly(polys[[1]],polys[[2]])
polys=lapply(c(1:2),function(x){
cbind(c(-2,-2,2,2,-2),c(-1,1,1,-1,-1))[,c(x,(1:2)[-x])])})

```

```
par(mfrow=c(1,1))
plot(do.call(rbind, polys), xlab="", yaxt="n")
for(.poly in polys){segments(x0 = .poly[-5,1], y0 = .poly[-5,2], .poly[-1,1], .poly[-1,2])}
distpolytopoly(polys[[1]], polys[[2]])
```

distpolytopoly2	<i>Computes distance between two polygons, only works for polygons that do not intersect</i>
-----------------	--

Description

Computes distance between two polygons, only works for polygons that do not intersect

Usage

```
distpolytopoly2(poly1, poly2)
```

Arguments

- poly1 a polygon (a n x 2 numerical matrix)
- poly2 a polygon (a n x 2 numerical matrix)

Value

a positive number, the distance between the two polygons

distsegmenttopoly	<i>Distance between a segment and a polygon</i>
-------------------	---

Description

Distance between a segment and a polygon

Usage

```
distsegmenttopoly(s, .poly)
```

Arguments

- s a 2x2 numeric matrix, representing a segment. Each row of the matrix are the coordinates of a extreme point of the segment.
- .poly a polygon (a nx2 matrix, each line is a point)

Examples

```
zz<-function(){
  .poly<-matrix(sample(0:6,6,T),3,2)[c(1:3,1),]
  s<-matrix(sample(0:6,6,T),2,2)
  plot(rbind(.poly,s),xlab="",yaxt="n")
  points(.poly,type="l");points(s,type="l")
  points(closestpointsonwopolygons(s,.poly),lty=3,col="red")}
```

distsegmenttosegment *distance segment to segment*

Description

distance segment to segment

Usage

```
distsegmenttosegment(s1, s2)
```

Arguments

s1 a 2x2 numeric matrix, representing a segment. Each row of the matrix are the coordinates of a extreme point of the segment.

s2 a 2x2 numeric matrix, representing a segment. Each row of the matrix are the coordinates of a extreme point of the segment.

Value

a number

Examples

```
zz<-function(){
  s1=matrix(sample(0:4,4,rep=T),2,2)
  s2=matrix(sample(0:4,4,rep=T),2,2)
  s<-rbind(s1,s2)
  dd<-distsegmenttosegment(s1,s2)
  plot(s,cex=.5,main=paste0("Distance: ", signif(dd,3)),asp=1,xlim=range(s),ylim=range(s),xaxt='n',yaxt='n',xlab=
  points(s1,type="l",lwd=2)
  points(s2,type="l",lwd=2)
  cc<-closestpointsonwosegments(s1,s2)
  points(cc ,col="red",cex=2)
  points(cc,type="l",col="red",lty=3)
}

par(oma=c(0,0,0,0),mfrow=c(3,3))
set.seed(3);replicate(9,zz())
```

dist_areas_f	<i>Distances between hexagonal bins</i>
--------------	---

Description

Distances between hexagonal bins

Usage

```
dist_areas_f(
  U,
  delta = (range(U$x)[2] - range(U$x)[1])/100,
  h = neighbourhoods(U, delta)
)
```

Arguments

U : a dataframe containing the numerical variables x and y and preferable hexagon
 delta : needed if hexagon is not a variable of U: bins will be recomputed

Value

a named matrix

Examples

```
data(U)
dist_areas_f(U)[1:3,1:3]
dist_areas_f(U,0.03)[1:3,1:3]
```

extractpolygonsaslist	<i>converts a shapefile to list of polygons (nx2 matrices)</i>
-----------------------	--

Description

converts a shapefile to list of polygons (nx2 matrices)

Usage

```
extractpolygonsaslist(shp)
```

Generate_Discrete_Time_Epidemic
Generate epidemic

Description

Generate epidemic

Usage

```
Generate_Discrete_Time_Epidemic(
  U,
  TT,
  .distriskhalf = 5 * 10-4,
  jumprisk = 10-6,
  delta = 0.05
)
```

Arguments

U	a data.frame
TT	an integer
.distriskhalf	a positive number(default 5*10 ⁻⁴)
jumprisk	=10 ⁻⁶ a positive number
delta	=0.05 a positive number

Examples

```
.distriskhalf=5*10-4;jumprisk=10-6;delta=0.05; TT=10
UE<-Generate_Discrete_Time_Epidemic(U,3)
```

Generate_U *Generate spatial data that matches population counts*

Description

Generate spatial data that matches population counts

Usage

```
Generate_U(SpatialData, .id = NULL, .spatialobject, type = "random")
```

Arguments

SpatialData	: an object of class that includes
type	: argument to be passed to sp::spsample

Examples

```
data(parish110217popest, package="dataONS")
data("mtcty150217population", package="dataONS")
shapeData2<-dataONS::dataParishes_December_2011_Boundaries_EW_BFC()
yy<-unique(get(data(Output_Area_to_Parish_to_Local_Authority_District_December_2011_Lookup_in_England_and_Wale
names(yy)<-tolower(names(yy))
shapeData<-sp::merge(shapeData2,yy,by="par11cd",duplicateGeoms = TRUE)
parish110217popest2<-parish110217popest[
  is.element(parish110217popest$PAR11CD,
    shapeData$par11cd)&
    parish110217popest$year=="mid_2006",
    c("PAR11CD", "Population")]
  names(parish110217popest2)<-tolower(names(parish110217popest2))
shapeData=sp::merge(shapeData,parish110217popest2,by="par11cd",duplicateGeoms = TRUE)
shapeData$population[is.na(shapeData$population)]<-mean(shapeData$population,na.rm=TRUE)
shapeData<-subset(shapeData,is.element(lad11nm ,c("Allerdale", "Barrow-in-Furness", "Carlisle", "C

U<-Generate_U(shapeData,.id="par11cd",.spatialobject="st_areasha",type="random")
popbins<-quantile(shapeData$population,(seq_len(11)-1)/10)
poppal <- colorBin(heat.colors(5), bins=popbins, na.color = "#aaff56",reverse = T)
library(leaflet)

leaflet(U) %>%
  addPolygons(data=shapeData,
    stroke=TRUE,
    weight=1,
    color="black",
    fillOpacity=5,
    fillColor=~poppal(shapeData$population)) %>%
  addTiles() %>%
  addLegend(title = "Population count", pal=poppal,
    values=shapeData$population,
    opacity=1,
    na.label = "Not Available")
```

neighbourhoods

hexagonal bins

Description

hexagonal bins

Usage

```
neighbourhoods(
  U,
  delta = (range(U$x, na.rm = TRUE)[2] - range(U$x, na.rm = TRUE)[1])/100
)
```

Arguments

U : a dataframe containing the numerical variables x and y
 delta: controls the bin diameter

Value

a hexbin object hexagonal bins

Examples

```
# plot the hex bins of cumbria
data(U)
plot(neighbourhoods(U,.1))
plot(neighbourhoods(U,.01))
plot(neighbourhoods(U,.001))
```

newdist	<i>compute distances between new infected and exposed</i>
---------	---

Description

compute distances between new infected and exposed

Usage

```
newdist(
  closeddistances = NULL,
  U,
  sick,
  new.sicks = NULL,
  delta = 0.005,
  dist_areas = dist_areas_f(U, delta)
)
```

Arguments

closeddistances NULL, or a named list with 2 named elements: closeddistances\$ra, closeddistances\$id
 U a data.frame with the variables hexagon (can be any bin identifier), x, y : coordinates,
 sick a vector of integers
 new.sicks a vector of integers
 delta a positive number : a threshold
 dist_areas: a function between

Value

NULL, or a named list with 2 named elements: closeddistances\$ra, closeddistances\$sd

Examples

```
data(UE,package="Strategy")
delta<-.005
sicks<-(1:nrow(UE))[UE$I001=="sick"]
closeddistances=newdist(NULL,UE,sicks)
do.call(cbind,closeddistances)[1:3,]
```

polydistmat

Compute distance matrix for a list of polygons

Description

Compute distance matrix for a list of polygons

Usage

```
polydistmat(list.poly)
```

Arguments

list.poly a list of nx2 numeric matrices

Value

a $(n*(n-1)/2) \times 3$ matrix

Examples

```
polys=lapply(c(0:3,5:7),function(x){
  cbind(c(x,x,x+.5,x+.5,x),c(0,1,1,0,0))})
par(mfrow=c(1,1))
plot(do.call(rbind,polys),xlab="",yaxt="n")
for(.poly in polys){segments(x0 = .poly[-5,1],y0 = .poly[-5,2],.poly[-1,1],.poly[-1,2])}
polydistmat(polys)
#data(Avo_fields,package="Strategy")
#polygons<-Avo_fields
#MM<-polydistmat(extractpolygonsaslist(Avo_fields))
#parallel::detectCores()
#save(MM,file=file.path(Mydirectories::googledrive.directory(),"Travail/Recherche/Travaux/Epidemiologie/Strate
```

polysmalldistmat	<i>Compute distance matrix for a list of polygons</i>
------------------	---

Description

Compute distance matrix for a list of polygons

Usage

```
polysmalldistmat(
  list.poly,
  delta,
  gradients = cbind(c(0, 1), c(1, 0), c(1, 1), c(1, -1))
)
```

Arguments

`list.poly` a list of nx2 numeric matrices

Value

a $(n*(n-1)/2) \times 3$ matrix

Examples

```
zz<-function(delta){
  list.poly=plyr::alply(cbind(rep(0:8,9),rep(0:8,each=9))[sample(81,20),],1,function(x){
    cbind(x[1]+c(0,0,.5,.5,0),x[2]+c(0,.5,.5,0,0))})
  gradients=cbind(c(0,1),c(1,0),c(1,1),c(1,-1))
  par(mfrow=c(1,1))
  plot(do.call(rbind,list.poly),xlab="",yaxt="n",ylab="",cex=.1,main=paste0("Match polygons distant less than ",delta))
  for(.poly in list.poly){points(.poly,type="l")}
  X=polysmalldistmat(list.poly,delta)
  for(i in 1:nrow(X)){
    points(closestpointsonwopolygons(list.poly[[X[i,1]]],list.poly[[X[i,2]]]),col="red",type="l",lty=3)
  }
  set.seed(1);zz(.5)
  set.seed(1);zz(1)
  set.seed(1);zz(2)
}
```

projpointonseg_a	<i>computes the position of a projected point in the basis formed by a segment</i>
------------------	--

Description

computes the position of a projected point in the basis formed by a segment

Usage

```
projpointonseg_a(p, s, method = "euclidean")
```

Arguments

p	a numeric vector of length 2
s	a 2x2 numeric matrix, representing a segment. Each row of the matrix are the coordinates of a extreme point of the segment.

Examples

```
zz<-function(p){
  s=matrix(c(0,1,0,0),2,2)
  plot(s,type="l",xlim=c(-.5,1.5),
    xlab="",ylab="",
    xaxt='n',yaxt='n')
  points(x=p[1],y=p[2] ,col="red",cex=2)
  points(closestpointonseg(p,s)[1],closestpointonseg(p,s)[2],col="red",cex=2)
  segments(x0 = p[1],y0=p[2],x1=closestpointonseg(p,s)[1],y1=closestpointonseg(p,s)[2],col="red")
  text(projpointonseg_a(p,s),-.8,paste0("a=",projpointonseg_a(p,s)))}
par(oma=c(0,0,0,0),mfrow=c(2,2))
zz(c(-.5,1))
zz(0:1)
zz(c(.5,1))
zz(c(1.5,1))
```

ranges.gap	<i>tells if two ranges overlap</i>
------------	------------------------------------

Description

tells if two ranges overlap

Usage

```
ranges.gap(r1, r2)
```


Examples

```
zz<-function(){
  x=sample(6,4,rep=F)
  r1=x[1:2];r2=x[3:4]
  plot(x,rep(0,4),main=ranges.gap(r1,r2),yaxt='n',xlab='',ylab='')
  segments(x[1],0,x[2],0,col="blue")
  segments(x[3],0,x[4],0,col="green")}
par(mfrow=c(2,2),oma=c(0,0,0,0))
set.seed(8);replicate(4,zz())
```

<code>rangesoverlap</code>	<i>tells if two ranges overlap</i>
----------------------------	------------------------------------

Description

tells if two ranges overlap

Usage

```
rangesoverlap(r1, r2)
```

<code>risktobeinfected</code>	<i>Computes the risk to be infected</i>
-------------------------------	---

Description

Computes the risk to be infected

Usage

```
risktobeinfected(
  U,
  closedistances = NULL,
  sick,
  new.sicks = NULL,
  .distriskhalf = 5 * 10^(-4),
  jumprisk = 10^-6,
  delta = 0.01,
  previouslyexposed = c(),
  previousrisk = numeric()
)
```

Examples

```
y=rep("Sane",nrow(U));y[sample(length(y),10)]<-"sick"
jumprisk=10^-6
.distriskhalf=10^-6
```

`risktobeinfectedbydistancetoallinfectedunit`

Risk to be infected by many neighbours a neighbour at a certain distance

Description

Risk to be infected by many neighbours a neighbour at a certain distance

Usage

```
risktobeinfectedbydistancetoallinfectedunit(
  .dist,
  nI,
  .distriskhalf = 5 * 10(-4),
  jumprisk = 10-6
)
```

Arguments

`.dist` : a vector (distances)
`.disthalfrisk` : distance for which the risk is one half
`nI`: total number of infected
`jumprisk`: probability to be infected by one person, no matter how far he(she) is

Value

$1 - (\text{prod}(1 - \text{risktobeinfectedbydistancetooneinfectedunit}(\text{.dist}, \text{distriskhalf})) * (1 - \text{jumprisk})^{\text{nI}})$

Examples

```
#Risk to be ingfected 2 m from the victim when the 50%risk distance is 1 m:
risktobeinfectedbydistancetooneinfectedunit(2,1)
```

`risktobeinfectedbydistancetooneinfectedunit`

Risk to be infected by a neighbour at a distance x

Description

Risk to be infected by a neighbour at a distance x

Usage

```
risktobeinfectedbydistancetooneinfectedunit(.dist, .distriskhalf = 5 * 10(-4))
```

Arguments

.dist : a distance
 .disthalfrisk : distance for which the risk is one half

Value

$\exp(-.dist/(\log(2)*.distriskhalf))$

Examples

```
#Risk to be ingfected 2 m from the victim when the 50%risk distance is 1 m:
risktobeinfectedbydistancetooneinfectedunit(2,1)
```

segment.intersect	<i>test if two segments intersect</i>
-------------------	---------------------------------------

Description

test if two segments intersect

Usage

```
segment.intersect(s1, s2)
```

Arguments

s1 a 2x2 numeric matrix, representing a segment. Each row of the matrix are the coordinates of an extreme point of the segment.
 s2 a 2x2 numeric matrix, representing a segment. Each row of the matrix are the coordinates of an extreme point of the segment.

Examples

```
zz<-function(s1=matrix(sample(0:3,4,rep=T),2,2),s2=matrix(sample(0:3,4,rep=T),2,2)){
  si<-segment.intersect(s1,s2)
  s<-rbind(s1,s2)
  plot(s,cex=.5,main=if(si){"Intersect"}else{"Disjoint"},xlab="",ylab="",xaxt='n', yaxt='n',xlim=range(s)+c(-1,1),
  points(s1,type="l")
  points(s2,type="l")
  text(s[,1],s[,2],toupper(letters[1:4]),cex=1,col="red")
}
par(mfrow=c(3,4),mar=c(5,3,2,2))
set.seed(12);replicate(4,zz())
zz(matrix(0,2,2),matrix(0,2,2))
zz(matrix(0,2,2),matrix(1,2,2))
zz(matrix(c(1,1,1,1),2,2),matrix(c(2,3,2,3),2,2))
zz(matrix(c(1,1,0,0),2,2),matrix(c(0,1,0,0),2,2))
```

```
zz(matrix(c(1,3,1,3),2,2),matrix(c(2,4,2,4),2,2))
zz(matrix(c(0,1,0,1),2,2),matrix(c(2,3,2,3),2,2))
zz(matrix(c(0,4,0,4),2,2),matrix(c(1,3,1,3),2,2))
zz(matrix(c(0,1,0,1),2,2),matrix(c(0,3,0,3),2,2))
```

test	<i>runCompare</i>
------	-------------------

Description

Shiny App to

Usage

test()

Examples

```
package1<-NULL
package2<-NULL
runCompare()
```

triangleorientation	<i>computes the orientation of a triangle</i>
---------------------	---

Description

computes the orientation of a triangle

Usage

triangleorientation(s)

Arguments

s a 3x2 numeric matrix, representing a triangle. Each row of the matrix are the coordinates of an extreme point of the triangle.

Examples

```
zz<-function(p){
s=matrix(sample(0:4,6,rep=T),3,2)
plot(s[c(1:3,1),],,type="l",main=if(triangleorientation(s)==1){"+"}else{if(triangleorientation(s)==-1){"-"}else
text(s[,1],s[,2],toupper(letters[1:3]),cex=1,col="red")
}
par(mfrow=c(2,2),mar=c(5,3,2,2))
set.seed(7);replicate(4,zz(c(sample(-2:3,1),sample(-2:2,1))))
```

updatedist	<i>update the list of the already nown distances between subjects with distances between new infected and exposed</i>
------------	---

Description

update the list of the already nown distances between subjects with distances between new infected and exposed

Usage

```
updatedist(
  closedistances = NULL,
  U,
  sick,
  new.sicks = NULL,
  delta = 0.005,
  dist_areas = dist_areas_f(U, delta)
)
```

Arguments

closedistances	NULL, or a named list with 2 named elements: closedistances\$ra, closedistances\$id
U	a data.frame with the variables hexagon (can be any bin identifier), x, y : coordinates,
sick	a vector of integers indicating the row numbers in U for sick
new.sicks	a vector of integers indicating the row numbers in U for new sick
delta	a positive number : a threshold
dist_areas:	a function between

Value

NULL, or a named list with 2 named elements: closedistances\$ra, closedistances\$id

Examples

```
data(UE, package="Strategy")
delta<-.005
sick<-(1:nrow(UE))[UE$I001=="sick"]
closedistances=updatedist(NULL,UE,sick)
do.call(cbind,closedistances)[1:3,]
```

Index

`addpiechartclustermarkers`, [2](#)

`closestpointonpolygon`, [3](#)
`closestpointonseg`, [4](#)
`closestpointsonwopolygons`, [4](#)
`closestpointsonwosegments`, [5](#)

`dist_areas_f`, [10](#)
`distpointtopoly`, [6](#)
`distpointtoseg`, [6](#)
`distpolytopoly`, [7](#)
`distpolytopoly2`, [8](#)
`distsegmenttopoly`, [8](#)
`distsegmenttosegment`, [9](#)

`extractpolygonsaslist`, [10](#)

`Generate_Discrete_Time_Epidemic`, [11](#)
`Generate_U`, [11](#)

`neighbourhoods`, [12](#)
`newdist`, [13](#)

`polydistmat`, [14](#)
`polysmalldistmat`, [15](#)
`projpointonseg_a`, [16](#)

`ranges.gap`, [16](#)
`rangesoverlap`, [17](#)
`risktobeinfected`, [17](#)
`risktobeinfectedbydistancetoallinfectedunit`,
[18](#)
`risktobeinfectedbydistancetooneinfectedunit`,
[18](#)

`segment.intersect`, [19](#)

`test`, [20](#)
`triangleorientation`, [20](#)

`updatedist`, [21](#)