

# Package ‘Strategy’

March 11, 2020

**Type** Package

**Title** X

**Version** 1.0

**Date** 2020-03-11

**Author** D. Bonnery

**Maintainer** D. Bonnery <dbonnery@umd.edu>

**Description** Data

**Depends** ggplot2,  
leaflet,  
spatstat,  
sf

**License** GPL (>= 2)

**LazyLoad** yes

**LazyData** true

**RoxygenNote** 7.0.2

## R topics documented:

addpiechartclustermarkers . . . . .	2
closestpointonpolygon . . . . .	3
closestpointonseg . . . . .	4
closestpointsonwopolygons . . . . .	4
closestpointsonwopolygons_n . . . . .	5
closestpointsonwosegments . . . . .	6
closestpointsonwosegments_n . . . . .	6
distpointtopoly . . . . .	7
distpointtoseg . . . . .	8
distpolytopoly . . . . .	9
distpolytopoly2 . . . . .	10
distsegmenttopoly . . . . .	10
distsegmenttosegment . . . . .	11
dist_areas_f . . . . .	12

extractpolygonsaslist . . . . .	12
Generate_Discrete_Time_Epidemic . . . . .	13
Generate_U . . . . .	13
neighbourhoods . . . . .	14
newdist . . . . .	15
polydistmat . . . . .	16
polysmalldistmat . . . . .	17
projpointonseg_a . . . . .	18
ranges.gap . . . . .	18
rangesoverlap . . . . .	19
risktobeinfected . . . . .	20
risktobeinfectedbydistancetoallinfectedunit . . . . .	20
risktobeinfectedbydistancetooneinfectedunit . . . . .	21
segment.intersect . . . . .	22
test . . . . .	22
triangleorientation . . . . .	23
updatedist . . . . .	23
<b>Index</b>	<b>25</b>

---

addpiechartclustermarkers
<i>Change leaflet cluster markers to pie charts</i>

---

**Description**

Change leaflet cluster markers to pie charts

**Usage**

addpiechartclustermarkers(map, .data, .colors, group)

**Arguments**

- map                    the map to add awesome pie chart cluster markers to
- .data                  data for the cluster markers
- .colors                a vector of colors of at least the same size that nlevels(.data[[group]])
- group                  the name of a factor variable of .data

**Examples**

```
data("breweries91",package="leaflet")
breweries91$goodbear<-sample(as.factor(c("terrific","marvelous","culparterretaping")),nrow(breweries91),replac
library(leaflet)
library(dplyr)
leaflet(breweries91) %>%
addTiles() %>%
addAwesomeMarkers()
```

```
map<-leaflet(breweries91) %>%addTiles()
addpiechartclustermarkers(map,.data=breweries91,.colors=c("red","green","blue"),group="goodbear")
leaflet(breweries91) %>%
addTiles() %>%
addpiechartclustermarkers(.data=breweries91,.colors=c("red","green","blue"),group="goodbear")
```

---

`closestpointonpolygon` *computes the coordinates of the closest point on the border of a polygon to a point in the plane*

---

### Description

computes the coordinates of the closest point on the border of a polygon to a point in the plane

### Usage

```
closestpointonpolygon(p, .poly)
```

### Arguments

<code>p</code>	a numeric vector of length 2
<code>.poly</code>	a nx2 numeric matrix, representing a polygon. Each row of the matrix are the coordinates of a vertice of the polygon.

### Value

the coordinates of the closest point on the polygon

### Examples

```
zz<-function(){
.poly=matrix(sample(0:4,6,rep=T),3,2)[c(1:3,1),]
p<-sample(0:4,2,rep=T)
dd<-distpointtopoly(p,.poly)
plot(rbind(p,.poly),cex=.5,main=paste0("Distance: ", signif(dd,3)),
asp=1,xlim=range(cbind(p,.poly)),ylim=range(cbind(p,.poly)),xaxt='n',yaxt='n',xlab='',ylab='')
points(.poly,type="l",lwd=2)
cc<-rbind(p,closestpointonpolygon(p,.poly))
points(cc,col="red",cex=2)
points(cc,type="l",lty=3,col="red")
}

par(oma=c(0,0,0,0),mfrow=c(2,2))
set.seed(3);replicate(4,zz())
```

---

closestpointonseg	<i>computes the coordinates of the closest point on a segment to a point in the plane</i>
-------------------	---

---

### Description

computes the coordinates of the closest point on a segment to a point in the plane

### Usage

```
closestpointonseg(p, s)
```

### Arguments

p	a numeric vector of length 2
s	a 2x2 numeric matrix, representing a segment. Each row of the matrix are the coordinates of a extreme point of the segment.

### Examples

```
zz<-function(p){
  s=matrix(c(0,1,0,0),2,2)
  plot(s,type="l",xlim=c(-.5,1.5),
    xlab="",ylab="",
    xaxt='n',yaxt='n')
  points(x=p[1],y=p[2] ,col="red",cex=.5)
  points(closestpointonseg(p,s)[1],closestpointonseg(p,s)[2],col="red",cex=.5)
  segments(x0 = p[1],y0=p[2],x1=closestpointonseg(p,s)[1],y1=closestpointonseg(p,s)[2],col="red")
  par(mfrow=c(3,3))
  set.seed(1);replicate(9,zz(c(runif(1,-.5,1.5),runif(1,-1,1))))
```

---

closestpointsonwopolygons	<i>computes the coordinates of the closest point on the border of a polygon to a point in the plane</i>
---------------------------	---

---

### Description

computes the coordinates of the closest point on the border of a polygon to a point in the plane

### Usage

```
closestpointsonwopolygons(poly1, poly2)
```

**Arguments**

poly1	a nx2 numeric matrix, representing a polygon. Each row of the matrix are the coordinates of a vertice of the polygon.
poly2	a nx2 numeric matrix, representing a polygon. Each row of the matrix are the coordinates of a vertice of the polygon.

**Value**

the coordinates of the closest point on the polygon

**Examples**

```

zz<-function(){
poly1=matrix(sample(0:6,6,rep=T),3,2)[c(1:3,1),]
poly2=matrix(sample(0:6,6,rep=T),3,2)[c(1:3,1),]
s<-rbind(poly1,poly2)
dd<-distpolytopoly(poly1,poly2)
plot(s,cex=.5,main=paste0("Distance: ", signif(dd,3)),asp=1,xlim=range(s),ylim=range(s),xaxt='n',yaxt='n',xlab=
points(poly1,type="l",lwd=2)
points(poly2,type="l",lwd=2)
cc<-closestpointstwopolygons(poly1,poly2)
points(cc,col="red",cex=2)
points(cc,type="l",col="red",lty=3)
}

par(oma=c(0,0,0,0),mfrow=c(2,2))
set.seed(2);replicate(4,zz())

```

---

closestpointstwopolygons\_n

*Compute minimum distance between two polygons*

---

**Description**

Compute minimum distance between two polygons

**Usage**

```
closestpointstwopolygons_n(poly1, poly2)
```

**Arguments**

poly1	a nx2 numeric matrix, representing a polygon. Each row of the matrix are the coordinates of a vertice of the polygon.
poly2	a nx2 numeric matrix, representing a polygon. Each row of the matrix are the coordinates of a vertice of the polygon.

**Examples**

```

zz<-function(){
poly1=matrix(sample(0:6,6,rep=T),3,2)[c(1:3,1),]
poly2=matrix(sample(0:6,6,rep=T),3,2)[c(1:3,1),]
s<-rbind(poly1,poly2)
dd<-distpolytopoly(poly1,poly2)
plot(s,cex=.5,main=paste0("Distance: ", signif(dd,3)),asp=1,xlim=range(s),ylim=range(s),xaxt='n',yaxt='n',xlab=
points(poly1,type="l",lwd=2)
points(poly2,type="l",lwd=2)
for(cc in closestpointsonwopolygons_n(poly1,poly2)){
points(cc ,col="red",cex=2)
points(cc,type="l",col="red",lty=3)}
}

par(oma=c(0,0,0,0),mfrow=c(2,2))
set.seed(2);replicate(4,zz())

```

---

closestpointsonwosegments

*computes the coordinates of the closest point on a segment to a point in the plane*

---

**Description**

computes the coordinates of the closest point on a segment to a point in the plane

**Usage**

```
closestpointsonwosegments(s1, s2)
```

**Arguments**

s1	a 2x2 numeric matrix, representing a segment. Each row of the matrix are the coordinates of a extreme point of the segment.
s2	a 2x2 numeric matrix, representing a segment. Each row of the matrix are the coordinates of a extreme point of the segment.

---

closestpointsonwosegments\_n

*returns a list of one or more pair of points, one on each of two segments, with minimal distance*

---

**Description**

returns a list of one or more pair of points, one on each of two segments, with minimal distance

**Usage**

```
closestpointsonwosegments_n(s1, s2)
```

**Arguments**

**s1** a 2x2 numeric matrix, representing a segment. Each row of the matrix are the coordinates of a extreme point of the segment.

**s2** a 2x2 numeric matrix, representing a segment. Each row of the matrix are the coordinates of a extreme point of the segment.

**Value**

a list of 2x2 numeric matrices, representing a segment.

**Examples**

```
zz<-function(){
  s1=matrix(sample(0:4,4,rep=T),2,2)
  s2=matrix(sample(0:4,4,rep=T),2,2)
  s<-rbind(s1,s2)
  dd<-distsegmenttosegment(s1,s2)
  plot(s,cex=.5,main=paste0("Distance: ", signif(dd,3)),asp=1,xlim=range(s),ylim=range(s),xaxt='n',yaxt='n',xlab=
  points(s1,type="l",lwd=2)
  points(s2,type="l",lwd=2)
  cc<-closestpointsonwosegments_n(s1,s2)
  for(ccc in cc){points(ccc,col="red",cex=2)
  points(ccc,type="l",col="red",lty=3)}
}

par(oma=c(0,0,0,0),mfrow=c(3,3))
set.seed(3);replicate(9,zz())
closestpointsonwosegments_n(matrix(c(0,3,0,0),2,2),matrix(c(1,2,0,0),2,2))
```

---

distpointtopoly	<i>computes the distance between a point and a polygon</i>
-----------------	--

---

**Description**

computes the distance between a point and a polygon

**Usage**

```
distpointtopoly(p, .poly)
```

**Arguments**

**p** a numeric vector of length 2

**.poly** a n x2 numeric matrix, representing a polygon. Each row of the matrix are the coordinates of a verticeof the polygon.

**Examples**

```

zz<-function(){
p<-sample(0:6,2,rep=T)
.poly<-matrix(sample(0:6,6,rep=T),3,2)[c(1:3,1),]
plot(rbind(.poly,p),
xlab="",ylab="",
cex=.2,main=paste0("Distance: ",signif(distpointtopoly(p,.poly),3)))
points(.poly,type='l')
points(x=p[1],y=p[2] ,col="red",cex=1)
points(closestpointonpolygon(p,.poly)[1],closestpointonpolygon(p,.poly)[2],col="red",cex=1)
points(rbind(p,closestpointonpolygon(p,.poly)),col="red",lty=3,type='l')
par(mfrow=c(3,3),oma=c(0,0,1,0),mar=c(2,2.1,1,0.1))
set.seed(1);replicate(9,zz())

```

---

distpointtoseg	<i>computes the distance between a point and a segment</i>
----------------	--

---

**Description**

computes the distance between a point and a segment

**Usage**

```
distpointtoseg(p, s)
```

**Arguments**

p	a numeric vector of length 2
s	a 2x2 numeric matrix, representing a segment. Each row of the matrix are the coordinates of a extreme point of the segment.

**Examples**

```

zz<-function(p){
s=matrix(c(0,3,0,0),2,2)
plot(s,type="l",xlim=c(-2,5),ylim=c(-2,2),
xlab="",ylab="",
xaxt='n',yaxt='n')
points(x=p[1],y=p[2] ,col="red",cex=.5)
points(closestpointonseg(p,s)[1],closestpointonseg(p,s)[2],col="red",cex=.5)
segments(x0 = p[1],y0=p[2],x1=closestpointonseg(p,s)[1],y1=closestpointonseg(p,s)[2],col="red")
text((closestpointonseg(p,s)[1]+p[1])/2,(closestpointonseg(p,s)[2]+p[2])/2,round(distpointtoseg(p,s),2))
par(mfrow=c(3,3))
set.seed(1);replicate(9,zz(c(sample(-2:3,1),sample(-2:2,1))))

```



---

distpolytopoly	<i>Computes distance between two polygons</i>
----------------	---

---

**Description**

Computes distance between two polygons

**Usage**

distpolytopoly(poly1, poly2)

**Arguments**

- poly1            a polygon (a n x 2 numerical matrix)
- poly2            a polygon (a n x 2 numerical matrix)

**Value**

a positive number, the distance between the two polygons

**See Also**

distsegmenttopoly

**Examples**

```
zz<-function(){
poly1=matrix(sample(0:6,6,rep=T),3,2)[c(1:3,1),]
poly2=matrix(sample(0:6,6,rep=T),3,2)[c(1:3,1),]
s<-rbind(poly1,poly2)
dd<-distpolytopoly(poly1,poly2)
plot(s,cex=.5,main=paste0("Distance: ", signif(dd,3)),asp=1,xlim=range(s),ylim=range(s),xaxt='n',yaxt='n',xlab=
points(poly1,type="l",lwd=2)
points(poly2,type="l",lwd=2)
for(cc in closestpointstwopolygons_n(poly1,poly2)){
points(cc,type="l",col="red",lty=3)}}

par(mfrow=c(2,2),oma=c(0,0,1,0),mar=c(0.1,0.1,1,0.1))
set.seed(2);replicate(4,zz())
```

---

distpolytopoly2	<i>Computes distance between two polygons, only works for polygons that do not intersect</i>
-----------------	--

---

**Description**

Computes distance between two polygons, only works for polygons that do not intersect

**Usage**

```
distpolytopoly2(poly1, poly2)
```

**Arguments**

poly1	a polygon (a n x 2 numerical matrix)
poly2	a polygon (a n x 2 numerical matrix)

**Value**

a positive number, the distance between the two polygons

---

distsegmenttopoly	<i>Distance between a segment and a polygon</i>
-------------------	---

---

**Description**

Distance between a segment and a polygon

**Usage**

```
distsegmenttopoly(s, .poly)
```

**Arguments**

s	a 2x2 numeric matrix, representing a segment. Each row of the matrix are the coordinates of a extreme point of the segment.
.poly	a polygon (a nx2 matrix, each line is a point)

**Examples**

```
zz<-function(){
  .poly<-matrix(sample(0:6,6,T),3,2)[c(1:3,1),]
  s<-matrix(sample(0:6,6,T),2,2)
  plot(rbind(.poly,s),xlab="",yaxt="n")
  points(.poly,type="l");points(s,type="l")
  points(closestpointsonwopolygons(s,.poly),lty=3,col="red")}
```

---

distsegmenttosegment    *distance segment to segment*


---

## Description

distance segment to segment

## Usage

```
distsegmenttosegment(s1, s2)
```

## Arguments

**s1**                    a 2x2 numeric matrix, representing a segment. Each row of the matrix are the coordinates of a extreme point of the segment.

**s2**                    a 2x2 numeric matrix, representing a segment. Each row of the matrix are the coordinates of a extreme point of the segment.

## Value

a number

## Examples

```
zz<-function(){
s1=matrix(sample(0:4,4,rep=T),2,2)
s2=matrix(sample(0:4,4,rep=T),2,2)
s<-rbind(s1,s2)
dd<-distsegmenttosegment(s1,s2)
plot(s,cex=.5,main=paste0("Distance: ", signif(dd,3)),asp=1,xlim=range(s),ylim=range(s),xaxt='n',yaxt='n',xlab=
points(s1,type="l",lwd=2)
points(s2,type="l",lwd=2)
cc<-closestpointstotwosegments(s1,s2)
points(cc,col="red",cex=2)
points(cc,type="l",col="red",lty=3)
}

par(mfrow=c(3,3),oma=c(0,0,0,0),mar=c(1.1,1.2,1,1.1))
set.seed(3);replicate(9,zz())
```

---

dist_areas_f	<i>Distances between hexagonal bins</i>
--------------	---

---

**Description**

Distances between hexagonal bins

**Usage**

```
dist_areas_f(
  U,
  delta = (range(U$x)[2] - range(U$x)[1])/100,
  h = neighbourhoods(U, delta)
)
```

**Arguments**

**U** : a dataframe containing the numerical variables x and y and preferable hexagon

**delta** : needed if hexagon is not a variable of U: bins will be recomputed

**Value**

a named matrix

**Examples**

```
data(U)
dist_areas_f(U)[1:3,1:3]
dist_areas_f(U,0.03)[1:3,1:3]
```

---

extractpolygonsaslist	<i>converts a shapefile to list of polygons (nx2 matrices)</i>
-----------------------	--

---

**Description**

converts a shapefile to list of polygons (nx2 matrices)

**Usage**

```
extractpolygonsaslist(shp)
```

---

Generate\_Discrete\_Time\_Epidemic  
*Generate epidemic*

---

**Description**

Generate epidemic

**Usage**

```
Generate_Discrete_Time_Epidemic(
  U,
  TT,
  .distriskhalf = 5 * 10(-4),
  jumprisk = 10-6,
  delta = 0.05
)
```

**Arguments**

U	a data.frame
TT	an integer
.distriskhalf	a positive number(default 5*10 <sup>(-4)</sup> )
jumprisk	=10 <sup>-6</sup> a positive number
delta	=0.05 a positive number

**Examples**

```
.distriskhalf=5*10(-4);jumprisk=10-6;delta=0.05; TT=10
UE<-Generate_Discrete_Time_Epidemic(U,3)
```

---

Generate\_U *Generate spatial data that matches population counts*

---

**Description**

Generate spatial data that matches population counts

**Usage**

```
Generate_U(SpatialData, .id = NULL, .spatialobject, type = "random")
```

**Arguments**

SpatialData	: an object of class that includes
type	: argument to be passed to sp::spsample

## Examples

```
data(parish110217popest,package="dataONS")
data("mtcty150217population",package="dataONS")
shapeData2<-dataONS::dataParishes_December_2011_Boundaries_EW_BFC()
yy<-unique(get(data(Output_Area_to_Parish_to_Local_Authority_District_December_2011_Lookup_in_England_and_Wale
names(yy)<-tolower(names(yy))
shapeData<-sp::merge(shapeData2,yy,by="par11cd",duplicateGeoms = TRUE)
parish110217popest2<-parish110217popest[
  is.element(parish110217popest$PAR11CD,
    shapeData$par11cd)&
    parish110217popest$year=="mid_2006",
    c("PAR11CD", "Population")]
  names(parish110217popest2)<-tolower(names(parish110217popest2))
shapeData=sp::merge(shapeData,parish110217popest2,by="par11cd",duplicateGeoms = TRUE)
shapeData$population[is.na(shapeData$population)]<-mean(shapeData$population,na.rm=TRUE)
shapeData<-subset(shapeData,is.element(lad11nm ,c("Allerdale", "Barrow-in-Furness", "Carlisle", "C

U<-Generate_U(shapeData,.id="par11cd",.spatialobject="st_areasha",type="random")
popbins<-quantile(shapeData$population,(seq_len(11)-1)/10)
poppal <- colorBin(heat.colors(5), bins=popbins, na.color = "#aaff56",reverse = T)
library(leaflet)

leaflet(U) %>%
  addPolygons(data=shapeData,
    stroke=TRUE,
    weight=1,
    color="black",
    fillOpacity=5,
    fillColor=~poppal(shapeData$population)) %>%
  addTiles() %>%
  addLegend(title = "Population count", pal=poppal,
    values=shapeData$population,
    opacity=1,
    na.label = "Not Available")
```

---

neighbourhoods

*hexagonal bins*


---

## Description

hexagonal bins

## Usage

```
neighbourhoods(
  U,
  delta = (range(U$x, na.rm = TRUE)[2] - range(U$x, na.rm = TRUE)[1])/100
)
```

**Arguments**

U : a dataframe containing the numerical variables x and y  
 delta: controls the bin diameter

**Value**

a hexbin object hexagonal bins

**Examples**

```
# plot the hex bins of cumbria
data(U,package="Strategy")
library("hexbin")
plot(neighbourhoods(U,.1))
plot(neighbourhoods(U,.01))
plot(neighbourhoods(U,.001))
```

---

newdist	<i>compute distances between new infected and exposed</i>
---------	---

---

**Description**

compute distances between new infected and exposed

**Usage**

```
newdist(
  closeddistances = NULL,
  U,
  sick,
  new.sicks = NULL,
  delta = 0.005,
  dist_areas = dist_areas_f(U, delta)
)
```

**Arguments**

closeddistances NULL, or a named list with 2 named elements: closeddistances\$ra, closeddistances\$id  
 U a data.frame with the variables hexagon (can be any bin identifier), x, y : coordinates,  
 sick a vector of integers  
 new.sicks a vector of integers  
 delta a positive number : a threshold  
 dist\_areas: a function between

**Value**

NULL, or a named list with 2 named elements: closedistances\$ra, closedistances\$Id

**Examples**

```
data(UE,package="Strategy")
delta<-.005
sicks<-(1:nrow(UE))[UE$I001=="sick"]
closedistances=newdist(NULL,UE,sicks)
do.call(cbind,closedistances)[1:3,]
```

---

polydistmat

---

*Compute distance matrix for a list of polygons*


---

**Description**

Compute distance matrix for a list of polygons

**Usage**

```
polydistmat(list.poly, .progress = "text")
```

**Arguments**

list.poly            a list of nx2 numeric matrices

**Value**

a  $(n*(n-1)/2) \times 3$  matrix

**Examples**

```
zz<-function(){
  list.poly=plyr::alply(cbind(rep(0:8,9),rep(0:8,each=9))[sample(81,4),],1,function(x){
    cbind(x[1]+c(0,0,.5,.5,0),x[2]+c(0,.5,.5,0,0))})
  gradients=cbind(c(0,1),c(1,0),c(1,1),c(1,-1))
  par(mfrow=c(1,1),oma=c(0,0,0,0),mar=c(0.1,0.1,.1,0.1))
  plot(do.call(rbind,list.poly),xlab="",yaxt="n",ylab="",cex=.1)
  for(i in 1:length(list.poly)){.poly=list.poly[[i]]
    points(.poly,type="l")
    text(mean(.poly[,1]),mean(.poly[,2]),as.roman(i))
  }
  X=polydistmat(list.poly,.progress="none")
  X<-cbind(X,floor(rank(X[,3])))
  colorlink=topo.colors(2*max(X[,4]))[X[,4]]
  for(i in 1:nrow(X)){
    cc<-closestpointontwopolygons(list.poly[[X[i,1]]],list.poly[[X[i,2]]])
    points(cc,col=colorlink[i],type="l",lty=3)
    text(mean(cc[,1]),mean(cc[,2]),signif(X[i,3],3))
  }
}
```



```

}
colnames(X)<-c("polygon 1","polygon 2", "distance","col")
X[,1:3]}
set.seed(1);zz()

```

---

polysmalldistmat

---

*Compute distance matrix for a list of polygons*


---

## Description

Compute distance matrix for a list of polygons

## Usage

```

polysmalldistmat(
  list.poly,
  delta,
  gradients = cbind(c(0, 1), c(1, 0), c(1, 1), c(1, -1)),
  .progress = "none"
)

```

## Arguments

`list.poly` a list of nx2 numeric matrices

## Value

a  $(n*(n-1)/2) \times 3$  matrix

## Examples

```

zz<-function(delta){
  list.poly=plyr::alply(cbind(rep(0:8,9),rep(0:8,each=9)))[sample(81,20),,1,function(x){
    cbind(x[1]+c(0,0,.5,.5,0),x[2]+c(0,.5,.5,0,0))}
  gradients=cbind(c(0,1),c(1,0),c(1,1),c(1,-1))
  par(mfrow=c(1,1),oma=c(0,0,1,0),mar=c(0.1,0.1,1,0.1))
  plot(do.call(rbind,list.poly),xlab="",yaxt="n",ylab="",cex=.1,main=paste0("Match polygons distant less than ",de
  for(.poly in list.poly){points(.poly,type="l")
  X=polysmalldistmat(list.poly,delta)
  for(i in 1:nrow(X)){
    points(closestpointson twopolygons(list.poly[[X[i,1]]],list.poly[[X[i,2]]]),col="red",type="l",lty=3)
  }
  set.seed(1);zz(.5)
  set.seed(1);zz(1)
  set.seed(1);zz(2)
}

```

---

projpointonseg_a	<i>computes the position of a projected point in the basis formed by a segment</i>
------------------	--

---

### Description

computes the position of a projected point in the basis formed by a segment

### Usage

```
projpointonseg_a(p, s, method = "euclidean")
```

### Arguments

p	a numeric vector of length 2
s	a 2x2 numeric matrix, representing a segment. Each row of the matrix are the coordinates of a extreme point of the segment.

### Examples

```
zz<-function(p){
  s=matrix(c(0,1,0,0),2,2)
  plot(s,type="l",xlim=c(-.5,1.5),
    xlab="",ylab="",
    xaxt='n',yaxt='n')
  points(x=p[1],y=p[2] ,col="red",cex=2)
  points(closestpointonseg(p,s)[1],closestpointonseg(p,s)[2],col="red",cex=2)
  segments(x0 = p[1],y0=p[2],x1=closestpointonseg(p,s)[1],y1=closestpointonseg(p,s)[2],col="red")
  text(projpointonseg_a(p,s),-.8,paste0("a=",projpointonseg_a(p,s)))}
par(oma=c(0,0,0,0),mfrow=c(1,4))
zz(c(-.5,1))
zz(0:1)
zz(c(.5,1))
zz(c(1.5,1))
```

---

ranges.gap	<i>Interval length between two ranges (0 if they overlap)</i>
------------	---

---

### Description

Interval length between two ranges (0 if they overlap)

### Usage

```
ranges.gap(r1, r2)
```

**Arguments**

`r1`                    a range a length 2 numerical vector  
`r2`                    a range a length 2 numerical vector

**Examples**

```
par(mfrow=c(1,4),oma=c(0,0,0,0))
set.seed(10);replicate(4,(function(){
r1<-sample(1:8,2);r2<-sample(1:5,2)
plot(cbind(c(r1,r2),0),yaxt='n',xlab='',ylab='',
main=paste0("Gap: ",ranges.gap(r1,r2)))
points(cbind(r1,0),type="l",lwd=3)
points(cbind(r2,0),type="l",col="red")
}))()
```

---

<code>rangesoverlap</code>	<i>tells if two ranges overlap</i>
----------------------------	------------------------------------

---

**Description**

tells if two ranges overlap

**Usage**

```
rangesoverlap(r1, r2)
```

**Arguments**

`r1`                    a range a length 2 numerical vector  
`r2`                    a range a length 2 numerical vector

**Examples**

```
par(mfrow=c(1,4),oma=c(0,0,0,0))
set.seed(8);replicate(4,(function(){
r1<-sample(1:8,2);r2<-sample(1:5,2)
plot(cbind(c(r1,r2),0),yaxt='n',xlab='',ylab='',xaxt='n',
main=paste0(if(rangesoverlap(r1,r2)){"0"}else{"Does not o"},"verlap"))
points(cbind(r1,0),type="l",lwd=3)
points(cbind(r2,0),type="l",col="red")
}))()
```

---

risktobeinfected	<i>Computes the risk to be infected</i>
------------------	---

---

**Description**

Computes the risk to be infected

**Usage**

```
risktobeinfected(
  U,
  closedistances = NULL,
  sick,
  new.sicks = NULL,
  .distriskhalf = 5 * 10^(-4),
  jumprisk = 10^-6,
  delta = 0.01,
  previouslyexposed = c(),
  previousrisk = numeric()
)
```

**Examples**

```
y=rep("Sane",nrow(U));y[sample(length(y),10)]<-"sick"
jumprisk=10^-6
.distriskhalf=10^-6
```

---

risktobeinfectedbydistancetoallinfectedunit	<i>Risk to be infected by many neighbours a neighbour at a certain distance</i>
---	---

---

**Description**

Risk to be infected by many neighbours a neighbour at a certain distance

**Usage**

```
risktobeinfectedbydistancetoallinfectedunit(
  .dist,
  nI,
  .distriskhalf = 5 * 10^(-4),
  jumprisk = 10^-6
)
```

**Arguments**

.dist : a vector (distances)  
 .disthalfrisk : distance for which the risk is one half  
 nI: total number of infected  
 jumprisk: probability to be infected by one person, no matter how far he/she is

**Value**

$1 - (\text{prod}(1 - \text{risktobeinfectedbydistancetooneinfectedunit}(\text{.dist}, \text{distriskhalf})) * (1 - \text{jumprisk})^{\text{nI}})$

**Examples**

```
#Risk to be ingfected 2 m from the victim when the 50%risk distance is 1 m:
risktobeinfectedbydistancetooneinfectedunit(2,1)
```

---

risktobeinfectedbydistancetooneinfectedunit

*Risk to be infected by a neighbour at a distance x*

---

**Description**

Risk to be infected by a neighbour at a distance x

**Usage**

```
risktobeinfectedbydistancetooneinfectedunit(.dist, .distriskhalf = 5 * 10^(-4))
```

**Arguments**

.dist : a distance  
 .disthalfrisk : distance for which the risk is one half

**Value**

$\exp(-\text{.dist}/(\log(2) * \text{distriskhalf}))$

**Examples**

```
#Risk to be ingfected 2 m from the victim when the 50%risk distance is 1 m:
risktobeinfectedbydistancetooneinfectedunit(2,1)
```

---

segment.intersect	<i>test if two segments intersect</i>
-------------------	---------------------------------------

---

**Description**

test if two segments intersect

**Usage**

segment.intersect(s1, s2)

**Arguments**

- s1            a 2x2 numeric matrix, representing a segment. Each row of the matrix are the coordinates of an extreme point of the segment.
- s2            a 2x2 numeric matrix, representing a segment. Each row of the matrix are the coordinates of an extreme point of the segment.

**Examples**

```
zz<-function(s1=matrix(sample(0:3,4,rep=T),2,2),s2=matrix(sample(0:3,4,rep=T),2,2)){
  si<-segment.intersect(s1,s2)
  s<-rbind(s1,s2)
  plot(s,cex=.5,main=if(si){"Intersect"}else{"Disjoint"},xlab="",ylab="",xaxt='n', yaxt='n',xlim=range(s)+c(-1,1),
  points(s1,type="l")
  points(s2,type="l")
  text(s[,1],s[,2],toupper(letters[1:4]),cex=1,col="red")
}
par(mfrow=c(3,4),mar=c(5,3,2,2))
set.seed(12);replicate(4,zz())
zz(matrix(0,2,2),matrix(0,2,2))
zz(matrix(0,2,2),matrix(1,2,2))
zz(matrix(c(1,1,1,1),2,2),matrix(c(2,3,2,3),2,2))
zz(matrix(c(1,1,0,0),2,2),matrix(c(0,1,0,0),2,2))
zz(matrix(c(1,3,1,3),2,2),matrix(c(2,4,2,4),2,2))
zz(matrix(c(0,1,0,1),2,2),matrix(c(2,3,2,3),2,2))
zz(matrix(c(0,4,0,4),2,2),matrix(c(1,3,1,3),2,2))
zz(matrix(c(0,1,0,1),2,2),matrix(c(0,3,0,3),2,2))
```

---

test	<i>runCompare</i>
------	-------------------

---

**Description**

Shiny App to

**Usage**

```
test()
```

**Examples**

```
package1<-NULL
package2<-NULL
runCompare()
```

---

triangleorientation	<i>computes the orientation of a triangle</i>
---------------------	---

---

**Description**

computes the orientation of a triangle

**Usage**

```
triangleorientation(s)
```

**Arguments**

**s** a 3x2 numeric matrix, representing a triangle. Each row of the matrix are the coordinates of an extreme point of the triangle.

**Examples**

```
zz<-function(p){
  s=matrix(sample(0:4,6,rep=T),3,2)
  plot(s[c(1:3,1),],type="l",main=if(triangleorientation(s)==1){"+"}else{if(triangleorientation(s)==-1){"-"}else
  text(s[,1],s[,2],toupper(letters[1:3]),cex=1,col="red")
}
  par(mfrow=c(2,2),mar=c(5,3,2,2))
  set.seed(7);replicate(4,zz(c(sample(-2:3,1),sample(-2:2,1))))
```

---

updatedist	<i>update the list of the already nown distances between subjects with distances between new infected and exposed</i>
------------	---

---

**Description**

update the list of the already nown distances between subjects with distances between new infected and exposed

**Usage**

```
updatedist(
  closedistances = NULL,
  U,
  sick,
  new.sicks = NULL,
  delta = 0.005,
  dist_areas = dist_areas_f(U, delta)
)
```

**Arguments**

<code>closedistances</code>	NULL, or a named list with 2 named elements: <code>closedistances\$ra</code> , <code>closedistances\$id</code>
<code>U</code>	a data.frame with the variables hexagon (can be any bin identifier), x, y : coordinates,
<code>sicks</code>	a vector of integers indicating the row numbers in U for sick
<code>new.sicks</code>	a vector of integers indicating the row numbers in U for new sick
<code>delta</code>	a positive number : a threshold
<code>dist_areas:</code>	a function between

**Value**

NULL, or a named list with 2 named elements: `closedistances$ra`, `closedistances$id`

**Examples**

```
data(UE, package="Strategy")
delta<-.005
sicks<-(1:nrow(UE))[UE$I001=="sick"]
closedistances=updatedist(NULL, UE, sick)
do.call(cbind, closedistances)[1:3,]
```



# Index

`addpiechartclustermarkers`, [2](#)

`closestpointonpolygon`, [3](#)  
`closestpointonseg`, [4](#)  
`closestpointsontwopolygons`, [4](#)  
`closestpointsontwopolygons_n`, [5](#)  
`closestpointsontwosegments`, [6](#)  
`closestpointsontwosegments_n`, [6](#)

`dist_areas_f`, [12](#)  
`distpointtopoly`, [7](#)  
`distpointtoseg`, [8](#)  
`distpolytopoly`, [9](#)  
`distpolytopoly2`, [10](#)  
`distsegmenttopoly`, [10](#)  
`distsegmenttosegment`, [11](#)

`extractpolygonsaslist`, [12](#)

`Generate_Discrete_Time_Epidemic`, [13](#)  
`Generate_U`, [13](#)

`neighbourhoods`, [14](#)  
`newdist`, [15](#)

`polydistmat`, [16](#)  
`polysmalldistmat`, [17](#)  
`projpointonseg_a`, [18](#)

`ranges.gap`, [18](#)  
`rangesoverlap`, [19](#)  
`risktobeinfected`, [20](#)  
`risktobeinfectedbydistancetoallinfectedunit`,  
[20](#)  
`risktobeinfectedbydistancetooneinfectedunit`,  
[21](#)

`segment.intersect`, [22](#)

`test`, [22](#)  
`triangleorientation`, [23](#)

`updatedist`, [23](#)