

Package ‘Strategy’

March 11, 2020

Type Package

Title X

Version 1.0

Date 2020-03-11

Author D. Bonnery

Maintainer D. Bonnery <dbonnery@umd.edu>

Description Data

Depends ggplot2,
leaflet,
spatstat,
sf

License GPL (>= 2)

LazyLoad yes

LazyData true

RoxygenNote 7.0.2

R topics documented:

addpiechartclustermarkers	2
closestpointonpolygon	3
closestpointonseg	4
closestpointsontwopolygons	4
closestpointsontwopolygons_n	5
closestpointsontwosegments	6
closestpointsontwosegments_n	6
distpointtopoly	7
distpointtoseg	8
distpolytopoly	9
distpolytopoly2	10
distsegmenttopoly	10
distsegmenttosegment	11
dist_areas_f	12

extractpolygonsaslist	12
Generate_Discrete_Time_Epidemic	13
Generate_U	13
generate_U2	14
neighbourhoods	15
newdist	15
polydistmat	16
polysmalldistmat	17
projpointonseg_a	18
ranges.gap	19
rangesbygradients_f	19
rangesoverlap	20
risktobeinfected	21
risktobeinfectedbydistancetoallinfectedunit	21
risktobeinfectedbydistancetooneinfectedunit	22
segment.intersect	23
test	23
triangleorientation	24
updatedist	24
Index	26

addpiechartclustermarkers
<i>Change leaflet cluster markers to pie charts</i>

Description

Change leaflet cluster markers to pie charts

Usage

addpiechartclustermarkers(map, .data, .colors, group)

Arguments

- | | |
|---------|---|
| map | the map to add awesome pie chart cluster markers to |
| .data | data for the cluster markers |
| .colors | a vector of colors of at least the same size that nlevels(.data[[group]]) |
| group | the name of a factor variable of .data |

Examples

```
data("breweries91",package="leaflet")
breweries91$goodbear<-sample(as.factor(c("terrific","marvelous","culparterretaping")),nrow(breweries91),replace=TRUE)
library(leaflet)
library(dplyr)
leaflet(breweries91) %>%
  addTiles() %>%
  addAwesomeMarkers()
map<-leaflet(breweries91) %>%addTiles()
addpiechartclustermarkers(map,.data=breweries91,.colors=c("red","green","blue"),group="goodbear")
leaflet(breweries91) %>%
  addTiles() %>%
  addpiechartclustermarkers(.data=breweries91,.colors=c("red","green","blue"),group="goodbear")
```

`closestpointonpolygon` *computes the coordinates of the closest point on the border of a polygon to a point in the plane*

Description

computes the coordinates of the closest point on the border of a polygon to a point in the plane

Usage

```
closestpointonpolygon(p, .poly)
```

Arguments

<code>p</code>	a numeric vector of length 2
<code>.poly</code>	a nx2 numeric matrix, representing a polygon. Each row of the matrix are the coordinates of a vertice of the polygon.

Value

the coordinates of the closest point on the polygon

Examples

```
zz<-function(){
  .poly=matrix(sample(0:4,6,rep=T),3,2)[c(1:3,1),]
  p<-sample(0:4,2,rep=T)
  dd<-distpointtopoly(p,.poly)
  plot(rbind(p,.poly),cex=.5,main=paste0("Distance: ", signif(dd,3)),
       asp=1,xlim=range(cbind(p,.poly)),ylim=range(cbind(p,.poly)),xaxt='n',yaxt='n',xlab='',ylab='')
  points(.poly,type="l",lwd=2)
  cc<-rbind(p,closestpointonpolygon(p,.poly))
  points(cc,col="red",cex=2)
  points(cc,type="l",lty=3,col="red")
}
```

```

}

par(oma=c(0,0,0,0),mfrow=c(2,2))
set.seed(3);replicate(4,zz())

```

closestpointonseg	<i>computes the coordinates of the closest point on a segment to a point in the plane</i>
-------------------	---

Description

computes the coordinates of the closest point on a segment to a point in the plane

Usage

```
closestpointonseg(p, s)
```

Arguments

p	a numeric vector of length 2
s	a 2x2 numeric matrix, representing a segment. Each row of the matrix are the coordinates of a extreme point of the segment.

Examples

```

zz<-function(p){
  s=matrix(c(0,1,0,0),2,2)
  plot(s,type="l",xlim=c(-.5,1.5),
    xlab="",ylab="",
    xaxt='n',yaxt='n')
  points(x=p[1],y=p[2] ,col="red",cex=.5)
  points(closestpointonseg(p,s)[1],closestpointonseg(p,s)[2],col="red",cex=.5)
  segments(x0 = p[1],y0=p[2],x1=closestpointonseg(p,s)[1],y1=closestpointonseg(p,s)[2],col="red")
  par(mfrow=c(3,3))
  set.seed(1);replicate(9,zz(c(runif(1,-.5,1.5),runif(1,-1,1))))

```

closestpointsonwopolygons	<i>computes the coordinates of the closest point on the border of a polygon to a point in the plane</i>
---------------------------	---

Description

computes the coordinates of the closest point on the border of a polygon to a point in the plane

Usage

```
closestpointstwopolygons(poly1, poly2)
```

Arguments

poly1 a nx2 numeric matrix, representing a polygon. Each row of the matrix are the coordinates of a vertex of the polygon.

poly2 a nx2 numeric matrix, representing a polygon. Each row of the matrix are the coordinates of a vertex of the polygon.

Value

the coordinates of the closest point on the polygon

Examples

```
zz<-function(){
  poly1=matrix(sample(0:6,6,rep=T),3,2)[c(1:3,1),]
  poly2=matrix(sample(0:6,6,rep=T),3,2)[c(1:3,1),]
  s<-rbind(poly1,poly2)
  dd<-distpolytopoly(poly1,poly2)
  plot(s,cex=.5,main=paste0("Distance: ", signif(dd,3)),asp=1,xlim=range(s),ylim=range(s),xaxt='n',yaxt='n',xlab=
  points(poly1,type="l",lwd=2)
  points(poly2,type="l",lwd=2)
  cc<-closestpointstwopolygons(poly1,poly2)
  points(cc,col="red",cex=2)
  points(cc,type="l",col="red",lty=3)
}

par(oma=c(0,0,0,0),mfrow=c(2,2))
set.seed(2);replicate(4,zz())
```

closestpointstwopolygons_n

Compute minimum distance between two polygons

Description

Compute minimum distance between two polygons

Usage

```
closestpointstwopolygons_n(poly1, poly2)
```

Arguments

poly1 a nx2 numeric matrix, representing a polygon. Each row of the matrix are the coordinates of a vertex of the polygon.

poly2 a nx2 numeric matrix, representing a polygon. Each row of the matrix are the coordinates of a vertex of the polygon.

Examples

```

zz<-function(){
poly1=matrix(sample(0:6,6,rep=T),3,2)[c(1:3,1),]
poly2=matrix(sample(0:6,6,rep=T),3,2)[c(1:3,1),]
s<-rbind(poly1,poly2)
dd<-distpolytopoly(poly1,poly2)
plot(s,cex=.5,main=paste0("Distance: ", signif(dd,3)),asp=1,xlim=range(s),ylim=range(s),xaxt='n',yaxt='n',xlab=
points(poly1,type="l",lwd=2)
points(poly2,type="l",lwd=2)
for(cc in closestpointsonwopolygons_n(poly1,poly2)){
points(cc ,col="red",cex=2)
points(cc,type="l",col="red",lty=3)}
}

par(oma=c(0,0,0,0),mfrow=c(2,2))
set.seed(2);replicate(4,zz())

```

closestpointsonwosegments

computes the coordinates of the closest point on a segment to a point in the plane

Description

computes the coordinates of the closest point on a segment to a point in the plane

Usage

```
closestpointsonwosegments(s1, s2)
```

Arguments

s1	a 2x2 numeric matrix, representing a segment. Each row of the matrix are the coordinates of a extreme point of the segment.
s2	a 2x2 numeric matrix, representing a segment. Each row of the matrix are the coordinates of a extreme point of the segment.

closestpointsonwosegments_n

returns a list of one or more pair of points, one on each of two segments, with minimal distance

Description

returns a list of one or more pair of points, one on each of two segments, with minimal distance

Usage

```
closestpointsonwosegments_n(s1, s2)
```

Arguments

s1 a 2x2 numeric matrix, representing a segment. Each row of the matrix are the coordinates of a extreme point of the segment.

s2 a 2x2 numeric matrix, representing a segment. Each row of the matrix are the coordinates of a extreme point of the segment.

Value

a list of 2x2 numeric matrices, representing a segment.

Examples

```
zz<-function(){
  s1=matrix(sample(0:4,4,rep=T),2,2)
  s2=matrix(sample(0:4,4,rep=T),2,2)
  s<-rbind(s1,s2)
  dd<-distsegmenttosegment(s1,s2)
  plot(s,cex=.5,main=paste0("Distance: ", signif(dd,3)),asp=1,xlim=range(s),ylim=range(s),xaxt='n',yaxt='n',xlab=
  points(s1,type="l",lwd=2)
  points(s2,type="l",lwd=2)
  cc<-closestpointsonwosegments_n(s1,s2)
  for(ccc in cc){points(ccc ,col="red",cex=2)
  points(ccc,type="l",col="red",lty=3)}
}

par(oma=c(0,0,0,0),mfrow=c(3,3))
set.seed(3);replicate(9,zz())
closestpointsonwosegments_n(matrix(c(0,3,0,0),2,2),matrix(c(1,2,0,0),2,2))
```

distpointtopoly	<i>computes the distance between a point and a polygon</i>
-----------------	--

Description

computes the distance between a point and a polygon

Usage

```
distpointtopoly(p, .poly)
```

Arguments

p a numeric vector of length 2

.poly a n x2 numeric matrix, representing a polygon. Each row of the matrix are the coordinates of a verticeof the polygon.

Examples

```
zz<-function(){
p<-sample(0:6,2,rep=T)
.poly<-matrix(sample(0:6,6,rep=T),3,2)[c(1:3,1),]
plot(rbind(.poly,p),
xlab="",ylab="",
cex=.2,main=paste0("Distance: ",signif(distpointtopoly(p,.poly),3)))
points(.poly,type='l')
points(x=p[1],y=p[2] ,col="red",cex=1)
points(closestpointonpolygon(p,.poly)[1],closestpointonpolygon(p,.poly)[2],col="red",cex=1)
points(rbind(p,closestpointonpolygon(p,.poly)),col="red",lty=3,type='l')
par(mfrow=c(3,3),oma=c(0,0,1,0),mar=c(2,2.1,1,0.1))
set.seed(1);replicate(9,zz())
```

distpointtoseg	<i>computes the distance between a point and a segment</i>
----------------	--

Description

computes the distance between a point and a segment

Usage

```
distpointtoseg(p, s)
```

Arguments

p	a numeric vector of length 2
s	a 2x2 numeric matrix, representing a segment. Each row of the matrix are the coordinates of a extreme point of the segment.

Examples

```
zz<-function(p){
s=matrix(c(0,3,0,0),2,2)
plot(s,type="l",xlim=c(-2,5),ylim=c(-2,2),
xlab="",ylab="",
xaxt='n',yaxt='n')
points(x=p[1],y=p[2] ,col="red",cex=.5)
points(closestpointonseg(p,s)[1],closestpointonseg(p,s)[2],col="red",cex=.5)
segments(x0 = p[1],y0=p[2],x1=closestpointonseg(p,s)[1],y1=closestpointonseg(p,s)[2],col="red")
text((closestpointonseg(p,s)[1]+p[1])/2,(closestpointonseg(p,s)[2]+p[2])/2,round(distpointtoseg(p,s),2))
par(mfrow=c(3,3))
set.seed(1);replicate(9,zz(c(sample(-2:3,1),sample(-2:2,1))))
```

distpolytopoly	<i>Computes distance between two polygons</i>
----------------	---

Description

Computes distance between two polygons

Usage

distpolytopoly(poly1, poly2)

Arguments

- poly1 a polygon (a n x 2 numerical matrix)
- poly2 a polygon (a n x 2 numerical matrix)

Value

a positive number, the distance between the two polygons

See Also

distsegmenttopoly

Examples

```
zz<-function(){
poly1=matrix(sample(0:6,6,rep=T),3,2)[c(1:3,1),]
poly2=matrix(sample(0:6,6,rep=T),3,2)[c(1:3,1),]
s<-rbind(poly1,poly2)
dd<-distpolytopoly(poly1,poly2)
plot(s,cex=.5,main=paste0("Distance: ", signif(dd,3)),asp=1,xlim=range(s),ylim=range(s),xaxt='n',yaxt='n',xlab=
points(poly1,type="l",lwd=2)
points(poly2,type="l",lwd=2)
for(cc in closestpointstwopolygons_n(poly1,poly2)){
points(cc,type="l",col="red",lty=3)}}

par(mfrow=c(2,2),oma=c(0,0,1,0),mar=c(0.1,0.1,1,0.1))
set.seed(2);replicate(4,zz())
```

distpolytopoly2	<i>Computes distance between two polygons, only works for polygons that do not intersect</i>
-----------------	--

Description

Computes distance between two polygons, only works for polygons that do not intersect

Usage

```
distpolytopoly2(poly1, poly2)
```

Arguments

poly1	a polygon (a n x 2 numerical matrix)
poly2	a polygon (a n x 2 numerical matrix)

Value

a positive number, the distance between the two polygons

distsegmenttopoly	<i>Distance between a segment and a polygon</i>
-------------------	---

Description

Distance between a segment and a polygon

Usage

```
distsegmenttopoly(s, .poly)
```

Arguments

s	a 2x2 numeric matrix, representing a segment. Each row of the matrix are the coordinates of a extreme point of the segment.
.poly	a polygon (a nx2 matrix, each line is a point)

Examples

```
zz<-function(){
  .poly<-matrix(sample(0:6,6,T),3,2)[c(1:3,1),]
  s<-matrix(sample(0:6,6,T),2,2)
  plot(rbind(.poly,s),xlab="",yaxt="n")
  points(.poly,type="l");points(s,type="l")
  points(closestpointsonwopolygons(s,.poly),lty=3,col="red")}
```

distsegmenttosegment *distance segment to segment*

Description

distance segment to segment

Usage

```
distsegmenttosegment(s1, s2)
```

Arguments

s1 a 2x2 numeric matrix, representing a segment. Each row of the matrix are the coordinates of a extreme point of the segment.

s2 a 2x2 numeric matrix, representing a segment. Each row of the matrix are the coordinates of a extreme point of the segment.

Value

a number

Examples

```
zz<-function(){
  s1=matrix(sample(0:4,4,rep=T),2,2)
  s2=matrix(sample(0:4,4,rep=T),2,2)
  s<-rbind(s1,s2)
  dd<-distsegmenttosegment(s1,s2)
  plot(s,cex=.5,main=paste0("Distance: ", signif(dd,3)),asp=1,xlim=range(s),ylim=range(s),xaxt='n',yaxt='n',xlab=
  points(s1,type="l",lwd=2)
  points(s2,type="l",lwd=2)
  cc<-closestpointstotwosegments(s1,s2)
  points(cc,col="red",cex=2)
  points(cc,type="l",col="red",lty=3)
}

par(mfrow=c(3,3),oma=c(0,0,0,0),mar=c(1.1,1.2,1,1.1))
set.seed(3);replicate(9,zz())
```

dist_areas_f	<i>Distances between hexagonal bins</i>
--------------	---

Description

Distances between hexagonal bins

Usage

```
dist_areas_f(
  U,
  delta = (range(U$x)[2] - range(U$x)[1])/100,
  h = neighbourhoods(U, delta)
)
```

Arguments

U : a dataframe containing the numerical variables x and y and preferable hexagon
 delta : needed if hexagon is not a variable of U: bins will be recomputed

Value

a named matrix

Examples

```
data(U)
dist_areas_f(U)[1:3,1:3]
dist_areas_f(U,0.03)[1:3,1:3]
```

extractpolygonsaslist	<i>converts a shapefile to list of polygons (nx2 matrices)</i>
-----------------------	--

Description

converts a shapefile to list of polygons (nx2 matrices)

Usage

```
extractpolygonsaslist(shp)
```

Generate_Discrete_Time_Epidemic
Generate epidemic

Description

Generate epidemic

Usage

```
Generate_Discrete_Time_Epidemic(
  U,
  TT,
  .distriskhalf = 5 * 10-4,
  jumprisk = 10-6,
  delta = 0.05
)
```

Arguments

U	a data.frame
TT	an integer
.distriskhalf	a positive number(default 5*10 ⁻⁴)
jumprisk	=10 ⁻⁶ a positive number
delta	=0.05 a positive number

Examples

```
.distriskhalf=5*10-4;jumprisk=10-6;delta=0.05; TT=10
UE<-Generate_Discrete_Time_Epidemic(U,3)
```

Generate_U *Generate spatial data that matches population counts*

Description

Generate spatial data that matches population counts

Usage

```
Generate_U(SpatialData, .id = NULL, .spatialobject, type = "random")
```

Arguments

SpatialData	: an object of class that includes
type	: argument to be passed to sp::spsample

Examples

```

data(parish110217popest,package="dataONS")
data("mtcty150217population",package="dataONS")
shapeData2<-dataONS::dataParishes_December_2011_Boundaries_EW_BFC()
yy<-unique(get(data(Output_Area_to_Parish_to_Local_Authority_District_December_2011_Lookup_in_England_and_Wale
names(yy)<-tolower(names(yy))
shapeData<-sp::merge(shapeData2,yy,by="par11cd",duplicateGeoms = TRUE)
parish110217popest2<-parish110217popest[
  is.element(parish110217popest$PAR11CD,
    shapeData$par11cd)&
    parish110217popest$year=="mid_2006",
    c("PAR11CD","Population")]
  names(parish110217popest2)<-tolower(names(parish110217popest2))
shapeData=sp::merge(shapeData,parish110217popest2,by="par11cd",duplicateGeoms = TRUE)
shapeData$population[is.na(shapeData$population)]<-mean(shapeData$population,na.rm=TRUE)
shapeData<-subset(shapeData,is.element(lad11nm ,c("Allerdale", "Barrow-in-Furness", "Carlisle", "C

U<-Generate_U(shapeData,.id="par11cd",.spatialobject="st_areasha",type="random")
popbins<-quantile(shapeData$population,(seq_len(11)-1)/10)
poppal <- colorBin(heat.colors(5), bins=popbins, na.color = "#aaff56",reverse = T)
library(leaflet)

leaflet(U) %>%
  addPolygons(data=shapeData,
    stroke=TRUE,
    weight=1,
    color="black",
    fillOpacity=5,
    fillColor=~poppal(shapeData$population)) %>%
  addTiles() %>%
  addLegend(title = "Population count", pal=poppal,
    values=shapeData$population,
    opacity=1,
    na.label = "Not Available")

```

generate_U2

*Generate a population of avocado trees***Description**

Generate a population of avocado trees

Usage

```
generate_U2()
```

neighbourhoods	<i>hexagonal bins</i>
----------------	-----------------------

Description

hexagonal bins

Usage

```
neighbourhoods(
  U,
  delta = (range(U$x, na.rm = TRUE)[2] - range(U$x, na.rm = TRUE)[1])/100
)
```

Arguments

`U` : a dataframe containing the numerical variables x and y
`delta`: controls the bin diameter

Value

a hexbin object hexagonal bins

Examples

```
# plot the hex bins of cumbria
data(U, package="Strategy")
library("hexbin")
plot(neighbourhoods(U, .1))
plot(neighbourhoods(U, .01))
plot(neighbourhoods(U, .001))
```

newdist	<i>compute distances between new infected and exposed</i>
---------	---

Description

compute distances between new infected and exposed

Usage

```
newdist(
  closedistances = NULL,
  U,
  sick,
  new.sicks = NULL,
  delta = 0.005,
  dist_areas = dist_areas_f(U, delta)
)
```

Arguments

<code>closedistances</code>	NULL, or a named list with 2 named elements: <code>closedistances\$ra</code> , <code>closedistances\$id</code>
<code>U</code>	a data.frame with the variables hexagon (can be any bin identifier), x, y : coordinates,
<code>sicks</code>	a vector of integers
<code>new.sicks</code>	a vector of integers
<code>delta</code>	a positive number : a threshold
<code>dist_areas:</code>	a function between

Value

NULL, or a named list with 2 named elements: `closedistances$ra`, `closedistances$id`

Examples

```
data(UE, package="Strategy")
delta<-.005
sicks<-(1:nrow(UE))[UE$I001=="sick"]
closedistances=newdist(NULL,UE,sicks)
do.call(cbind,closedistances)[1:3,]
```

polydistmat

Compute distance matrix for a list of polygons

Description

Compute distance matrix for a list of polygons

Usage

```
polydistmat(list.poly)
```

Arguments

<code>list.poly</code>	a list of nx2 numeric matrices
------------------------	--------------------------------

Value

a $(n*(n-1)/2) \times 3$ matrix

Examples

```
zz<-function(){
  list.poly=plyr::alply(cbind(rep(0:8,9),rep(0:8,each=9))[sample(81,4),],1,function(x){
    cbind(x[1]+c(0,0,.5,.5,0),x[2]+c(0,.5,.5,0,0))})
  gradients=cbind(c(0,1),c(1,0),c(1,1),c(1,-1))
  par(mfrow=c(1,1),oma=c(0,0,0,0),mar=c(0.1,0.1,.1,0.1))
  plot(do.call(rbind,list.poly),xlab="",yaxt="n",ylab="",cex=.1)
  for(i in 1:length(list.poly)){.poly=list.poly[[i]]
    points(.poly,type="l")
    text(mean(.poly[,1]),mean(.poly[,2]),as.roman(i))
  }
  X=polydistmat(list.poly,.progress="none")
  X<-cbind(X,floor(rank(X[,3])))
  colorlink=topo.colors(2*max(X[,4]))[X[,4]]
  for(i in 1:nrow(X)){
    cc<-closestpointsonwopolygons(list.poly[[X[i,1]]],list.poly[[X[i,2]]])
    points(cc,col=colorlink[i],type="l",lty=3)
    text(mean(cc[,1]),mean(cc[,2]),signif(X[i,3],3))
  }
  colnames(X)<-c("polygon 1","polygon 2", "distance","col")
  X[,1:3]}
  set.seed(1);zz()
```

polysmallldistmat

Compute distance matrix for a list of polygons

Description

Compute distance matrix for a list of polygons

Usage

```
polysmallldistmat(
  list.poly,
  delta,
  gradients = apply(cbind(c(0, 1), c(1, 0), c(1, 1), c(1, -1)), 2, function(x) {
    x/(sqrt(sum(x^2))) })
)
```

Arguments

`list.poly` a list of nx2 numeric matrices
`delta` a positive number
`gradients` a 2x n matrix each column representing a vector.

Value

a $(n*(n-1)/2) \times 3$ matrix

Examples

```
zz<-function(delta){
  list.poly=plyr::alply(cbind(rep(0:8,9),rep(0:8,each=9))[sample(81,20),],1,function(x){
    cbind(x[1]+c(0,0,.5,.5,0),x[2]+c(0,.5,.5,0,0)))
    gradients=cbind(c(0,1),c(1,0),c(1,1),c(1,-1))
    par(mfrow=c(1,1),oma=c(0,0,1,0),mar=c(0.1,0.1,1,0.1))
    plot(do.call(rbind,list.poly),xlab="",yaxt="n",ylab="",cex=.1,main=paste0("Match polygons distant less than ",de
    for(.poly in list.poly){points(.poly,type="l")}
    X=polysmallldistmat(list.poly,delta)
    for(i in 1:nrow(X)){
      points(closestpointson twopolygons(list.poly[[X[i,1]]],list.poly[[X[i,2]]]),col="red",type="l",lty=3)
    }
    set.seed(1);zz(.5)
    set.seed(1);zz(1)
    set.seed(1);zz(2)
```

projpointonseg_a	<i>computes the position of a projected point in the basis formed by a segment</i>
------------------	--

Description

computes the position of a projected point in the basis formed by a segment

Usage

```
projpointonseg_a(p, s, method = "euclidean")
```

Arguments

p	a numeric vector of length 2
s	a 2x2 numeric matrix, representing a segment. Each row of the matrix are the coordinates of a extreme point of the segment.

Examples

```
zz<-function(p){
  s=matrix(c(0,1,0,0),2,2)
  plot(s,type="l",xlim=c(-.5,1.5),
  xlab="",ylab="",
  yaxt='n',yaxt='n')
  points(x=p[1],y=p[2],col="red",cex=2)
  points(closestpointonseg(p,s)[1],closestpointonseg(p,s)[2],col="red",cex=2)
  segments(x0 = p[1],y0=p[2],x1=closestpointonseg(p,s)[1],y1=closestpointonseg(p,s)[2],col="red")
  text(projpointonseg_a(p,s),-.8,paste0("a=",projpointonseg_a(p,s)))}
```

```
par(oma=c(0,0,0,0),mfrow=c(1,4))
zz(c(-.5,1))
zz(0:1)
zz(c(.5,1))
zz(c(1.5,1))
```

ranges.gap

Interval length between two ranges (0 if they overlap)

Description

Interval length between two ranges (0 if they overlap)

Usage

```
ranges.gap(r1, r2)
```

Arguments

r1 a range a length 2 numerical vector
r2 a range a length 2 numerical vector

Examples

```
par(mfrow=c(1,4),oma=c(0,0,0,0))
set.seed(10);replicate(4,(function(){
r1<-sample(1:8,2);r2<-sample(1:5,2)
plot(cbind(c(r1,r2),0),yaxt='n',xlab='',ylab='',
main=paste0("Gap: ",ranges.gap(r1,r2)))
points(cbind(r1,0),type="l",lwd=3)
points(cbind(r2,0),type="l",col="red")
}))()
```

rangesbygradients_f

Compute range of a polygon along certain gradients

Description

Compute range of a polygon along certain gradients

Usage

```
rangesbygradients_f(
  .poly,
  gradients = -apply(cbind(c(0, 1), c(1, 0), c(1, 1), c(1, -1)), 2, function(x) {
    x/(sqrt(sum(x^2))) })
)
```

Arguments

- gradients a 2x n matrix each column representing a vector.
- list.poly a list of nx2 numeric matrices
- delta a positive number

Examples

```
a=c(1-1/sqrt(2),1/sqrt(2));.poly=cbind(1+c(0,0,a,1,1,a[2:1]),1+c(a,1,1,a[2:1],0,0))[c(1:8,1),]  
plot(.poly,type='l',xlab='',ylab='')  
rangesbygradients_f(.poly,gradients=cbind(c(0,1),c(1,0),c(1,-1)))
```

rangesoverlap	<i>tells if two ranges overlap</i>
---------------	------------------------------------

Description

tells if two ranges overlap

Usage

```
rangesoverlap(r1, r2)
```

Arguments

- r1 a range a length 2 numerical vector
- r2 a range a length 2 numerical vector

Examples

```
par(mfrow=c(1,4),oma=c(0,0,0,0))  
set.seed(8);replicate(4,(function(){  
  r1<-sample(1:8,2);r2<-sample(1:5,2)  
  plot(cbind(c(r1,r2),0),yaxt='n',xlab='',ylab='',xaxt='n',  
  main=paste0(if(rangesoverlap(r1,r2)){"0"}else{"Does not o"},"verlap"))  
  points(cbind(r1,0),type="l",lwd=3)  
  points(cbind(r2,0),type="l",col="red")  
}()))
```

risktobeinfected	<i>Computes the risk to be infected</i>
------------------	---

Description

Computes the risk to be infected

Usage

```
risktobeinfected(
  U,
  closedistances = NULL,
  sick,
  new.sicks = NULL,
  .distriskhalf = 5 * 10^(-4),
  jumprisk = 10^-6,
  delta = 0.01,
  previouslyexposed = c(),
  previousrisk = NULL
)
```

Examples

```
y=rep("Sane",nrow(U));y[sample(length(y),10)]<-"sick"
jumprisk=10^-6
.distriskhalf=10^-6
```

risktobeinfectedbydistancetoallinfectedunit	<i>Risk to be infected by many neighbours a neighbour at a certain distance</i>
---	---

Description

Risk to be infected by many neighbours a neighbour at a certain distance

Usage

```
risktobeinfectedbydistancetoallinfectedunit(
  .dist,
  nI,
  .distriskhalf = 5 * 10^(-4),
  jumprisk = 10^-6
)
```

Arguments

`.dist` : a vector (distances)
`.disthalfrisk` : distance for which the risk is one half
`nI`: total number of infected
`jumprisk`: probability to be infected by one person, no matter how far he/she is

Value

$1 - (\text{prod}(1 - \text{risktobeinfectedbydistancetooneinfectedunit}(\text{.dist}, \text{distriskhalf})) * (1 - \text{jumprisk})^{\text{nI}})$

Examples

```
#Risk to be ingfected 2 m from the victim when the 50%risk distance is 1 m:
risktobeinfectedbydistancetooneinfectedunit(2,1)
```

`risktobeinfectedbydistancetooneinfectedunit`

Risk to be infected by a neighbour at a distance x

Description

Risk to be infected by a neighbour at a distance x

Usage

```
risktobeinfectedbydistancetooneinfectedunit(.dist, .distriskhalf = 5 * 10^(-4))
```

Arguments

`.dist` : a distance
`.disthalfrisk` : distance for which the risk is one half

Value

$\exp(-\text{.dist}/(\log(2) * \text{distriskhalf}))$

Examples

```
#Risk to be ingfected 2 m from the victim when the 50%risk distance is 1 m:
risktobeinfectedbydistancetooneinfectedunit(2,1)
```

segment.intersect	<i>test if two segments intersect</i>
-------------------	---------------------------------------

Description

test if two segments intersect

Usage

```
segment.intersect(s1, s2)
```

Arguments

s1	a 2x2 numeric matrix, representing a segment. Each row of the matrix are the coordinates of an extreme point of the segment.
s2	a 2x2 numeric matrix, representing a segment. Each row of the matrix are the coordinates of an extreme point of the segment.

Examples

```
zz<-function(s1=matrix(sample(0:3,4,rep=T),2,2),s2=matrix(sample(0:3,4,rep=T),2,2)){
  si<-segment.intersect(s1,s2)
  s<-rbind(s1,s2)
  plot(s,cex=.5,main=if(si){"Intersect"}else{"Disjoint"},xlab="",ylab="",xaxt='n', yaxt='n',xlim=range(s)+c(-1,1),
  points(s1,type="l")
  points(s2,type="l")
  text(s[,1],s[,2],toupper(letters[1:4]),cex=1,col="red")
}
par(mfrow=c(3,4),mar=c(5,3,2,2))
set.seed(12);replicate(4,zz())
zz(matrix(0,2,2),matrix(0,2,2))
zz(matrix(0,2,2),matrix(1,2,2))
zz(matrix(c(1,1,1,1),2,2),matrix(c(2,3,2,3),2,2))
zz(matrix(c(1,1,0,0),2,2),matrix(c(0,1,0,0),2,2))
zz(matrix(c(1,3,1,3),2,2),matrix(c(2,4,2,4),2,2))
zz(matrix(c(0,1,0,1),2,2),matrix(c(2,3,2,3),2,2))
zz(matrix(c(0,4,0,4),2,2),matrix(c(1,3,1,3),2,2))
zz(matrix(c(0,1,0,1),2,2),matrix(c(0,3,0,3),2,2))
```

test	<i>runCompare</i>
------	-------------------

Description

Shiny App to

Usage

test()

Examples

```
package1<-NULL
package2<-NULL
runCompare()
```

triangleorientation	<i>computes the orientation of a triangle</i>
---------------------	---

Description

computes the orientation of a triangle

Usage

triangleorientation(s)

Arguments

s a 3x2 numeric matrix, representing a triangle. Each row of the matrix are the coordinates of an extreme point of the triangle.

Examples

```
zz<-function(p){
s=matrix(sample(0:4,6,rep=T),3,2)
plot(s[c(1:3,1),],type="l",main=if(triangleorientation(s)==1){"+"}else{if(triangleorientation(s)==-1){"-"}else
text(s[,1],s[,2],toupper(letters[1:3]),cex=1,col="red")
}
par(mfrow=c(2,2),mar=c(5,3,2,2))
set.seed(7);replicate(4,zz(c(sample(-2:3,1),sample(-2:2,1))))
```

updatedist	<i>update the list of the already nown distances between subjects with distances between new infected and exposed</i>
------------	---

Description

update the list of the already nown distances between subjects with distances between new infected and exposed

Usage

```
updatedist(
  closedistances = NULL,
  U,
  sick,
  new.sicks = NULL,
  delta = 0.005,
  dist_areas = dist_areas_f(U, delta)
)
```

Arguments

<code>closedistances</code>	NULL, or a named list with 2 named elements: <code>closedistances\$ra</code> , <code>closedistances\$id</code>
<code>U</code>	a data.frame with the variables hexagon (can be any bin identifier), x, y : coordinates,
<code>sicks</code>	a vector of integers indicating the row numbers in U for sick
<code>new.sicks</code>	a vector of integers indicating the row numbers in U for new sick
<code>delta</code>	a positive number : a threshold
<code>dist_areas:</code>	a function between

Value

NULL, or a named list with 2 named elements: `closedistances$ra`, `closedistances$id`

Examples

```
data(UE, package="Strategy")
delta<-.005
sicks<-(1:nrow(UE))[UE$I001=="sick"]
closedistances=updatedist(NULL, UE, sick)
do.call(cbind, closedistances)[1:3,]
```

Index

`addpiechartclustermarkers`, [2](#)

`closestpointonpolygon`, [3](#)
`closestpointonseg`, [4](#)
`closestpointstwopolygons`, [4](#)
`closestpointstwopolygons_n`, [5](#)
`closestpointstwosegments`, [6](#)
`closestpointstwosegments_n`, [6](#)

`dist_areas_f`, [12](#)
`distpointtopoly`, [7](#)
`distpointtoseg`, [8](#)
`distpolytopoly`, [9](#)
`distpolytopoly2`, [10](#)
`distsegmenttopoly`, [10](#)
`distsegmenttosegment`, [11](#)

`extractpolygonsaslist`, [12](#)

`Generate_Discrete_Time_Epidemic`, [13](#)
`Generate_U`, [13](#)
`generate_U2`, [14](#)

`neighbourhoods`, [15](#)
`newdist`, [15](#)

`polydistmat`, [16](#)
`polysmalldistmat`, [17](#)
`projpointonseg_a`, [18](#)

`ranges.gap`, [19](#)
`rangesbygradients_f`, [19](#)
`rangesoverlap`, [20](#)
`risktobeinfected`, [21](#)
`risktobeinfectedbydistancetoallinfectedunit`,
[21](#)
`risktobeinfectedbydistancetooneinfectedunit`,
[22](#)

`segment.intersect`, [23](#)

`test`, [23](#)

`triangleorientation`, [24](#)
`updatedist`, [24](#)