

5 - Deep Learning Overview

5.7 - Common Problems in Deep Learning

Wendley S. Silva

Setembro, 2020



Index

1. Deep Learning Summary
2. Training Rules
3. Activation Function
4. Normalizer
5. Optimizer
6. Types of Neural Networks
7. **Common Problems**



Data Imbalance (1)

- Problem description: In the dataset consisting of various task categories, the number of samples varies greatly from one category to another. One or more categories in the predicted categories contain very few samples.
- For example, in an image recognition experiment, more than 2,000 categories among a total of 4251 training images contain just one image each. Some of the others have 2-5 images.
- Impacts:
 - Due to the unbalanced number of samples, we cannot get the optimal real-time result because model/algorithm never examines categories with very few samples adequately.
 - Since few observation objects may not be representative for a class, we may fail to obtain adequate samples for verification and test.



Data Imbalance (2)

Random undersampling

- Deleting redundant samples in a category

Random oversampling

- Copying samples

Synthetic Minority Oversampling Technique

- Sampling
- Merging samples




Vanishing Gradient and Exploding Gradient Problem

- Vanishing gradient: As network layers increase, the derivative value of backpropagation decreases, which causes a vanishing gradient problem.
- Exploding gradient: As network layers increase, the derivative value of backpropagation increases, which causes an exploding gradient problem.

- Cause:

$$y_i = \sigma(z_i) = \sigma(w_i x_i + b_i) \quad \text{Where } \sigma \text{ is sigmoid function.}$$




- Backpropagation can be deduced as follows:

$$\begin{aligned} \frac{\partial C}{\partial b_1} &= \frac{\partial C}{\partial y_4} \frac{\partial y_4}{\partial z_4} \frac{\partial z_4}{\partial x_4} \frac{\partial x_4}{\partial z_3} \frac{\partial z_3}{\partial x_3} \frac{\partial x_3}{\partial z_2} \frac{\partial z_2}{\partial x_2} \frac{\partial x_2}{\partial z_1} \frac{\partial z_1}{\partial b_1} \\ &= \frac{\partial C}{\partial y_4} \sigma'(z_4) w_4 \sigma'(z_3) w_3 \sigma'(z_2) w_2 \sigma'(z_1) x \end{aligned}$$



Vanishing Gradient and Exploding Gradient Problem (2)

- The maximum value of $\sigma'(x)$ is $\frac{1}{4}$.



- However, the network weight $|w|$ is usually smaller than 1. Therefore, $|\sigma'(z)w| \leq \frac{1}{4}$. According to the chain rule, as layers increase, the derivation result $\frac{\partial C}{\partial b_1}$ decreases, resulting in the vanishing gradient problem.
- When the network weight $|w|$ is large, resulting in $|\sigma'(z)w| > 1$, the exploding gradient problem occurs.
- Solution: For example, gradient clipping is used to alleviate the exploding gradient problem, ReLU activation function and LSTM are used to alleviate the vanishing gradient problem.



Overfitting

- Problem description: The model performs well in the training set, but badly in the test set.
- Root cause: There are too many feature dimensions, model assumptions, and parameters, too much noise, but very few training data. As a result, the fitting function perfectly predicts the training set, while the prediction result of the test set of new data is poor. Training data is overfitted without considering generalization capabilities.
- Solution: For example, data augmentation, regularization, early stopping, and dropout



Thank You!

Next: 6.0 - Development Environments for Deep Learning

Wendley Silva

Setembro, 2020

