

Loops & Iterations

- What are loop
- While loops
- For loops

Loops

- Loops help us whenever we wish to run a block of code multiple times.


Bart must write down a hundred times
"I'm Sorry"



```
print ("I'm Sorry")
```



x100





While Loop

- A, *while* loop in Python, helps us repeat a group of statements as long as a condition is **true**!
- We can look at the '*while*' expression as – “*As long as..*”
- It requires **conditions** and **statements**.
- A *while* loop receives a *Boolean condition*.
- *As long as* a condition is evaluated as *True*, the code block inside a '*while*' loop executes repeatedly.
- We create a *while* loop in Python using the '*while*' key-word!


While Loop – Syntax

```
while (Boolean Condition):  
    Statements
```

- Starts with '*while*' keyword.
- A *Boolean Condition*.
- A colon. (:))
- The line after the colon **must** be indented. (4 Spaces)
- Indented Statements.

While Loop – Flow Chart

- **As long as** the **Boolean Condition** evaluates as *True*, the *while* loop keeps on looping!
- **Once** the **Boolean Condition** evaluates as *False*, we exit the *while* loop!



While Loop – Example

```
num = 0
while (num < 10):
    print(num)
    num = num + 1
```

- Create an a variable and name it as “**num**” before-hand!
- Declare a *while* loop using the ‘*while*’ keyword!
- **As long as** the *Boolean Condition* evaluates as true:
 - *Print* out the value of **num**.
 - Update the value of **num** by assigning the value of **num + 1** to **num**
- **Once** the *Boolean Condition* evaluates as *false*; we *exit* the loop!



Infinite Loops

- What is wrong with this loop?

```
num = 5  
while (num > 0):  
    print(num)
```





For Loop!

- A *for* loop in Python, helps us repeat a group of statements a specified number of times!
- It requires *three* features in order to work.
 - *(Iterating Variable, Statements, Sequence)*
- We declare a *for* loop in Python using the '*for*' key-word!

The Three Features


- In order to use a *for* Loop in Python, it must consist of **three** features:

Iterating Variable




An indicator
For Starting State

Statement(s)



What to do next

Sequence




Something to Loop
over

Iterating Variable

- An *iteration* is one step in a loop.
- Bart had to write down a hundred times that he is sorry.
→ Once Bart writes down for the first time "I am Sorry", he makes an iteration of the punishment.
- An *Iterating Variable* is a variable used as an indicator for the
- program to keep track of our loop iterations!

```
print ("I'm Sorry")
```



Statement

- *Statement*_(s) is a block of code indented inside a *for* a loop.
- For each iteration of a loop, the desired block of code is being executed!
- Without mentioning any statement, we will face a *Syntax Error*!



Sequence

- A *sequence* is a collection of some objects.
- A *sequence* can be anything we can iterate over!
- For instance →
 - A string is a collection of characters that we can loop over it, character by character!
 - A simple integer/float *does not* have an iterator.

For Loop – Syntax

```
for iterating_var in sequence:  
    Statement(s)
```

- Starts with '*for*' keyword.
- A *Boolean Condition*.
- A colon. (:)
- The line after the colon **must** be indented. (4 Spaces)
- Indented Statement.


Implementation of the three-features

```
for letter in 'AI Accelerator':  
    print(letter)
```

- *Iterating Variable* → letter
- *Sequence* → 'AI Accelerator'
- *Statement* → *print*(letter)

For Loop – Flow Chart

- *Initialization* is the part where we create the loop.
- *Initialization* is also the part where we assign the **first** value into the *iterating variable*.
- **Once** the *Boolean Condition* evaluates as *True*, we enter the body of the *for* loop and execute the *statements*!
- **Once** the first iteration is done, we update the *iterating variable* and check the *Boolean Condition* once again!
- **Once** the *Boolean Condition* evaluates as *False*; we exit the *for* loop!





Looping Over Numbers

- Many times, we would like to loop over numbers in order.
- In the previous example, we created *a sequence*, using characters of a string.
- What if we want to create *a sequence* of numbers?
- Let us get to know the *range()* function!

range() Function!

Using the *range()* function, we can create a *sequence* of numbers.

For instance →

range(10) creates a *sequence* of numbers between 0 and 10.

Counting in Python always *starts with 0* and *ends on $n-1$* , with *n* being the length of the object being counted.

range(10) →

(0,10) →

[0, 1, 2, 3, 4, 5, 6, 7, 8, 9] →

starts with 0, ends with 10-1

range() Function – List View

- We can look at a *range()* as a *list*!
- Calling out *range*(10) returns as:
- *range*(0, 10)
- We can use the *list()* function to cast a range *sequence* into a *list*!

```
list(range(10))  
[0, 1, 2, 3, 4, 5, 6, 7, 8, 9]
```

For Loop – Example

```
for number in range(10):  
    print(number)
```

- Declare a for loop using the *'for'* keyword!
- Create an *Iterating Variable* "**number**"!
- Create a *sequence* of digits from 0 to 9, using *range(10)*.
- In the *first iteration*, the *first* value in the *sequence* is assigned to the *number*. (0)
- *For each iteration* of the *sequence*, we execute the statement: print out the value of stored inside *number*.
- The value stored inside the *number* is set to the next value stored inside the *sequence*!

- Looping Over Numbers - Demonstration

```
for number in range(10):  
    print(number)
```



Same Output!

```
for number in [0,1,2,3,4,5,6,7,8,9]:  
    print(number)
```

Looping Over Numbers – Bart!

Bart must write down a hundred times “I’m Sorry”



```
for number in range(100):  
    print(number, “I’m Sorry!”)
```



range() Function - Arguments

Instead of only specifying the *upper limit* of the *range*, we can also specify the *bottom limit*:

range(a, b)

The *sequence* is going to start from **a** to **b-1**, For Instance:

range(3,10) → Creates a *sequence* of digits starting from 3 and ends on 9.

We can also add a *third argument*, to specify the exact number to *increment/decrement* by:

range(a, b, c)

For instance:

range(2, 11, 2) → Creates a *sequence* of digits starting from 2 and ends on 10. ([2, 4, 6, 8, 10])

For Loop Variable Names

- *Iterating Variables* i, j, and k are the conventional variable names used for loops.
- That being said, if the iterations have meaning, a more indicative name should be used, to improve readability:

```
for celebrity name in ['The Rock', 'Bruno Mars', 'Cristiano Ronaldo']:  
    print(celebrity name)
```


When do we use FOR, and when do we use WHILE?

- Rule of thumb:
 - If we know ahead of the loop execution how many loops we will want, use *for*.
 - If we will only know when to stop the loop during the loop execution, use *while*.

- Nested Loops

Remember Nested *if* Condition?
(an *if* statement inside an *if* statement)

```
if (flavor == "Chocolate"):  
    print("Yes!")  
    if (price < 15):  
        print("Buy")
```



A loop inside another loop is called a **Nested Loop**!



Nested Loops

- Python allows us to use one loop inside another loop!
- A Nested loop can be either a Nested '*for*' loop or a Nested '*while*' loop!
- A Nested loop can also be a mix of the two.

Nested for Loop – Syntax

```
for iterating_var in sequence:  
    for iterating_var2 in sequence2:  
        Statements  
    Statements
```

- A colon for both loops. (:)
- The line after the colon **must** be indented. (4 Spaces)
- Indented Statements for each loop!

Nested for Loop – Logic

```
for iterating_var in sequence:  
    for iterating_var2 in sequence2:  
        Statements  
    Statements
```

- Declare a '*for*' loop. (We are going to refer to this as "**outer loop**")
- Declare another '*for*' loop inside the *outer* '*for*' loop. (We are going to refer to this as "**inner loop**")
- For every iteration of the **outer** loop, the **inner** loop executes.
- The **inner** loop continues until all iterations over the given *sequence* are complete and then heads back to the **outer** loop.

Nested while Loop – Syntax

```
while (Condition):  
    while (Condition):  
        Statements  
    Statements
```

- A colon. (:)
- The line after the colon **must** be indented. (4 Spaces)
- Indented Statements.

Nested while Loop – Logic

```
while (Condition):  
    while (Condition):  
        Statements  
    Statements
```

- Declare a '*while*' loop. (*outer loop*)
- Declare another '*while*' loop inside the *outer* '*while*' loop. (*inner loop*)
- *Once* the *outer* loop condition evaluates as *True*, the *inner* '*while*' loop is being called.
- *Once* the *inner* loop condition evaluates as *True*, the *inner* statements are executed.
- *As long as* the *inner* loop condition evaluates as *True*, the *inner* loop keeps iterating.
- *As long as* the *outer* loop condition evaluates as *True*, the *outer* loop keeps iterating.

pass

- The *pass* command is a place-holder.
- It continues execution with the next line.
- This is very useful when a *loop* is written, in which an indented code block is *needed* but we want to deal with it *later*.

```
for i in range(100):  
    pass
```




break


- The *break* command *stops* the current loop and jumps *out of it*.
- Example:

```
for i in range(100):  
    if i == 3:  
        break  
    print(i)
```

continue

- The *continue* command *stops* the current iteration in the loop, *continuing* with the *next* iteration.
- Example:

```
for i in range(10):  
    if (i % 3):  
        continue  
    print (i)
```



✓ What are loop
✓ While loops
✓ For loops

Thank you