

TypeScript & Git - MCQ Test (30 Questions)

1. Which of the following is a primitive type in TypeScript?
A. interface
B. string
C. class
D. enum
2. Which keyword is used to declare a variable in TypeScript that cannot be reassigned?
A. var
B. let
C. const
D. static
3. What is the correct way to define an array of numbers in TypeScript?
A. number[]
B. array
C. numbers[]
D. Array(number)
4. What does the 'any' type do?
A. Prevents reassignment
B. Disables type checking
C. Allows only numbers
D. Makes variable constant
5. Which type represents a value that may be null or undefined?
A. void
B. never
C. union type
D. boolean
6. What is the return type of a function that does not return anything?
A. null
B. undefined
C. void
D. never
7. Which keyword is used to define a custom object type?
A. type
B. object
C. define
D. struct
8. What is the main purpose of an interface?
A. To store data
B. To define structure of an object
C. To create arrays
D. To execute functions

9. How do you define a union type?

- A. Using &
- B. Using |
- C. Using +
- D. Using /

10. What does an enum represent?

- A. A collection of constants
- B. A function
- C. A class
- D. A loop

11. Which symbol is used for intersection types?

- A. |
- B. &
- C. *
- D. %

12. Generics allow you to:

- A. Disable typing
- B. Write reusable type-safe components
- C. Create global variables
- D. Avoid functions

13. What is Git primarily used for?

- A. Writing code
- B. Styling webpages
- C. Version control
- D. Database management

14. Which command initializes a new Git repository?

- A. git start
- B. git init
- C. git create
- D. git new

15. Which command stages files for commit?

- A. git push
- B. git commit
- C. git add
- D. git stage

16. Which command saves changes with a message?

- A. git save
- B. git commit -m
- C. git push
- D. git add

17. Which command uploads local commits to a remote repository?

- A. git pull
- B. git fetch
- C. git push
- D. git merge

18. What does 'git clone' do?

- A. Deletes repository
- B. Copies a remote repository locally
- C. Merges branches
- D. Creates a branch

19. What is the purpose of modules in TypeScript/JavaScript?

- A. To style applications
- B. To organize code into separate files
- C. To debug code
- D. To delete functions

20. Which keyword is used to export a function?

- A. public
- B. export
- C. return
- D. share

21. Which keyword is used to import a module?

- A. require
- B. fetch
- C. import
- D. include

22. What is a default export?

- A. Multiple exports from a file
- B. The main exported value from a file
- C. A private function
- D. A global variable

23. Can a file have multiple named exports?

- A. No
- B. Yes
- C. Only two
- D. Only in Java

24. Modules help prevent:

- A. Compilation
- B. Code duplication and global scope pollution
- C. Execution
- D. Installation

25. What is type inference in TypeScript?

- A. Manually defining types
- B. Automatic detection of variable type
- C. Converting string to number
- D. Disabling types

26. What is the purpose of 'readonly'?

- A. Makes variable writable
- B. Prevents modification after initialization

- C. Deletes property
- D. Hides property

27. Which of the following is a correct arrow function syntax?

- A. `function => {}`
- B. `() => {}`
- C. `=> () {}`
- D. `function() -> {}`

28. What does 'git branch' do?

- A. Deletes branch
- B. Lists or creates branches
- C. Merges branches
- D. Clones repository

29. What is merging in Git?

- A. Deleting files
- B. Combining changes from different branches
- C. Creating repository
- D. Resetting project

30. What does 'never' type represent?

- A. A variable that never changes
- B. A function that never returns
- C. A null value
- D. A string value

Answer Key

1. B
2. C
3. A
4. B
5. C
6. C
7. A
8. B
9. B
10. A
11. B
12. B
13. C
14. B
15. C
16. B
17. C
18. B
19. B
20. B
21. C
22. B
23. B
24. B
25. B
26. B
27. B
28. B
29. B
30. B