

Lecture

At the lecture we will talk about string matching algorithms: Rabin-Karp fingerprinting and the Knuth-Morris-Pratt algorithm (KMP). You should read Jeff Erickson's notes (see webpage).

Exercises

1 KMP Solve

- 1.1 [w] Compute the prefix function π for the pattern $P = abcaba$ and draw the corresponding automaton with failure links. Run the matching algorithm on the text string $T = aaabcababcbbaabcabaab$.
- 1.2 [w] Compute the prefix function π for the pattern $ababbabbabbabbabbabb$ when the alphabet is $\Sigma = \{a, b\}$ and draw the corresponding automaton with failure links.
- 1.3 Explain how to determine the occurrences of pattern P in the text T by examining the π function for the string $P\$T$, where $\$$ is a new character not in the alphabet.

Rabin-Karp[w] Run the Karp-Rabin fingerprinting algorithm with the following fingerprint function:

$$F(P) = \sum_{i=1}^m 2^{m-i} P[i] \mod 5 \qquad F(T_s) = \sum_{i=1}^m 2^{m-i} T[s+i-1] \mod 5$$

on the following example: $T = 100101110110001$ and $P = 1011$.

2 String matching with gaps In *string matching with gaps* the pattern P can contain a *gap character* \star that can match *any* string (of arbitrary length even length zero). An example of such a string is $P = ab \star ac \star a$, which occurs in the text $T = bababacbcc a$ in two ways:

T:	b	ab	ab	ac	bcc	a
P:		ab	\star	ac	\star	a

or

T:	bab	ab		ac	bcc	a
P:		ab	\star	ac	\star	a

There are no gap characters in the text—only in the pattern.

Give an algorithm to find an occurrence of a pattern P containing gap characters in a text T in time $O(n + m)$. That is, preprocessing time + matching time should be $O(n + m)$.

3 Christmas songs (exam 2015) You are putting together a set of Christmas songs that will be handed out at the Christmas party. The Dean has declared that every song must contain the sentence "Merry_Christmas_Dear_Dean", where "_" denotes a blank space. E.g. the song:

```
We_wish_you_a_Merry_Christmas_
We_wish_you_a_Merry_Christmas_
We_wish_you_a_Merry_Christmas_
Dear_Dean_
Dear_Dean
```

contains one occurrence of the sentence "Merry_Christmas_Dear_Dean" (line breaks are disregarded).

Formally, you are given a set S of songs S_1, \dots, S_k and a sentence P . Song S_i contains n_i characters and P contains m characters. Let $n = \sum_{i=1}^k n_i$ denote the total number of characters in the songs. All the strings are over an alphabet of size $O(1)$. Describe an algorithm that returns all the songs that contain P . Analyze the asymptotic running time of your algorithm. Remember to argue that your algorithm is correct.

- 4 [†] **Implement KMP** Implement the KMP algorithm on CodeJudge.
- 5 **Pattern matching on trees** Solve exercise 9 in Jeff Ericksons notes.
- 6 **Finite String Matching Automaton** Consider the following automaton: Instead of having failure edges as in the KMP automaton each state/node has $|\Sigma|$ edges out of it. The automaton should still have the property that if you are in state i after having read j characters from T then $P[1 \dots i]$ is the longest prefix of P that matches a suffix of $T[1 \dots j]$ (as is the case in the KMP automaton).
- 6.1 Construct both the string-matching automaton for the pattern $P = abcaba$ and run the matching algorithm on the text string $T = aaabcbababbaabcbabaab$.
- 6.2 What is the running time of matching a text T given the finite string matching automaton?
- 6.3 Argue that it takes at least $\Omega(m|\Sigma|)$ time to construct the finite string matching automaton
- 6.4 [*] Give an efficient algorithm for computing the transition function δ for the string-matching automaton corresponding to a given pattern P . Your algorithm should run in time $O(m|\Sigma|)$. (Hint: Prove that $\delta(q, a) = \delta(\pi[q], a)$ if $q = m$ or $P[q + 1] \neq a$.)