

Package ‘infPackage’

February 7, 2025

Type Package
Title Ecological Inference Elections
Version 0.1.0
Author Charles Thraves, Pablo Ubilla, Daniel Hermosilla
Maintainer Daniel Hermosilla <daniel.hermosilla.r@uchile.cl>
Description A package to implement the RxG ecological inference algorithms as exposed in Thraves, C and Ubilla, P paper.
License MIT
Encoding UTF-8
LinkingTo Rcpp
Imports Rcpp,
 jsonlite,
 R6,
 devtools,
 roxygen2
Roxygen list(markdown = FALSE, load = ``source", r6 = FALSE, old_usage = TRUE)
RoxygenNote 7.3.2

Contents

as.matrix.rxc	2
ballots.rxc	2
candidates.rxc	3
groups.rxc	3
predict.rxc	4
sum.rxc	4
summary.rxc	5
update.rxc	5
Index	6

as.matrix.rxc

Extract Probability Matrix from rxc Object

Description

Extracts the probability matrix from an rxc object.

Usage

```
## S3 method for class 'rxc'
as.matrix(object)
```

Arguments

object An rxc object.

Value

A matrix containing the estimated probabilities.

Examples

```
model <- rxc$new(X = matrix(1:15, 5, 3), W = matrix(1:50, 5, 10))
as.matrix(model)
```

ballots.rxc

Get Number of Ballot Boxes

Description

Returns the number of ballot boxes in an rxc object.

Usage

```
ballots.rxc(object)
```

Arguments

object An rxc object.

Value

An integer representing the number of ballots.

Examples

```
model <- rxc$new(X = matrix(1:15, 5, 3), W = matrix(1:50, 5, 10))
ballots(model)
```

candidates.rxc	<i>Get Number of Candidates</i>
----------------	---------------------------------

Description

Returns the current number of candidates in an rxc object.

Usage

```
candidates.rxc(object)
```

Arguments

object	An rxc object.
--------	----------------

Value

An integer representing the number of candidates.

Examples

```
model <- rxc$new(X = matrix(1:15, 5, 3), W = matrix(1:50, 5, 10))
candidates(model)
```

groups.rxc	<i>Get Number of Groups</i>
------------	-----------------------------

Description

Returns the current number of groups in an rxc object.

Usage

```
groups.rxc(object)
```

Arguments

object	An rxc object.
--------	----------------

Value

An integer representing the number of groups.

Examples

```
model <- rxc$new(X = matrix(1:15, 5, 3), W = matrix(1:50, 5, 10))
groups(model)
```

predict.rxc	<i>Predict RxC Probabilities</i>
-------------	----------------------------------

Description

Predicts the RxC probability using the EM algorithm of an rxc object. This function is a wrapper around `compute()`.

Usage

```
## S3 method for class 'rxc'
predict(object, ...)
```

Arguments

object	An rxc object.
...	Additional arguments to pass to <code>compute()</code> .

Value

A matrix of estimated probabilities.

Examples

```
model <- rxc$new(X = matrix(1:9, 3, 3), W = matrix(1:9, 3, 3))
predict(model, "Hit and Run", step_size = 1000, samples = 5000)
```

sum.rxc	<i>Get Total Number of Voters</i>
---------	-----------------------------------

Description

Returns the total number of voters in the system from an rxc object.

Usage

```
## S3 method for class 'rxc'
sum(object)
```

Arguments

object	An rxc object.
--------	----------------

Value

An integer representing the total number of voters.

Examples

```
model <- rxc$new(X = matrix(1:15, 5, 3), W = matrix(1:50, 5, 10))
sum(model)
```

summary.rxc*Summarize rxc Object*

Description

Returns a list with the principal attributes of an rxc object.

Usage

```
## S3 method for class 'rxc'  
summary(object)
```

Arguments

object An rxc object.

Value

A list with the principal attributes.

Examples

```
model <- rxc$new(X = matrix(1:15, 5, 3), W = matrix(1:10, 2, 5))  
summary(model)
```

update.rxc*Update an rxc Object*

Description

Updates an existing rxc model with a new EM algorithm computation.

Usage

```
## S3 method for class 'rxc'  
update(object, ...)
```

Arguments

object An rxc object.
... New parameters to pass to compute().

Value

The updated rxc object.

Examples

```
model <- rxc$new(X = matrix(1:15, 5, 3), W = matrix(1:50, 5, 10))  
update(model, "MVN PDF")
```

Index

`as.matrix.rxc`, [2](#)
`ballots.rxc`, [2](#)
`candidates.rxc`, [3](#)
`groups.rxc`, [3](#)
`predict.rxc`, [4](#)
`sum.rxc`, [4](#)
`summary.rxc`, [5](#)
`update.rxc`, [5](#)