

OOP Exam Retake – PlayersAndMonsters

Overview

PlayersAndMonsters is a battle game. It's all about battles between players with their cards. Each player has health and deck of cards. Each card gives bonus damage and bonus health. The players fight on the battle field with their cards.

Setup

You are **allowed only to write classes**. You are **not allowed to modify the existing**.

Task 1: Structure (50 points)

You are given **6** interfaces, and you have to implement their functionality in the **correct classes**.

There are **3** types of models in the application: **Player**, **Card** and **BattleField**:

BasePlayer

BasePlayer is a **base class** for any **type of player** and it **should not be able to be instantiated**.

Data

- **username** – **String** (If the username is **null or empty**, throw an **IllegalArgumentException** with message "Player's username cannot be null or an empty string.")
- **health** – **int** - the health of a player (if the health is below **0**, throw an **IllegalArgumentException** with message "Player's health bonus cannot be less than zero.")
- **cardRepository** – **CardRepository** repository of all user's cards.
- **isDead** – **boolean** – shows if player is alive(**false**) or dead(**true**).

Behavior

void takeDamage(int damagePoints)

The takeDamage() method decreases players' points.

- If the **damagePoints** are **below 0** throw an **IllegalArgumentException** with message "Damage points cannot be less than zero."
- Player's health should not drop below zero

Constructor

BasePlayer should take the following values upon initialization:

CardRepository cardRepository, **String** username, **int** health

Child Classes

There are several concrete types of **BasePlayer**:

Beginner

- **defaultHealthPoints** - constant value equal to 50

Constructor should take the following values upon initialization:

CardRepository cardRepository, **String** username

Advanced

- **defaultHealthPoints** - constant value equal to 250

Constructor should take the following values upon initialization:

`CardRepository` cardRepository, `String` username

BaseCard

BaseCard is a base class for any type of card and it should not be able to be instantiated.

Data

- **name** – `String` (If the card name is **null or empty** throw an `IllegalArgumentException` with message "Card's name cannot be null or an empty string.")
- **damagePoints** – `int` (If the damage points are **below zero**, throw an `IllegalArgumentException` with message "Card's damage points cannot be less than zero.")
- **healthPoints** - `int` (If the health points are **below zero**, throw an `IllegalArgumentException` with message "Card's HP cannot be less than zero.")

Constructor

BaseCard should take the following values upon initialization:

`String` name, `int` damagePoints, `int` healthPoints

Child Classes

There are several concrete types of **BaseCard**:

MagicCard

- **defaultDamagePoints** - constant value equal to 5
- **defaultHealthPoints** - constant value equal to 80

TrapCard

- **defaultDamagePoints** - constant value equal to 120
- **defaultHealthPoints** - constant value equal to 5

BattleFieldImpl

The battle field is the place where the fight happens.

Behavior

void fight(Player attacker, Player enemy)

That's the most interesting method.

- If one of the users is **dead**, throw new `IllegalArgumentException` with message "Player is dead!"
- If the player is a **beginner**, increase his **health** with 40 points and **increase** all damage **points** of all **cards** for the user with 30.
- Before the fight, both players get bonus health points from their deck.
- Attacker attacks **first** and after that the enemy attacks. If **one of the players** is dead you should **stop** the fight.

PlayerRepositoryImpl

The player repository holds information for all users.

Data

- `getCount()` – `int` – returns the count of players
- `players` – collection of players

Behavior

`void add(Player player)`

Adds a player in the collection.

- If the player is **null**, throw an **IllegalArgumentException** with message **"Player cannot be null"**.
- If a player exists with a name equal to the name of the given player, throw an **IllegalArgumentException** with message **"Player {username} already exists!"**.

`boolean remove(Player player)`

Removes a player from the collection.

- If the player is **null**, throw an **IllegalArgumentException** with message **"Player cannot be null"**.

`Player find(String username)`

Returns a player with that username.

CardRepositoryImpl

The card repository holds information for all cards.

Data

- `getCount()` – `int` – return the count of cards
- `cards` – collection of cards

Behavior

`void add(Card card)`

Adds a card in the collection.

- If the card is **null**, throw an **IllegalArgumentException** with message **"Card cannot be null!"**.
- If a card exists with a name equal to the name of the given card, throw an **IllegalArgumentException** with message **"Card {name} already exists!"**.

`boolean remove(Card card)`

Removes a card from the collection.

- If the **card** is **null**, throw an **IllegalArgumentException** with message **"Card cannot be null!"**.

`Card find(String name)`

Returns a card with that name.

Task 2: Business Logic (150 points)

The Controller Class

The business logic of the program should be concentrated around several **commands**. You are given interfaces, which you have to implement in the correct classes.

Note: The `ManagerControllerImpl` class SHOULD NOT handle exceptions! The tests are designed to expect exceptions, not messages!

The first interface is **ManagerController**. You must create a **ManagerControllerImpl** class, which implements the interface and implements all of its methods. The given methods should have the following logic:

Commands

There are several commands, which control the business logic of the application. They are stated below.

AddPlayer Command

Parameters

- `type` - `String`
- `username` - `String`

Functionality

Creates a **player** with the provided **type** and **name**. The method should **return** the following **message**:

"Successfully added player of type {type} with username: {username}"

AddCard Command

Parameters

- `type` - `string`
- `name` - `string`

Functionality

Creates a **card** with the provided **type** and **name**. The method should **return** the following message:

"Successfully added card of type {type}Card with name: {name}"

AddPlayerCard Command

Parameters

- `username` - `String`
- `cardName` - `String`

Functionality

Adds the given **card** to the **user card repository**. The method should **return** the following message:

"Successfully added card: {cardName} to user: {username}"

Fight Command

Parameters

- `attackPlayer` - `String`
- `enemyPlayer` - `String`

Functionality

Sends the **attacker** player and **enemy** player to the **battle field**. The method should return the following message:

```
"Attack user health {attack player} - Enemy user health {enemy player}"
```

Report Command

Functionality

Returns a report message in format:

```
"Username: {username} - Health: {health} - Cards {cards count}"
```

```
"Card: {name} - Damage: {card damage}"
```

```
"###"
```

Exit Command

Functionality

Terminate program.

Input / Output

Input

Below, you can see the **format** in which **each command** will be given in the input:

- **AddPlayer** {player type} {player username}
- **AddCard** {card type} {card name}
- **AddPlayerCard** {username} {card name}
- **Fight** {attack user} {enemy user}
- **Report**

Output

Print the output from each command when issued. If an exception is thrown during any of the commands' execution, print the exception message.

Examples

Input

```

AddPlayer Beginner handyUser33
AddPlayer Advanced cool11
AddPlayer Beginner testUser
AddPlayer Advanced goro5
AddPlayer Beginner ivan12
AddPlayer Advanced goerge00
AddPlayer Advanced userUser
AddPlayer Beginner fakeAccount123
AddCard Trap Cyber
AddCard Magic Sorcerer
AddCard Trap Iris
AddCard Trap Jar
AddCard Magic Blaster
AddCard Trap Scientist
AddCard Magic Plushfire
AddCard Magic Substitoad
AddCard Trap Neptune
AddPlayerCard handyUser33 Cyber
AddPlayerCard handyUser33 Blaster
AddPlayerCard handyUser33 Neptune
AddPlayerCard ivan12 Iris
AddPlayerCard ivan12 Scientist
AddPlayerCard ivan12 Plushfire
AddPlayerCard goro5 Plushfire
AddPlayerCard userUser Neptune
Fight handyUser33 ivan12
Fight goro5 userUser
Report
Exit

```

Output

```

Successfully added player of type Beginner with username: handyUser33
Successfully added player of type Advanced with username: cool11
Successfully added player of type Beginner with username: testUser
Successfully added player of type Advanced with username: goro5
Successfully added player of type Beginner with username: ivan12
Successfully added player of type Advanced with username: goerge00
Successfully added player of type Advanced with username: userUser
Successfully added player of type Beginner with username: fakeAccount123
Successfully added card of type TrapCard with name: Cyber
Successfully added card of type MagicCard with name: Sorcerer
Successfully added card of type TrapCard with name: Iris
Successfully added card of type TrapCard with name: Jar
Successfully added card of type MagicCard with name: Blaster
Successfully added card of type TrapCard with name: Scientist
Successfully added card of type MagicCard with name: Plushfire
Successfully added card of type MagicCard with name: Substitoad
Successfully added card of type TrapCard with name: Neptune
Successfully added card: Cyber to user: handyUser33
Successfully added card: Blaster to user: handyUser33
Successfully added card: Neptune to user: handyUser33
Successfully added card: Iris to user: ivan12
Successfully added card: Scientist to user: ivan12
Successfully added card: Plushfire to user: ivan12
Successfully added card: Plushfire to user: goro5
Successfully added card: Neptune to user: userUser
Attack user health 180 - Enemy user health 0
Attack user health 0 - Enemy user health 150
Username: handyUser33 - Health: 180 - Cards 3
Card: Cyber - Damage: 150
Card: Blaster - Damage: 35
Card: Neptune - Damage: 150
###

```

```

Username: cool11 - Health: 250 - Cards 0
###
Username: testUser - Health: 50 - Cards 0
###
Username: goro5 - Health: 0 - Cards 1
Card: Plushfire - Damage: 35
###
Username: ivan12 - Health: 0 - Cards 3
Card: Iris - Damage: 150
Card: Scientist - Damage: 150
Card: Plushfire - Damage: 35
###
Username: goerge00 - Health: 250 - Cards 0
###
Username: userUser - Health: 150 - Cards 1
Card: Neptune - Damage: 150
###
Username: fakeAccount123 - Health: 50 - Cards 0
###

```

Input

```

AddPlayer Beginner handyUser33
AddPlayer Advanced handyUser33
AddPlayer Advanced cool11
AddPlayer Beginner testUser
AddCard Trap Cyber
AddCard Magic Sorcerer
AddCard Trap Iris
AddCard Trap Iris
AddCard Trap Jar
AddPlayerCard handyUser33 Cyber
AddPlayerCard handyUser33 Blaster
AddPlayerCard cool11 Neptune
AddPlayerCard testUser Neptune
Fight handyUser33 testUser
Fight handyUser33 testUser
Fight handyUser33 testUser
Fight cool11 testUser
Report
Exit

```

Output

```

Successfully added player of type Beginner with username: handyUser33
Player handyUser33 already exists!
Successfully added player of type Advanced with username: cool11
Successfully added player of type Beginner with username: testUser
Successfully added card of type TrapCard with name: Cyber
Successfully added card of type MagicCard with name: Sorcerer
Successfully added card of type TrapCard with name: Iris
Card Iris already exists!
Successfully added card of type TrapCard with name: Jar
Successfully added card: Cyber to user: handyUser33
Card cannot be null!
Card cannot be null!
Card cannot be null!
Attack user health 95 - Enemy user health 0
Player is dead!
Player is dead!
Player is dead!
Username: handyUser33 - Health: 95 - Cards 1
Card: Cyber - Damage: 150
###

```

```
Username: cool11 - Health: 250 - Cards 0
###
Username: testUser - Health: 0 - Cards 0
###
```