Bits, Bytes, and Integers

Computer Systems
2^{nd} Lecture, Sep 5 2018

Michael Kirkedal Thomsen

Based on slides by:

Randal E. Bryant and David R. O'Hallaron

Today: Bits, Bytes, and Integers

- **Representing information as bits**
- **Bit-level manipulations**
- **Integers**
  - Representation: unsigned and signed
  - Conversion, casting
  - Expanding, truncating

Everything is bits

- **Each bit is 0 or 1**
- **By encoding/interpreting sets of bits in various ways**
  - Computers determine what to do (instructions)
  - … and represent and manipulate numbers, sets, strings, etc…



- **Why bits? Why no decimals? Does there exist another possibility?**

5 minutes discussions!

Everything is bits

- **Why bits? Electronic Implementation**
  - Easy to store with bistable elements
  - Reliably transmitted on noisy and inaccurate wires



- **... But there exist many models that are not**
  - E.g. Ternary (3-state) logic, analog computers, quantum computers

For example, can count in binary

- **Base 2 Number Representation**
  - Represent 15213_{10} as 11101101101101_2
  - Represent 1.20_{10} as $1.0011001100110011[0011]..._2$
  - Represent 1.5213×10^4 as $1.1101101101101_2 \times 2^{13}$

Encoding Byte Values

- **Byte = 8 bits**
  - Binary 00000000_2 to 11111111_2
  - Decimal: 0_{10} to 255_{10}
  - Hexadecimal 00_{16} to FF_{16}
    - Base 16 number representation
    - Use characters ‘0’ to ‘9’ and ‘A’ to ‘F’
    - Write $FA1D37B_{16}$ in C as
      - 0xFA1D37B
      - 0xfa1d37b

Hex	Decimal	Binary
0	0	0000
1	1	0001
2	2	0010
3	3	0011
4	4	0100
5	5	0101
6	6	0110
7	7	0111
8	8	1000
9	9	1001
A	10	1010
B	11	1011
C	12	1100
D	13	1101
E	14	1110
F	15	1111

Let's play a game

- http://bit.ly/integer-representation

Example Data Representations

C Data Type	Typical 32-bit	Typical 64-bit	x86-64
`char`	1	1	1
`short`	2	2	2
`int`	4	4	4
`long`	4	8	8
`int32_t`	4	4	4
`int64_t`	8	8	8
`float`	4	4	4
`double`	8	8	8
`long double`	–	–	10/16
pointer	4	8	8

Today: Bits, Bytes, and Integers

- Representing information as bits
- **Bit-level manipulations**
- Integers
  - Representation: unsigned and signed
  - Conversion, casting
  - Expanding, truncating
  - Summary

Boolean Algebra

- **Developed by George Boole in 19th Century**
  - Algebraic representation of logic
    - Encode "True" as 1 and "False" as 0

And

- A&B = 1 when both A=1 and B=1

&	0	1
0	0	0
1	0	1

Or

- A|B = 1 when either A=1 or B=1

|	0	1
0	0	1
1	1	1

Not

- ~A = 1 when A=0

~	
0	1
1	0

Exclusive-Or (Xor)

- A^B = 1 when either A=1 or B=1, but not both

^	0	1
0	0	1
1	1	0

Implementation of Boolean Algebra

- **Transistor**



Implementation of Boolean Algebra

- **CMOS Circuit diagram**



Inverter



NAND gate

Implementation of Boolean Algebra

- **Logic diagram**



Application of Boolean Algebra

- **Applied to Digital Systems by Claude Shannon**
  - 1937 MIT Master's Thesis
  - Reason about networks of relay switches
    - Encode closed switch as 1, open switch as 0



Connection when

A&~B | ~A&B

= A^B

General Boolean Algebras

- **Operate on Bit Vectors**
  - Operations applied bitwise

```
  01101001     01101001     01101001
& 01010101   | 01010101   ^ 01010101   ~ 01010101
  01000001     01111101     00111100     10101010
```

- **All of the Properties of Boolean Algebra Apply**

Example: Representing & Manipulating Sets

- **Representation**
  - Width w bit vector represents subsets of {0, …, w–1}
  - $a_j = 1$ if $j \in A$

    - 01101001 { 0, 3, 5, 6 }
    - *76543210*

    - 01010101 { 0, 2, 4, 6 }
    - *76543210*

- **Operations**

&	Intersection	01000001	{ 0, 6 }
|	Union	01111101	{ 0, 2, 3, 4, 5, 6 }
^	Symmetric difference	00111100	{ 2, 3, 4, 5 }
~	Complement	10101010	{ 1, 3, 5, 7 }

Bit-Level Operations in C

- **Operations &, |, ~, ^ Available in C**
  - Apply to any “integral” data type
    - `long, int, short, char, unsigned`
  - View arguments as bit vectors
  - Arguments applied bit-wise
- **Examples (Char data type)**
  - `~0x41` → `0xBE`
    - $\sim 01000001_2 \rightarrow 10111110_2$
  - `~0x00` → `0xFF`
    - $\sim 00000000_2 \rightarrow 11111111_2$
  - `0x69 & 0x55` → `0x41`
    - $01101001_2 \,\&\, 01010101_2 \rightarrow 01000001_2$
  - `0x69 | 0x55` → `0x7D`
    - $01101001_2 \mid 01010101_2 \rightarrow 01111101_2$

Contrast: Logic Operations in C

- **Contrast to Logical Operators**
  - `&&, ||, !`
    - View 0 as "False"
    - Anything nonzero as "True"
    - Always return 0 or 1
    - Early termination
- **Examples (char data type)**
  - `!0x41` → `0x00`
  - `!0x00` → `0x01`
  - `!!0x41` → `0x01`
  - `0x69 && 0x55` → `0x01`
  - `0x69 || 0x55` → `0x01`
  - `p && *p` (avoids null pointer access)

Contrast: Logic Operations in C

- **Contrast to Logical Operators**
  - `&&, ||, !`
    - View 0 as "False"
    - Anything nonzero as "True"
    - Always return 0 or 1
    - Early termination
- **Examples (char data type)**
  - `!0x41` → `0x00`
  - `!0x00` → `0x01`
  - `!!0x41` → `0x01`
  - `0x69 && 0x55` → `0x01`
  - `0x69 || 0x55` → `0x01`
  - `p && *p` (avoids null pointer access)

Watch out for && vs. & (and || vs. |)... one of the more common oopsies in C programming

Shift Operations

- **Left Shift: `x << y`**
  - Shift bit-vector **`x`** left **`y`** positions
    - – Throw away extra bits on left
    - Fill with 0's on right
- **Right Shift: `x >> y`**
  - Shift bit-vector **`x`** right **`y`** positions
    - Throw away extra bits on right
  - Logical shift
    - Fill with 0's on left
  - Arithmetic shift
    - Replicate most significant bit on left
- **Undefined Behavior**
  - Shift amount < 0 or ≥ word size

Argument `x`	`01100010`
`<< 3`	`00010000`
Log. `>> 2`	`00011000`
Arith. `>> 2`	`00011000`

Argument `x`	`10100010`
`<< 3`	`00010000`
Log. `>> 2`	`00101000`
Arith. `>> 2`	`11101000`

Today: Bits, Bytes, and Integers

- Representing information as bits
- Bit-level manipulations
- **Integers**
  - **Representation: unsigned and signed**
  - Conversion, casting
  - Expanding, truncating
  - Summary

Encoding Integers

Unsigned

$$B2U(X) = \sum_{i=0}^{w-1} x_i \cdot 2^i$$

Two's Complement

$$B2T(X) = -x_{w-1} \cdot 2^{w-1} + \sum_{i=0}^{w-2} x_i \cdot 2^i$$

Sign Bit

```
short int x =  15213;
short int y = -15213;
```

- **C `short` 2 bytes long**

	Decimal	Hex	Binary
`x`	15213	`3B 6D`	`00111011 01101101`
`y`	-15213	`C4 93`	`11000100 10010011`

- **Sign Bit**
  - For 2's complement, most significant bit indicates sign
    - 0 for nonnegative
    - 1 for negative

Two-complement Encoding Example (Cont.)

```
x =      15213: 00111011 01101101
y =     -15213: 11000100 10010011
```

Weight	15213		-15213	
1	1	1	1	1
2	0	0	1	2
4	1	4	0	0
8	1	8	0	0
16	0	0	1	16
32	1	32	0	0
64	1	64	0	0
128	0	0	1	128
256	1	256	0	0
512	1	512	0	0
1024	0	0	1	1024
2048	1	2048	0	0
4096	1	4096	0	0
8192	1	8192	0	0
16384	0	0	1	16384
-32768	0	0	1	-32768
Sum		**15213**		**-15213**

Numeric Ranges

- **Unsigned Values**
  - *UMin* = 0
    000…0
  - *UMax* = $2^w - 1$
    111…1

- **Two's Complement Values**
  - *TMin* = -2^{w-1}
    100…0
  - *TMax* = $2^{w-1} - 1$
    011…1
- **Other Values**
  - Minus 1
    111…1

Values for *W* = 16

	Decimal	Hex	Binary
`UMax`	65535	FF FF	11111111 11111111
`TMax`	32767	7F FF	01111111 11111111
`TMin`	-32768	80 00	10000000 00000000
`-1`	-1	FF FF	11111111 11111111
`0`	0	00 00	00000000 00000000

Values for Different Word Sizes

	W			
	8	**16**	**32**	**64**
UMax	255	65,535	4,294,967,295	18,446,744,073,709,551,615
TMax	127	32,767	2,147,483,647	9,223,372,036,854,775,807
TMin	-128	-32,768	-2,147,483,648	-9,223,372,036,854,775,808

- **Observations**
  - $|TMin| = TMax + 1$
    - Asymmetric range
  - $UMax = 2 * TMax + 1$

- **C Programming**
  - #include <limits.h>
  - Declares constants, e.g.,
    - ULONG_MAX
    - LONG_MAX
    - LONG_MIN
  - Values platform specific

Unsigned & Signed Numeric Values

X	B2U(X)	B2T(X)
0000	0	0
0001	1	1
0010	2	2
0011	3	3
0100	4	4
0101	5	5
0110	6	6
0111	7	7
1000	8	–8
1001	9	–7
1010	10	–6
1011	11	–5
1100	12	–4
1101	13	–3
1110	14	–2
1111	15	–1

- **Equivalence**
  - Same encodings for nonnegative values
- **Uniqueness**
  - Every bit pattern represents unique integer value
  - Each representable integer has unique bit encoding
- **⇒ Can Invert Mappings**
  - U2B(x) = B2U^{-1}(x)
    - Bit pattern for unsigned integer
  - T2B(x) = B2T^{-1}(x)
    - Bit pattern for two's comp integer

Today: Bits, Bytes, and Integers

- Representing information as bits
- Bit-level manipulations
- **Integers**
  - Representation: unsigned and signed
  - **Conversion, casting**
  - Expanding, truncating
  - Addition, negation, multiplication, shifting
  - Summary

Mapping Between Signed & Unsigned





- **Mappings between unsigned and two's complement numbers:**
  Keep bit representations and reinterpret

Mapping Signed ↔ Unsigned

Bits	Signed		Unsigned
0000	0		0
0001	1		1
0010	2		2
0011	3		3
0100	4		4
0101	5	→ T2U →	5
0110	6	← U2T ←	6
0111	7		7
1000	-8		8
1001	-7		9
1010	-6		10
1011	-5		11
1100	-4		12
1101	-3		13
1110	-2		14
1111	-1		15

Mapping Signed ↔ Unsigned

Bits	Signed	Unsigned
0000	0	0
0001	1	1
0010	2	2
0011	3	3
0100	4	4
0101	5	5
0110	6	6
0111	7	7
1000	-8	8
1001	-7	9
1010	-6	10
1011	-5	11
1100	-4	12
1101	-3	13
1110	-2	14
1111	-1	15

=

+/- 16

Relation between Signed & Unsigned



Maintain Same Bit Pattern



Large negative weight
becomes
Large positive weight

Conversion Visualized

- **2's Comp. → Unsigned**
  - Ordering Inversion
  - Negative → Big Positive



Signed vs. Unsigned in C

- **Constants**
  - By default are considered to be signed integers
  - Unsigned if have "U" as suffix

```
0U, 4294967259U
```

- **Casting**
  - Explicit casting between signed & unsigned same as U2T and T2U

```
int tx, ty;
unsigned ux, uy;
tx = (int) ux;
uy = (unsigned) ty;
```

  - Implicit casting also occurs via assignments and procedure calls

```
tx = ux;
uy = ty;
```

Casting Surprises

- **Expression Evaluation**
  - If there is a mix of unsigned and signed in single expression, ***signed values implicitly cast to unsigned***
  - Including comparison operations **<, >, ==, <=, >=**
  - Examples for *W* = 32: **TMIN = -2,147,483,648 , TMAX = 2,147,483,647**

- **Constant$_1$ / Constant$_2$ / Relation / Evaluation**

Constant$_1$	Constant$_2$	Relation	Evaluation
0	0U	**==**	**unsigned**
-1	0	**<**	**signed**
-1	0U	**>**	**unsigned**
2147483647	-2147483647-1	**>**	**signed**
2147483647U	-2147483647-1	**<**	**unsigned**
-1	-2	**>**	**signed**
(unsigned)-1	-2	**>**	**unsigned**
2147483647	2147483648U	**<**	**unsigned**
2147483647	(int) 2147483648U	**>**	**signed**

Summary
Casting Signed ↔ Unsigned: Basic Rules

- **Bit pattern is maintained**
- **But reinterpreted**
- **Can have unexpected effects: adding or subtracting 2^w**

- **Expression containing signed and unsigned int**
  - `int` is cast to `unsigned`!!

Today: Bits, Bytes, and Integers

- Representing information as bits
- Bit-level manipulations
- **Integers**
  - Representation: unsigned and signed
  - Conversion, casting
  - **Expanding, truncating**
  - Summary

Sign Extension

- **Task:**
  - Given *w*-bit signed integer *x*
  - Convert it to *w*+*k*-bit integer with same value
- **Rule:**
  - Make *k* copies of sign bit:
  - $X' = \underbrace{x_{w-1}, \ldots, x_{w-1}}_{k \text{ copies of MSB}}, x_{w-1}, x_{w-2}, \ldots, x_0$



Sign Extension Example

```
short int x =  15213;
int      ix = (int) x;
short int y = -15213;
int      iy = (int) y;
```

	Decimal	Hex	Binary
x	15213	3B 6D	00111011 01101101
ix	15213	00 00 3B 6D	00000000 00000000 00111011 01101101
y	-15213	C4 93	11000100 10010011
iy	-15213	FF FF C4 93	11111111 11111111 11000100 10010011

- Converting from smaller to larger integer data type
- C automatically performs sign extension

Today: Bits, Bytes, and Integers

- Representing information as bits
- Bit-level manipulations
- **Integers**
  - Representation: unsigned and signed
  - Conversion, casting
  - Expanding, truncating
  - **Summary**

Summary:
Expanding, Truncating: Basic Rules

- **Expanding (e.g., short int to int)**
  - Unsigned: zeros added
  - Signed: sign extension
  - Both yield expected result

- **Truncating (e.g., unsigned to unsigned short)**
  - Unsigned/signed: bits are truncated
  - Result reinterpreted
  - Unsigned: mod operation
  - Signed: similar to mod
  - For small numbers yields expected behavior

Integer C Puzzles

Initialization

```
int x = foo();
int y = bar();
unsigned ux = x;
unsigned uy = y;
```

- `x < 0` ⇒ `((x*2) < 0)`
- `ux >= 0`
- `x & 7 == 7` ⇒ `(x<<30) < 0`
- `ux > -1`
- `x > y` ⇒ `-x < -y`
- `x * x >= 0`
- `x > 0 && y > 0` ⇒ `x + y > 0`
- `x >= 0` ⇒ `-x <= 0`
- `x <= 0` ⇒ `-x >= 0`
- `(x|-x)>>31 == -1`
- `ux >> 3 == ux/8`
- `x >> 3 == x/8`
- `x & (x-1) != 0`