

UNIVERSIDAD RAFAEL LANDÍVAR

ÁREA DE INGENIERÍA

Programacion Web



PRÁCTICA

Componentes con React

AUTOR

Sajvin Gómez, Mario Daniel (1612921)

Componente Contador



Ejemplo de componente con React

Contador: 4



```
import React, { useState } from "react";
import "./Contador.css"; // Importamos los estilos externos

const Counter = () => {
  const [count, setCount] = useState(0);

  return (
    <div className="counter-container">
      <h2>Contador: {count}</h2>
      <div>
        <button
          onClick={() => setCount(count + 1)}
          style={{ backgroundColor: "green", color: "white", margin: "5px"
        }}
      >
        Sumar
      </button>
      <button
          onClick={() => setCount(count - 1)}
          style={{ backgroundColor: "red", color: "white", margin: "5px" }}
        >
        Restar
      </button>
      <button onClick={() => setCount(0)} className="reset-button">
        Resetear
      </button>
    </div>
  )
}
```

```

    </div>
  </div>
);
};

export default Counter;

```

Componente listar nombre



```

import React, { useState } from "react";
import "./ListaNombre.css"; // Importamos los estilos

const NameList = () => {
  const [firstName, setFirstName] = useState("");
  const [lastName, setLastName] = useState("");
  const [names, setNames] = useState([]);

  const addName = () => {
    if (firstName.trim() && lastName.trim()) {
      setNames([...names, `${firstName} ${lastName}`]);
      setFirstName("");
      setLastName("");
    }
  };

  return (
    <div className="name-list-container">

```

```
<h2>Agregar Nombre y Apellido</h2>
<input
  type="text"
  placeholder="Nombre"
  value={firstName}
  onChange={(e) => setFirstName(e.target.value)}
/>
<input
  type="text"
  placeholder="Apellido"
  value={lastName}
  onChange={(e) => setLastName(e.target.value)}
/>
<button onClick={addName}>Agregar</button>

<ul>
  {names.map((name, index) => (
    <li key={index}>{name}</li>
  ))}
</ul>
</div>
);
};

export default NameList;
```