1 2 3 4 5 6 7 8 9 10

Submit Assessment

The information below is common to Questions **1 to 2**

(Question 1 and 2) Train a Linear Regression model on the training dataset with fit_intercept = False and compute 'r2_score' on the test dataset

Use arrows ← and → to navigate

Question 1 / 10 Flag for review • **1 mark**

What is the value of the r2_score obtained on the test dataset? [Enter 3 decimal places]

Your answer

Enter your answer

Only numeric input is accepted for this question.

Video2PPT.com

← Previous

Next →

The information below is common to Questions **1 to 2**

(Question 1 and 2) Train a Linear Regression model on the training dataset with fit_intercept = False and compute 'r2_score' on the test dataset

Question 2 / 10 Flag for review • 1 mark

What is the index of the feature with the highest absolute coefficient value? Note that index starts from 0

Your answer

Enter your answer

Only numeric input is accepted for this question.

Video2PPT.com

The information below is common to Questions **3 to 4**

(Question 3 and 4) Train a Ridge model on the training data with the following parameters:

- solver = 'sag'

- tol = 0.0005

- random_state = 42

Compute the 'r2_score' on the test data

Question 3 / 10 Flag for review • 1 mark

What is the value of the r2_score obtained on the test dataset? [Enter 3 decimal places]

Your answer

Enter your answer

Only numeric input is accepted for this question.

Video2PPT.com

The information below is common to Questions **3 to 4**

(Question 3 and 4) Train a Ridge model on the training data with the following parameters:

- solver = 'sag'

- tol = 0.0005

- random_state = 42

Compute the 'r2_score' on the test data

Question 4 / 10 Flag for review • 1 mark

Enter the value of the intercept_ attribute obtained after training the model. [Enter 3 decimal places]

Your answer

Enter your answer

Only numeric input is accepted for this question.

Video2PPT.com

The information below is common to Questions **5 to 6**

(Question 5 and 6) Train a Lasso model on the training data with the following parameters:

- alpha = 100

- random_state = 42

Compute the 'r2_score' on the test data

Use arrows ← and → to navigate

Question 5 / 10 Flag for review • **1 mark**

What is the value of the r2_score obtained on the test dataset? [Enter 3 decimal places]

Your answer

Enter your answer

Only numeric input is accepted for this question.

Video2PPT.com

The information below is common to Questions **5 to 6**

(Question 5 and 6) Train a Lasso model on the training data with the following parameters:

- alpha = 100

- random_state = 42

Compute the 'r2_score' on the test data

Use arrows ← and → to navigate

Question 6 / 10 Flag for review • **1 mark**

How many coefficients have a value in the range [-1,1]?

Your answer

Enter your answer

Only numeric input is accepted for this question.

Video2PPT.com

The information below is common to Questions **7 to 7**

(Question 7) Train a KNeighborsRegressor with the following parameters:

- n_neighbors = 10

- p = 1

Predict the target for the test data and compute the root_mean_squared_error(RMSE) on the same

Use arrows ← and → to navigate

Question 7 / 10 Flag for review • **1 mark**

What is the value of the rmse obtained on the test dataset? [Enter 3 decimal places]

Your answer

Enter your answer

Only numeric input is accepted for this question.

Video2PPT.com

The information below is common to Questions **8 to 8**

(Question 8) Train a Decision Tree Regressor with the following parameters:

- max_depth = 10

- min_samples_split = 6

- min_samples_leaf = 6

- random_state = 42

Predict the target for the test data and compute the root_mean_squared_error(RMSE) on the same

Use arrows ← and → to navigate

Question 8 / 10 Flag for review • **1 mark**

What is the value of the rmse obtained on the test dataset? [Enter 3 decimal places]

Your answer

Enter your answer

Only numeric input is accepted for this question.

Video2PPT.com

The information below is common to Questions **9 to 10**

(Question 9 and 10) Perform Hyperparameter Tuning using GridSearchCV on AdaBoostRegressor. Use random_state = 42. Value of cv = 4. Hyperparameter tuning is to be done over:

- n_estimators as [10,50,100,200,500]

- learning_rate as [0.1,0.5,1,2]

Use the best model obtained to compute the score on the test data

Use arrows ← and → to navigate

Question 9 / 10 Flag for review • 1 mark

What is the value of the r2_score obtained on the test dataset? [Enter 3 decimal places]

Your answer

Enter your answer

Only numeric input is accepted for this question.

Video2PPT.com

The information below is common to Questions **9 to 10**

(Question 9 and 10) Perform Hyperparameter Tuning using GridSearchCV on AdaBoostRegressor. Use random_state = 42. Value of cv = 4. Hyperparameter tuning is to be done over:

- n_estimators as [10,50,100,200,500]

- learning_rate as [0.1,0.5,1,2]

Use the best model obtained to compute the score on the test data

Use arrows ← and → to navigate

Question 10 / 10 Flag for review • **1 mark**

What is the value of n_estimators obtained for the best model after training with GridSearchCV?

Your answer

Enter your answer

Only numeric input is accepted for this question.

Video2PPT.com

VIDEO2PPT

.MP4

From Video to Slides in One Click

Try it Now

- Save time
- Auto-generate slides
- Clean, editable layouts

