

# Network Security - Week 3

João Soares

DCC/FCUP

2023

# Web Security Considerations

The World Wide Web is fundamentally a *client/server application* running over the internet and TCP/IP intranets

# Web Security Considerations

The World Wide Web is fundamentally a *client/server application* running over the internet and TCP/IP intranets

## Tailored security tools are necessary

- Web servers easy to configure and manage
- Web content increasingly easy to develop
- Underlying software extraordinarily complex
- Security flaws may be hidden

# Web Security Considerations

A Web server can be exploited as a **launching pad** into the corporation/agency's entire computer complex

A Web server can be exploited as a **launching pad** into the corporation/agency's entire computer complex


## Casual/untrained users for web-based services

- Not aware of the security risks
- Don't have the tools/knowledge to take effective countermeasures...


# Web threats - a quick list

	Threats	Consequences	Countermeasures
<b>Integrity</b>	<ul style="list-style-type: none"><li>- Modification of user data</li><li>- Trojan horse browser</li><li>- Modification of memory</li><li>- Modification of communication messages</li></ul>	<ul style="list-style-type: none"><li>- Loss of information</li><li>- Compromise of machine</li><li>- Vulnerability to all other threats</li></ul>	<ul style="list-style-type: none"><li>- Checksums</li><li>- Erasure Codes</li><li>- Message Authentication Codes</li></ul>
<b>Confidentiality</b>	<ul style="list-style-type: none"><li>- Eavesdropping on the network</li><li>- Theft of information from the server</li><li>- Theft of data from the client</li><li>- Information about network configuration</li><li>- Information about clients</li></ul>	<ul style="list-style-type: none"><li>- Privacy breaches</li><li>- Loss of anonymity</li></ul>	<ul style="list-style-type: none"><li>- Encryption algorithms</li><li>- Web proxies</li></ul>
<b>Denial of Service</b>	<ul style="list-style-type: none"><li>- Killing of user threads</li><li>- Flooding machine with bogus requests</li><li>- Filling up disk/memory</li><li>- Isolating machine via DNS disruption</li></ul>	<ul style="list-style-type: none"><li>- Disruptive</li><li>- Annoying</li><li>- Preventing user from performing key tasks</li></ul>	<b>Very hard to prevent</b> <ul style="list-style-type: none"><li>- Traffic monitoring</li><li>- Response plan</li></ul>
<b>Authentication</b>	<ul style="list-style-type: none"><li>- Impersonation of legitimate users</li><li>- Man-in-the-Middle</li></ul>	<ul style="list-style-type: none"><li>- Misrepresentation of user</li><li>- Covert eavesdrop channels</li><li>- Covert message injection</li></ul>	<ul style="list-style-type: none"><li>- <b>What we learned last class!</b></li></ul>

# Open Systems Interconnection Layers




# Open Systems Interconnection Layers






# Open Systems Interconnection Layers




# Security at the OSI Layers




- Kerberos is at the application level - over UDP

# Security at the OSI Layers



- SSL/TLS is a middleware between application and TCP

# Security at the OSI Layers



- IPsec refines the IP protocol

# What is SSL?

- Secure Sockets Layer (SSL) is the protocol used for the majority of secure internet transactions today

# What is SSL?

- Secure Sockets Layer (SSL) is the protocol used for the majority of secure internet transactions today
- For instance, if you want to buy a book at *amazon.com* ...
  - You want to be sure you are talking with Amazon (authentication)

# What is SSL?

- Secure Sockets Layer (SSL) is the protocol used for the majority of secure internet transactions today
- For instance, if you want to buy a book at *amazon.com* ...
  - You want to be sure you are talking with Amazon (authentication)
  - Credit card data must be protected (confidentiality + integrity)

# What is SSL?

- Secure Sockets Layer (SSL) is the protocol used for the majority of secure internet transactions today
- For instance, if you want to buy a book at *amazon.com* ...
  - You want to be sure you are talking with Amazon (authentication)
  - Credit card data must be protected (confidentiality + integrity)
  - If payment is successful, Amazon does not care who you are
  - ... no need for mutual authentication



General-purpose system implemented as a set of protocols that **rely on TCP** to ensure message delivery guarantees

General-purpose system implemented as a set of protocols that **rely on TCP** to ensure message delivery guarantees

Implementation choices:

- Part of the underlying protocol suite
- Embedded in specific packages

General-purpose system implemented as a set of protocols that **rely on TCP** to ensure message delivery guarantees


Implementation choices:

- Part of the underlying protocol suite
- Embedded in specific packages


## Transport Layer Security

- Evolved from the commercial protocol SSL
- Improved configurability, protocols, ...

# SSL/TLS Protocol Stack




# SSL/TLS Protocol Stack



## Record Protocol

- Message Integrity and Confidentiality
- Uses key agreed on handshake


# SSL/TLS Protocol Stack



## Handshake

- Most complex protocol
- Crucial to establish a cryptographic key


# SSL/TLS Protocol Stack



## Change Cipher Spec

- Single message
- Establishes agreed cipher specifications

# SSL/TLS Protocol Stack




## Alert protocol

- TLS alerts
- Can provoke warning, or terminate connections



# SSL/TLS Protocol Stack



## Heartbeat protocol

- Pings regularly
- Prevents connection from shutting down

## TLS connection

- A transport that provides a suitable type of service
- For TLS, such connections are peer-to-peer
- Connections are transient
- Every connection is associated with *one session*

## TLS connection

- A transport that provides a suitable type of service
- For TLS, such connections are peer-to-peer
- Connections are transient
- Every connection is associated with *one session*

## TLS session

- An association between a client and a server
- Created by the handshake protocol
- Defines a set of crypto security parameters, shared among multiple connections
- Used to avoid expensive negotiation stages, at the start of each connection

- Session identifier
- Peer certificate
- Compression method
- Cipher spec
- Master secret
- Is resumable

- Session identifier
  - An arbitrary byte sequence chosen by the server to identify an active or resumable session state
- Peer certificate
- Compression method
- Cipher spec
- Master secret
- Is resumable

- Session identifier
- Peer certificate
  - An X509.v3 certificate of the peer. Optional element of the state
- Compression method
- Cipher spec
- Master secret
- Is resumable

- Session identifier
- Peer certificate
- Compression method
  - The algorithm used to compress data prior to encryption
- Cipher spec
- Master secret
- Is resumable

- Session identifier
- Peer certificate
- Compression method
- Cipher spec
  - Specified the bulk data encryption algorithm and a hash algorithm used for MAC computation; also defines cryptographic attributes, e.g. hash\_size
- Master secret
- Is resumable



- Session identifier
- Peer certificate
- Compression method
- Cipher spec
- Master secret
  - A symmetric secret key shared between client and server
- Is resumable

- Session identifier
- Peer certificate
- Compression method
- Cipher spec
- Master secret
- Is resumable
  - A flag indicating whether the session can be used to initiate new connections

# TLS Connection State

- Server and client randomness
- Server write MAC key
- Client write MAC key
- Server write key
- Client write key
- Initialization vectors
- Sequence numbers

# TLS Connection State

- Server and client randomness
  - Byte sequences chosen by the server and client for each connection
- Server write MAC key
- Client write MAC key
- Server write key
- Client write key
- Initialization vectors
- Sequence numbers

# TLS Connection State

- Server and client randomness
- Server write MAC key
  - Cryptographic key used to authenticate messages sent by the server
- Client write MAC key
  - Cryptographic key used to authenticate messages sent by the client
- Server write key
- Client write key
- Initialization vectors
- Sequence numbers

# TLS Connection State

- Server and client randomness
- Server write MAC key
- Client write MAC key
- Server write key
  - Cryptographic key used to encrypt messages sent by the server
- Client write key
  - Cryptographic key used to encrypt messages sent by the client
- Initialization vectors
- Sequence numbers

# TLS Connection State


- Server and client randomness
- Server write MAC key
- Client write MAC key
- Server write key
- Client write key
- Initialization vectors
  - Values used in encryption to ensure freshness of ciphertexts, so that two encryptions of the same message do not produce the same ciphertext
  - Initialized by the handshake protocol
  - Final ciphertext of each record used as IV for the next one – chaining blocks
- Sequence numbers

# TLS Connection State

- Server and client randomness
- Server write MAC key
- Client write MAC key
- Server write key
- Client write key
- Initialization vectors
- Sequence numbers
  - Each party maintains sequence numbers for messages sent/received
  - Initialized at the cipher spec message
  - May not exceed  $2^{64} - 1$



# Record Protocol Operation



- Resulting unit transmitted via TCP
- Receiver decrypts, verifies, decompresses and reassembles

# Handshake Protocol

- Most complex part of TLS
- Used before any application data is transmitted

# Handshake Protocol

- Most complex part of TLS
- Used before any application data is transmitted
- Allows the server and client to:
  - Mutually authenticate

# Handshake Protocol

- Most complex part of TLS
- Used before any application data is transmitted
- Allows the server and client to:
  - Mutually authenticate
  - Negotiate encryption and MAC algorithms

# Handshake Protocol

- Most complex part of TLS
- Used before any application data is transmitted
- Allows the server and client to:
  - Mutually authenticate
  - Negotiate encryption and MAC algorithms
  - Negotiate cryptographic keys

# Handshake Protocol

- Most complex part of TLS
- Used before any application data is transmitted
- Allows the server and client to:
  - Mutually authenticate
  - Negotiate encryption and MAC algorithms
  - Negotiate cryptographic keys
- Comprises a series of messages exchanged by client and server
- Exchange made on four stages

# Handshake Protocol - 4 stages




Figure 22.6 Handshake Protocol Action

## Stage 1

- Hello!
- Here are the specs I can use
  - TLS version
  - Session ID
  - CipherSuite
  - Compression method

# Handshake Protocol - 4 stages




Figure 22.6 Handshake Protocol Action

## Stage 2 and 3

- Certificate exchange
- Certificate verification
- Key agreement
  - RSA/Diffie-Hellman

## Stage 4

- Client sends cipher specs
- Client sends a finished protected with authenticated encryption using new algorithms, keys and secrets
- Server verifies and does the same



# Change Cipher Spec Protocol

- The simplest of the four
- A single message of a single byte. Value is either 0 or 1

# Change Cipher Spec Protocol

- The simplest of the four
- A single message of a single byte. Value is either 0 or 1
- Sole purpose of this message is to cause pending state to be copied into the current state – used as confirmation message
- Hence updating the cipher suite in usage

- Conveys TLS-related alerts to peer entity
  - Alert messages are compressed and encrypted
  - Example of fatal alert: incorrect MAC
  - Example of non-fatal alert: close\_notify (notifies the recipient that the sender will not send any more messages in this communication)

# Alert Protocol

- Conveys TLS-related alerts to peer entity
  - Alert messages are compressed and encrypted
  - Example of fatal alert: incorrect MAC
  - Example of non-fatal alert: close\_notify (notifies the recipient that the sender will not send any more messages in this communication)
- Each message consists of two bytes
- First byte refers to the severity; the second specifies

- Conveys TLS-related alerts to peer entity
  - Alert messages are compressed and encrypted
  - Example of fatal alert: incorrect MAC
  - Example of non-fatal alert: close\_notify (notifies the recipient that the sender will not send any more messages in this communication)
- Each message consists of two bytes
- First byte refers to the severity; the second specifies
  - Fatal messages terminate the connection immediately
  - Other connections for that session may continue, but no additional connections are established

# Heartbeat Protocol - P1

- A periodic signal is generated by hardware or software to indicate normal operation, or to synchronize with other parts of a system

# Heartbeat Protocol - P1

- A periodic signal is generated by hardware or software to indicate normal operation, or to synchronize with other parts of a system
- Typically used to monitor the availability of a protocol entity – the name should be self-explanatory!

# Heartbeat Protocol - P1

- A periodic signal is generated by hardware or software to indicate normal operation, or to synchronize with other parts of a system
- Typically used to monitor the availability of a protocol entity – the name should be self-explanatory!
- The heartbeat protocol runs on top of the TLS record protocol
- Relies on two message types



# Heartbeat Protocol - P1

- A periodic signal is generated by hardware or software to indicate normal operation, or to synchronize with other parts of a system
- Typically used to monitor the availability of a protocol entity – the name should be self-explanatory!
- The heartbeat protocol runs on top of the TLS record protocol
- Relies on two message types
  - HEARTBEAT\_REQUEST - prove you are alive
  - HEARTBEAT\_RESPONSE - i am, indeed, alive

- Request includes payload length; payload; padding fields

# Heartbeat Protocol - P2


- Request includes payload length; payload; padding fields
- Response must include **an exact copy** of the received payload
  - Prevent replay attacks!

- Request includes payload length; payload; padding fields
- Response must include **an exact copy** of the received payload
  - Prevent replay attacks!
- Serves two main purposes
  - Assures the sender that the recipient is still alive, even if there is no regular activity in the underlying TCP connection
  - Generates activity across the connection during idle periods, which avoids closure by a firewall automatic mechanisms to disable idle connections



- OpenSSL contains an open-source implementation of SSL/TLS
- A fatal flaw in OpenSSL, breaching privacy of log-in data
- Estimated victims: **two-thirds** of Web servers

# Heartbleed - How it works



## Heartbeat

- Send heartbeat message
- Extract; prep payload; send reply
- Response contains exactly the expected payload size
- Check for payload validity

## Heartbleed

- Small payload disguised as big one
- Extract; prep (bad) payload; send reply
- Response contains **much** more than expected
- Gets TLS keys, cookies, passwords!

# SSL/TLS Applications

- Secure e-commerce using SSL/TLS
- Client authentication not needed until client decides to buy something, which triggers the authentication stage

# SSL/TLS Applications

- Secure e-commerce using SSL/TLS
- Client authentication not needed until client decides to buy something, which triggers the authentication stage
- SSL provides secure channel for sending credit card information



- Secure e-commerce using SSL/TLS
- Client authentication not needed until client decides to buy something, which triggers the authentication stage
- SSL provides secure channel for sending credit card information
- Client authenticated using credit card information, merchant bears (most of) the risk
- Widely deployed

- Secure e-commerce using SSL/TLS
- Client authentication not needed until client decides to buy something, which triggers the authentication stage
- SSL provides secure channel for sending credit card information
- Client authenticated using credit card information, merchant bears (most of) the risk
- Widely deployed
- Secure remote login / **Secure Shell**
- Authenticated, encrypted path to the OS over the network

# HTTPS

## HTTP over SSL

- Combination of HTTP and SSL to implement secure communication between a Web browser and a Web server

# HTTPS

## HTTP over SSL

- Combination of HTTP and SSL to implement secure communication between a Web browser and a Web server
- Build into all modern Web browsers
  - URL addresses begin with HTTPS://

# HTTPS

## HTTP over SSL

- Combination of HTTP and SSL to implement secure communication between a Web browser and a Web server
- Build into all modern Web browsers
  - URL addresses begin with HTTPS://
- Agent acting as HTTP client also acts as the TLS client

# HTTPS

## HTTP over SSL

- Combination of HTTP and SSL to implement secure communication between a Web browser and a Web server
- Build into all modern Web browsers
  - URL addresses begin with HTTPS://
- Agent acting as HTTP client also acts as the TLS client
- When HTTPS is used, the following elements are protected:
  - URL of requested document

# HTTPS

## HTTP over SSL

- Combination of HTTP and SSL to implement secure communication between a Web browser and a Web server
- Build into all modern Web browsers
  - URL addresses begin with HTTPS://
- Agent acting as HTTP client also acts as the TLS client
- When HTTPS is used, the following elements are protected:
  - URL of requested document
  - Document contents
  - Contents of browser forms

# HTTPS

## HTTP over SSL

- Combination of HTTP and SSL to implement secure communication between a Web browser and a Web server
- Build into all modern Web browsers
  - URL addresses begin with HTTPS://
- Agent acting as HTTP client also acts as the TLS client
- When HTTPS is used, the following elements are protected:
  - URL of requested document
  - Document contents
  - Contents of browser forms
  - Cookies sent from browser to server and vice-versa




# HTTPS

## HTTP over SSL

- Combination of HTTP and SSL to implement secure communication between a Web browser and a Web server
- Build into all modern Web browsers
  - URL addresses begin with HTTPS://
- Agent acting as HTTP client also acts as the TLS client
- When HTTPS is used, the following elements are protected:
  - URL of requested document
  - Document contents
  - Contents of browser forms
  - Cookies sent from browser to server and vice-versa
  - Contents of HTTP header

# First handshake, then HTTP through TLS



## Layered connection

- Connection begins with a TLS CLIENTHELLO, which triggers the TLS handshake
- When it finishes, the client sends the first HTTP request
- All data sent as TLS application data

# Closing Connections

- An HTTP client or server can indicate the closing of a connection by including the line `CONNECTION: CLOSE` in an HTTP record

# Closing Connections

- An HTTP client or server can indicate the closing of a connection by including the line `CONNECTION: CLOSE` in an HTTP record
- The closure of an HTTPS connection requires TLS to close the connection with the peer TLS entity on the remote side – closing the underlying TCP connection

# Closing Connections

- An HTTP client or server can indicate the closing of a connection by including the line `CONNECTION: CLOSE` in an HTTP record
- The closure of an HTTPS connection requires TLS to close the connection with the peer TLS entity on the remote side – closing the underlying TCP connection
- TLS implementation must initiate an exchange of closure alerts before closing a connection

# Closing Connections

- An HTTP client or server can indicate the closing of a connection by including the line `CONNECTION: CLOSE` in an HTTP record
- The closure of an HTTPS connection requires TLS to close the connection with the peer TLS entity on the remote side – closing the underlying TCP connection
- TLS implementation must initiate an exchange of closure alerts before closing a connection
- TLS session ensures that cryptographic parameters are kept (avoiding expensive negotiations)



- Originally developed for UNIX, now available on most OSs

# Secure Shell Protocol



- Originally developed for UNIX, now available on most OSs
- Provides an authenticated, encrypted path to the OS command line over the network





- Originally developed for UNIX, now available on most OSs
- Provides an authenticated, encrypted path to the OS command line over the network
- Replacement for insecure utilities such as Telnet, rlogin, rsh




- Originally developed for UNIX, now available on most OSs
- Provides an authenticated, encrypted path to the OS command line over the network
- Replacement for insecure utilities such as Telnet, rlogin, rsh
- Protects against spoofing attacks and modification of data




- Originally developed for UNIX, now available on most OSs
- Provides an authenticated, encrypted path to the OS command line over the network
- Replacement for insecure utilities such as Telnet, rlogin, rsh
- Protects against spoofing attacks and modification of data
- The *de facto* method to access remote resources

# SSH Protocol(s)




# SSH Protocol(s)




- **Transport Layer Protocol** provides server authentication, confidentiality, and integrity.

# SSH Protocol(s)




- **Transport Layer Protocol** provides server authentication, confidentiality, and integrity.
- **User Authentication Protocol** authenticates the client-side user to the server

# SSH Protocol(s)



- **Transport Layer Protocol** provides server authentication, confidentiality, and integrity.
- **User Authentication Protocol** authenticates the client-side user to the server
- **Connection Protocol** multiplexes the encrypted tunnel into several logical channels

# SSH Transport Layer Protocol




## Multiple stages

- 1 Protocol and SW versions agreement
- 2 Supported algorithms exchanged
- 3 Key exchange finishes
- 4 Service ready to execute



# SSH Transport Layer Protocol



## Algorithm Agreement

- One (or more) algorithms must be listed
- Encryption algorithm used for confidentiality
- MAC algorithm used for data authentication
- Compression algorithm optional

# SSH Authentication Methods

## Public Key

- The client sends a message to the server that has the client's public key. Signed with the private key
- Upon receiving the message, the server check if the key is acceptable for authentication, and if the signature is correct

## Password

## Hostbased

# SSH Authentication Methods

## Public Key

## Password

- The client sends a message containing a plaintext password, encrypted via the Transport Layer Protocol

## Hostbased

# SSH Authentication Methods

Public Key

Password

Hostbased

- Authentication is performed on the client's host rather than the client itself
- This method works by having the client send a signature created with the private key of its host
- Instead of verifying the client identity, the host identity is checked
- Provides group anonymity

# SSH Connection Protocol

- SSH Connection Protocol runs on top of the Transport Layer Protocol
  - The secure authenticated connection, referred to as *tunnel*, is used by the Connection Protocol to multiplex a number of logical channels

# SSH Connection Protocol

- SSH Connection Protocol runs on top of the Transport Layer Protocol
  - The secure authenticated connection, referred to as *tunnel*, is used by the Connection Protocol to multiplex a number of logical channels
- Channel mechanism
  - All types of communications using SSH supported via separate channels
  - Either side can open a channel
  - Channel type identifies the application/purpose of the channel

- **Session**

- The remote execution of a program
- Program may be a shell, an application such as file transfer, a system command, or a built-in subsystem

- **Session**

- The remote execution of a program
- Program may be a shell, an application such as file transfer, a system command, or a built-in subsystem

- **X11**

- Refers to the X Window System, a computer software system and network protocol that provide a GUI for networked computers



- **Session**

- The remote execution of a program
- Program may be a shell, an application such as file transfer, a system command, or a built-in subsystem

- **X11**

- Refers to the X Window System, a computer software system and network protocol that provide a GUI for networked computers

- **Forwarded-tcpip**

- Remote port forwarding (from a remote computer to the local computer)

- **Direct-tcpip**

- Local port forwarding (insecure TCP connection → SSH tunnel)

- Provides the ability to convert any insecure TCP connection into a secure SSH connection – a.k.a. SSH tunneling

# Port Forwarding

- Provides the ability to convert any insecure TCP connection into a secure SSH connection – a.k.a. SSH tunneling
- Incoming TCP traffic is delivered to the appropriate application on the basis of the port number (an identifier of a user in TCP)

# Port Forwarding

- Provides the ability to convert any insecure TCP connection into a secure SSH connection – a.k.a. SSH tunneling
- Incoming TCP traffic is delivered to the appropriate application on the basis of the port number (an identifier of a user in TCP)
- An application may employ multiple port numbers
  - HTTP servers usually listen on port 80 (443 for HTTPS)

## SSL and TLS

- Architecture over classical network layers

## SSL and TLS

- Architecture over classical network layers
- TLS sessions are ephemeral, connections allow for multiple sessions

## SSL and TLS

- Architecture over classical network layers
- TLS sessions are ephemeral, connections allow for multiple sessions
- Protocols rely on TLS for secure communication

## SSL and TLS

- Architecture over classical network layers
- TLS sessions are ephemeral, connections allow for multiple sessions
- Protocols rely on TLS for secure communication
- HTTPS uses TLS over HTTP



## SSL and TLS

- Architecture over classical network layers
- TLS sessions are ephemeral, connections allow for multiple sessions
- Protocols rely on TLS for secure communication
- HTTPS uses TLS over HTTP
- Attacks at the TLS layer - Heartbleed

## SSL and TLS

- Architecture over classical network layers
- TLS sessions are ephemeral, connections allow for multiple sessions
- Protocols rely on TLS for secure communication
- HTTPS uses TLS over HTTP
- Attacks at the TLS layer - Heartbleed

## SSH

- Relies on an handshake similar to TLS...

## SSL and TLS

- Architecture over classical network layers
- TLS sessions are ephemeral, connections allow for multiple sessions
- Protocols rely on TLS for secure communication
- HTTPS uses TLS over HTTP
- Attacks at the TLS layer - Heartbleed

## SSH

- Relies on an handshake similar to TLS...
- ... but authentication is not certificate-based

## SSL and TLS

- Architecture over classical network layers
- TLS sessions are ephemeral, connections allow for multiple sessions
- Protocols rely on TLS for secure communication
- HTTPS uses TLS over HTTP
- Attacks at the TLS layer - Heartbleed

## SSH

- Relies on an handshake similar to TLS...
- ... but authentication is not certificate-based
- Allows for different channels with different purposes

# Network Security - Week 3

João Soares

DCC/FCUP

2023