SENTINEL Lab 1 Primer: `make`, tests and `/proc`

ECE 476 Engineering System Software • Fall 2026 • University of Victoria

This primer gives the basic knowledge for three parts of Lab 1: your `Makefile`, your tests, and `proc.c`. It has no marks, and it adds no rule. The Lab 1 Brief[1] and `syscall.h`[2] state the contract. Run each command of this primer in the top directory of your repository.

1 `make` and your Makefile

`make` builds files from rules. It reads the file `Makefile` in the current directory. `make <target>` runs the rule for that target, and `make` alone runs the first rule of the file. The examples below come from two files that you have: `Makefile` (the top-level Makefile) and `common/Makefile`.

1.1 A rule

```
$(BUILD):
        mkdir -p $(BUILD)
```

A rule has a **target**, a colon, the **prerequisites**, and on the next lines the **recipe**. The target is the file that the rule makes. The prerequisites are the files that the target needs; this rule has none. The recipe is the shell commands. **Each recipe line starts with a TAB character.** Spaces give an error that starts with `Makefile:2: *** missing separator`. `make` runs a recipe only when the target does not exist, or when a prerequisite is newer than the target.

1.2 Variables

```
CC      := gcc
PROFILE ?= world
export CC CFLAGS LDFLAGS BUILD
```

- `NAME := value` sets a variable. `$(NAME)` gives its value.
- `NAME ?= value` sets it only when it has no value yet.
- A value on the command line replaces the value in the file: `make lab1 PROFILE=dirty`.[3]
- `export` gives the variables to each `make` that this one starts, such as the `make` of your lab: `$(MAKE) -C src/libsyscall` runs `make` in that directory. In your Makefile, `CC := gcc` replaces that value, and `CC ?= gcc` keeps it. So the Brief, Section 4.1, asks for `?=`.

1.3 Patterns and automatic variables

```
$(LIB): $(OBJS)
        ar rcs $@ $^

$(BUILD)/common/%.o: %.c $(HDRS) | $(BUILD)/common
        $(CC) $(CFLAGS) -c -o $@ $<
```

Item	What it means
`$@`, `$<`, `$^`	the target; the first prerequisite; all the prerequisites
`%`	a pattern: the same text in the target and in the prerequisite. One rule makes `contact.o` from `contact.c`, and each other `.o` from its `.c`
`| $(BUILD)/common`	this prerequisite must exist before the recipe runs, but its time does not cause a new build. Use it for a directory
`gcc -c -o x.o x.c`	compile one source file to one object file, with no link
`ar rcs lib.a a.o b.o`	put the object files into a static library

Your library needs the same two rules, with `src/%.c` as the prerequisite, `include/sentinel/syscall.h` as the header, and `-Iinclude -I../../common` in the compile command. `-I` adds a directory in which the compiler finds the files of `#include`. Put the object files in a directory of their own, for example `ODIR := $(BUILD)/libsyscall`.

A program has no extension. One pattern rule, `$(BUILD)/%: tests/%.c $(LIB)`, makes `$(BUILD)/demo_lab1` and each `$(BUILD)/test_*`. Its recipe is `$(CC) $(CFLAGS) -Iinclude -I../../common -o $@ $<`, then the three libraries in the order that the Brief gives in Section 4.1. The linker reads from left to right, so a library comes after the file that uses it. `-lm` is the mathematics library.

[1] The Lab 1 Brief, `docs/lab1/lab1_brief.pdf` in your repository. It states the contract of Lab 1.

[2] `src/libsyscall/include/sentinel/syscall.h`, in your repository. It states what each function of Lab 1 does, and each of its errors.

[3] `make lab1` writes a new feed, `build/live/feed.txt`, from the four sensors, and it runs your demo on it. The SENTINEL Lab Manual, Section 4, `docs/manual/sentinel_manual.pdf`, lists each make target.

Two functions give lists of files:

- `$(wildcard src/*.c)` gives each file on the disk that matches. The top-level Makefile uses `$(wildcard $(d)/Makefile)`. `*` is a shell pattern: any text.
- `$(patsubst src/%.c,$(ODIR)/%.o,$(SRCS))` changes each name in a list: `src/io.c` becomes `$(ODIR)/io.o`. Here `%` is the pattern of `make`. Use `*` to find files on the disk, and `%` to change a name or to write a pattern rule.

1.4 Recipes are shell commands

```
test: all
	@for d in $(READY); do $(MAKE) -C $$d test || exit 1; done
```

- `.PHONY: all test ...` names the targets that are not files. Without it, if a file `test` exists, `make` prints `make: 'test' is up to date.` and does not run the rule.
- `@` at the start of a line: `make` does not print the command.
- `$$d`: `make` changes `$$` to `$`, so the shell sees `$d`. One `$` is for `make`.
- `|| exit 1`: when one command fails, the loop stops, and `make` stops. Your `test` target uses this to stop at the first failure.

1.5 What your Makefile needs

Brief,[4] Section 4.1	**What you use**
1. `$(BUILD)/libsyscall.a`	`$(wildcard src/*.c)`, `patsubst` to the names in `$(ODIR)`, the object rule, `ar rcs`, and a rule with `mkdir -p $(ODIR)`
2. `$(BUILD)/demo_lab1`	the program rule, and a first rule `all: $(LIB) $(BUILD)/demo_lab1`: the top level runs your `make` with no target
3. the `test` target	`TESTS`, the names `$(BUILD)/test_*` from `$(wildcard tests/test_*.c)` and `patsubst`; then `test: $(TESTS)`, and a recipe `for t in $(TESTS); do $$t || exit 1; done`
4. the `clean` target	`rm -rf` of each file and directory that your rules made. Run it with `make -C src/libsyscall clean`

`make -n` prints the commands only. To read more, use the GNU make manual, https://www.gnu.org/software/make/manual/make.html, first "An Introduction to Makefiles".

2 Tests and `assert`

A test is a C program. It calls your functions and checks each result with `assert`. When each check is true, it returns 0. `make test`[5] runs it.

`assert(expression)` comes from `<assert.h>`. When the expression is false, it prints the file, the line, the function and the expression, and it stops the program. The shell prints `Aborted`, and the exit status is 134. So `make` sees a failure. For example, with `ENOENT` changed to `EACCES` in the test below:

```
test_device: /tmp/test_device.c:25: missing_then_file: Assertion `errno == EACCES' failed.
Aborted (core dumped)
```

Do not put a call that does work inside `assert`. With `-DNDEBUG`, the compiler removes each `assert` and the call in it.

The example below tests the promises of `common/device.h`, the smallest given file. It is an example only: the Brief, Section 4.2, tells you not to test `common/`. Your four tests have the same form, and test the promises and errors of `syscall.h`.[6]

[4] The Lab 1 Brief, `docs/lab1/lab1_brief.pdf` in your repository. It states the contract of Lab 1.

[5] `make test` runs the tests of each lab that has a `Makefile`, and `make test LAB=2` those of Labs 1 and 2 only. The SENTINEL Lab Manual, Section 4, `docs/manual/sentinel_manual.pdf`, lists each make target.

[6] `src/libsyscall/include/sentinel/syscall.h`, in your repository. It states what each function of Lab 1 does, and each of its errors.

```c
/* Example: the promises of common/device.h. */
#include "device.h"

#include <assert.h>
#include <errno.h>
#include <fcntl.h>
#include <stdio.h>
#include <unistd.h>

/* A NULL path gives -1 and EINVAL. */
static void null_path(void)
{
    errno = 0;
    int fd = device_open(NULL, 0);
    assert(fd == -1);
    assert(errno == EINVAL);
}
```

```c
/* ENOENT, and then a file still opens. */
static void missing_then_file(void)
{
    int fd = device_open("/tmp/no_such_device", 0);
    assert(fd == -1);
    assert(errno == ENOENT);
    const char *path = "/tmp/test_device.txt";
    int w = open(path, O_WRONLY | O_CREAT, 0600);
    assert(w >= 0);
    close(w);
    fd = device_open(path, 0);
    assert(fd >= 0);
    close(fd);
    unlink(path);
}

int main(void)
{
    null_path();
    missing_then_file();
    printf("test_device: OK\n");
    return 0;
}
```

The demo and the tests link with the whole library. Until each of the 15 functions exists, the link fails with an `undefined reference` error that names a missing function. So first write a stub of each function: it sets `errno` to `ENOSYS` and returns -1 (or `NULL`). Write each test before its code (test-driven development). Take one promise or one error of `syscall.h`,[7] write a test function for it, and see `make test`[8] fail. Then write the code until the test passes, and go to the next promise. To read more, run `man 3 assert` and `man 3 errno`.

A test without a Makefile. You type each command. To test `proc.c`, run these commands in the top directory, after one `make`. `F` holds the flags, so that each line is short.

```
$ F="-std=c11 -D_GNU_SOURCE -Wall -Wextra -Werror -g -Isrc/libsyscall/include -Icommon"
$ mkdir -p build/libsyscall
$ gcc $F -c -o build/libsyscall/io.o    src/libsyscall/src/io.c
$ gcc $F -c -o build/libsyscall/clock.o src/libsyscall/src/clock.c
$ gcc $F -c -o build/libsyscall/log.o   src/libsyscall/src/log.c
$ gcc $F -c -o build/libsyscall/proc.o  src/libsyscall/src/proc.c
$ ar rcs build/libsyscall.a build/libsyscall/*.o
$ gcc $F -o build/test_proc src/libsyscall/tests/test_proc.c build/libsyscall.a build/libcommon.a -lm
$ build/test_proc
```

After each change, you type them again. **A test with your Makefile.** Your rules hold the same commands, and one `make` command runs them. `make` also compiles only the files that changed: after a change to `proc.c`, it compiles `proc.c` again, but not `io.c`, `clock.c` and `log.c`. A target of your Makefile is a full path, because `BUILD` is an absolute path, so the commands use `$PWD`, the current directory.

To test	Commands
one file	`make -C src/libsyscall $PWD/build/test_proc`, then `build/test_proc`
two files	`make -C src/libsyscall $PWD/build/test_io $PWD/build/test_log`, then `build/test_io && build/test_log`: `&&` stops at the first failure
each file	`make test`: it builds and runs each test in turn, and stops at the first failure

3 /proc and proc.c

Linux shows each process that runs as a directory, `/proc/<pid>`. The kernel makes its files at the time that you read them, and they are not on a disk. `/proc/self` is the directory of the process that reads it.

3.1 The file status

```
$ grep -E 'Name|VmRSS|ctxt' /proc/self/status
Name:        grep
VmRSS:            1736 kB
```

[7] `src/libsyscall/include/sentinel/syscall.h`, in your repository. It states what each function of Lab 1 does, and each of its errors.

[8] `make test` runs the tests of each lab that has a `Makefile`, and `make test LAB=2` those of Labs 1 and 2 only. The SENTINEL Lab Manual, Section 4, `docs/manual/sentinel_manual.pdf`, lists each make target.

```
voluntary_ctxt_switches:        0
nonvoluntary_ctxt_switches:        0
```

Each line is a key, a colon, spaces or tabs, and the value. The comment of `proc_info_t` in `syscall.h`[9] gives the key of each field. The keys are the same on aarch64 and on x86_64.

3.2 Where `open_fds` comes from

`/proc/<pid>/fd` is a directory. It has one entry for each open descriptor of the process. The name of an entry is the descriptor number, and the entry points to the open file.

```
$ ls -la /proc/self/fd
total 0
dr-x------ 2 linux linux  0 Oct 22 05:24 .
dr-xr-xr-x 9 linux linux  0 Oct 22 05:24 ..
lrwx------ 1 linux linux 64 Oct 22 05:24 0 -> /dev/pts/1
lrwx------ 1 linux linux 64 Oct 22 05:24 1 -> /dev/pts/1
lrwx------ 1 linux linux 64 Oct 22 05:24 2 -> /dev/pts/1
lr-x------ 1 linux linux 64 Oct 22 05:24 3 -> /proc/98364/fd
```

- `0`, `1` and `2` are the standard input, output and error of `ls`. Here they point to the terminal.
- `.` and `..` are in each directory. `ls -a` shows them, and `readdir` also gives them. They are not descriptors, so do not count them.
- `3` points to this directory: 98364 is the pid of `ls`, the process that read `/proc/self`. `ls` opened it to read the directory. `opendir` in your `proc_report` also opens one. So when the process is the caller, do not count it.

So here `open_fds` is 3. To check it exactly, your test counts `/proc/self/fd` itself with `opendir`, and compares. It compares `name` with `/proc/self/comm`. A test causes each error in this way:

Error	A call that causes it
`ENOENT`	`proc_report(INT_MAX, &info)`: no pid is that large
`EACCES`	`proc_report(1, &info)`: root owns pid 1. Skip it when `getuid()` is 0
a failed write	`proc_report_write(-1, &info)` gives `EBADF`; a descriptor of `/dev/full` gives `ENOSPC`

3.3 The steps

Use your library where it has a function, and the C library (`man 3 opendir`, and so on) only where it has none. To check your work, run `make test`,[10] then the acceptance test[11] (`make accept1`), which has 6 checks of `proc.c`.

`proc_report(pid, out)`:

1. If `out` is `NULL`, set `errno` to `EINVAL` and return -1. Then set each field of `out` to 0 (`memset`).
2. If `pid` is 0, the directory is `/proc/self`, and `out->pid` is `getpid()`. If not, the directory is `/proc/<pid>`, and `out->pid` is `pid`.
3. Open `<directory>/status` with `sc_open_read`. If it fails, return -1: `errno` is already `ENOENT` when no process has that pid.
4. Read the file into a buffer of 4096 bytes with `sc_read_full`. Ask for one byte less than the buffer. If it fails, save `errno`, close the file, put `errno` back, and return -1.
5. Close the file now: if it is still open at step 8, the count includes it. Put `'\0'` after the last byte read.
6. Divide the buffer into lines at each `'\n'` (`strchr`). A line holds a key when `strncmp` finds the key at its start, and the next character is `':'`. Skip the spaces and tabs after it. `strtol` reads a number and stops at `" kB"`. Copy the name with `snprintf` into `name`: it stops at 63 characters and adds the `'\0'`.
7. Open `<directory>/fd` with `opendir`. If it fails, return -1: `errno` is `EACCES` for a process of another user.
8. Count each entry that `readdir` gives, except `.` and `...` Set `errno` to 0 before each `readdir`: it gives `NULL` at the end and on an error, and only `errno` shows which. Then call `closedir`.
9. Put the count in `out->open_fds`, minus 1 when the process is the caller (`pid` is 0 or `getpid()`). Return 0.

`proc_report_write(fd, info)`: if `info` is `NULL`, set `errno` to `EINVAL` and return -1. Then write the whole report into one buffer of 512 bytes with one `snprintf`, in the layout of `syscall.h`. A label left-aligned in 10 characters is `%-10s`. Write the buffer with `sc_write_all`, and return its result.

[9] `src/libsyscall/include/sentinel/syscall.h`, in your repository. It states what each function of Lab 1 does, and each of its errors.

[10] `make test` runs the tests of each lab that has a `Makefile`, and `make test LAB=2` those of Labs 1 and 2 only. The SENTINEL Lab Manual, Section 4, `docs/manual/sentinel_manual.pdf`, lists each make target.

[11] The acceptance test of Lab 1, `make accept1`, runs 34 checks of your library and your demo. The Lab 1 Brief, Section 4.3, `docs/lab1/lab1_brief.pdf`, describes it.