

# Adaptive Mesh Refinement in Chapel

## Part II: A really hard problem, greatly simplified

Jonathan Claridge  
University of Washington  
March 2, 2011




# Overview of two talks

- Previous talk:
  - Several AMR challenges that Chapel makes easy
- This talk:
  - A difficult part of AMR that Chapel sets us up to solve


# Data refinement

- Data from a coarse grid provides boundary values to fine grids that it overlaps




# Data refinement

- Data from a coarse grid provides boundary values to fine grids that it overlaps
- Only need to fill fine ghost cells that are not overlapped by a fine sibling grid




# Data refinement

- Data from a coarse grid provides boundary values to fine grids that it overlaps
- Only need to fill fine ghost cells that are not overlapped by a fine sibling grid



# Data refinement


- Data from a coarse grid provides boundary values to fine grids that it overlaps
- Only need to fill fine ghost cells that are not overlapped by a fine sibling grid






# Data refinement

- Data from a coarse grid provides boundary values to fine grids that it overlaps
- Only need to fill fine ghost cells that are not overlapped by a fine sibling grid
- Resulting region is a **union of rectangles**, most naturally defined by **set subtraction**




# Data refinement

- Data from a coarse grid provides boundary values to fine grids that it overlaps
- Only need to fill fine ghost cells that are not overlapped by a fine sibling grid
- Resulting region is a **union of rectangles**, most naturally defined by **set subtraction**
- Chapel: Define an object to store unions of domains, which supports domain subtraction in a set-minus fashion






# Regridding




- New grids determined by a **partitioning algorithm** (Berger & Rigoutsos, 1991)


# Regridding




- New grids determined by a **partitioning algorithm** (Berger & Rigoutsos, 1991)




# Regridding



- New grids determined by a **partitioning algorithm** (Berger & Rigoutsos, 1991)




# Regridding




- As with refinement, **unions** of rectangles (domains) are essential

# Regridding



- As with refinement, **unions** of rectangles (domains) are essential
- Subtractions in Berger-Rigoutsos always remove a subset that spans a domain in `rank-1` dimensions; general domain subtraction is convenient, but not necessary

# Regridding



- As with refinement, **unions** of rectangles (domains) are essential
- Subtractions in Berger-Rigoutsos always remove a subset that spans a domain in `rank-1` dimensions; general domain subtraction is convenient, but not necessary
- However, domain subtraction **is** important after partitioning, when refining data onto a newly created level



# Unions of domains: MultiDomain class

Precedents in AMR libraries:

# Unions of domains: `MultiDomain` class

Precedents in AMR libraries:

- Chombo *BoxTools* library
  - Class `Box` represents rectangular sets of integer tuples (`IntVects`)
  - Class `IntVectSet` represents irregular sets of integer tuples, supporting full set calculus

# Unions of domains: MultiDomain class

Precedents in AMR libraries:

- Chombo *BoxTools* library
  - Class `Box` represents rectangular sets of integer tuples (`IntVects`)
  - Class `IntVectSet` represents irregular sets of integer tuples, supporting full set calculus
- SAMRAI *Hierarchy* library
  - Class `Box` (see above)
  - Classes `BoxArray`, `BoxList`, `BoxTree` represent unions of boxes, supporting various set operations

# Unions of domains: MultiDomain class

- MultiDomain fields:

# Unions of domains: MultiDomain class

- MultiDomain fields:

```
param rank:          int;  
param stridable:     bool = false;
```

Parameters to specify child domains; compile time constants

# Unions of domains: MultiDomain class

- MultiDomain fields:

```
param rank:           int;  
param stridable:      bool = false;  
var    stride:        rank*int;
```

Parameters to specify child domains; compile time constants

Child domains will have equal stride



# Unions of domains: MultiDomain class

- MultiDomain fields:

```
param rank:          int;  
param stridable:     bool = false;  
var    stride:       rank*int;  
var    subindices:   domain(1);
```

Parameters to specify child domains; compile time constants

Child domains will have equal stride

Indices for array of child domains

# Unions of domains: MultiDomain class

- MultiDomain fields:

**param** rank:            **int**;

Parameters to specify child domains; compile time constants

**param** stridable:    **bool** = **false**;

**var**    stride:            rank\***int**;

Child domains will have equal stride

**var**    subindices:    **domain**(1);

Indices for array of child domains

**var** domains: [subindices] **domain**(rank, stridable=stridable);

Array of child domains

# Unions of domains: MultiDomain class

- MultiDomain fields:

**param** rank:            **int**;

Parameters to specify child domains; compile time constants

**param** stridable:    **bool** = **false**;

**var**    stride:            rank\***int**;

Child domains will have equal stride

**var**    subindices:    **domain**(1);

Indices for array of child domains

**var** domains: [subindices] **domain**(rank, stridable=stridable);

Array of child domains

- In principle, `domains` could be an associative domain of rectangular domains

# Unions of domains: MultiDomain class

- MultiDomain fields:

**param** rank:            **int**;

Parameters to specify child domains; compile time constants

**param** stridable:    **bool** = **false**;

**var**     stride:        rank\***int**;

Child domains will have equal stride

**var**     subindices:   **domain**(1);

Indices for array of child domains

**var** domains: [subindices] **domain**(rank, stridable=stridable);

Array of child domains

- In principle, `domains` could be an associative domain of rectangular domains
- Tree-based storage of `domains`, with bounding boxes at nodes, will allow better performance for set operations; direction for future improvement

# Unions of domains: MultiDomain class

- MultiDomain operations:

```
MultiDomain = domain;
```

```
MultiDomain.add(domain);
```

```
MultiDomain = domain - domain;
```

```
MultiDomain.subtract(domain);
```


```
MultiDomain.intersect(domain);
```

etc...

- Most operations allow a MultiDomain as an argument as well

# Domain subtraction


- Recursive procedure, reducing to `rank-1` subtraction at each step





# Domain subtraction


- Recursive procedure, reducing to `rank-1` subtraction at each step



- Calculate `Yellow - Red`, working along the horizontal:

# Domain subtraction


- Recursive procedure, reducing to `rank-1` subtraction at each step



- Calculate `Yellow - Red`, working along the horizontal:
  - `Yellow` splits into 3 pieces: `Y_lower`, `Y_inner`, and `Y_upper`, any of which may be empty

# Domain subtraction

- Recursive procedure, reducing to `rank-1` subtraction at each step




- Calculate `Yellow - Red`, working along the horizontal:
  - `Yellow` splits into 3 pieces: `Y_lower`, `Y_inner`, and `Y_upper`, any of which may be empty
  - `Y_lower` and `Y_upper` consist of 0 or 1 domains, disjoint from `Red`

# Domain subtraction

- Recursive procedure, reducing to


$Y\_inner - Red$  is much more complicated than this in higher dimensions



- Calculate Yellow - Red, working along the horizontal:
  - Yellow splits into 3 pieces:  $Y\_lower$ ,  $Y\_inner$ , and  $Y\_upper$ , any of which may be empty
  - $Y\_lower$  and  $Y\_upper$  consist of 0 or 1 domains, disjoint from Red
  - Now calculate  $Y\_inner - Red$ , but project onto remaining dimensions since  $Y\_inner.dim(1) == Red.dim(1)$


# Class GridCFGhostRegion

- Represents ghost cells of a fine grid that will receive data from “coarse neighbor” grids



# Class GridCFGhostRegion

- Represents ghost cells of a fine grid that will receive data from “coarse neighbor” grids






# Class GridCFGhostRegion

- Represents ghost cells of a fine grid that will receive data from “coarse neighbor” grids
- Fields are:

```
const grid: Grid; The fine grid in question  
  
const coarse_neighbors: domain(Grid);  
  
const multidomains: [coarse_neighbors]  
    MultiDomain(dimension, stridable=true);
```




# Class GridCFGhostRegion

- Represents ghost cells of a fine grid that will receive data from “coarse neighbor” grids
- Fields are:

```
const grid: Grid; The fine grid in question  
  
const coarse_neighbors: domain(Grid);  
  
const multidomains: [coarse_neighbors]  
    MultiDomain(dimension, stridable=true);
```

- Constructor also needs to know:
  - parent\_level of grid
  - coarse\_level
  - ref\_ratio, the refinement ratio between coarse\_level and parent\_level



# Class GridCFGhostRegion

```
for coarse_grid in coarse_level.grids {  
    var fine_intersection =  
        grid.extended_cells( refine(coarse_grid.cells, ref_ratio) );  
  
    if fine_intersection.numIndices > 0 {  
        var boundary_multidomain = fine_intersection - grid.cells;  
  
        for (neighbor, region) in parent_level.sibling_ghost_regions(grid)  
        {  
            if fine_intersection(region).numIndices > 0 then  
                boundary_multidomain.subtract(region);  
        }  
  
        if boundary_multidomain.length > 0 {  
            coarse_neighbors.add(coarse_grid);  
            multidomains(coarse_grid) = boundary_multidomain;  
        }  
        else delete boundary_multidomain;  
    }  
}
```

Iterate over coarse grids; all are potentially coarse neighbors

# Class GridCFGhostRegion

```
for coarse_grid in coarse_level.grids {  
    var fine_intersection =  
        grid.extended_cells( refine(coarse_grid.cells, ref_ratio) );  
  
    if fine_intersection.intersect(coarse_grid.cells) {  
        var fine_intersection =  
            grid.cells;  
  
        for (neighbor, region) in parent_level.sibling_ghost_regions(grid)  
        {  
            if fine_intersection(region).numIndices > 0 then  
                boundary_multidomain.subtract(region);  
        }  
  
        if boundary_multidomain.length > 0 {  
            coarse_neighbors.add(coarse_grid);  
            multidomains(coarse_grid) = boundary_multidomain;  
        }  
        else delete boundary_multidomain;  
    }  
}
```

Intersect the coarse grid (interior only) – in fine index space – with the fine grid (ghost cells included)

# Class GridCFGhostRegion

```
for coarse_grid in coarse_level.grids {  
    var fine_intersection =  
        grid.extended_cells( refine(coarse_grid.cells, ref_ratio) );  
  
    if fine_intersection.numIndices > 0 {  
        var boundary_multidomain = fine_intersection  
  
        for (neighbor, region) in parent_level.sibling_ghost_regions(grid)  
        {  
            if fine_intersection(region).numIndices > 0 then  
                boundary_multidomain.subtract(region);  
        }  
  
        if boundary_multidomain.length > 0 {  
            coarse_neighbors.add(coarse_grid);  
            multidomains(coarse_grid) = boundary_multidomain;  
        }  
        else delete boundary_multidomain;  
    }  
}
```

If fine\_intersection is empty,  
there's no reason to continue

# Class GridCFGhostRegion

```
for coarse_grid in coarse_level.grids {  
    var fine_intersection =  
        grid.extended_cells( refine(coarse_grid.cells, ref_ratio) );  
  
    if fine_intersection.numIndices > 0 {  
        var boundary_multidomain = fine_intersection - grid.cells;  
  
        for (nei in grid.neighbors) {  
            boundary_multidomain will still contain the ghost  
            region that overlaps sibling grids  
            _regions(grid)  
            {  
                if fine_intersection(region).numIndices > 0 then  
                    boundary_multidomain.subtract(region);  
            }  
        }  
  
        if boundary_multidomain.length > 0 {  
            coarse_neighbors.add(coarse_grid);  
            multidomains(coarse_grid) = boundary_multidomain;  
        }  
        else delete boundary_multidomain;  
    }  
}
```

# Class GridCFGhostRegion

```
for coarse_grid in coarse_level.grids {  
    var fine_intersection =  
        grid.extended_cells( refine(coarse_grid.cells, ref_ratio) );  
  
    if fine_intersection.numIndices > 0 {  
        var boundary_multidomain = fine_intersection - grid.cells;  
  
        for (neighbor, region) in parent_level.sibling_ghost_regions(grid)  
        {  
            if fine_ Iterate over the grid's SiblingGhostRegion; a these() method has been defined to make the object iterable  
                boundary_multidomain.subtract(region);  
        }  
  
        if boundary_multidomain.length > 0 {  
            coarse_neighbors.add(coarse_grid);  
            multidomains(coarse_grid) = boundary_multidomain;  
        }  
        else delete boundary_multidomain;  
    }  
}
```

# Class GridCFGhostRegion

```
for coarse_grid in coarse_level.grids {  
    var fine_intersection =  
        grid.extended_cells( refine(coarse_grid.cells, ref_ratio) );  
  
    if fine_intersection.numIndices > 0 {  
        var boundary_multidomain = fine_intersection - grid.cells;  
  
        for (neighbor, region) in parent_level.sibling_ghost_regions(grid)  
        {  
            if fine_intersection(region).numIndices > 0 then  
                boundary_multidomain.subtract(region);  
        }  
  
        if boundary_multidomain.length > 0 {  
            coarse_neighbors.add(coarse_grid);  
            multidomains(coarse_grid) = boundary_multidomain;  
        }  
        else delete boundary_multidomain;  
    }  
}
```

Subtract the region of overlap, pre-scanning for obviously disjoint cases



# Class GridCFGhostRegion

```
for coarse_grid in coarse_level.grids {
    var fine_intersection =
        grid.extended_cells( refine(coarse_grid.cells, ref_ratio) );

    if fine_intersection.numIndices > 0 {
        var boundary_multidomain = fine_intersection - grid.cells;

        for (neighbor, region) in parent_level.sibling_ghost_regions(grid)
        {
            if fine_intersection(region).numIndices > 0 then
                boundary_multidomain.subtract(region);
        }

        if boundary_multidomain.length > 0 {
            coarse_neighbors.add(coarse_grid);
            multidomains(coarse_grid) = boundary_multidomain;
        }
        else delete boundary_multidomain;
    }
}
```

# Class GridCFGhostRegion

```
for coarse_grid in coarse_level.grids {  
    var fine_intersection =  
        grid.extended_cells( refine(coarse_grid.cells, ref_ratio) );  
  
    if fine_intersection.numIndices > 0 {  
        var boundary_multidomain = fine_intersection - grid.cells;  
  
        for (neighbor, region) in parent_level.sibling_ghost_regions(grid)  
        {  
            if fine_intersection(region).numIndices > 0 then  
                boundary_multidomain.subtract(region);  
        }  
  
        if boundary_multidomain.length > 0 {  
            coarse_neighbors.add(coarse_grid);  
            multidomains(coarse_grid) = boundary_multidomain;  
        }  
        else delete boundary_multidomain;  
    }  
}
```

If boundary\_multidomain is nonempty, update the GridCFGhostRegion fields

# Class GridCFGhostRegion

```
for coarse_grid in coarse_level.grids {  
    var fine_intersection =  
        grid.extended_cells( refine(coarse_grid.cells, ref_ratio) );  
  
    if fine_intersection.numIndices > 0 {  
        var boundary_multidomain = fine_intersection - grid.cells;  
  
        for (neighbor, region) in parent_level.sibling_ghost_regions(grid)  
        {  
            if fine_intersection(region).numIndices > 0 then  
                boundary_multidomain.subtract(region);  
        }  
  
        if boundary_multidomain.length > 0 {  
            coarse_neighbors.add(coarse_grid);  
            multidomains(coarse_grid) = boundary_multidomain;  
        }  
        else delete boundary_multidomain;  
    }  
}
```

Otherwise, get rid of it

# Class GridCFGhostRegion

```
for coarse_grid in coarse_level.grids {
```

- ```
    va
```
- MultiDomains greatly simplify the hard part
    - Internally, MultiDomains heavily rely on Chapel infrastructure for domains
    - Simple ≠ cheap; misuse of MultiDomains can be expensive
- ```
    if
```

```
);
```

```
    }  
    else delete boundary_multidomain;
```

```
}
```

```
}
```

# Class GridCFGhostRegion

```
for coarse_grid in coarse_level.grids {
```

- MultiDomains greatly simplify the hard part
  - Internally, MultiDomains heavily rely on Chapel infrastructure for domains
  - Simple  $\neq$  cheap; misuse of MultiDomains can be expensive
- Development of full AMR framework also required:
  - Assemble Grid data structures into Level data structures
  - Define spatial variables on GridCFGhostRegions
  - Space-time interpolation from coarse to fine variables

```
);
```

```
if
```

```
}
```

```
else delete boundary_multidomain;
```

```
}
```

```
}
```

# Conclusions

Final recap of code size:

Language	Parallelism	SLOC <sup>1</sup>	Tokens	Relative size (tokens)
C++ (D≤6) <sup>3</sup>	Dist. mem.	40200	261427	100%
Fortran (2D+3D) <sup>2</sup>	Serial	16562	151992	58%
2D		8297	71639	27%
3D		8265	80353	31%
Chapel (any D)	Shared mem.	1988	13783	<b>5%</b>

<sup>1</sup> source lines of code, <sup>2</sup> AMRClaw, <sup>3</sup> Chombo BoxTools+AMRTools

# Conclusions

Final recap of code size:

Language	Parallelism	SLOC <sup>1</sup>	Tokens	Relative size (tokens)
C++ (D≤6) <sup>3</sup>	Dist. mem.	40200	261427	100%
Fortran (2D+3D) <sup>2</sup>	Serial	16562	151992	58%
2D		8297	71639	27%
3D		8265	80353	31%
Chapel (any D)	Shared mem.	1988	13783	<b>5%</b>

<sup>1</sup> source lines of code, <sup>2</sup> AMRClaw, <sup>3</sup> Chombo BoxTools+AMRTools

- Hopefully you have a better sense of why the Chapel code is short – and how might translate to a full-featured AMR system

# Conclusions

Final recap of code size:

Language	Parallelism	SLOC <sup>1</sup>	Tokens	Relative size (tokens)
C++ (D≤6) <sup>3</sup>	Dist. mem.	40200	261427	100%
Fortran (2D+3D) <sup>2</sup>	Serial	16562	151992	58%
2D		8297	71639	27%
3D		8265	80353	31%
Chapel (any D)	Shared mem.	1988	13783	<b>5%</b>

<sup>1</sup> source lines of code, <sup>2</sup> AMRClaw, <sup>3</sup> Chombo BoxTools+AMRTools

- Hopefully you have a better sense of why the Chapel code is short – and how might translate to a full-featured AMR system

Suggestion for future language evaluation

- Use rectangular set operations (“box calculus”) as a problem representative of, and more tractable than, AMR



# Conclusions

What did Chapel do for us?

# Conclusions

What did Chapel do for us?

- Integer tuples and rectangular sets thereof are native data types
  - Drastically simplifies construction of MultiDomains

# Conclusions

What did Chapel do for us?

- Integer tuples and rectangular sets thereof are native data types
  - Drastically simplifies construction of MultiDomains
- Dimension-independence
  - After defining MultiDomains, spatial dimension only appears in variable declarations

# Conclusions

What did Chapel do for us?

- Integer tuples and rectangular sets thereof are native data types
  - Drastically simplifies construction of MultiDomains
- Dimension-independence
  - After defining MultiDomains, spatial dimension only appears in variable declarations
- Clean, clear iteration syntax
  - Ability to define any object as an iterator with `these()` method

# Conclusions

What did Chapel do for us?

- Integer tuples and rectangular sets thereof are native data types
  - Drastically simplifies construction of MultiDomains
- Dimension-independence
  - After defining MultiDomains, spatial dimension only appears in variable declarations
- Clean, clear iteration syntax
  - Ability to define any object as an iterator with `these()` method

Recall Chapel's main goal:

- **Improve programmer productivity**

# Where can I learn more?

Chapel:

<http://chapel.cray.com>

Today's presentations, and many more:

<http://chapel.cray.com/presentations.html>

Chapel source:

<https://sourceforge.net/projects/chapel>

Application studies:

<http://chapel.svn.sourceforge.net/viewvc/chapel/trunk/...>

AMR: <...test/studies/amr>

SSCA2: [...test/users/jglewis/ssca2\\_version2](...test/users/jglewis/ssca2_version2)

PTRANS: <...test/studies/hpcc/PTRANS/jglewis>