

[Space to Write for Answers]

1)	Sleep	Wait
1.	sleep() pauses a process for a fixed amount of time.	wait() makes a process wait for a specific event, usually a child process to finish.
2.	The process becomes sleeps for the given time.	The parent process waits until the child process terminates or changes state.
3.	It does not depend on another process.	It is mainly used to process synchronization.
4.	E.g. sleep(5) : pauses for 5 sec	E.g. wait() : waits for a child process to complete

- 2) ~~SIGHUP (1)~~
 SIGINT (2)
 SIGQUIT (3)
 SIGKILL (9)
 SIGTERM (15)
 SIGSTOP (19)
 SIGCONT (18)
 SIGTSTP (20)

3)

- 4) 1. fork()
 2. exec()
 3. wait()
 4. exit()

5. getpid()
6. getppid()
7. kill()

5) Nice command

This command is used to start a new process with a specific priority, known as the "nice value". A higher nice value lowers the processes priority, while a lower (negative) nice value increases it. Processes with higher priority receive more CPU time.

Renice command

This command modifies the priority of an already running process. This flexibility allows system administrators to manage process priorities based on the current system load dynamically.

6) ps : Displays processes running in the current shell.

ps -e : Displays all running processes.

ps -f : Displays processes in full-format listing.

ps -ef : Displays all processes with detailed information.

ps -u username : Displays processes of a particular user.

ps -x : Shows processes of all users running without a controlling terminal.

ps -a : Shows processes of all users except session leaders.

ps -l : Displays processes in long format

ps -aux : Displays detailed information about processes for all users.

ps -p PID : Displays information about a specific process.