

Practical no. 23

Name :- Danish Altaf Solkar

Enrolment no. :-24111590805

Class :- CO3K – B

Subject :- DMS

Aim:- Implement PL/SQL program based on Exception Handling
(User-defined exceptions)

Program :-

```
Run SQL Command Line
SQL> set serveroutput on;
SQL> DECLARE
  2  user_ex exception;
  3  i number:=7000;
  4  BEGIN
  5  IF i>=6000
  6  THEN RAISE user_ex;
  7  ELSE
  8  UPDATE emp set salary=salary+i where eno=1;
  9  END IF;
 10  EXCEPTION
 11  WHEN user_ex
 12  then dbms_output.put_line('Increament amount cannot be more than 6000');
 13  END;
 14  /
Increament amount cannot be more than 6000

PL/SQL procedure successfully completed.
```

Program :-

```
Run SQL Command Line
SQL> DECLARE
  2  min_age exception;
  3  vno number(2):=1;
  4  vname varchar(20):='Danish';
  5  vage number(2):=16;
  6  BEGIN
  7  IF vage <18
  8  then RAISE min_age;
  9  ELSE
 10  insert into emp(e_no,e_name,e_age)values (vno,vname,vage);
 11  DBMS_output.put_line('Employee successfully added');
 12  END if;
 13  EXCEPTION
 14  when min_age
 15  then dbms_output.put_line('Minor employee not to be Appointed');
 16  END;
 17  /
Minor employee not to be Appointed

PL/SQL procedure successfully completed.
```

Program :-

```
Run SQL Command Line
SQL> DECLARE
  2  wempno Exception;
  3  vempno number:=1;
  4  vempname varchar(25):='Danish';
  5  cempno number;
  6  BEGIN
  7  cempno:=LENGTH(to_char(vempno));
  8  if cempno=3
  9  then insert into emp(e_no,e_name)values(vempno,vempname);
 10  dbms_output.put_line('Employee added successfully');
 11  else raise wempno;
 12  end if;
 13  exception
 14  when wempno
 15  then dbms_output.put_line('Employee id must be 3 digit number only');
 16  End;
 17  /
Employee id must be 3 digit number only

PL/SQL procedure successfully completed.
```

Exercise :-

Program :-

```
SQL> Run SQL Command Line
SQL> DECLARE
  2  v_customer_id NUMBER;
  3  v_name VARCHAR2(50);
  4  v_count NUMBER;
  5  invalid_id EXCEPTION;  -- user defined exception
  6  BEGIN
  7  v_customer_id := &enter_customer_id;
  8  SELECT COUNT(*)
  9  INTO v_count
 10  FROM customer
 11  WHERE c_id = v_customer_id;
 12  IF v_count = 0 THEN
 13  RAISE invalid_id;
 14  ELSE
 15  SELECT c_name
 16  INTO v_name
 17  FROM customer
 18  WHERE c_id = v_customer_id;
 19  DBMS_OUTPUT.PUT_LINE('Customer Found: ' || v_name);
 20  END IF;
 21  EXCEPTION
 22  WHEN invalid_id THEN
 23  DBMS_OUTPUT.PUT_LINE('Error: Invalid Customer ID entered.');
```

24 END;

25 /

Enter value for enter_customer_id: 10

old 7: v_customer_id := &enter_customer_id;

new 7: v_customer_id := 10;

Error: Invalid Customer ID entered.

PL/SQL procedure successfully completed.