

Model: T9FB985541

Zoeller Flow-Mate M98 Sump Pump For Septic Tanks 98-0001, LPP, Enhanced Flow Step Systems

★★★★★ (0)



Ships in 8 Business Days (ships from US)

Product Description

Zoeller M98 Flow-Mate for septic tank, low pressure pipe (LPP) and enhanced flow step systems. Designed for use in residential or light commercial dewatering applications and can be used to transfer groundwater or effluent. Automatic effluent or dewatering pump that is submersible with 1 1/2" NPT discharge. The sizing of effluent systems normally requires variable level float(s) controls and properly sized basins to achieve required pumping cycles. Corrosion-resistant, powder coated epoxy finish - Durable cast iron construction - Cast iron switch case, motor, pump housing and base - No sheet metal parts to rust or corrode - All castings are cast iron class 25-30 25000# tensile strength.

Specifications

Weights & Dimensions

Length	10-1/8 in
Width	10-1/8 in
Height	12 in
Weight	36 lbs
Cord Length	15 ft
Switch Off Height	3 in
Switch On Height	9-1/2 in
Max Head	23 ft
Max Diameter Solids	1/2 in
Discharge Connection Size	1-1/2 in
Min Sump Pit Diameter	18

Product Details

Max Fluid Temperature	130 °F
Impeller Material	Engineered Plastic
Phase	1
Manufacturers Part Number	98-0001
Discharge Connection Type	NPT
Submersible	Yes
Brand	Zoeller
Solids Handling	Yes
Type	Submersible Sump Pump
Horsepower	1/2 HP

Color	Green
Series	Flow-Mate Series
Amperage	9.4 A
Hertz	60 Hz
Switch Type	Automatic
Voltage	115 V
Gallons per Hour	4320 gal/hr
Housing Material	Cast Iron
Base Material	Cast Iron
Shaft Seal Material	Carbon/ceramic

Warranty

Warranty	3
----------	---

Compliance & Certifications

Certifications	CSA, SSMPA, UL
----------------	----------------