

Assignment 4

In this assignment you will explore a simple variation of the single-server queue: when there are two or more servers instead of a single server.



In this system, customers arrive as usual from the outside. Now there are K servers available instead of one. A customer can go to any of the K servers for service. Thus, all K of them have to be busy serving for a customer to need to wait.

For this assignment:

- Use the simulation of a single-server queue covered in class as a starting point.
- Write code for general K , and make a K a variable.
- Assume the service time is the same at all the servers, and that each service time is exponentially distributed with mean 1.0 .
- For the case $K=2$, plot the system time vs. increasing arrival rate λ .
- What is the value of the system time when $\lambda=1.5$?
- What value of λ would cause the queue to become unstable?
- What value of λ would cause the queue to become unstable when $K=3$?
- What did you do to assess the accuracy of your estimates?
- Write down two applications of the above queueing model?

Submission:

- Put all your code for this assignment in a single directory so that your code unpacks into that directory. Embed your username in the directory name.
 - Write all your code in a file called `ThreeServerQueue.java`.
 - Note: there is no animation required. Your program should compile and execute at the command-line, printing aggregate results to the terminal.
 - Your directory should contain answers to the questions, and the plot (as a JPEG, GIF or PNG).
 - Include a plain-text README file that tells us how to run your code.
 - Include the PDF scan of your "key distributions" (Bernoulli etc) exercise with this zip.
 - Upload your zip file into Blackboard.
 - Name your zip file `karel4.zip` (for username `karel`).
-