Novatek HDAL Design Specification - hd_debug

Table of Content

1 Introduction

The major purpose of hd_debug is for HDAL level debugging. hd_debug is responsible for message printing, debug command switching, run module's test flow, and program trace controlling.

The Debug function list is as follow:

```
static HD_DBG_MENU root_menu[] = {
    {0x01, "AUDIOCAPTURE",   hd_audiocap_menu,   TRUE},
    {0x02, "AUDIOOUT",        hd_audioout_menu,   TRUE},
    {0x03, "AUDIOENC",        hd_audioenc_menu,   TRUE},
    {0x04, "AUDIODEC",        hd_audiodec_menu,   TRUE},
    {0x05, "VIDEOCAPTURE",   hd_videocap_menu,   TRUE},
    {0x06, "VIDEOOUT",        hd_videoout_menu,   TRUE},
    {0x07, "VIDEOPROCESS",   hd_videoproc_menu,  TRUE},
    {0x08, "VIDEOENC",        hd_videoenc_menu,   TRUE},
    {0x09, "VIDEODEC",        NULL,               TRUE},
    {0x0A, "OSG",              hd_osg_menu,        TRUE},
    {0x0B, "COMMON",         hd_common_menu,    TRUE},
    {0x0C, "UTIL",              hd_util_menu,         TRUE},
    {0x0D, "DEBUG",           hd_debug_menu,      TRUE},
    // escape must be last
    {HD_DEBUG_MENU_ID_LAST,  "", NULL,           FALSE},
};
```

2 Function and data structure definition.

2.1 Data structure definition for hd_debug

2.1.1 Structure for Debug function list

```
typedef struct _HD_DBG_MENU {
    int             menu_id;          ///< user command value
    const char      *p_name;          ///< command string
    HD_RESULT       (*p_func)(void);  ///< command function
    BOOL            b_enable;         ///< execution option
} HD_DBG_MENU;
```

2.2 Function definition

2.2.1 Global function

1. HD_RESULT hd_debug_init(void);

   Description:

   Initiate the requirement of debug, such as open a file handle to save the log to file

   Param:

   None

   Return value:

   HD_RESULT

2. HD_RESULT hd_debug_get(HD_DEBUG_PARAM_ID idx, void *p_data);

   Description:

   A universal interface to get data from hd_debug

   Param:

   idx : refers HD_DEBUG_PARAM_ID

   p_data : a pointer that address to returned data. The pointer type depends on what HD_DEBUG_PARAM_ID get to that has defined on description of HD_DEBUG_PARAM_ID.

   Return value:

   HD_RESULT

3. HD_RESULT hd_debug_set(HD_DEBUG_PARAM_ID idx, void *p_data);

   Description:

A universal interface to set data into hd_debug

Param:

idx : refers HD_DEBUG_PARAM_ID.

p_data : a pointer that address to returned data. The pointer type depends on what HD_DEBUG_PARAM_ID get to that has defined on description of HD_DEBUG_PARAM_ID.

Return value:

HD_RESULT

4. HD_RESULT hd_debug_uninit(void);

Description:

Un-initiate the debug, there is nothing to do in it, currently

Param:

None

Return value:

HD_RESULT

5. HD_RESULT hd_debug_run_menu(void);

Description:

Display an interactive menu on console and can,

1. Enable or disable message mask of each module.
2. Dump module's information.
3. Run module's test flow.

Param:

None

Return value:

HD_RESULT

2.3 Software control flow

2.3.1 hd_debug control flow

There are two operations in hd_debug: HDAL debug menu, and HDAL level message output.

2.3.2 HDAL debug menu control flow

Software procedures to switch to HDAL debug function.



Figure 2-1 flow chart to open and start section filter

2.3.3 HDAL debug level message

Each type of message has its own unsigned integer and each its bit present a HDAL module. For example, a variable named g_hd_mask_err and its LSB indicate the enable or disable of hd_audiocapture's error message.

3 Use cases

3.1 Example

To disable all error level messages on debug menu, do this,

1. Type 13 enter => select 13.DEBUG
2. Type 2 enter => select 2. All ERR mask disable
3. Type 255 enter => return back to upper menu

To disable all error level messages by using API call, do this,

```
unsigned int disable_all = 0;

hd_debug_set(HD_DEBUG_PARAM_ERR_MASK, &disable_all);
```