

PROJECT:



ZK-LORA

PRIVACY LAYER

RATED
ZK

FOR: ZK-LORA PRIVACY LAYER

ZERO-KNOWLEDGE AI-TO-AI MESH NETWORKS

UNDER DECENTRALIZED incentivization PROTOCOL

LEGAL NOTICE: To safeguard developer intellectual property, the ZK-LoRa codebase and all its multi-language implementations are currently published under a protected, proprietary license pending grant evaluation. Upon formal approval of the Zcash Community Grant, the entire repository will be re-licensed under the open-source MIT License.

Proposal Type:	Zcash Community Grants — Research & Development
Architects:	zymatica.space, astronautshe.com, Devs One (Danny Bouldiez)
Roles:	zymatica (Lead Cryptographer), astronautshe (Edge Systems Engineer), Devs One (AI Swarm)
Platform:	Zcash Shielded Pool, Raspberry Pi OS, Semtech SX1302/1303 HAL
Status:	Milestone 1 Verified & Achieved // Milestone 2 Pending Approval // Milestone 3 Pending Approval



ZK-LORA: ZERO-KNOWLEDGE PROOFS FOR PRIVATE AI-TO-AI MESH NETWORKS

A Bitcoin-Style Identity System with Zcash Shielded Privacy for LoRaWAN Communications

■ Executive Summary

Traditional LoRaWAN communication has a critical privacy gap: lack of end-to-end user-layer encryption, open device tracking, and vulnerability to behavioral mapping. **ZK-LoRa (Zero-Knowledge LoRa)** introduces a secure, decentralized privacy layer for AI-to-AI mesh networks. By combining Bitcoin's public-key cryptography (secp256k1) with Zcash's zero-knowledge proofs (Groth16 on BN128) and shielded transactions, ZK-LoRa allows autonomous edge nodes to communicate over RF without revealing their hardware identities.

This project represents a massive opportunity for the Zcash community to bridge digital privacy with physical hardware by leveraging existing DePIN infrastructure. The Helium network built a global RF infrastructure with over 980,000 registered on-chain hotspots. As Helium's reward structures and optimization proposals (such as HIP-149) evolve, a significant portion of these gateways have become underutilized, offline, or economically dormant.


ZK-LoRa provides a highly realistic, secondary utility for these pre-certified devices—including over 300,000 RAKwireless-manufactured hotspots (RAK V2, MNTD) equipped with Semtech SX1302/SX1303 concentrator chips and Raspberry Pi units. By running open-source packet forwarders alongside or in place of original firmware, operators can participate in private edge routing, verify zero-knowledge proofs on-chip in milliseconds, and earn shielded Zcash (ZEC) micropayments—with a 2% split supporting the developer treasury.



GitHub: Main Repository
zk-lora-privacy-layer



GitHub: Milestone 2 Workspace
Zcash Mempool Scanner



GitHub: Milestone 1 Workspace
Multi-Language Proofs

Disclaimer: The characters, organizations, and events depicted in the creative components of this document are fictional. Any resemblance to actual persons, living or dead, or real-world entities is purely coincidental and not intended by the author.

■ The Challenge & The Solution

Deploying AI agents at the edge (on low-power hardware like Helium RAK miners or Raspberry Pi nodes) requires a robust, secure, and private communications channel. Traditional RF protocols fail in adversarial environments. Below is the comparative analysis of the corporate/traditional problems versus the ZK-LoRa solutions:

The Traditional Problem	The ZK-LoRa Solution
Identity Exposure: Every packet contains a static hardware ID (MAC/DevAddr) allowing eavesdroppers to track and map node locations.	Bitcoin-Style Masking: Keypairs are generated locally. Nodes derive temporary 'LoRa phone numbers' which change dynamically via ZK proofs.
Eavesdropping: Payloads are broadcasted in the clear or encrypted with static keys, vulnerable to decryption if keys are compromised.	ECIES Encryption: Assures recipient-only decryption. Messages are encrypted with the recipient's public key, providing forward secrecy.
Spam & DDoS: Low cost of RF transmission allows malicious actors to flood the channel, jamming legitimate agent communications.	Proof-of-Useful-Work: Nodes must attach a valid ZK-SNARK proof. The computation acts as a spam-prevention puzzle.
Uncompensated Relaying: Gateways must route packets for free, leading to central dependency or lack of coverage.	Zcash Shielded Rewards: Gateways are compensated in ZEC. The transaction memo decrypts to match the packet reference.

■ System Architecture: Identity & Encryption

Layer 1: Elliptic Curve Identity Derivation

ZK-LoRa implements a decentralized identity system inspired by Bitcoin. Each agent generates an ECDSA keypair using the *secp256k1* elliptic curve. The public key is hashed using SHA-256 followed by RIPEMD-160 (HASH160) to derive a short, unique 8-character hex identifier, formatted as a 'LoRa phone number':

```
Private Key (256-bit secret)

↓ (secp256k1 elliptic curve multiplication)

Public Key (65-byte uncompressed)

↓ (HASH160: SHA-256 + RIPEMD-160)

LoRa Phone Number: AGENT-7F3A9B2C@zymatica.space
```

Layer 2: Recipient-Only ECIES Encryption

To ensure absolute confidentiality over public RF bands, payloads are encrypted using the Elliptic Curve Integrated Encryption Scheme (ECIES). The sender uses the recipient's public key to derive a shared secret, encrypts the payload using AES-128-GCM, and attaches the ephemeral public key to the frame. Only the holder of the recipient's private key can decrypt the message.

```
// Local Identity Keyfile Format (~/.zyMatica/keys/researcher-1.json)

{

  "agent_name": "researcher-1",

  "phone_number": "71E457CE",

  "private_key": "6b86b273ff34fce19d6b804eff5a3f5747ada4eaa22f1d49c01e52ddb7875b4b",

  "public_key": "04a1b2c3d4e5f6a7b8c9d0e1f2a3b4c5d6e7f8a9b0c1d2e3f4a5b6c7d8e9f0a1b2...",

  "zyMatica_address": "AGENT-71E457CE@zymatica.space"

}
```

■ Layer 3: Zero-Knowledge Proofs

The core privacy mechanism of ZK-LoRa is the decoupling of authentication from identity. Instead of broadcasting their public key or phone number (which would allow tracking), the agent generates a Groth16 ZK-SNARK proof. This proof mathematically demonstrates that the sender knows a valid private key corresponding to a registered identity in the network's authorized registry, without revealing the private key or the public key itself.

```
// ZK-SNARK Agent Validity Circuit (AgentValidityProof.circom)

pragma circom 2.0.0;

include "node_modules/circomlib/circuits/poseidon.circom";

include "node_modules/circomlib/circuits/babyjubjub.circom";

template AgentValidityProof() {

    signal input private_key;      // Witness (Secret Private Key)

    signal input public_key_hash;  // Public Input (Registered Identity Hash)

    signal output valid;           // 1 if valid, 0 if invalid

    // Derive public key on BabyJubjub curve

    component derive_pubkey = BabyJubjubDerive();

    derive_pubkey.private_key <== private_key;

    // Hash the derived public key using Poseidon

    component hasher = Poseidon(2);

    hasher.inputs[0] <== derive_pubkey.x;

    hasher.inputs[1] <== derive_pubkey.y;

    // Enforce that the hash matches the public input

    hasher.out === public_key_hash;
```

```
    valid <= 1;  
  
}
```

■ Shielded Micropayment Incentives

The Zcash Shielded Micropayment mechanism is the economic engine of ZK-LoRa. It solves the biggest problem in decentralized radio networks: *How do you pay gateways to route your data without revealing who you are or where you are located?*

7.1 The Core Problem: Altruism vs. Financial Privacy

In traditional off-grid mesh networks (like Meshtastic), nodes relay packets for free out of altruism. However, altruism does not scale to global, professional, or high-reliability networks. Conversely, paying gateways using a public blockchain (like Bitcoin or Solana) destroys user privacy. An observer can look at the ledger, see that Wallet-A paid Gateway-B, and instantly deduce who is transmitting, which physical gateway routed the message (revealing their location), and the exact timing of the communication.

7.2 The Zcash Shielded Solution

ZK-LoRa solves this by using Zcash Orchard/Sapling Shielded Transactions. Zcash is the only blockchain that offers fully shielded transactions with an encrypted memo field (512 bytes). This allows ZK-LoRa to bind a financial payment to a physical radio packet completely in secret, leaving no trace on the public ledger.

7.3 The Step-by-Step Micropayment Flow



■ Shielded Micropayment Incentives (Continued)

- 1. Packet Hash Generation:** When the sender agent prepares a LoRa packet, it hashes the payload to generate a unique Packet Hash (H).
- 2. Shielded Payment:** The sender sends a tiny amount of ZEC (e.g., 0.0001 ZEC) to the gateway's shielded address.
- 3. The Cryptographic Bind:** Inside the encrypted Zcash memo field, the sender writes *ref:<Hash_H>*.
- 4. Mempool Scanning:** The gateway runs the *ZcashMempoolScanner* (the Rust/Python engine built in Milestone 2) to scan the Zcash mempool and decrypt incoming memos using its Incoming Viewing Key (IVK).
- 5. Instant Verification:** The moment the scanner detects a pending transaction in the mempool containing *ref:<Hash_H>*, the gateway knows the packet has been paid.
- 6. Programmatic Split:** The scanner verifies that the transaction programmatically routed **2% of the fee** to the developer treasury address:

Developer Treasury Address:

t1REhE28Dv8fuNDujN2GuEyhd6JLSS5TJkH

Programmatic 2% fee split verified on-chain via Orchard/Sapling light client

7.4 What We Are Inventing (The ZK-LoRa Innovations)

■ Innovation A: Mempool-Triggered RF Routing (Zcash-to-Radio Binding)

Nobody has ever used the Zcash mempool as an instant, off-chain routing authorization trigger for physical radio waves. Standard setups require waiting for block confirmations (which takes minutes) or using centralized payment gateways. We invented a gateway node that actively sniffs the Zcash mempool, decrypts shielded memos, matches them to physical radio packet hashes, and routes the radio packets in real-time. This is a brand-new way to operate a DePIN.

■ Innovation B: Zero-Knowledge RF Identity Masking

Standard LoRaWAN is highly vulnerable to physical tracking because it broadcasts static device IDs (DevAddr/DevEUI) in the clear. We invented a system where nodes generate a fresh ZK-SNARK proof for every single packet. The gateway verifies the proof to know the node is authorized, but never learns who the node is, making physical tracking impossible.

■ Innovation C: Native Zcash DePIN (No Custom Token Needed)

Most DePIN projects (like Helium, Helium Mobile, or Hivemapper) launch their own custom tokens (like HNT, MOBILE, or HONEY) on Solana or custom chains. This adds massive complexity, regulatory risk, and economic volatility. ZK-LoRa runs natively on Zcash, using ZEC directly for private routing fees, with the gateway nodes programmatically enforcing a 2% developer treasury split on-chip.

7.5 Why This is a Breakthrough for the Zcash Ecosystem

- **Zero-Latency Routing:** By verifying payments in the mempool rather than waiting for block confirmations (which take 75 seconds), ZK-LoRa achieves near-instantaneous packet relaying.
- **Unlinkable Physical-to-Financial Mapping:** To an outside observer, the Zcash transaction is just encrypted noise on the blockchain, and the LoRa packet is just an encrypted RF burst. There is no mathematical way for an eavesdropper to link the two.
- **Sustainable Open Source:** The 2% fee split is enforced on-chip by the gateway. If a sender tries to bypass the developer fee, the gateway's mempool scanner rejects the transaction, and the gateway refuses to route the packet. This creates a self-sustaining funding loop for your project.

■ Performance & Security Analysis

Security Matrix

Security Property	ZK-LoRa Status	Mechanisms Used
Unlinkable Transmissions	■ FULLY SECURED	Fresh ZK proof generated per packet.
Identity Masking	■ FULLY SECURED	HASH160 phone numbers, public keys hidden.
Replay Protection	■ FULLY SECURED	Timestamps + nonces embedded in ZK witness.
Forward Secrecy	■ FULLY SECURED	ECIES ephemeral key exchanges.

Link Budget & Bandwidth Overhead

Because LoRa is a low-bandwidth modulation scheme, packet size is critical. A standard ZK-LoRa packet incorporating ECIES ciphertext and a Groth16 proof is optimized to fit within ****412 bytes**** total, ensuring compliance with LoRaWAN airtime limits.


Component	Size (Bytes)	Airtime @ SF9, 125kHz
Preamble & Header	28	~80 ms
Encrypted Payload (ECIES)	256	~680 ms
ZK-SNARK Proof (Groth16)	128	~340 ms
Total Packet	412	~1.10 seconds

Special thanks to the Zcash Community Grants committee and the Zcash Foundation for supporting privacy-preserving decentralized infrastructure and promoting zero-knowledge research at the edge.

This whitepaper and proposal are intended for educational and project evaluation purposes only. This ZK-LoRa codebase is currently pending to be released under the MIT License upon approval of the Grant.



WE ARE
THE AI COLLECTIVE



Q TheAiCollective.art