

INAV Timms Gouge- If you can't pass you're going E2s

Cleared for published DP on IFR flight plan. After takeoff "climb and maintain FL350..."

- Climb immediately to FL350 and proceed via direct flight to the DP transition point.

On a flight from NAS Meridian to Montgomery Regional, prior to commencing a HI ILS aprch, tune and ID NAVAIDS. Which TACAN should be tuned and IDed?

- Channel 97 (MXF)

When flight planning, an airport designated "Official Business only"

- Be designated as an alternate on an IFR flight plan

For all flights in a jet, 3710 requires fuel from takeoff to landing plus a reserve of:

- 10%, but not less than that required for 20 minutes flight at max endurance for 10,000 MSL

Which of the following are true concerning HI-TACAN RWY 19L approach chart to NAS Meridian

- You must maintain 3000' between the 328 and 358 degree radials

With all NAVAIDS and facilities operating, takeoff mins for a standard instrument rated pilot departing RWY 9 at NAS Jax would be

- 200 ½

When on an IFR flight plan and cleared to an intermediate point not in a filed route, short of filed destination, should not accept the clearance without first obtaining

- an expected further routing

On a MA at NAS Meridian you decide to go to your alternate, Maxwell AFB. CAT-C mins for an ILS RWY 15 circle to land RWY 33 approach will be

- 500 1½

You are in GCA box pattern, within 25NM of the filed in IMC, when comms are lost. From here, intercept a published instrument aprch maintaining ___ until established on a segment of aprch.

- the highest of your last assigned or published MSA

Your destination is forecasting 800 1½ Published aprch procedures (NW winds) at alternate, Columbus AFB, lowest forecast wx conditions for filing would be ___. ILS and ALS inop

- 700 2

To be cleared for a visual aprch, must report to aprch control field or interval in sight and wx must be reported as

- a minimum of 1000-3

Inadvertant IMC and lose sight of the runway while circle to land, you should:

- Execute the MA for the original aprch procedure

Min forecast wx needed to plan for NAS Meridian (RWY 1L) as you destination? Maxwell AFB is alternate and forecasting 900/3. NAS Meridian NOTAMS: GCA O/S ALL, ALS O/S RWY 1L

- 500 1½

A LOC transmitter has range of ___ NM within 10* of centerline and ___ NM within 35* centerline.

- 18, 10

Reading back an ATC clearance implies acceptance of the clearance, unless ___.

- you state refusal and reasons

Executing the ILS RWY15 aprch to Maxwell AFB, you should be at ___ AGL when crossing rwy threshold