

When planning for a direct flight btw two high alt NAVAIDs in the jet route structure, do not exceed the normal anticipated interference free reception range of each NAVAID, which is ____
- 130 NM

Planning for a flight from NAS Jax to BAM ETA 1500Z and alt of Columbus AFB

Your filed destination is NMM with arrived weather best to be 300-1. The alt field has PAR and TCN. The approach min weather required at the alt would be TCN min plus 300-1

If you experience radio failure enroute in IMC, you should maintain...the last assigned alt but no lower than the min enroute alt for each route segment.

You are halfway enroute filed destination on extended IFR flight at FL 290. Radio fails, in VMC and dest has marginal weather. If you determine you can maintain VMC in flt...squawk 7600 maintain VMC and something traffic pattern and land at a suitable airport.

Which publication would provide information on preferred IFR routing...FLIP AP/1

You are cleared to the PIGMY IAF @ NMM with EFC 1610Z. Presently at or above 14K. enroute you experience radio failure so as to depart PIGMY at 1610Z or after descend and commence approach.

30 miles SE of MGM at FL350 you are directed to change freq. unable on assigned freq attempt to contact center on...319.1 CATC center alt subdivided.

For a canceled DP to be reinstated ATC must...indicate the portion of the DP routing that still applies and reinstated altitude restrictions.

You have been cleared via DP. After takeoff, control advises climb and maintain FL350...

PAR pickup question last comm. Pass through highest initiated penetration alt of the IAFs at airfield.

High alt NAVAID 130