



REST API for managing organization GitHub App installations

Use the REST API to manage which GitHub Apps are installed in your enterprise's organizations.

Get enterprise-owned organizations that can have GitHub Apps installed

List the organizations owned by the enterprise, intended for use by GitHub Apps that are managing applications across the enterprise.

This API can only be called by a GitHub App installed on the enterprise that owns the organization.

Fine-grained access tokens for "Get enterprise-owned organizations that can have GitHub Apps installed"

This endpoint works with the following fine-grained token types:

- [GitHub App user access tokens](#)
- [GitHub App installation access tokens](#)

The fine-grained token must have the following permission set:

- "Enterprise organization installations" enterprise permissions (read)

Parameters for "Get enterprise-owned organizations that can have GitHub Apps installed"

Headers

accept string

Setting to `application/vnd.github+json` is recommended.

Path parameters

enterprise string **Required**

The slug version of the enterprise name.

Query parameters

per_page integer

The number of results per page (max 100). For more information, see "[Using pagination in the REST API](#)."

Default: 30

page integer

The page number of the results to fetch. For more information, see "[Using pagination in the REST API](#)."

Default: 1

HTTP response status codes for "Get enterprise-owned organizations that can have GitHub Apps installed"

Status code	Description
200	A list of organizations owned by the enterprise on which the authenticated GitHub App is installed.

Code samples for "Get enterprise-owned organizations that can have GitHub Apps installed"

❗ If you access GitHub at GHE.com, replace `api.github.com` with your enterprise's dedicated subdomain at `api.SUBDOMAIN.ghe.com`.

Request example

GET /enterprises/{enterprise}/apps/installable_organizations

cURL

JavaScript

GitHub CLI



```
curl -L \
-H "Accept: application/vnd.github+json" \
-H "Authorization: Bearer <YOUR-TOKEN>" \
-H "X-GitHub-API-Version: 2022-11-28" \
https://api.github.com/enterprises/ENTERPRISE/apps/installable_organizations
```

A list of organizations owned by the enterprise on which the authenticated GitHub App is installed.

Example response

Response schema

Status: 200

```
[
  {
    "id": 1,
    "login": "github"
  },
  {
    "id": 2,
    "login": "microsoft"
  }
]
```

Get repositories belonging to an enterprise-owned organization

List the repositories belonging to an enterprise-owned organization that can be made accessible to a GitHub App installed on that organization. This API provides a shallow list of repositories in the organization, allowing the caller to then add or remove those repositories to an installation in that organization.

This API can only be called by a GitHub App installed on the enterprise that owns the organization.

Fine-grained access tokens for "Get repositories belonging to an enterprise-owned organization"

This endpoint works with the following fine-grained token types:

- [GitHub App user access tokens](#)
- [GitHub App installation access tokens](#)

The fine-grained token must have at least one of the following permission sets:

- "Enterprise organization installation repositories" enterprise permissions (read)
- "Enterprise organization installations" enterprise permissions (read)

Parameters for "Get repositories belonging to an enterprise-owned organization"

Headers

accept string

Setting to `application/vnd.github+json` is recommended.

Path parameters

enterprise string **Required**

The slug version of the enterprise name.

org string **Required**

The organization name. The name is not case sensitive.

Query parameters

per_page integer

The number of results per page (max 100). For more information, see "[Using pagination in the REST API](#)."

Default: 30

page integer

The page number of the results to fetch. For more information, see "[Using pagination in the REST API](#)."

Default: 1

HTTP response status codes for "Get repositories belonging to an enterprise-owned organization"

Status code	Description
200	A list of repositories owned by the enterprise organization on which the authenticated GitHub App is installed.

Code samples for "Get repositories belonging to an enterprise-owned organization"

 If you access GitHub at GHE.com, replace `api.github.com` with your enterprise's dedicated subdomain at `api.SUBDOMAIN.ghe.com`.

Request example

```
GET /enterprises/{enterprise}/apps/installable_organizations/{org}/accessible_repositories
```

cURL

JavaScript

GitHub CLI



```
curl -L \  
  -H "Accept: application/vnd.github+json" \  
  -H "Authorization: Bearer <YOUR-TOKEN>" \  
  -H "X-GitHub-API-Version: 2022-11-28" \  
  
https://api.github.com/enterprises/ENTERPRISE/apps/installable_organizations/ORG/accessible_repositories
```

A list of repositories owned by the enterprise organization on which the authenticated GitHub App is installed.

Example response

Response schema

Status: 200

```
[  
  {  
    "id": 1,
```

```
[{"name": "Hello World",
  "full_name": "octocat/Hello-World"},
{
  "id": 2,
  "login": "Goodbye World",
  "full_name": "octocat/Goodbye-World"
}]
```

List GitHub Apps installed on an enterprise-owned organization

Lists the GitHub App installations associated with the given enterprise-owned organization. This lists all GitHub Apps that have been installed on the organization, regardless of who owns the application.

This API can only be called by a GitHub App installed on the enterprise that owns the organization.

Fine-grained access tokens for "List GitHub Apps installed on an enterprise-owned organization"

This endpoint works with the following fine-grained token types:

- [GitHub App user access tokens](#)
- [GitHub App installation access tokens](#)

The fine-grained token must have the following permission set:

- "Enterprise organization installations" enterprise permissions (read)

Parameters for "List GitHub Apps installed on an enterprise-owned organization"

Headers

accept string

Setting to `application/vnd.github+json` is recommended.

Path parameters

enterprise string **Required**

The slug version of the enterprise name.

org string **Required**

The organization name. The name is not case sensitive.

Query parameters

per_page integer

The number of results per page (max 100). For more information, see "[Using pagination in the REST API](#)."

Default: 30

page integer

The page number of the results to fetch. For more information, see "[Using pagination in the REST API](#)."

Default: 1

HTTP response status codes for "List GitHub Apps installed on an enterprise-owned organization"

Status code	Description
200	A list of GitHub App installations that have been granted access to the organization

Code samples for "List GitHub Apps installed on an enterprise-owned organization"

❗ If you access GitHub at GHE.com, replace `api.github.com` with your enterprise's dedicated subdomain at `api.SUBDOMAIN.ghe.com`.

Request example

```
GET /enterprises/{enterprise}/apps/organizations/{org}/installations
```

cURL

JavaScript

GitHub CLI



```
curl -L \  
  -H "Accept: application/vnd.github+json" \  
  -H "Authorization: Bearer <YOUR-TOKEN>" \  
  -H "X-GitHub-API-Version: 2022-11-28" \  
  https://api.github.com/enterprises/ENTERPRISE/apps/organizations/ORG/installations
```

A list of GitHub App installations that have been granted access to the organization

Example response

Response schema

Status: 200

```
[  
  {  
    "value": {  
      "id": 1,  
      "app_slug": "monalisa/orbit",  
      "repository_selection": "selected",  
      "repositories_url": "https://api.github.com/enterprises/acme-  
corp/apps/organizations/some-org/installations/1/repositories",  
      "permissions": {  
        "checks": "write",  
        "metadata": "read",  
        "contents": "read"  
      },  
      "events": [  
        "push",  
        "pull_request"  
      ],  
      "created_at": "2017-07-08T16:18:44-04:00",  
      "updated_at": "2017-07-08T16:18:44-04:00"  
    },  
  },  
]  
]
```

Install a GitHub App on an enterprise-owned organization

Installs any valid GitHub App on the specified organization owned by the enterprise. If the app is already installed on the organization, and is suspended, it will be unsuspended. If the app has a pending installation request, they will all be approved.

If the app is already installed and has a pending update request, it will be updated to the latest version. If the app is now requesting repository permissions, it will be given access to the repositories listed in the request or fail if no `repository_selection` is provided.

This API can only be called by a GitHub App installed on the enterprise that owns the organization.

Fine-grained access tokens for "Install a GitHub App on an enterprise-owned organization"

This endpoint works with the following fine-grained token types:

- [GitHub App user access tokens](#)
- [GitHub App installation access tokens](#)

The fine-grained token must have the following permission set:

- "Enterprise organization installations" enterprise permissions (write)

Parameters for "Install a GitHub App on an enterprise-owned organization"

Headers

accept string

Setting to `application/vnd.github+json` is recommended.

Path parameters

enterprise string **Required**

The slug version of the enterprise name.

org string **Required**

The organization name. The name is not case sensitive.

Body parameters

client_id string **Required**

The Client ID of the GitHub App to install.

repository_selection string **Required**

The repository selection for the GitHub App. Must be one of:

- `all` - the installation can access all repositories in the organization.
- `selected` - the installation can access only the listed repositories.
- `none` - no repository permissions are requested. Only use when the app does not request repository permissions.

Can be one of: `all` , `selected` , `none`

repositories array of strings

The names of the repositories to which the installation will be granted access. This is the simple name of the repository, not the full name (e.g., `hello-world` not `octocat/hello-world`). This is only required when `repository_selection` is `selected` .

HTTP response status codes for "Install a GitHub App on an enterprise-owned organization"

Status code	Description
200	A GitHub App installation that was installed previously.
201	A GitHub App installation.

Code samples for "Install a GitHub App on an enterprise-owned organization"

❗ If you access GitHub at GHE.com, replace `api.github.com` with your enterprise's dedicated subdomain at `api.SUBDOMAIN.ghe.com` .

Request example

```
POST /enterprises/{enterprise}/apps/organizations/{org}/installations
```

cURL

JavaScript

GitHub CLI



```
curl -L \
  -X POST \
  -H "Accept: application/vnd.github+json" \
  -H "Authorization: Bearer <YOUR-TOKEN>" \
  -H "X-GitHub-API-Version: 2022-11-28" \
  https://api.github.com/enterprises/ENTERPRISE/apps/organizations/ORG/installations \
  -d '{"client_id":"Iv2abc123aabbcc","repository_selection":"all"}'
```

A GitHub App installation that was installed previously.

Example response

Response schema

Status: 200

```
{
  "id": 1,
  "account": {
    "login": "octocat",
    "id": 1,
    "node_id": "MDQ6VXNlcjE=",
    "avatar_url": "https://github.com/images/error/octocat_happy.gif",
    "gravatar_id": "",
    "url": "https://api.github.com/users/octocat",
    "html_url": "https://github.com/octocat",
    "followers_url": "https://api.github.com/users/octocat/followers",
    "following_url": "https://api.github.com/users/octocat/following{/other_user}",
    "gists_url": "https://api.github.com/users/octocat/gists{/gist_id}",
    "starred_url": "https://api.github.com/users/octocat/starred{/owner}/{/repo}",
    "subscriptions_url": "https://api.github.com/users/octocat/subscriptions",
    "organizations_url": "https://api.github.com/users/octocat/orgs",
    "repos_url": "https://api.github.com/users/octocat/repos",
    "events_url": "https://api.github.com/users/octocat/events{/privacy}",
    "received_events_url": "https://api.github.com/users/octocat/received_events",
    "type": "User",
    "site_admin": false
  },
  "access_tokens_url": "https://api.github.com/app/installations/1/access_tokens",
  "repositories_url": "https://api.github.com/installation/repositories",
  "html_url": "https://github.com/organizations/github/settings/installations/1",
  "app_id": 1,
  "target_id": 1,
  "target_type": "Organization",
  "permissions": {
    "checks": "write",
    "metadata": "read",
    "contents": "read"
  }
},
```

Uninstall a GitHub App from an enterprise-owned organization

Uninstall a GitHub App from an organization. Any app installed on the organization can be removed.

This API can only be called by a GitHub App installed on the enterprise that owns the organization.

Fine-grained access tokens for "Uninstall a GitHub App from an enterprise-owned organization"

This endpoint works with the following fine-grained token types:

- [GitHub App user access tokens](#)
- [GitHub App installation access tokens](#)

The fine-grained token must have the following permission set:

- "Enterprise organization installations" enterprise permissions (write)

Parameters for "Uninstall a GitHub App from an enterprise-owned organization"

Headers

accept string

Setting to `application/vnd.github+json` is recommended.

Path parameters

enterprise string **Required**

The slug version of the enterprise name.

org string **Required**

The organization name. The name is not case sensitive.

installation_id integer **Required**

The unique identifier of the installation.

HTTP response status codes for "Uninstall a GitHub App from an enterprise-owned organization"

Status code	Description
204	An empty response indicates that the installation was successfully removed.
403	Forbidden
404	Resource not found

Code samples for "Uninstall a GitHub App from an enterprise-owned organization"

 If you access GitHub at GHE.com, replace `api.github.com` with your enterprise's dedicated subdomain at `api.SUBDOMAIN.ghe.com`.

Request example

```
DELETE /enterprises/{enterprise}/apps/organizations/{org}/installations/{installation_id}
```

cURL

JavaScript

GitHub CLI



```
curl -L \
-X DELETE \
-H "Accept: application/vnd.github+json" \
-H "Authorization: Bearer <YOUR-TOKEN>" \
-H "X-GitHub-API-Version: 2022-11-28" \
https://api.github.com/enterprises/ENTERPRISE/apps/organizations/ORG/installations/1
```

An empty response indicates that the installation was successfully removed.

Status: 204

Get the repositories accessible to a given GitHub App installation

Lists the repositories accessible to a given GitHub App installation on an enterprise-owned organization.

This API can only be called by a GitHub App installed on the enterprise that owns the organization.

Fine-grained access tokens for "Get the repositories accessible to a given GitHub App installation"

This endpoint works with the following fine-grained token types:

- [GitHub App user access tokens](#)
- [GitHub App installation access tokens](#)

The fine-grained token must have at least one of the following permission sets:

- "Enterprise organization installation repositories" enterprise permissions (read)
- "Enterprise organization installations" enterprise permissions (read)

Parameters for "Get the repositories accessible to a given GitHub App installation"

Headers

accept string

Setting to `application/vnd.github+json` is recommended.

Path parameters

enterprise string **Required**

The slug version of the enterprise name.

org string **Required**

The organization name. The name is not case sensitive.

installation_id integer **Required**

The unique identifier of the installation.

Query parameters

per_page integer

The number of results per page (max 100). For more information, see "[Using pagination in the REST API](#)."

Default: 30

page integer

The page number of the results to fetch. For more information, see "[Using pagination in the REST API](#)."

Default: 1

HTTP response status codes for "Get the repositories accessible to a given GitHub App installation"

Status code	Description
200	A list of repositories owned by the enterprise organization to which the installation has access.

Code samples for "Get the repositories accessible to a given GitHub App installation"

❗ If you access GitHub at GHE.com, replace `api.github.com` with your enterprise's dedicated subdomain at `api.SUBDOMAIN.ghe.com`.

Request example

```
GET /enterprises/{enterprise}/apps/organizations/{org}/installations/{installation_id}/repositories
```

cURL

JavaScript

GitHub CLI



```
curl -L \
-H "Accept: application/vnd.github+json" \
-H "Authorization: Bearer <YOUR-TOKEN>" \
-H "X-GitHub-API-Version: 2022-11-28" \
```

`https://api.github.com/enterprises/ENTERPRISE/apps/organizations/ORG/installations/1/repositories`

A list of repositories owned by the enterprise organization to which the installation has access.

Example response

Response schema

Status: 200

```
[
  {
    "id": 1,
    "name": "Hello World",
    "full_name": "octocat/Hello-World"
  },
  {
    "id": 2,
    "login": "Goodbye World",
    "full_name": "octocat/Goodbye-World"
  }
]
```

Toggle installation repository access between selected and all repositories

Toggle repository access for a GitHub App installation between all repositories and selected repositories. You must provide at least one repository when changing the access to 'selected'. If you change the access to 'all', the repositories list must not be provided.

This API can only be called by a GitHub App installed on the enterprise that owns the organization.

Fine-grained access tokens for "Toggle installation repository access between selected and all repositories"

This endpoint works with the following fine-grained token types:

- [GitHub App user access tokens](#)
- [GitHub App installation access tokens](#)

The fine-grained token must have at least one of the following permission sets:

- "Enterprise organization installation repositories" enterprise permissions (write)
- "Enterprise organization installations" enterprise permissions (write)

Parameters for "Toggle installation repository access between selected and all repositories"

Headers

accept string

Setting to `application/vnd.github+json` is recommended.

Path parameters

enterprise string **Required**

The slug version of the enterprise name.

org string **Required**

The organization name. The name is not case sensitive.

installation_id integer **Required**

The unique identifier of the installation.

Body parameters

repository_selection string **Required**

One of either 'all' or 'selected'

Can be one of: `all` , `selected`

repositories array of strings

The repository names to add to the installation. Only required when `repository_selection` is 'selected'

HTTP response status codes for "Toggle installation repository access between selected and all repositories"

Status code	Description
200	The GitHub App installation that was updated.

Code samples for "Toggle installation repository access between selected and all repositories"

❶ If you access GitHub at GHE.com, replace `api.github.com` with your enterprise's dedicated subdomain at `api.SUBDOMAIN.ghe.com`.

Request example

PATCH `/enterprises/{enterprise}/apps/organizations/{org}/installations/{installation_id}/repositories`

cURL

JavaScript

GitHub CLI



```
curl -L \
  -X PATCH \
  -H "Accept: application/vnd.github+json" \
  -H "Authorization: Bearer <YOUR-TOKEN>" \
  -H "X-GitHub-API-Version: 2022-11-28" \
  https://api.github.com/enterprises/ENTERPRISE/apps/organizations/ORG/installations/1/repositories \
  -d '{"repository_selection":"selected","repositories":["hello-world","hello-world-2"]}'
```

The GitHub App installation that was updated.

Example response

Response schema

Status: 200

```
{
  "id": 1,
  "account": {
    "login": "octocat",
    "id": 1,
```

```

"node_id": "MDQ6VXNlcjE=",
"avatar_url": "https://github.com/images/error/octocat_happy.gif",
"gravatar_id": "",
"url": "https://api.github.com/users/octocat",
"html_url": "https://github.com/octocat",
"followers_url": "https://api.github.com/users/octocat/followers",
"following_url": "https://api.github.com/users/octocat/following{/other_user}",
"gists_url": "https://api.github.com/users/octocat/gists{/gist_id}",
"starred_url": "https://api.github.com/users/octocat/starred{/owner}/{/repo}",
"subscriptions_url": "https://api.github.com/users/octocat/subscriptions",
"organizations_url": "https://api.github.com/users/octocat/orgs",
"repos_url": "https://api.github.com/users/octocat/repos",
"events_url": "https://api.github.com/users/octocat/events{/privacy}",
"received_events_url": "https://api.github.com/users/octocat/received_events",
"type": "User",
"site_admin": false
},
"access_tokens_url": "https://api.github.com/app/installations/1/access_tokens",
"repositories_url": "https://api.github.com/installation/repositories",
"html_url": "https://github.com/organizations/github/settings/installations/1",
"app_id": 1,
"target_id": 1,
"target_type": "Organization",
"permissions": {
  "checks": "write",
  "metadata": "read",
  "contents": "read"
}

```

Grant repository access to an organization installation

Grant repository access to an organization installation. You can add up to 50 repositories at a time. If the installation already has access to the repository, it will not be added again.

This API can only be called by a GitHub App installed on the enterprise that owns the organization.

Fine-grained access tokens for "Grant repository access to an organization installation"

This endpoint works with the following fine-grained token types:

- [GitHub App user access tokens](#)
- [GitHub App installation access tokens](#)

The fine-grained token must have at least one of the following permission sets:

- "Enterprise organization installation repositories" enterprise permissions (write)
- "Enterprise organization installations" enterprise permissions (write)

Parameters for "Grant repository access to an organization installation"

Headers

accept string

Setting to `application/vnd.github+json` is recommended.

Path parameters

enterprise string Required

The slug version of the enterprise name.

org string Required

The organization name. The name is not case sensitive.

installation_id integer Required

The unique identifier of the installation.

Body parameters

repositories array of strings Required

The repository names to add to the installation.

HTTP response status codes for "Grant repository access to an organization installation"

Status code	Description
200	A list of repositories which the authenticated GitHub App should be granted access to.

Code samples for "Grant repository access to an organization installation"

❗ If you access GitHub at GHE.com, replace `api.github.com` with your enterprise's dedicated subdomain at `api.SUBDOMAIN.ghe.com`.

Request example

PATCH `/enterprises/{enterprise}/apps/organizations/{org}/installations/{installation_id}/repositories/add`

cURL

JavaScript

GitHub CLI



```
curl -L \
  -X PATCH \
  -H "Accept: application/vnd.github+json" \
  -H "Authorization: Bearer <YOUR-TOKEN>" \
  -H "X-GitHub-API-Version: 2022-11-28" \
  https://api.github.com/enterprises/ENTERPRISE/apps/organizations/ORG/installations/1/repositories/add \
  -d '{"repositories":["hello-world","hello-world-2"]}'
```

A list of repositories which the authenticated GitHub App should be granted access to.

Example response

Response schema

Status: 200

```
[
  {
    "id": 1,
    "name": "Hello World",
    "full_name": "octocat/Hello-World"
  },
  {
    "id": 2,
    "login": "Goodbye World",
    "full_name": "octocat/Goodbye-World"
  }
]
```

Remove repository access from an organization installation

Remove repository access from a GitHub App installed on an organization. You can remove up to 50 repositories at a time. You cannot remove repositories from an app installed on all repositories, nor can you remove the last repository for an app. If you attempt to do so, the API will return a 422 Unprocessable Entity error.

This API can only be called by a GitHub App installed on the enterprise that owns the organization.

Fine-grained access tokens for "Remove repository access from an organization installation"

This endpoint works with the following fine-grained token types:

- [GitHub App user access tokens](#)
- [GitHub App installation access tokens](#)

The fine-grained token must have at least one of the following permission sets:

- "Enterprise organization installation repositories" enterprise permissions (write)
- "Enterprise organization installations" enterprise permissions (write)

Parameters for "Remove repository access from an organization installation"

Headers

accept string

Setting to `application/vnd.github+json` is recommended.

Path parameters

enterprise string **Required**

The slug version of the enterprise name.

org string **Required**

The organization name. The name is not case sensitive.

installation_id integer **Required**

The unique identifier of the installation.

Body parameters

repositories array of strings **Required**

The repository names to remove from the installation.

HTTP response status codes for "Remove repository access from an organization installation"

Status code	Description
200	A list of repositories which the authenticated GitHub App has lost access to.
422	The request was well-formed but was unable to be followed due to semantic errors. This can happen if you attempt to remove a repository from an installation that has access to all repositories, or if you attempt to remove the last repository from an installation.

Code samples for "Remove repository access from an organization installation"

 If you access GitHub at GHE.com, replace `api.github.com` with your enterprise's dedicated subdomain at `api.SUBDOMAIN.ghe.com`.

Request example

```
PATCH /enterprises/{enterprise}/apps/organizations/{org}/installations/{installation_id}/repositories/remove
```

cURL

JavaScript

GitHub CLI



```
curl -L \
  -X PATCH \
  -H "Accept: application/vnd.github+json" \
  -H "Authorization: Bearer <YOUR-TOKEN>" \
  -H "X-GitHub-API-Version: 2022-11-28" \
```

```
https://api.github.com/enterprises/ENTERPRISE/apps/organizations/ORG/installations/1/reposi
```

```
ories/remove \
-d '{"repositories":["hello-world","hello-world-2"]}'
```

A list of repositories which the authenticated GitHub App has lost access to.

Example response

Response schema

Status: 200

```
[
  {
    "id": 1,
    "name": "Hello World",
    "full_name": "octocat/Hello-World"
  },
  {
    "id": 2,
    "login": "Goodbye World",
    "full_name": "octocat/Goodbye-World"
  }
]
```

Legal

© 2025 GitHub, Inc. [Terms](#) [Privacy](#) [Status](#) [Pricing](#) [Expert services](#) [Blog](#)