[SuperDSP 平台化] 串接 Studio 素材管理 – API 規格文件

- SuperDSP
  - API 規格
    - Redirect
    - AdFormatType
    - Banners
    - Videos
    - Packs
    - AdGroup
- MASA
  - API 規格
    - Users
    - AdFormatType
    - 素材(Video)
    - 素材(Banner)
    - 素材包

SuperDSP

API 規格

Redirect

按一下此處以展開...

name	前往 OneAD Studio
methods	GET
path	`api/v1/superdsp/companies/#{company_id}/redirect/studio`
status	新 API
開發狀態	
request type	

```
header
{
  "Authorization": string, required: true
}

path
company_id # 必填

query
action_type # [create / copy / edit / preview]
```

	pack_id # action_type 為 copy / edit / preview 必填 ad_format_type_id # 選填

request sample	header
	{
	"Authorization": "abcde"
	}

controller	app/controllers/api/v1/users_controller.rb

response	{
	status: 'success',
	data: 'url'
	}

who	

備註	1. 使用 JWT 產出一組 token
	{
	"user_id"
	"source": 'SuperDSP'
	"exp": Time.now.to_i + 1.day.to_i
	}
	2. redirect page with access token
	3. 帶入參數：
	a. packageID: 素材包 ID
	b. clientID: 目前使用者所選擇的廣告主 ID
	c. ad_format_type universal id

AdFormatType

按一下此處以展開...

name	撈取格式列表 API
methods	Get
path	`/api/v1/superdsp/ad_format_types`
status	舊 API
開發狀態	

request type	{
	...,
	}

request sample	```
	{
	  ...,
	}
	``

controller	app/controllers/api/v1/superdsp/banners_controller.rb

response	```
	{
	  "data": [
	  {
	  "superdsp_enabled": true
	  ...,
	  }
	  ]
	}
	``

who	
備註	1. 改成 enabled = true 的都回傳 2. `superdsp_enabled` 值回傳，這個值用 SuperDSP 格式細項白名單來判斷 3. 白名單需使用 universal_id，因在 staging 上也要能濾掉

Banners

按一下此處以展開...

name	撈取 banner 素材列表 API
methods	Get
path	`/api/v1/superdsp/companies/#{client_id}/banners`
status	舊 API
開發狀態	

request type	```
	{
	  ...,
	}
	``

request sample	```
	{
	  ...,
	}
	``

controller	app/controllers/api/v1/superdsp/banners_controller.rb

response	```
	{
	``

	``
	  "data": [
	  {
	  "id": 29741,
	  "banner_source": "SuperDSP"
	  ...,
	  }
	  ]
	}
	``

who	
備註	1. banner_source 有分 SuperDSP 和 OneAD Studio

Videos

按一下此處以展開...

name	撈取 video 素材列表 API
methods	Get
path	`/api/v1/superdsp/companies/#{client_id}/videos`
status	舊 API
開發狀態	

request type	```
	{
	  ...,
	}
	``

request sample	```
	{
	  ...,
	}
	``

controller	app/controllers/api/v1/superdsp/videos_controller.rb

response	```
	{
	  "data": [
	  {
	  "id": 29741,
	  "video_source": "SuperDSP"
	  ...,
	  }
	  ]
	}
	``

who	
備註	1. video_source 有分 SuperDSP 和 OneAD Studio

Packs

按一下此處以展開...

name	撈取 pack 素材包列表 API
methods	Get
path	`/api/v1/superdsp/companies/#{client_id}/packs`
status	舊 API
開發狀態	
request type	`{ ..., }`
request sample	`{ ..., }`
controller	app/controllers/api/v1/superdsp/banners_controller.rb
response	`{ "data": [ { "id": 29741, "pack_source": "SuperDSP" ..., } ] }`
who	
備註	1. pack_source 有分 SuperDSP 和 OneAD Studio

name	建立 pack 素材包 API
methods	POST
path	`/api/v1/superdsp/companies/#{client_id}/packs`
status	舊 API
開發狀態	
request type	`{ ..., tracking_codes: type string Array # 移除`

	`}`

request sample	`{`
	`...,`
	`tracking_codes # 移除`
	`}`

controller	app/controllers/api/v1/superdsp/banners_controller.rb

response	`{`
	`"data": [`
	`{`
	`"id": 29741,`
	`"pack_source": "SuperDSP"`
	`...,`
	`}`
	`]`
	`}`

who	
備註	1. 移除 tracking codes

name	更新 pack 素材包 API
methods	POST
path	`/api/v1/superdsp/companies/#{client_id}/packs/#{pack_id}`
status	舊 API
開發狀態	

request type	`{`
	`...,`
	`tracking_codes: type string Array # 移除`
	`}`

request sample	`{`
	`...,`
	`tracking_codes # 移除`
	`}`

controller	app/controllers/api/v1/superdsp/banners_controller.rb

response	`{`
	`"data": [`
	`{`
	`"id": 29741,`
	`"pack_source": "SuperDSP"`

	``
	        ...,
	      }
	    ]
	}
	``

who	
備註	1. 移除 tracking codes

name	撈取 pack 素材包 API
methods	POST
path	`/api/v1/superdsp/companies/#{client_id}/packs/#{pack_id}`
status	舊 API
開發狀態	

request type	```
	{
	  ...
	}
	``

request sample	```
	{
	  ...
	}
	``

controller	app/controllers/api/v1/superdsp/banners_controller.rb

response	```
	{
	  "data": [
	    {
	      "id": 29741,
	      "pack_source": "SuperDSP",
	      "tracking_codes": # 移除
	      ...,
	    }
	  ]
	}
	``

who	
備註	1. 移除 tracking codes

AdGroup

按一下此處以展開...

name	撈取 Ad Group(含 instream)
methods	Get
path	`/api/v1/superdsp/ad_groups(/instream)/{ad_group_id}`
status	舊 API
開發狀態	

request type	```
	header
	{
	  ...,
	}
	``

request sample	```
	header
	{
	  ...,
	}
	
	``

controller	app/controllers/api/v1/superdsp/ad_groups_controller.rb

response	```
	{
	  "data": {
	  ...,
	  tracking_codes: ["https://onead.com.tw"]
	  }
	}
	``

who	

備註	1. 建立的時候，要在 `UseCases::SuperdspAdGroupCreateUseCase` 中調整
	``
	# 84
	def tracking_code(ad_group)
	  # 要加入參數的 tracking_codes
	  tracking_codes.each |tc|
	  << {
	  "intent": "custom",
	  "format": "pixel",
	  "content": tc,
	  "event_type_id": 1,
	  }
	  end
	``
	2. response 中要加入 tracking_codes 回傳

name	建立 Ad Group(含instream)
methods	POST
path	`/api/v1/superdsp/campaigns/{campaign_id}/ad_group(/instream)`
status	舊 API
開發狀態	
request type	

```
header
{
  ...,
}

body
{
  ...,
  "ad_group": {
    ...,
    tracking_codes: String Array
  }
}
```

request sample

```
header
{
  ...,
}

body
{
  "ad_group": {
    ...,
    tracking_codes: ["https://onead.com.tw"]
  }
}
```

controller	app/controllers/api/v1/superdsp/ad_groups_controller.rb

response

```
{
  "data": {
    ...,
    tracking_codes: ["https://onead.com.tw"]
  }
}
```

who	
備註	1. 建立的時候，要在 `UseCases::SuperdspAdGroupCreateUseCase` 中調整

```
# 84
```

```
def tracking_code(ad_group)
  # 要加入參數的 tracking_codes
  tracking_codes.each |tc|
    << {
      "intent": "custom",
      "format": "pixel",
      "content": tc,
      "event_type_id": 1,
    }
  end
```

2. response 中要加入 tracking_codes 回傳

name	更新 Ad Group(含 instream)
methods	PUT
path	`/api/v1/superdsp/ad_groups(/instream)/{id}`
status	舊 API
開發狀態	
request type	

```
header
{
  ...,
}

body
{
  ...,
  "ad_group": {
    ...,
    tracking_codes: String Array
  }
}
```

request sample

```
header
{
  ...,
}

body
{
  "ad_group": {
    ...,
    tracking_codes: ["https://onead.com.tw"]
  }
}
```

controller	app/controllers/api/v1/superdsp/ad_groups_controller.rb
response	

```
{
  "data": {
```

	``
	  ...,
	  tracking_codes: ["https://onead.com.tw"]
	  }
	}
	``

who	

備註	1. 更新的時候，要在 `UseCases::SuperdspAdGroupCreateUseCase` 中調整
	``
	# 84
	def tracking_code(ad_group)
	  # 要加入參數的 tracking_codes
	  tracking_codes.each |tc|
	  << {
	  "intent": "custom",
	  "format": "pixel",
	  "content": tc,
	  "event_type_id": 1,
	  }
	  end
	``
	2. response 中要加入 tracking_codes 回傳

MASA

API 規格

Users

按一下此處以展開...

name	刷新 User Token
methods	GET
path	`/api/v1/users/refresh_token`
status	新 API
開發狀態	

request type	```
	header
	{
	  Authorization: string, required: true
	  X-User: string, required: true
	}
	``

request sample	```
	header
	{
	  Authorization: 'a123f'
	``

	``
	  X-User: 'abcde'
	}
	``

controller	app/controllers/api/v1/users_controller.rb

response	```
	{
	  "status": "success",
	  "data": {
	  "token": user_token,
	  "expired_at": "2016-07-15T08:28:21+08:00"
	  }
	}
	``

who	

備註	如果 token 驗證成功，使用 JWT 產出一組新的 token
	``
	# 成功解開
	decode_token = JWT.decode(token, SECRETS[:oss_secret_key], 'HS256')
	
	payload = decode_token[0]
	payload["exp""] = Time.now.to_i + 1.day.to_i
	
	JWT.encode(payload, SECRETS[:oss_secret_key], 'HS256')
	``

name	撈取 profile
methods	GET
path	`/api/v1/users/profile`
status	新 API
開發狀態	

request type	```
	header
	{
	  Authorization: string, required: true
	  X-User: string, required: true
	}
	``

request sample	```
	header
	{
	  Authorization: 'a123f'
	  X-User: 'abcde'
	}
	``

controller	app/controllers/api/v1/users_controller.rb

response	```
	{
	  "status": "success",
	  "data": {
	``

```
    email: 'abd@onead.tw',
    username: 'kirthsu',
    ability: "viewer",
    companies: [{
      id: 1,
      name: 'OneAD',
      type: "Client",
      advertisers: [{
        id: 1,
        name: 'OneAD 汽車'
      }]
    }]
  }
}
```

who	
備註	

```
{
  email: user.email
  username: user.fullname
  ability: enum ["viewer", "editor"] # user.roles 看 SuperDSP 編輯權限
  companies: [{
    id: integer
    name: string
    type: enum string ["Client", "Agency", "Media"]
    advertisers: [{
      id: integer
      name: string
    }]
  }]
}
```

1. 需排除 SuperDSP 白名單格式細項

AdFormatType

按一下此處以展開...

name	撈取格式(格式細項)選項 API
methods	GET
path	`/api/v1/ad_format_types/option`
status	新 API
開發狀態	
request type	

```
header
{
  Authorization: string, required: true
  X-User: string, required: true
}
```

request sample	request header
	{
	"Authorization": source token,
	"X-User": 'AAAA'
	}

controller	app/controllers/api/v1/ad_format_types_controller.rb

response	{
	"status": "success",
	"data": [
	{
	"id": 1,
	"name": "IP (Landscape Video)"
	"universal_id": "2674e8ab-73d8-11ea-9ef3-42010a006ae7",
	"ad_format_id": 1,
	"ad_format_name": "IP"
	"sub_ad_type_id": 1,
	"sub_ad_type_name": "640x360_video only",
	},
	...
	]
	}

who	
備註	1. 這邊回傳增加用使用者做 filter

素材(Video)

按一下此處以展開...

name	創建影片素材 API
methods	POST
path	`/api/v1/advertisers/:advertiser_id/material/videos`
status	舊 API
開發狀態	

request type	# 新增 SuperDSP 素材
	header
	{
	Authorization: string, required: true
	X-User: string, required: true
	}
	
	# type = form-data
	{

	``
	  "title": string, default: ""
	  "description": string, default: ""
	  "source": enum string, ["superdsp"]
	  "file": (二進位檔)
	}
	``

request sample	```
	header
	{
	  Authorization: 'a123f'
	  X-User: 'abcde'
	}
	
	# type = form-data
	{
	  "title": "wqeqweq"
	  "description": "qweqweqwe"
	  "source": "superdsp"
	  "file": (二進位檔)
	}
	``

controller	app/controllers/api/v1/material/videos_controller.rb

response	```
	{
	  ...,
	}
	``

who	
備註	1. 如果是建立 superdsp 素材包，要檢查 user token

素材(Banner)

按一下此處以展開...

name	創建 banner 素材 API
methods	POST
path	`/api/v1/advertisers/:advertiser_id/material/banners`
status	舊 API
開發狀態	

request type	```
	# 新增 SuperDSP 素材
	header
	{
	  Authorization: string, required: true
	  X-User: string, required: true
	}
	
	``

	``
	# type = form-data
	{
	  "title": string, default: ""
	  "description": string, default: ""
	  "source": enum string, ["superdsp"]
	  "file": (二進位檔)
	}
	``

request sample	```
	# 新增 SuperDSP 素材
	header
	{
	  Authorization: 'a123f'
	  X-User: 'abcde'
	}
	
	# type = form-data
	{
	  "title": "wqeqweq"
	  "description": "qweqweqwe"
	  "source": "superdsp"
	  "file": (二進位檔)
	}
	``

controller	app/controllers/api/v1/material/banners_controller.rb

response	```
	{
	  ...,
	}
	``

who	
備註	1. 如果是建立 superdsp 素材包，要檢查 user token

素材包

按一下此處以展開...

name	創建素材包 API
methods	Post
path	`/api/v1/advertisers/:advertiser_id/material/packs`
status	舊 API
開發狀態	

request type	```
	# 新增 SuperDSP 素材
	header
	{
	  Authorization: string, required: true
	``

```
  X-User: string, required: true
}

body
{
  "title": string, default: ""
  "click_urls": [
      {
          "material_type": enum string, ["Material::Video", "Material::Banner", "Material::Text"]
          "device_type": string, default: "Desktop",
          "position": integer, default: 1,
          "click_url": string[], default: [""],
          "url_count": integer, default: 1,
          "material_id": integer, 必填,
      }
  ],
  "text_contents": [
    {
      "position": integer,
      "text_content": string
    }
  ],
  "banner_ids": integer[], default: []
  "video_ids": integer[], default: []
  "source_id": string, 必填, # binding occ id
  "ad_format_id": integer, 必填,
  "ad_format_type_id": integer, 必填
  "vast_feature": enum string, ['NONE']
  "source": enum string, ["superdsp"]
  "video_duration": integer, 必填,
  "qrcode_setting": {
      "short_url_id": integer, default: null,
      "binded_pack_id": integer, default: null,
      "direct_url": string, default: ""
  },
  "description": string, default: "",
  "url_link_to: string, default: "", ["inside", "outside"]
}
```

request sample

```
# 新增 SuperDSP 素材
header
{
  Authorization: 'a123f'
  X-User: 'abcde'
}

body
{
  "title": "ssssss",
  "click_urls": [
      {
          "material_type": "Material::Video",
          "device_type": "Desktop",
          "position": 1,
          "click_url": [
              ""
          ],
          "url_count": 1,
          "material_id": 17387
```

```
    },
    {
        "material_type": "Material::Banner",
        "device_type": "Desktop",
        "position": 1,
        "click_url": [
            ""
        ],
        "url_count": 1,
        "material_id": 17460
    },
    {
        "material_type": "Material::Text",
        "device_type": "Desktop",
        "position": 1,
        "click_url": [
            ""
        ],
        "url_count": 1
    }
  ],
  "banner_ids": [
    17460
  ],
  "video_ids": [
    17387
  ],
  "text_contents": [
    {
        "position": 1,
        "text_content": "aasdasdasdasd"
    }
  ],
  "source_id": '507f191e810c19729de860ea',
  "ad_format_id": 1,
  "ad_format_type_id": 1,
  "vast_feature": "NONE",
  "source": "superdsp",
  "video_duration": 30,
  "qrcode_setting": {
    "short_url_id": null,
    "binded_pack_id": null,
    "direct_url": ""
  },
  "description": "",
  "url_link_to": ""
}
```


controller	app/controllers/api/v1/material/packs_controller.rb

response	{
	...,
	}

who	
備註	1. 有放入 user token 的情況下，會根據 token 中的 type 寫入資料

```
"pack_source": "OneAD",
"ron": false,
"vast_feature": "NONE",
"hold_on_sec": 0,
"emoji_id": nil,
"pack_type": "onead",
"review_status": "reviewing"
```

2. source_id 為 CC 上的素材包id
3. url_link_to 只有在媒體公司，且在 Quality Traffic(文字素材)，才有區分導內導外

name	更新素材包 API
methods	Put
path	`/api/v1/advertisers/:advertiser_id/material/packs/:pack_id`
status	舊 API
開發狀態	
request type	

```
# 新增 SuperDSP 素材
header
{
  Authorization: string, required: true
  X-User: string, required: true
}

body
{
  "title": string, default: ""
  "click_urls": [
      {
          "material_type": enum string, ["Material::Video", "Material::Banner", "Material::Text"]
          "device_type": string, default: "Desktop",
          "position": integer, default: 1,
          "click_url": string[], default: [""],
          "url_count": integer, default: 1,
          "material_id": integer, 必填,
      }
  ],
  "text_contents": [
    {
      "position": integer,
      "text_content": string
    }
  ],
  "banner_ids": integer[], default: []
  "video_ids": integer[], default: []
  "source_id": string, 必填, # binding occ id
```

```
  "ad_format_id": integer, 必填,
  "ad_format_type_id": integer, 必填
  "vast_feature": enum string, ['NONE']
  "source": enum string, ["superdsp"]
  "video_duration": integer, 必填,
  "qrcode_setting": {
      "short_url_id": integer, default: null,
      "binded_pack_id": integer, default: null,
      "direct_url": string, default: ""
  },
  "description": string, default: "",
  "url_link_to: string, default: "", ["inside", "outside"]
}
```

request sample

```
# 新增 SuperDSP 素材
header
{
  Authorization: 'a123f'
  X-User: 'abcde'
}

body
{
  "title": "ssssss",
  "click_urls": [
      {
          "material_type": "Material::Video",
          "device_type": "Desktop",
          "position": 1,
          "click_url": [
              ""
          ],
          "url_count": 1,
          "material_id": 17387
      },
      {
          "material_type": "Material::Banner",
          "device_type": "Desktop",
          "position": 1,
          "click_url": [
              ""
          ],
          "url_count": 1,
          "material_id": 17460
      },
      {
          "material_type": "Material::Text",
          "device_type": "Desktop",
          "position": 1,
          "click_url": [
              ""
          ],
          "url_count": 1
      }
  ],
  "banner_ids": [
      17460
  ],
  "video_ids": [
```

```
    17387
  ],
  "text_contents": [
    {
      "position": 1,
      "text_content": "aasdasdasdasd"
    }
  ],
  "source_id": '507f191e810c19729de860ea',
  "ad_format_id": 1,
  "ad_format_type_id": 1,
  "vast_feature": "NONE",
  "source": "superdsp",
  "video_duration": 30,
  "qrcode_setting": {
    "short_url_id": null,
    "binded_pack_id": null,
    "direct_url": ""
  },
  "description": "",
  "url_link_to": ""
}
```


controller	app/controllers/api/v1/material/packs_controller.rb
response	`{ ..., }`
who	
備註	1. 有放入 user token 的情況下，會根據 token 中的 type 寫入資料 `"pack_source": "OneAD", "ron": false, "vast_feature": "NONE", "source": "superdsp", "hold_on_sec": 0, "emoji_id": nil, "pack_type": "onead", "review_status": "reviewing"` 2. source_id 為 CC 上的素材包id 3. url_link_to 只有在媒體公司，且在 Quality Traffic(文字素材)，才有區分導內導外