SuperDSP 從IO到Sequence

- 建立IO單
- 建立廣告活動
- 建立受眾組合
- 建立素材包
- 建立廣告組合
- 設置為上刊
- 排程產Sequence
- 查詢Sequence

建立IO單

url	`POST /api/v1/superdsp/companies/{id}/insertion_orders`
controller	app/controllers/api/v1/superdsp/insertion_orders_controller.rb
function	create

request body	<pre>{
	"insertion_order": {
	"name": "麥當勞廣告案",
	"insertion_order_purpose_id": 1,
	"category_id": 1,
	"sub_category_id": 1,
	}
	}</pre>

邏輯	1. 建立IO單 `InsertionOrder`

建立廣告活動

url	`POST /api/v1/superdsp/insertion_orders/{id}/campaigns`

controller	app/controllers/api/v1/superdsp/campaigns_controller.rb
function	create

request body	{
	"campaign": {
	"name": "New campaign",
	"budget": 12345,
	"start_date": "2021-02-04",
	"end_date": "2021-03-01",
	"product_category_id": 1
	}
	}

邏輯	1. 建立one_campaign `OneCampaign` 2. 關聯IO單 3. 關聯廣告主 4. 設置狀態為 `oncue` 5. 設置組織和對應的管理者 `Agency（代理商）/ Client（直客）/ Media（媒體）` 6. 設置建立者 7. 設置類別 `IO單上的主/副類別` 8. 設置序列號和版號 `AdRequestNumberService.next_ad_request_number` 9. 更新資料回IO單 `start date, end date, budget 與 product_categories`

建立受眾組合

url	`POST /api/v1/superdsp/companies/{id}/audiences`
controller	app/controllers/api/v1/superdsp/audiences_controller.rb
function	create
request body	{ "audience": {

	``` 3 "name": "受眾組合A", 4 "demographic_ids": [1, 2], 5 "interest_ids": [3, 4], 6 "keyword_ids": [5, 6], 7 "audience_size: 987000, 8 } 9 } ```
邏輯	1. 建立資料 `Audience`

建立素材包

url	`POST /api/v1/superdsp/companies/{id}/packs`
controller	app/controllers/api/v1/superdsp/packs_controller.rb
function	create

request body	```
	1 {
	2 "pack": {
	3 "title": "Pack 新名字",
	4 "description": "Pack 新說明",
	5 "ad_format_type_id": 8,
	6 "video_ids": [1, 2],
	7 "banner_ids": [50],
	8 "redirect_url": "https://www.onead.com.tw/",
	9 "tracking_codes": ["tracking_code1", "tracking_code2"],
	10 "product_category_id": 1,
	11 "text_context": "文字素材",
	12 "url_link_to": "outside",
	13 }
	14 }
	``

邏輯	1. 取得產品組合 `ProductCategory` 2. 取得廣告格式 `AdFormatType` 3. 取得素材長度(時間) 4. 設置導內導外 5. 建立素材包 `Pack`

建立廣告組合

url	`POST /api/v1/superdsp/campaigns/{campaign_id}/ad_groups`
controller	app/controllers/api/v1/superdsp/ad_groups_controller.rb
function	create

request body	{
	"ad_group": {
	"name": "麥當勞大麥克活動",
	"ad_format_type_id": 2,
	"start_date": "2021-02-04",
	"end_date": "2021-03-01",
	"budget": 12345,
	"markup": 20,
	"pricing_model_id": 2,
	"uniprice": 100,
	"freq": 2,
	"audience_id": 2,
	"superdsp_pack_id": 34,
	"target_devices": [2, 3],
	"excluded_medium_ids": [1, 2],
	"hourlies": [1, 2, 4],
	"regions": [1, 2, 4],
	"cities": [1, 4],
	}
	}

邏輯	1. 驗證日期是否合法 2. 驗證預算是否合法 3. 建立廣告組合 `SuperdspAdGroup` 4. 素材包導內導外 5. 計算每日可使用預算 6. 更新預算資料 7. 建立one_campaign的 `grouping_association`

設置為上刊

url	`POST /ad_groups/{id}/to_status`
controller	app/controllers/api/v1/superdsp/ad_groups_controller.rb

function	`to_status`

request body	{
	"ad_group": {
	"superdsp_status": "on cue"
	}
	}

邏輯	1. 檢查狀態參數 2. 檢查起訖日 3. 檢查廣告組合能否變更成該狀態 4. 狀態變更

排程產Sequence

指令	`rake sequence`
controller	lib/tasks/sequence.rake
邏輯	1. 移除當天的sequence 2. 查詢當天需建立sequnence的pre_campaign `SELECT \`pre_campaign_dailyreach\`.* FROM \`pre_campaign_dailyreach\`` `INNER JOIN \`pre_campaign_detail\` ON \`pre_campaign_detail\`.\`id\` = \`pre_campaign_dailyreach\`.\`pre_ca` `INNER JOIN \`pre_campaign\` ON \`pre_campaign\`.\`id\` = \`pre_campaign_detail\`.\`pre_campaign_id\`` `WHERE \`pre_campaign_dailyreach\`.\`c_date\` = '2023-07-07'` `AND \`pre_campaign_detail\`.\`enable\` = 1` `AND (\`pre_campaign_detail\`.\`pack_id\` IS NOT NULL)` `AND \`pre_campaign\`.\`status\` = 'oncue'` `AND \`pre_campaign\`.\`has_sequence\` = 1` 3. 建立sequence

查詢Sequence

帳密	erp/config/basic_auth.yml
url	`REMOTE_URLS[:OSS] + /adserv/v5/sequences`