[開發規格文件] IAS 內文比對

ERP

內文比對分類 index api

methods	`GET`
path	`pre_campaigns/moat_contextual_segment_categories`
status	old
request	
controller	`app/controllers/pre_campaigns/moat_contextual_segments_controller.rb` index
response	`{ status: success, data: [ { ....., is_include: 1, }, ], }`
備註	新增 is_include

內文比對分類 create api

methods	`POST`
path	`pre_campaigns/moat_contextual_segment_categories`
status	old
request	`{ ....., is_incldue: 1, }`
controller	`app/controllers/pre_campaigns/moat_contextual_segments_controller.rb` create
response	
備註	新增 is_include

內文比對分類 update api

methods	`PUT`
path	`pre_campaigns/moat_contextual_segment_categories`
status	old
request	`{ ....., is_include: 1, }`

controller	`app/controllers/pre_campaigns/moat_contextual_segments_controller.rb` update
response	
備註	新增 is_include

內文比對 index api

methods	`GET`
path	pre_campaigns/moat_contextual_segments?~~type=cea~~ pre_campaigns/moat_contextual_segments?is_include=1
status	old
request	
controller	`app/controllers/pre_campaigns/moat_contextual_segments_controller.rb` index
response	
備註	type 改 is_include boolean

ODM

內文比對 system_contextual api

methods	`GET`
path	api/v1/odm/moat_segments/system_contextual?~~type=cea~~&placement_id=99318 api/v1/odm/moat_segments/system_contextual?is_include=1&placement_id=99318
status	old
request	
controller	`app/controllers/api/v1/programmatics/moat_segments_controller.rb` `system_contextual`
response	
備註	type 改 is_include boolean

SuperDSP

內文比對 options api

methods	`GET`
path	`api/v1/superdsp/options/moat_contextual_segments` ?is_include=1
status	new api
request	
controller	`api/v1/superdsp/options/moat_contextual_segments_controller.rb` index
response	

```
{
  status: success,
```

```
  data: {
    category_id: 1,
    category_name: 'Topical Segments'
    category_name_ch: '特定主題',
    contextual_segments: [
      {
        id: 1,
        name: '抗議與示威 – 負面情緒',
        name_en: 'Protests & Demonstrations – Negative Emotions',
      },
    ],
  }
}
```

備註	is_include boolean

ad_group create

methods	`POST`
path	`api/v1/superdsp/ad_groups`
status	old api
request	

```
{
  ad_group:{
    targets:{
      type: 0 || 1 //'audience' || 'content',
      include: {
        contextual_ids: [1, 2],
      },
      exclude: {
        contextual_ids: [4],
      },
    },
  },
}
```

controller	`api/v1/superdsp/ad_groups_controller.rb` create
response	

```
{
  status: success
}
```

備註	

ad_group update

methods	`PUT`
path	`api/v1/superdsp/ad_groups/{ad_group_id}`
status	old api
request	

```
{
  ad_group:{
    targets:{
      type: 0 || 1 //'audience' || 'content',
      include: {
        contextual_ids: [],
      },
      exclude: {
        contextual_ids: [],
      },
    },
  },
}
```

controller	`api/v1/superdsp/ad_groups_controller.rb` update

response	`{ status: success }`
備註	

ad_group show

methods	`GET`
path	`api/v1/superdsp/ad_groups/{ad_group_id}`
status	old api
request	
controller	`api/v1/superdsp/ad_groups_controller.rb` show
response	`{ status: success, data: { targets: { type: 0 || 1 //'audience' || 'content', include: { contextual_ids: [], }, exclude: { contextual_ids: [], }, }, }, }`
備註	

ad_group duplicate

methods	`POST`
path	`api/v1/superdsp/ad_groups/duplicate`
status	old api
request	`{ ad_group:{ targets:{ type: 0 || 1 //'audience' || 'content', include: { contextual_ids: [], }, exclude: { contextual_ids: [], }, }, }, }`
controller	`api/v1/superdsp/ad_groups_controller.rb` duplicate
response	`{ status: success }`
備註	

ad_group instream create

methods	`POST`

path	`api/v1/superdsp/ad_groups_instream`
status	old api
request	

```
{
  ad_group:{
    targets:{
      type: 0 || 1 //'audience' || 'content',
      include: {
        contextual_ids: [1, 2],
      },
      exclude: {
        contextual_ids: [4],
      },
    },
  },
}
```

controller	`api/v1/superdsp/ad_groups_instream_controller.rb`
response	

```
{
  status: success
}
```

備註	

ad_group instream update

methods	`PUT`
path	`api/v1/superdsp/ad_groups_instream/{ad_group_id}`
status	old api
request	

```
{
  ad_group:{
    targets:{
      type: 0 || 1 //'audience' || 'content',
      include: {
        contextual_ids: [],
      },
      exclude: {
        contextual_ids: [],
      },
    },
  },
}
```

controller	`api/v1/superdsp/ad_groups_instream_controller.rb`
response	

```
{
  status: success
}
```

備註	

ad_group instream show

methods	`GET`
path	`api/v1/superdsp/ad_groups_instream/{ad_group_id}`
status	old api
request	
controller	`api/v1/superdsp/`
response	

```
{
  status: success,
```

```
  data: {
    targets: {
      type: 0 || 1 //'audience' || 'content',
      include: {
        contextual_ids: [],
      },
      exclude: {
        contextual_ids: [],
      },
    },
  },
}
```

備註	