

Parada de Emergencia



Tipo de acción	Con retención
Material	Plástico
Color del pulsador	Verde
Dimensiones (ancho x alto x profundidad)	68 mm x 68 m x 80 mm
Peso	139 g

RP 065		Con botón pulsador tipo “golpe de puño”. Bloqueo automático. Desbloqueo por rotación del pulsador. Color: Rojo (R).
--------	---	---

Complementary

Operating position	Any position
Device mounting	Fixing hole - diameter: 22 mm
Fixing center	$\geq 30 \times 40$ mm (panel) - thickness: 1...5 mm
Fixing mode	Fixing nut: 2...2.4 N.m
Shape of signaling unit head	Round
Type of operator	turn to release
Reset	Turn to release
Operator profile	Red mushroom Ø 40 mm
Contacts type and composition	1 NC
Contact operation	Slow-break
Positive opening	With NC contact
Mechanical durability	100000 cycles
Connections - terminals	Screw clamp terminal, $\leq 2 \times 1.5$ mm ² Screw clamp terminal, $\leq 1 \times 2.5$ mm ² Screw clamp terminal, $\geq 1 \times 0.5$ mm ² Faston terminals, connection size: 6.3 mm
Tightening torque	0.8 N.m
Short-circuit protection	10 A gL fuse conforming to IEC 60269-1
[Ith] conventional free air thermal current	10 A
[Ui] rated insulation voltage	600 V conforming to IEC 60947-1

Main

Range of product	Harmony Easy XA2
Product or component type	Complete emergency switching off push-button
Device short name	XA2
Bezel material	Plastic
Mounting diameter	22 mm