

Document routing decides which extraction pipeline a file deserves.

A converter that ignores page geometry will interleave columns of text.

The probe reads the file header instead of trusting the extension.

Layout is measured per horizontal band, not from the page as a whole.

A scanned page carries no text layer and must be rendered as an image.

Structure is lost when a layout-aware reader is replaced by a naive one.

Magic bytes are authoritative because extensions are frequently wrong.

Every decision here is deterministic, offline, and free of model calls.

The gutter between columns is found by merging text intervals per band.

Superscripts, italics and headings survive a layout-aware conversion.

A single reference page must not outvote multi-column body pages.

The correct pipeline for a two-column paper is the layout-aware one.

界面残留会显著降低器件性能

环境稳定性决定工艺窗口宽窄

晶格匹配程度影响外延薄膜质量

水溶性牺牲层可在数分钟内溶解

工艺兼容性要求可原位生长薄膜

衬底可重复使用且物性不退化

远程外延依赖衬底表面的电荷分布

二维材料转移需要完整的界面接触

牺牲层厚度影响剥离后的表面粗糙度

化学腐蚀速率必须与薄膜厚度匹配

外延层与衬底之间保持共格界面

退火温度决定结晶质量与缺陷密度

大面积制备仍需解决均匀性问题

器件性能对界面缺陷非常敏感