



Database SQLite3 & FastAPI


DR. MOHAMMED AL-HUBAISHI

Introduction to SQLite3 and Python

- ▶ SQLite3 is a lightweight, disk-based database.
- ▶ Python provides built-in support for SQLite3.
- ▶ Ideal for small to medium-sized applications.


Setting Up the Environment

- ▶ Ensure Python and SQLite3 are installed.
- ▶ Install FastAPI using pip: **pip install fastapi**
- ▶ Install an ASGI server like uvicorn: **pip install uvicorn**



Understanding the Code Structure

- ▶ The code is structured into functions and API endpoints.
- ▶ Includes database setup, CRUD operations, and error handling.



The screenshot shows a database viewer interface. At the top, there are tabs for 'main.py' and 'students.db'. Below the tabs, the 'students.db' database is selected, and a list of tables is shown on the left: 'sqlite_sequence' and 'students'. The 'students' table is selected and highlighted. The main area displays the data from the 'students' table, which has 3 rows. The columns are 'id', 'name', and 'grade'. The data is as follows:

id	name	grade
1	Ali	44
2	Rim	33
3	mustafa	5

http://127.0.0.1:8000/docs

FastAPI 0.1.0 OAS 3.1
/openapi.json

```
SQLite3> fastapi dev .\main.py
```

default

GET /students/ Read Students

POST /students/ Create Student

PUT /students/{student_id} Update Student

DELETE /students/{student_id} Delete Student

FastAPI CLI - Development mode

Serving at: http://127.0.0.1:8000

API docs: http://127.0.0.1:8000/docs

Running in development mode, for production use:

fastapi run

<https://www.youtube.com/watch?v=gczCPjNyg9U>

<https://github.com/DrMohammedhbi/DBSqlite3/tree/main>

Updated codes files

- ▶ SQLite3 is a lightweight, disk-based database.
- ▶ Python provides built-in support for SQLite3.
- ▶ Ideal for small to medium-sized applications.

<https://youtu.be/mAe2xWO3MZw>

<https://github.com/DrMohammedhbi/FastapiSQL3Html.git>

Defining the Student Model

```
class Student(BaseModel):
```

```
    id: int
```

```
    name: str
```

```
    grade: int
```

- Uses Pydantic for data validation.

```
2  from fastapi import FastAPI
3  from pydantic import BaseModel
4  import sqlite3
5
6  app = FastAPI()
7
8  class Student(BaseModel):
9      id: int
10     name: str
11     grade: int
12
```

Database Connection

```
conn = sqlite3.connect('students.db')
```

```
cursor = conn.cursor()
```

- Establishes a connection to the SQLite3 database.

```
def setup_database():  
    try:  
        conn = sqlite3.connect('students.db') # Create a connection  
        cursor = conn.cursor() # Create a cursor  
        cursor.execute('''  
            CREATE TABLE IF NOT EXISTS students (  
                id INTEGER PRIMARY KEY AUTOINCREMENT,  
                name TEXT NOT NULL,  
                grade INTEGER  
            )  
        ''')  
        conn.commit() # Save changes  
    except sqlite3.Error as e: # Handle potential errors  
        print(e) # Print the error  
        return {"error": "Failed to fetch students"} # Return error message  
  
setup_database()
```


Creating the Database Table

```
cursor.execute("""  
CREATE TABLE IF NOT EXISTS students (  
    id INTEGER PRIMARY KEY AUTOINCREMENT,  
    name TEXT NOT NULL,  
    grade INTEGER  
    )""")
```

```
def setup_database():  
    try:  
        conn = sqlite3.connect('students.db') # Create a connection  
        cursor = conn.cursor() # Create a cursor  
        cursor.execute('''  
            CREATE TABLE IF NOT EXISTS students (  
                id INTEGER PRIMARY KEY AUTOINCREMENT,  
                name TEXT NOT NULL,  
                grade INTEGER  
            )  
        ''')  
        conn.commit() # Save changes  
    except sqlite3.Error as e: # Handle potential errors  
        print(e) # Print the error  
        return {"error": "Failed to fetch students"} # Return error message  
  
setup_database()
```

Error Handling in SQLite3

try:

Database operations

except sqlite3.Error as e:

print(e)

- Handles potential database errors.

```
def setup_database():  
    try:  
        conn = sqlite3.connect('students.db') # Create a connection  
        cursor = conn.cursor() # Create a cursor  
        cursor.execute('''  
            CREATE TABLE IF NOT EXISTS students (  
                id INTEGER PRIMARY KEY AUTOINCREMENT,  
                name TEXT NOT NULL,  
                grade INTEGER  
            )  
        ''')  
        conn.commit() # Save changes  
    except sqlite3.Error as e: # Handle potential errors  
        print(e) # Print the error  
        return {"error": "Failed to fetch students"} # Return error message  
  
setup_database()
```

Setting Up the Database Function

def `setup_database()`:

- ▶ # Connect and create table
- ▶ Ensures the database and table are ready for use.

```
def setup_database():  
    try:  
        conn = sqlite3.connect('students.db') # Create a connection  
        cursor = conn.cursor() # Create a cursor  
        cursor.execute('''  
            CREATE TABLE IF NOT EXISTS students (  
                id INTEGER PRIMARY KEY AUTOINCREMENT,  
                name TEXT NOT NULL,  
                grade INTEGER  
            )  
        ''')  
        conn.commit() # Save changes  
    except sqlite3.Error as e: # Handle potential errors  
        print(e) # Print the error  
        return {"error": "Failed to fetch students"} # Return error  
  
setup_database()
```

Reading Data from the Database

```
cursor.execute('SELECT * FROM students')
```

```
rows = cursor.fetchall()
```

- Fetches all student records from the database.

```
@app.get("/students/")
async def read_students():
    try:
        conn = sqlite3.connect('students.db') # Create a connection
        cursor = conn.cursor() # Create a cursor to interact with the database
        cursor.execute("SELECT * FROM students") # Execute the query
        rows = cursor.fetchall() # Fetch all results
        conn.close() # Close the database connection
        return rows # Return the data fetched from the database
    except sqlite3.Error as e: # Handle potential errors
        print(e) # Print the error
        return {"error": "Failed to fetch students"}
```

Creating a Student Record

```
cursor.execute('INSERT INTO students (name, grade) VALUES (?, ?)',  
(student.name, student.grade))
```

- Adds a new student record to the database.

```
@app.post("/students/")  
async def create_student(student: Student):  
    try:  
        conn = sqlite3.connect('students.db')  
        cursor = conn.cursor()  
        cursor.execute("INSERT INTO students (name, grade) VALUES (?, ?)", (student.name, student.grade))  
        conn.commit()  
        conn.close()  
        return {"message": "Student added successfully"}  
    except sqlite3.Error as e:  
        print(e)  
        return {"error": "Failed to create student"}
```

Updating Student Records

```
cursor.execute('UPDATE students SET name = ?, grade = ? WHERE id = ?',  
(student.name, student.grade, student_id))
```

- Updates existing student records.

```
@app.put("/students/{student_id}")  
async def update_student(student_id: int, student: Student):  
    try:  
        conn = sqlite3.connect('students.db') # Create a connection to the database  
        cursor = conn.cursor() # Create a cursor  
        cursor.execute("UPDATE students SET name = ?, grade = ? WHERE id = ?",  
                        (student.name, student.grade, student_id)) # SQL to update student data  
        conn.commit() # Save changes to the database  
        conn.close() # Close the connection  
        return {"id": student_id, **student.dict()} # Return the updated student data  
    except sqlite3.Error as e: # In case of an error  
        print(e) # Print the error  
        return {"error": "Failed to update student"} # Return an error message
```


Deleting Student Records

`cursor.execute('DELETE FROM students WHERE id = ?', (student_id,))`

- Removes a student record from the database.

```
@app.delete("/students/{student_id}")
async def delete_student(student_id: int):
    try:
        conn = sqlite3.connect('students.db') # Create a connection to the database
        cursor = conn.cursor() # Create a cursor
        cursor.execute("DELETE FROM students WHERE id = ?", (student_id,)) # Execute an SQL query
        conn.commit() # Save changes to the database
        conn.close() # Close the connection
        return {"message": "Student deleted"} # Return a confirmation message of deletion
    except sqlite3.Error as e: # In case of an error
        print(e) # Print the error
        return {"error": "Failed to delete student"} # Return an error message
```

Asynchronous Programming in FastAPI

- ▶ FastAPI supports async functions for non-blocking operations.
- ▶ Improves performance and scalability.

API Endpoints Overview

- ▶ GET /students/ - Fetch all students
- ▶ POST /students/ - Add a new student
- ▶ PUT /students/{id} - Update a student
- ▶ DELETE /students/{id} - Delete a student

GET Endpoint for Students

```
async def read_students():
```

- ▶ # Fetch and return all students
- ▶ Returns a list of all students in JSON format.

POST Endpoint for Creating Students

```
async def create_student(student: Student):
```

- ▶ `# Add a new student to the database`
- ▶ `Validates and adds a new student record.`

PUT Endpoint for Updating Students

```
async def update_student(student_id: int, student: Student):
```

- ▶ # Update student information
- ▶ Modifies existing student data based on ID.

DELETE Endpoint for Removing Students

```
async def delete_student(student_id: int):
```

- ▶ # Remove a student from the database
- ▶ Deletes a student record by ID.

Testing the API

<http://127.0.0.1:8000/docs>

FastAPI 0.1.0 OAS 3.1
[/openapi.json](#)

```
SQLite3> fastapi dev .\main.py
```

default

GET /students/ Read Students

POST /students/ Create Student

PUT /students/{student_id} Update Student

DELETE /students/{student_id} Delete Student

FastAPI CLI - Development mode

Serving at: <http://127.0.0.1:8000>

API docs: <http://127.0.0.1:8000/docs>

Running in development mode, for production use:

`fastapi run`

<https://www.youtube.com/watch?v=gczCPjNyg9U>

<https://github.com/DrMohammedhbi/DBSqlite3/tree/main>

Security Considerations

- ▶ Implement authentication and authorization.
- ▶ Sanitize inputs to prevent SQL injection.

Performance Optimization

- ▶ Use indexes to speed up queries.
- ▶ Optimize database schema and queries.

Conclusion and Further Learning

- ▶ SQLite3 and FastAPI provide a powerful combination for building APIs.
- ▶ Explore more advanced features and best practices.