

EN - For pricing and availability in your local country please visit one of the below links:

DE - Informationen zu Preisen und Verfügbarkeit in Ihrem Land erhalten Sie über die unten aufgeführten Links:

FR - Pour connaître les tarifs et la disponibilité dans votre pays, cliquez sur l'un des liens suivants:

[MV5754A](#)

EN

This Datasheet is presented by
the manufacturer

DE

Dieses Datenblatt wird vom
Hersteller bereitgestellt

FR

Cette fiche technique est
présentée par le fabricant

Standard LED




Red Emitting Colour

Features:

- High intensity
- Standard T-1 3/4 diameter package
- General purpose leads
- Reliable and rugged

Package Dimensions:



Specification Table

Chip Material	Lens Colour	Source Colour	Part Number
AlGaAs	Diffused	Red	MV5754A

Notes:

1. Tolerance is ± 0.25 mm (0.01") unless otherwise noted
2. Protruded resin under flange is 1 mm (0.04") maximum
3. Lead spacing is measured where the leads emerge from the package



Standard LED

Red Emitting Colour



Absolute Maximum Ratings at $T_a = 25^\circ\text{C}$

Parameter	Maximum	Unit
Power Dissipation	80	mW
Peak Forward Current (1/10 Duty Cycle, 0.1 ms Pulse Width)	100	mA
Continuous Forward Current	20	
Derating Linear From 50°C	0.4	mA / $^\circ\text{C}$
Reverse Voltage	5	V
Operating Temperature Range	-25°C to $+80^\circ\text{C}$	
Storage Temperature Range	-40°C to $+100^\circ\text{C}$	
Lead Soldering Temperature (4 mm (0.157) Inches from Body)	260 $^\circ\text{C}$ for 5 s	

Electrical Optical Characteristics at $T_a = 25^\circ\text{C}$

Parameter	Symbol	Minimum	Typical	Maximum	Unit	Test Condition
Luminous Intensity	I_v		40		mcd	$I_f = 20\text{ mA}$ (Note 1)
Viewing Angle	$2\theta_{1/2}$		25		Deg	(Note 2)
Peak Emission Wavelength	λ_p		640		nm	$I_f = 20\text{ mA}$
Dominant Wavelength	λ_d		635		nm	$I_f = 20\text{ mA}$ (Note 3)
Spectral Line Half-Width	$\Delta\lambda$		25		nm	$I_f = 20\text{ mA}$
Forward Voltage	V_f		2	2.5	V	$I_f = 20\text{ mA}$
Reverse Current	I_R	-	-	100	μA	$V_R = 5\text{ V}$

Notes:


1. Luminous intensity is measured with a light sensor and filter combination that approximates the CIE eye-response curve
2. $\theta_{1/2}$ is the off-axis angle at which the luminous intensity is half the axial luminous intensity
3. The dominant wavelength (λ_d) is derived from the CIE chromaticity diagram and represents the single wavelength which defines the colour of the device

Standard LED


Red Emitting Colour

Typical Characteristics


$I_F - V_F$ ($T_a = 25^\circ\text{C}$)




Relative Luminous Intensity - I_F ($T_a = 25^\circ\text{C}$)




Wavelength Characteristics ($T_a = 25^\circ\text{C}$)




Relative Luminous Intensity - T_a



$I_F - T_a$



Directive Characteristics ($T_a = 25^\circ\text{C}$)



Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp is the registered trademark of the Group. © Premier Farnell plc 2011.

EN - For pricing and availability in your local country please visit one of the below links:

DE - Informationen zu Preisen und Verfügbarkeit in Ihrem Land erhalten Sie über die unten aufgeführten Links:

FR - Pour connaître les tarifs et la disponibilité dans votre pays, cliquez sur l'un des liens suivants:

[MV5754A](#)

EN

This Datasheet is presented by
the manufacturer

DE

Dieses Datenblatt wird vom
Hersteller bereitgestellt

FR

Cette fiche technique est
présentée par le fabricant