

pentest exam

Report generated by Tenable Nessus™ Tue, 05 May 2026 15:11:57 IST

TABLE OF CONTENTS

Vulnerabilities by Host

- 10.10.10.101 4
- 10.10.10.102 104
- 10.10.10.109 150

Vulnerabilities by Host

10.10.10.101

CRITICAL	HIGH	MEDIUM	LOW	INFO
3	1	5	4	69

Scan Information

Start time: Tue May 5 14:52:58 2026
End time: Tue May 5 15:11:57 2026

Host Information

Netbios Name: METASPLOITABLE3-UB1404
IP: 10.10.10.101
MAC Address: 08:00:27:31:8E:8F
OS: Linux Kernel 3.13 on Ubuntu 14.04 (trusty)

Vulnerabilities

201408 - Canonical Ubuntu Linux SEoL (14.04.x)

Synopsis

An unsupported version of Canonical Ubuntu Linux is installed on the remote host.

Description

According to its version, Canonical Ubuntu Linux is 14.04.x. It is, therefore, no longer maintained by its vendor or provider.

Lack of support implies that no new security patches for the product will be released by the vendor. As a result, it may contain security vulnerabilities.

See Also

http://www.nessus.org/u?5afc4199

Solution

Upgrade to a version of Canonical Ubuntu Linux that is currently supported.

Risk Factor

Critical

CVSS v3.0 Base Score

10.0 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:C/C:H/I:H/A:H)

CVSS v2.0 Base Score

10.0 (CVSS2#AV:N/AC:L/Au:N/C:C/I:C/A:C)

Plugin Information

Published: 2024/07/03, Modified: 2025/03/26

Plugin Output

tcp/80/www

```
OS                                    : Ubuntu Linux 14.04
Security End of Life                  : April 25, 2019
Time since Security End of Life (Est.) : >= 7 years
```

92626 - Drupal Coder Module Deserialization RCE

Synopsis

A PHP application running on the remote web server is affected by a remote code execution vulnerability.

Description

The version of Drupal running on the remote web server is affected by a remote code execution vulnerability in the Coder module, specifically in file coder_upgrade.run.php, due to improper validation of user-supplied input to the unserialize() function. An unauthenticated, remote attacker can exploit this, via a specially crafted request, to execute arbitrary PHP code.

See Also

https://www.drupal.org/node/2765575

https://www.drupal.org/project/coder

Solution

Upgrade the Coder module to version 7.x-1.3 / 7.x-2.6 or later.

Alternatively, remove the entire Coder module directory from any publicly accessible website.

Risk Factor

Critical

CVSS v2.0 Base Score

10.0 (CVSS2#AV:N/AC:L/Au:N/C:C/I:C/A:C)

CVSS v2.0 Temporal Score

8.3 (CVSS2#E:F/RL:OF/RC:ND)

References

XREF EDB-ID:40149

Plugin Information

Published: 2016/07/29, Modified: 2022/04/11

Plugin Output

tcp/80/www

```
Nessus was able to exploit the issue using the following request :

http://10.10.10.101/drupal/sites/all/modules/coder/coder_upgrade/scripts/coder_upgrade.run.php


This produced the following truncated output (limited to 10 lines) :
------------------------------ snip ------------------------------
file parameter is not setNo path to parameter file

------------------------------ snip ------------------------------
```

84215 - ProFTPD mod_copy Information Disclosure

Synopsis

The remote host is running a ProFTPD module that is affected by an information disclosure vulnerability.

Description

The remote host is running a version of ProFTPD that is affected by an information disclosure vulnerability in the mod_copy module due to the SITE CPFR and SITE CPTO commands being available to unauthenticated clients. An unauthenticated, remote attacker can exploit this flaw to read and write to arbitrary files on any web accessible path on the host.

See Also

http://bugs.proftpd.org/show_bug.cgi?id=4169

Solution

Upgrade to ProFTPD 1.3.5a / 1.3.6rc1 or later.

Risk Factor

Critical

CVSS v3.0 Base Score

9.8 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H)

CVSS v3.0 Temporal Score

9.1 (CVSS:3.0/E:F/RL:O/RC:C)

VPR Score

7.4

EPSS Score

0.9368

CVSS v2.0 Base Score

10.0 (CVSS2#AV:N/AC:L/Au:N/C:C/I:C/A:C)

CVSS v2.0 Temporal Score

8.3 (CVSS2#E:F/RL:OF/RC:C)

References

BID	74238
CVE	CVE-2015-3306
XREF	EDB-ID:36742
XREF	EDB-ID:36803

Exploitable With

CANVAS (true) Metasploit (true)

Plugin Information

Published: 2015/06/16, Modified: 2024/01/16

Plugin Output

tcp/21/ftp

```
Nessus received a 350 response from sending the following unauthenticated request :

SITE CPFR /etc/passwd
```

78515 - Drupal Database Abstraction API SQLi

Synopsis

The remote web server is running a PHP application that is affected by a SQL injection vulnerability.

Description

The remote web server is running a version of Drupal that is affected by a SQL injection vulnerability due to a flaw in the Drupal database abstraction API, which allows a remote attacker to use specially crafted requests that can result in arbitrary SQL execution. This may lead to privilege escalation, arbitrary PHP execution, or remote code execution.

See Also

https://www.drupal.org/SA-CORE-2014-005

https://www.drupal.org/project/drupal/releases/7.32

Solution

Upgrade to version 7.32 or later.

Risk Factor

High

VPR Score

7.4

EPSS Score

0.9387

CVSS v2.0 Base Score

7.5 (CVSS2#AV:N/AC:L/Au:N/C:P/I:P/A:P)

CVSS v2.0 Temporal Score

6.2 (CVSS2#E:F/RL:OF/RC:C)

References

BID	70595
CVE	CVE-2014-3704
XREF	EDB-ID:34984
XREF	EDB-ID:34992

XREF EDB-ID:34993
XREF EDB-ID:35150

Exploitable With

CANVAS (true) Core Impact (true) (true) Metasploit (true)

Plugin Information

Published: 2014/10/16, Modified: 2022/04/11

Plugin Output

tcp/80/www

```
Nessus was able to exploit the issue using the following request :

POST /drupal/?q=node&destination=node HTTP/1.1
Host: 10.10.10.101
Accept-Charset: iso-8859-1,utf-8;q=0.9,*;q=0.1
Accept-Language: en
Content-Type: application/x-www-form-urlencoded
Connection: Keep-Alive
Content-Length: 117
Pragma: no-cache
User-Agent: Mozilla/4.0 (compatible; MSIE 8.0; Windows NT 5.1; Trident/4.0)
Accept: image/gif, image/x-xbitmap, image/jpeg, image/pjpeg, image/png, */*
name[0;SELECT
+@@version;#]=0;&name[0]=nessus&pass=nessus&test2=test&form_build_id=&form_id=user_login_block&op=Log
+in


This produced the following truncated output (limited to 5 lines) :
------------------------------ snip ------------------------------
>Warning</em>: mb_strlen() expects parameter 1 to be string, array given in <em
 class="placeholder">drupal_strlen()</em> (line <em class="placeholder">441</em> of <em
 class="placeholder">/var/www/html/drupal/includes/unicode.inc</em>).</li>
<li><em class="placeholder">Warning</em>: addcslashes() expects parameter 1 to be string,
 array given in <em class="placeholder">DatabaseConnection-&gt;escapeLike()</em> (line <em
 class="placeholder">965</em> of <em class="placeholder">/var/www/html/drupal/includes/database/
database.inc</em>).</li>
<li>Sorry, unrecognized username or password. <a href="/drupal/?q=user/password">Have you forgotten
 your password?</a></li>
</ul>
</div>
[...]

------------------------------ snip ------------------------------
```

10704 - Apache Multiviews Arbitrary Directory Listing

Synopsis

The remote web server is affected by an information disclosure vulnerability.

Description

The Apache web server running on the remote host is affected by an information disclosure vulnerability. An unauthenticated, remote attacker can exploit this, by sending a crafted request, to display a listing of a remote directory, even if a valid index file exists in the directory.

For Apache web server later than 1.3.22, review listing directory configuration to avoid disclosing sensitive information

See Also

http://www.nessus.org/u?f39e976b

http://www.nessus.org/u?a96611bc

http://www.nessus.org/u?c1c382bc

Solution

Upgrade to Apache version 1.3.22 or later. Alternatively, as a workaround, disable Multiviews.

Risk Factor

Medium

CVSS v3.0 Base Score

5.3 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:L/I:N/A:N)

CVSS v3.0 Temporal Score

4.8 (CVSS:3.0/E:P/RL:O/RC:C)

VPR Score

2.2

EPSS Score

0.8079

CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:P/I:N/A:N)

CVSS v2.0 Temporal Score

3.9 (CVSS2#E:POC/RL:OF/RC:C)

References

BID	3009
CVE	CVE-2001-0731
XREF	OWASP:OWASP-CM-004
XREF	EDB-ID:21002

Plugin Information

Published: 2016/02/16, Modified: 2020/10/21

Plugin Output

tcp/80/www

```
Nessus was able to exploit the issue using the following request :

http://10.10.10.101/?M=A


This produced the following truncated output (limited to 10 lines) :
------------------------------ snip ------------------------------
<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 3.2 Final//EN">
<html>
<head>
<title>Index of /</title>
</head>
<body>
<h1>Index of /</h1>
<table>
<tr><th valign="top"><img src="/icons/blank.gif" alt="[ICO]"></th><th><a href="?C=N;O=D">Name</a></
th><th><a href="?C=M;O=A">Last modified</a></th><th><a href="?C=S;O=A">Size</a></th><th><a href="?
C=D;O=A">Description</a></th></tr>
<tr><th colspan="5"><hr></th></tr>
[...]

------------------------------ snip ------------------------------
```

50686 - IP Forwarding Enabled

Synopsis

The remote host has IP forwarding enabled.

Description

The remote host has IP forwarding enabled. An attacker can exploit this to route packets through the host and potentially bypass some firewalls / routers / NAC filtering.

Unless the remote host is a router, it is recommended that you disable IP forwarding.

Solution

On Linux, you can disable IP forwarding by doing :

echo 0 > /proc/sys/net/ipv4/ip_forward

On Windows, set the key 'IPEnableRouter' to 0 under

HKEY_LOCAL_MACHINE\System\CurrentControlSet\Services\Tcpip\Parameters

On Mac OS X, you can disable IP forwarding by executing the command :

sysctl -w net.inet.ip.forwarding=0

For other systems, check with your vendor.

Risk Factor

Medium

CVSS v3.0 Base Score

6.5 (CVSS:3.0/AV:A/AC:L/PR:L/UI:N/S:C/C:L/I:L/A:L)

VPR Score

4.0

EPSS Score

0.0596

CVSS v2.0 Base Score

5.8 (CVSS2#AV:A/AC:L/Au:N/C:P/I:P/A:P)

References

CVE CVE-1999-0511

Plugin Information

Published: 2010/11/23, Modified: 2023/10/17

Plugin Output

tcp/0

```
IP forwarding appears to be enabled on the remote host.

 Detected local MAC Address        : 22f76697b803
 Response from local MAC Address   : 22f76697b803

 Detected Gateway MAC Address      : 080027318e8f
 Response from Gateway MAC Address : 080027318e8f
```

57608 - SMB Signing not required

Synopsis

Signing is not required on the remote SMB server.

Description

Signing is not required on the remote SMB server. An unauthenticated, remote attacker can exploit this to conduct man-in-the-middle attacks against the SMB server.

See Also

http://www.nessus.org/u?df39b8b3

http://technet.microsoft.com/en-us/library/cc731957.aspx

http://www.nessus.org/u?74b80723

https://www.samba.org/samba/docs/current/man-html/smb.conf.5.html

http://www.nessus.org/u?a3cac4ea

Solution

Enforce message signing in the host's configuration. On Windows, this is found in the policy setting 'Microsoft network server: Digitally sign communications (always)'. On Samba, the setting is called 'server signing'. See the 'see also' links for further details.

Risk Factor

Medium

CVSS v3.0 Base Score

5.3 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:N/I:L/A:N)

CVSS v3.0 Temporal Score

4.6 (CVSS:3.0/E:U/RL:O/RC:C)

CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:N/I:P/A:N)

CVSS v2.0 Temporal Score

3.7 (CVSS2#E:U/RL:OF/RC:C)

Plugin Information

Published: 2012/01/19, Modified: 2022/10/05

Plugin Output

tcp/445/cifs

187315 - SSH Terrapin Prefix Truncation Weakness (CVE-2023-48795)

Synopsis

The remote SSH server is vulnerable to a mitm prefix truncation attack.

Description

The remote SSH server is vulnerable to a man-in-the-middle prefix truncation weakness known as Terrapin. This can allow a remote, man-in-the-middle attacker to bypass integrity checks and downgrade the connection's security.

Note that this plugin only checks for remote SSH servers that support either ChaCha20-Poly1305 or CBC with Encrypt-then-MAC and do not support the strict key exchange countermeasures. It does not check for vulnerable software versions.

See Also

https://terrapin-attack.com/

Solution

Contact the vendor for an update with the strict key exchange countermeasures or disable the affected algorithms.

Risk Factor

Medium

CVSS v3.0 Base Score

5.9 (CVSS:3.0/AV:N/AC:H/PR:N/UI:N/S:U/C:N/I:H/A:N)

CVSS v3.0 Temporal Score

5.3 (CVSS:3.0/E:P/RL:O/RC:C)

VPR Score

6.1

EPSS Score

0.586

CVSS v2.0 Base Score

5.4 (CVSS2#AV:N/AC:H/Au:N/C:N/I:C/A:N)

CVSS v2.0 Temporal Score

4.2 (CVSS2#E:POC/RL:OF/RC:C)

References

CVE	CVE-2023-48795

Plugin Information

Published: 2023/12/27, Modified: 2026/01/12

Plugin Output

tcp/22/ssh

```
Supports following ChaCha20-Poly1305 Client to Server algorithm : aes128-ctr,aes192-
ctr,aes256-ctr,arcfour256,arcfour128,aes128-gcm@openssh.com,aes256-gcm@openssh.com,chacha20-
poly1305@openssh.com,aes128-cbc,3des-cbc,blowfish-cbc,cast128-cbc,aes192-cbc,aes256-
cbc,arcfour,rijndael-cbc@lysator.liu.se
Supports following CBC Client to Server algorithm              : aes128-ctr,aes192-
ctr,aes256-ctr,arcfour256,arcfour128,aes128-gcm@openssh.com,aes256-gcm@openssh.com,chacha20-
poly1305@openssh.com,aes128-cbc,3des-cbc,blowfish-cbc,cast128-cbc,aes192-cbc,aes256-
cbc,arcfour,rijndael-cbc@lysator.liu.se
Supports following Encrypt-then-MAC Client to Server algorithm  : hmac-md5-
etm@openssh.com,hmac-sha1-etm@openssh.com,umac-64-etm@openssh.com,umac-128-
etm@openssh.com,hmac-sha2-256-etm@openssh.com,hmac-sha2-512-etm@openssh.com,hmac-ripemd160-
etm@openssh.com,hmac-sha1-96-etm@openssh.com,hmac-md5-96-etm@openssh.com,hmac-md5,hmac-
sha1,umac-64@openssh.com,umac-128@openssh.com,hmac-sha2-256,hmac-sha2-512,hmac-ripemd160,hmac-
ripemd160@openssh.com,hmac-sha1-96,hmac-md5-96
Supports following ChaCha20-Poly1305 Server to Client algorithm : aes128-ctr,aes192-
ctr,aes256-ctr,arcfour256,arcfour128,aes128-gcm@openssh.com,aes256-gcm@openssh.com,chacha20-
poly1305@openssh.com,aes128-cbc,3des-cbc,blowfish-cbc,cast128-cbc,aes192-cbc,aes256-
cbc,arcfour,rijndael-cbc@lysator.liu.se
Supports following CBC Server to Client algorithm              : aes128-ctr,aes192-
ctr,aes256-ctr,arcfour256,arcfour128,aes128-gcm@openssh.com,aes256-gcm@openssh.com,chacha20-
poly1305@openssh.com,aes128-cbc,3des-cbc,blowfish-cbc,cast128-cbc,aes192-cbc,aes256-
cbc,arcfour,rijndael-cbc@lysator.liu.se
Supports following Encrypt-then-MAC Server to Client algorithm  : hmac-md5-
etm@openssh.com,hmac-sha1-etm@openssh.com,umac-64-etm@openssh.com,umac-128-
etm@openssh.com,hmac-sha2-256-etm@openssh.com,hmac-sha2-512-etm@openssh.com,hmac-ripemd160-
etm@openssh.com,hmac-sha1-96-etm@openssh.com,hmac-md5-96-etm@openssh.com,hmac-md5,hmac-
sha1,umac-64@openssh.com,umac-128@openssh.com,hmac-s [...]
```

90317 - SSH Weak Algorithms Supported

Synopsis

The remote SSH server is configured to allow weak encryption algorithms or no algorithm at all.

Description

Nessus has detected that the remote SSH server is configured to use the Arcfour stream cipher or no cipher at all. RFC 4253 advises against using Arcfour due to an issue with weak keys.

See Also

https://tools.ietf.org/html/rfc4253#section-6.3

Solution

Contact the vendor or consult product documentation to remove the weak ciphers.

Risk Factor

Medium

CVSS v2.0 Base Score

4.3 (CVSS2#AV:N/AC:M/Au:N/C:P/I:N/A:N)

Plugin Information

Published: 2016/04/04, Modified: 2026/01/12

Plugin Output

tcp/22/ssh

```
The following weak server-to-client encryption algorithms are supported :

  aes128-ctr,aes192-ctr,aes256-ctr,arcfour256,arcfour128,aes128-gcm@openssh.com,aes256-
gcm@openssh.com,chacha20-poly1305@openssh.com,aes128-cbc,3des-cbc,blowfish-cbc,cast128-cbc,aes192-
cbc,aes256-cbc,arcfour,rijndael-cbc@lysator.liu.se

The following weak client-to-server encryption algorithms are supported :

  aes128-ctr,aes192-ctr,aes256-ctr,arcfour256,arcfour128,aes128-gcm@openssh.com,aes256-
gcm@openssh.com,chacha20-poly1305@openssh.com,aes128-cbc,3des-cbc,blowfish-cbc,cast128-cbc,aes192-
cbc,aes256-cbc,arcfour,rijndael-cbc@lysator.liu.se
```

10114 - ICMP Timestamp Request Remote Date Disclosure

Synopsis

It is possible to determine the exact time set on the remote host.

Description

The remote host answers to an ICMP timestamp request. This allows an attacker to know the date that is set on the targeted machine, which may assist an unauthenticated, remote attacker in defeating time-based authentication protocols.

Timestamps returned from machines running Windows Vista / 7 / 2008 / 2008 R2 are deliberately incorrect, but usually within 1000 seconds of the actual system time.

Solution

Filter out the ICMP timestamp requests (13), and the outgoing ICMP timestamp replies (14).

Risk Factor

Low

VPR Score

2.2

EPSS Score

0.0037

CVSS v2.0 Base Score

2.1 (CVSS2#AV:L/AC:L/Au:N/C:P/I:N/A:N)

References

CVE	CVE-1999-0524
XREF	CWE:200

Plugin Information

Published: 1999/08/01, Modified: 2024/10/07

Plugin Output

icmp/0

```
The remote clock is synchronized with the local clock.
```

70658 - SSH Server CBC Mode Ciphers Enabled

Synopsis

The SSH server is configured to use Cipher Block Chaining.

Description

The SSH server is configured to support Cipher Block Chaining (CBC) encryption. This may allow an attacker to recover the plaintext message from the ciphertext.

Note that this plugin only checks for the options of the SSH server and does not check for vulnerable software versions.

Solution

Contact the vendor or consult product documentation to disable CBC mode cipher encryption, and enable CTR or GCM cipher mode encryption.

Risk Factor

Low

CVSS v3.0 Base Score

3.7 (CVSS:3.0/AV:N/AC:H/PR:N/UI:N/S:U/C:L/I:N/A:N)

VPR Score

1.4

EPSS Score

0.0307

CVSS v2.0 Base Score

2.6 (CVSS2#AV:N/AC:H/Au:N/C:P/I:N/A:N)

CVSS v2.0 Temporal Score

1.9 (CVSS2#E:U/RL:OF/RC:C)

References

BID	32319
CVE	CVE-2008-5161
XREF	CERT:958563
XREF	CWE:200

Plugin Information

Published: 2013/10/28, Modified: 2026/01/12

Plugin Output

tcp/22/ssh

```
The following client-to-server Cipher Block Chaining (CBC) algorithms
are supported :

  aes128-ctr,aes192-ctr,aes256-ctr,arcfour256,arcfour128,aes128-gcm@openssh.com,aes256-
gcm@openssh.com,chacha20-poly1305@openssh.com,aes128-cbc,3des-cbc,blowfish-cbc,cast128-cbc,aes192-
cbc,aes256-cbc,arcfour,rijndael-cbc@lysator.liu.se

The following server-to-client Cipher Block Chaining (CBC) algorithms
are supported :

  aes128-ctr,aes192-ctr,aes256-ctr,arcfour256,arcfour128,aes128-gcm@openssh.com,aes256-
gcm@openssh.com,chacha20-poly1305@openssh.com,aes128-cbc,3des-cbc,blowfish-cbc,cast128-cbc,aes192-
cbc,aes256-cbc,arcfour,rijndael-cbc@lysator.liu.se
```

153953 - SSH Weak Key Exchange Algorithms Enabled

Synopsis

The remote SSH server is configured to allow weak key exchange algorithms.

Description

The remote SSH server is configured to allow key exchange algorithms which are considered weak.

This is based on the IETF draft document Key Exchange (KEX) Method Updates and Recommendations for Secure Shell (SSH) RFC9142. Section 4 lists guidance on key exchange algorithms that SHOULD NOT and MUST NOT be enabled. This includes:

diffie-hellman-group-exchange-sha1

diffie-hellman-group1-sha1

gss-gex-sha1-*

gss-group1-sha1-*

gss-group14-sha1-*

rsa1024-sha1

Note that this plugin only checks for the options of the SSH server, and it does not check for vulnerable software versions.

See Also

https://datatracker.ietf.org/doc/html/rfc9142

Solution

Contact the vendor or consult product documentation to disable the weak algorithms.

Risk Factor

Low

CVSS v3.0 Base Score

3.7 (CVSS:3.0/AV:N/AC:H/PR:N/UI:N/S:U/C:L/I:N/A:N)

CVSS v2.0 Base Score

2.6 (CVSS2#AV:N/AC:H/Au:N/C:P/I:N/A:N)

Plugin Information

Published: 2021/10/13, Modified: 2026/01/12

Plugin Output

tcp/22/ssh

```
The following weak key exchange algorithms are enabled :

  curve25519-sha256@libssh.org,ecdh-sha2-nistp256,ecdh-sha2-nistp384,ecdh-sha2-nistp521,diffie-
hellman-group-exchange-sha256,diffie-hellman-group-exchange-sha1,diffie-hellman-group14-sha1,diffie-
hellman-group1-sha1
  curve25519-sha256@libssh.org,ecdh-sha2-nistp256,ecdh-sha2-nistp384,ecdh-sha2-nistp521,diffie-
hellman-group-exchange-sha256,diffie-hellman-group-exchange-sha1,diffie-hellman-group14-sha1,diffie-
hellman-group1-sha1
```

71049 - SSH Weak MAC Algorithms Enabled

Synopsis

The remote SSH server is configured to allow MD5 and 96-bit MAC algorithms.

Description

The remote SSH server is configured to allow either MD5 or 96-bit MAC algorithms, both of which are considered weak.

Note that this plugin only checks for the options of the SSH server, and it does not check for vulnerable software versions.

Solution

Contact the vendor or consult product documentation to disable MD5 and 96-bit MAC algorithms.

Risk Factor

Low

CVSS v2.0 Base Score

2.6 (CVSS2#AV:N/AC:H/Au:N/C:P/I:N/A:N)

Plugin Information

Published: 2013/11/22, Modified: 2026/01/12

Plugin Output

tcp/22/ssh

```
The following client-to-server Message Authentication Code (MAC) algorithms
are supported :

  hmac-md5-etm@openssh.com,hmac-sha1-etm@openssh.com,umac-64-etm@openssh.com,umac-128-
etm@openssh.com,hmac-sha2-256-etm@openssh.com,hmac-sha2-512-etm@openssh.com,hmac-ripemd160-
etm@openssh.com,hmac-sha1-96-etm@openssh.com,hmac-md5-96-etm@openssh.com,hmac-md5,hmac-
sha1,umac-64@openssh.com,umac-128@openssh.com,hmac-sha2-256,hmac-sha2-512,hmac-ripemd160,hmac-
ripemd160@openssh.com,hmac-sha1-96,hmac-md5-96

The following server-to-client Message Authentication Code (MAC) algorithms
are supported :

  hmac-md5-etm@openssh.com,hmac-sha1-etm@openssh.com,umac-64-etm@openssh.com,umac-128-
etm@openssh.com,hmac-sha2-256-etm@openssh.com,hmac-sha2-512-etm@openssh.com,hmac-ripemd160-
etm@openssh.com,hmac-sha1-96-etm@openssh.com,hmac-md5-96-etm@openssh.com,hmac-md5,hmac-
sha1,umac-64@openssh.com,umac-128@openssh.com,hmac-sha2-256,hmac-sha2-512,hmac-ripemd160,hmac-
ripemd160@openssh.com,hmac-sha1-96,hmac-md5-96
```

18261 - Apache Banner Linux Distribution Disclosure

Synopsis

The name of the Linux distribution running on the remote host was found in the banner of the web server.

Description

Nessus was able to extract the banner of the Apache web server and determine which Linux distribution the remote host is running.

Solution

If you do not wish to display this information, edit 'httpd.conf' and set the directive 'ServerTokens Prod' and restart Apache.

Risk Factor

None

Plugin Information

Published: 2005/05/15, Modified: 2025/03/31

Plugin Output

tcp/0

```
The Linux distribution detected was :
 - Ubuntu 14.04 (trusty)
```

48204 - Apache HTTP Server Version

Synopsis

It is possible to obtain the version number of the remote Apache HTTP server.

Description

The remote host is running the Apache HTTP Server, an open source web server. It was possible to read the version number from the banner.

See Also

https://httpd.apache.org/

Solution

n/a

Risk Factor

None

References

XREF	IAVT:0001-T-0030
XREF	IAVT:0001-T-0530

Plugin Information

Published: 2010/07/30, Modified: 2026/01/22

Plugin Output

tcp/80/www

```
URL        : http://10.10.10.101/
Version    : 2.4.7
Source     : Server: Apache/2.4.7 (Ubuntu)
backported : 1
os         : Ubuntu
```

39519 - Backported Security Patch Detection (FTP)

Synopsis

Security patches are backported.

Description

Security patches may have been 'backported' to the remote FTP server without changing its version number.

Banner-based checks have been disabled to avoid false positives.

Note that this test is informational only and does not denote any security problem.

See Also

https://access.redhat.com/security/updates/backporting/?sc_cid=3093

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2009/06/25, Modified: 2026/01/22

Plugin Output

tcp/21/ftp

```
Give Nessus credentials to perform local checks.
```

39520 - Backported Security Patch Detection (SSH)

Synopsis

Security patches are backported.

Description

Security patches may have been 'backported' to the remote SSH server without changing its version number.

Banner-based checks have been disabled to avoid false positives.

Note that this test is informational only and does not denote any security problem.

See Also

https://access.redhat.com/security/updates/backporting/?sc_cid=3093

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2009/06/25, Modified: 2026/01/22

Plugin Output

tcp/22/ssh

```
Give Nessus credentials to perform local checks.
```

39521 - Backported Security Patch Detection (WWW)

Synopsis

Security patches are backported.

Description

Security patches may have been 'backported' to the remote HTTP server without changing its version number.

Banner-based checks have been disabled to avoid false positives.

Note that this test is informational only and does not denote any security problem.

See Also

https://access.redhat.com/security/updates/backporting/?sc_cid=3093

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2009/06/25, Modified: 2026/01/22

Plugin Output

tcp/80/www

```
Give Nessus credentials to perform local checks.
```

45590 - Common Platform Enumeration (CPE)

Synopsis

It was possible to enumerate CPE names that matched on the remote system.

Description

By using information obtained from a Nessus scan, this plugin reports CPE (Common Platform Enumeration) matches for various hardware and software products found on a host.

Note that if an official CPE is not available for the product, this plugin computes the best possible CPE based on the information available from the scan.

See Also

http://cpe.mitre.org/

https://nvd.nist.gov/products/cpe

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2010/04/21, Modified: 2026/01/05

Plugin Output

tcp/0

```
Following application CPE's matched on the remote system :

  cpe:/a:apache:http_server:2.4.7 -> Apache Software Foundation Apache HTTP Server
  cpe:/a:drupal:drupal:7.5 -> Drupal
  cpe:/a:eclipse:jetty:8.1.7 -> Eclipse Jetty
  cpe:/a:mysql:mysql -> MySQL MySQL
  cpe:/a:openbsd:openssh:6.6 -> OpenBSD OpenSSH
  cpe:/a:openbsd:openssh:6.6.1p1 -> OpenBSD OpenSSH
  cpe:/a:samba:samba -> Samba Samba
  cpe:/a:samba:samba:4.3.11 -> Samba Samba
```

54615 - Device Type

Synopsis

It is possible to guess the remote device type.

Description

Based on the remote operating system, it is possible to determine what the remote system type is (eg: a printer, router, general-purpose computer, etc).

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2011/05/23, Modified: 2025/03/12

Plugin Output

tcp/0

```
Remote device type : general-purpose
Confidence level : 95
```

18638 - Drupal Software Detection

Synopsis

A content management system is running on the remote web server.

Description

Drupal, an open source content management system written in PHP, is running on the remote web server.

See Also

https://www.drupal.org/

Solution

Ensure that the use of this software aligns with your organization's security and acceptable use policies.

Risk Factor

None

References

XREF	IAVT:0001-T-0586

Plugin Information

Published: 2005/07/07, Modified: 2023/05/24

Plugin Output

tcp/80/www

```
URL     : http://10.10.10.101/drupal
Version : 7.5
```

194915 - Eclipse Jetty Web Server Detection

Synopsis

The Eclipse Jetty web server was detected on the remote host.

Description

The Eclipse Jetty web server was detected on the remote host.

See Also

https://eclipse.dev/jetty/

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2024/05/02, Modified: 2026/03/23

Plugin Output

tcp/0

```
URL     : http://10.10.10.101:8080/
Version : 8.1.7
Source  : Server: Jetty(8.1.7.v20120910)
```

35716 - Ethernet Card Manufacturer Detection

Synopsis

The manufacturer can be identified from the Ethernet OUI.

Description

Each ethernet MAC address starts with a 24-bit Organizationally Unique Identifier (OUI). These OUIs are registered by IEEE.

See Also

https://standards.ieee.org/faqs/regauth.html

http://www.nessus.org/u?794673b4

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2009/02/19, Modified: 2020/05/13

Plugin Output

tcp/0

```
The following card manufacturers were identified :

08:00:27:31:8E:8F : PCS Systemtechnik GmbH
```

86420 - Ethernet MAC Addresses

Synopsis

This plugin gathers MAC addresses from various sources and consolidates them into a list.

Description

This plugin gathers MAC addresses discovered from both remote probing of the host (e.g. SNMP and Netbios) and from running local checks (e.g. ifconfig). It then consolidates the MAC addresses into a single, unique, and uniform list.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2015/10/16, Modified: 2025/06/10

Plugin Output

tcp/0

```
The following is a consolidated list of detected MAC addresses:
  - 08:00:27:31:8E:8F
```

10092 - FTP Server Detection

Synopsis

An FTP server is listening on a remote port.

Description

It is possible to obtain the banner of the remote FTP server by connecting to a remote port.

Solution

n/a

Risk Factor

None

References

XREF	IAVT:0001-T-0030
XREF	IAVT:0001-T-0943

Plugin Information

Published: 1999/10/12, Modified: 2023/08/17

Plugin Output

tcp/21/ftp

```
The remote FTP banner is :

220 ProFTPD 1.3.5 Server (ProFTPD Default Installation) [10.10.10.101]
```

43111 - HTTP Methods Allowed (per directory)

Synopsis

This plugin determines which HTTP methods are allowed on various CGI directories.

Description

By calling the OPTIONS method, it is possible to determine which HTTP methods are allowed on each directory.

The following HTTP methods are considered insecure:

PUT, DELETE, CONNECT, TRACE, HEAD

Many frameworks and languages treat 'HEAD' as a 'GET' request, albeit one without any body in the response. If a security constraint was set on 'GET' requests such that only 'authenticatedUsers' could access GET requests for a particular servlet or resource, it would be bypassed for the 'HEAD' version. This allowed unauthorized blind submission of any privileged GET request.

As this list may be incomplete, the plugin also tests - if 'Thorough tests' are enabled or 'Enable web applications tests' is set to 'yes'

in the scan policy - various known HTTP methods on each directory and considers them as unsupported if it receives a response code of 400, 403, 405, or 501.

Note that the plugin output is only informational and does not necessarily indicate the presence of any security vulnerabilities.

See Also

http://www.nessus.org/u?d9c03a9a

http://www.nessus.org/u?b019cbdb

https://www.owasp.org/index.php/Test_HTTP_Methods_(OTG-CONFIG-006)

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2009/12/10, Modified: 2022/04/11

Plugin Output

tcp/80/www

```
Based on the response to an OPTIONS request :

  - HTTP methods GET HEAD OPTIONS POST are allowed on :

    /
```

10107 - HTTP Server Type and Version

Synopsis

A web server is running on the remote host.

Description

This plugin attempts to determine the type and the version of the remote web server.

Solution

n/a

Risk Factor

None

References

XREF IAVT:0001-T-0931

Plugin Information

Published: 2000/01/04, Modified: 2020/10/30

Plugin Output

tcp/80/www

```
The remote web server type is :

Apache/2.4.7 (Ubuntu)
```

10107 - HTTP Server Type and Version

Synopsis

A web server is running on the remote host.

Description

This plugin attempts to determine the type and the version of the remote web server.

Solution

n/a

Risk Factor

None

References

XREF IAVT:0001-T-0931

Plugin Information

Published: 2000/01/04, Modified: 2020/10/30

Plugin Output

tcp/3500/www

```
The remote web server type is :

WEBrick/1.3.1 (Ruby/2.3.8/2018-10-18)
```

10107 - HTTP Server Type and Version

Synopsis

A web server is running on the remote host.

Description

This plugin attempts to determine the type and the version of the remote web server.

Solution

n/a

Risk Factor

None

References

XREF IAVT:0001-T-0931

Plugin Information

Published: 2000/01/04, Modified: 2020/10/30

Plugin Output

tcp/8080/www

```
The remote web server type is :

Jetty(8.1.7.v20120910)
```

24260 - HyperText Transfer Protocol (HTTP) Information

Synopsis

Some information about the remote HTTP configuration can be extracted.

Description

This test gives some information about the remote HTTP protocol - the version used, whether HTTP Keep-Alive is enabled, etc...

This test is informational only and does not denote any security problem.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/01/30, Modified: 2024/02/26

Plugin Output

tcp/80/www

```
Response Code : HTTP/1.1 200 OK

Protocol version : HTTP/1.1
HTTP/2 TLS Support: No
HTTP/2 Cleartext Support: No
SSL : no
Keep-Alive : yes
Options allowed : (Not implemented)
Headers :

  Date: Tue, 05 May 2026 13:57:11 GMT
  Server: Apache/2.4.7 (Ubuntu)
  Vary: Accept-Encoding
  Content-Length: 1350
  Keep-Alive: timeout=5, max=98
  Connection: Keep-Alive
  Content-Type: text/html;charset=UTF-8

Response Body :

<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 3.2 Final//EN">
<html>
 <head>
  <title>Index of /</title>
 </head>
 <body>
<h1>Index of /</h1>
```

```
  <table>
   <tr><th valign="top"><img src="/icons/blank.gif" alt="[ICO]"></th><th><a href="?C=N;O=D">Name</
a></th><th><a href="?C=M;O=A">Last modified</a></th><th><a href="?C=S;O=A">Size</a></th><th><a
 href="?C=D;O=A">Description</a></th></tr>
   <tr><th colspan="5"><hr></th></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="chat/">chat/</a></
td><td align="right">2020-10-29 19:37  </td><td align="right">  - </td><td> </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="drupal/">drupal/</
a></td><td align="right">2011-07-27 20:17  </td><td align="right">  - </td><td> </td></tr>
<tr><td valign="top"><img src="/icons/unknown.gif" alt="[   ]"></td><td><a
 href="payroll_app.php">payroll_app.php</a></td><td align="right">2020-10-29 19:37  </td><td
 align="right">1.7K</td><td> </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a
 href="phpmyadmin/">phpmyadmin/</a></td><td align="right">2013-04-08 12:06  </td><td align="right">
 - </td><td> </td></tr>
   <tr><th colspan="5"><hr></th></tr>
</table>
<address>Apache/2.4.7 (Ubuntu) Server at 10.10.10.101 Port 80</address>
</body></html>
```

24260 - HyperText Transfer Protocol (HTTP) Information

Synopsis

Some information about the remote HTTP configuration can be extracted.

Description

This test gives some information about the remote HTTP protocol - the version used, whether HTTP Keep-Alive is enabled, etc...

This test is informational only and does not denote any security problem.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/01/30, Modified: 2024/02/26

Plugin Output

tcp/3500/www

```
Response Code : HTTP/1.1 200 OK

Protocol version : HTTP/1.1
HTTP/2 TLS Support: No
HTTP/2 Cleartext Support: No
SSL : no
Keep-Alive : yes
Options allowed : GET,HEAD,POST,OPTIONS
Headers :

  X-Frame-Options: SAMEORIGIN
  X-Xss-Protection: 1; mode=block
  X-Content-Type-Options: nosniff
  Content-Type: text/html; charset=utf-8
  Etag: W/"b56dd5f9363ed0f7bd4d11c36d9471dd"
  Cache-Control: max-age=0, private, must-revalidate
  X-Request-Id: 8efe4f2b-ff35-4f58-9bb2-9b66ecd59862
  X-Runtime: 0.004520
  Server: WEBrick/1.3.1 (Ruby/2.3.8/2018-10-18)
  Date: Tue, 05 May 2026 13:57:11 GMT
  Content-Length: 14935
  Connection: Keep-Alive

Response Body :

<!DOCTYPE html>
<html>
```

```
  <head>
    <title>Ruby on Rails: Welcome aboard</title>
    <style media="screen">
      body {
        margin: 0;
        margin-bottom: 25px;
        padding: 0;
        background-color: #f0f0f0;
        font-family: "Lucida Grande", "Bitstream Vera Sans", "Verdana";
        font-size: 13px;
        color: #333;
      }

      h1 {
        font-size: 28px;
        color: #000;
      }

      a  {color: #03c}

      a:hover {
        background-color: #03c;
        color: white;
        text-decoration: none;
      }

      #page {
        background-color: #f0f0f0;
        width: 750px;
        margin: 0;
        margin-left: auto;
        margin-right: auto;
      }

      #content {
        float: left;
        background-color: white;
        border: 3px solid #aaa;
        border-top: none;
        padding: 25px;
        width: 500px;
      }

      #sidebar {
        float: right;
        width: 175px;
      }

      #footer {
        clear: both;
      }

      #header, #about, #getting-started {
        padding-left: 75px;
        padding-right: 30px;
      }

      #header {
        background-image: url(
t5Sr9aurl6qO013Z9/DEoJh18gZQGAUxPHIyQHH7eioZ8bjnAFHZ0RndNxxRBhGcUbxoKIHBkTEcUYREIHIGpKQjUDS6 [...]
```

24260 - HyperText Transfer Protocol (HTTP) Information

Synopsis

Some information about the remote HTTP configuration can be extracted.

Description

This test gives some information about the remote HTTP protocol - the version used, whether HTTP Keep-Alive is enabled, etc...

This test is informational only and does not denote any security problem.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/01/30, Modified: 2024/02/26

Plugin Output

tcp/8080/www

```
Response Code : HTTP/1.1 404 Not Found

Protocol version : HTTP/1.1
HTTP/2 TLS Support: No
HTTP/2 Cleartext Support: No
SSL : no
Keep-Alive : no
Options allowed : (Not implemented)
Headers :

  Date: Tue, 05 May 2026 13:57:11 GMT
  Content-Type: text/html
  Content-Length: 795
  Server: Jetty(8.1.7.v20120910)

Response Body :
```

42410 - Microsoft Windows NTLMSSP Authentication Request Remote Network Name Disclosure

Synopsis

It is possible to obtain the network name of the remote host.

Description

The remote host listens on tcp port 445 and replies to SMB requests.

By sending an NTLMSSP authentication request it is possible to obtain the name of the remote system and the name of its domain.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2009/11/06, Modified: 2019/11/22

Plugin Output

tcp/445/cifs

```
The following 2 NetBIOS names have been gathered :

 METASPLOITABLE3-UB1404 = Computer name
 METASPLOITABLE3-UB1404 = Workgroup / Domain name
```

17651 - Microsoft Windows SMB : Obtains the Password Policy

Synopsis

It is possible to retrieve the remote host's password policy using the supplied credentials.

Description

Using the supplied credentials it was possible to extract the password policy for the remote Windows host. The password policy must conform to the Informational System Policy.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2005/03/30, Modified: 2015/01/12

Plugin Output

tcp/445/cifs

```
The following password policy is defined on the remote host:

Minimum password len: 5
Password history len: 0
Maximum password age (d): No limit
Password must meet complexity requirements: Disabled
Minimum password age (d): 0
Forced logoff time (s): Not set
Locked account time (s): 1800
Time between failed logon (s): 1800
Number of invalid logon before locked out (s): 0
```

10859 - Microsoft Windows SMB LsaQueryInformationPolicy Function SID Enumeration

Synopsis

It is possible to obtain the host SID for the remote host.

Description

By emulating the call to LsaQueryInformationPolicy(), it was possible to obtain the host SID (Security Identifier).

The host SID can then be used to get the list of local users.

See Also

http://technet.microsoft.com/en-us/library/bb418944.aspx

Solution

You can prevent anonymous lookups of the host SID by setting the 'RestrictAnonymous' registry setting to an appropriate value.

Refer to the 'See also' section for guidance.

Risk Factor

None

Plugin Information

Published: 2002/02/13, Modified: 2024/01/31

Plugin Output

tcp/445/cifs

```
The remote host SID value is : S-1-5-21-2892692244-97591703-1708969968

The value of 'RestrictAnonymous' setting is : unknown
```

10785 - Microsoft Windows SMB NativeLanManager Remote System Information Disclosure

Synopsis

It was possible to obtain information about the remote operating system.

Description

Nessus was able to obtain the remote operating system name and version (Windows and/or Samba) by sending an authentication request to port 139 or 445. Note that this plugin requires SMB to be enabled on the host.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2001/10/17, Modified: 2021/09/20

Plugin Output

tcp/445/cifs

```
The remote Operating System is : Windows 6.1
The remote native LAN manager is : Samba 4.3.11-Ubuntu
The remote SMB Domain Name is : METASPLOITABLE3-UB1404
```

11011 - Microsoft Windows SMB Service Detection

Synopsis

A file / print sharing service is listening on the remote host.

Description

The remote service understands the CIFS (Common Internet File System) or Server Message Block (SMB) protocol, used to provide shared access to files, printers, etc between nodes on a network.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2002/06/05, Modified: 2021/02/11

Plugin Output

tcp/445/cifs

```
A CIFS server is running on this port.
```

60119 - Microsoft Windows SMB Share Permissions Enumeration

Synopsis

It was possible to enumerate the permissions of remote network shares.

Description

By using the supplied credentials, Nessus was able to enumerate the permissions of network shares. User permissions are enumerated for each network share that has a list of access control entries (ACEs).

See Also

https://technet.microsoft.com/en-us/library/bb456988.aspx

https://technet.microsoft.com/en-us/library/cc783530.aspx

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2012/07/25, Modified: 2022/08/11

Plugin Output

tcp/445/cifs

```
Share path : \\METASPLOITABLE3-UB1404\print$
Local path : C:\var\lib\samba\printers
Comment : Printer Drivers
[*] Allow ACE for Everyone (S-1-1-0): 0x001f01ff
    FILE_GENERIC_READ:         YES
    FILE_GENERIC_WRITE:        YES
    FILE_GENERIC_EXECUTE:      YES

Share path : \\METASPLOITABLE3-UB1404\public
Local path : C:\var\www\html\
Comment : WWW
[*] Allow ACE for Everyone (S-1-1-0): 0x001f01ff
    FILE_GENERIC_READ:         YES
    FILE_GENERIC_WRITE:        YES
    FILE_GENERIC_EXECUTE:      YES

Share path : \\METASPLOITABLE3-UB1404\IPC$
Local path : C:\tmp
Comment : IPC Service (metasploitable3-ub1404 server (Samba, Ubuntu))
[*] Allow ACE for Everyone (S-1-1-0): 0x001f01ff
    FILE_GENERIC_READ:         YES
```

```
    FILE_GENERIC_WRITE:         YES
    FILE_GENERIC_EXECUTE:       YES
```

10395 - Microsoft Windows SMB Shares Enumeration

Synopsis

It is possible to enumerate remote network shares.

Description

By connecting to the remote host, Nessus was able to enumerate the network share names.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2000/05/09, Modified: 2022/02/01

Plugin Output

tcp/445/cifs

```
Here are the SMB shares available on the remote host :

  - print$
  - public
  - IPC$
```

100871 - Microsoft Windows SMB Versions Supported (remote check)

Synopsis

It was possible to obtain information about the version of SMB running on the remote host.

Description

Nessus was able to obtain the version of SMB running on the remote host by sending an authentication request to port 139 or 445.

Note that this plugin is a remote check and does not work on agents.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2017/06/19, Modified: 2019/11/22

Plugin Output

tcp/445/cifs

```
The remote host supports the following versions of SMB :
  SMBv1
  SMBv2
```

106716 - Microsoft Windows SMB2 and SMB3 Dialects Supported (remote check)

Synopsis

It was possible to obtain information about the dialects of SMB2 and SMB3 available on the remote host.

Description

Nessus was able to obtain the set of SMB2 and SMB3 dialects running on the remote host by sending an authentication request to port 139 or 445.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2018/02/09, Modified: 2020/03/11

Plugin Output

tcp/445/cifs

```
The remote host supports the following SMB dialects :
_version_  _introduced in windows version_
2.0.2      Windows 2008
2.1        Windows 7
2.2.2      Windows 8 Beta
2.2.4      Windows 8 Beta
3.0        Windows 8
3.0.2      Windows 8.1
3.1        Windows 10
3.1.1      Windows 10
```

10719 - MySQL Server Detection

Synopsis

A database server is listening on the remote port.

Description

The remote host is running MySQL, an open source database server.

Solution

n/a

Risk Factor

None

References

XREF IAVT:0001-T-0802

Plugin Information

Published: 2001/08/13, Modified: 2025/09/24

Plugin Output

tcp/3306/mysql

```
Service : mysql
Version : unknown
```

tcp/3306/mysql

```
The remote database access is restricted and configured to reject access
from unauthorized IPs.  Therefore it was not possible to extract its
version number.
```

11219 - Nessus SYN scanner

Synopsis

It is possible to determine which TCP ports are open.

Description

This plugin is a SYN 'half-open' port scanner. It shall be reasonably quick even against a firewalled target.

Note that SYN scans are less intrusive than TCP (full connect) scans against broken services, but they might cause problems for less robust firewalls and also leave unclosed connections on the remote target, if the network is loaded.

Solution

Protect your target with an IP filter.

Risk Factor

None

Plugin Information

Published: 2009/02/04, Modified: 2025/07/14

Plugin Output

tcp/21/ftp

```
Port 21/tcp was found to be open
```

11219 - Nessus SYN scanner

Synopsis

It is possible to determine which TCP ports are open.

Description

This plugin is a SYN 'half-open' port scanner. It shall be reasonably quick even against a firewalled target.

Note that SYN scans are less intrusive than TCP (full connect) scans against broken services, but they might cause problems for less robust firewalls and also leave unclosed connections on the remote target, if the network is loaded.

Solution

Protect your target with an IP filter.

Risk Factor

None

Plugin Information

Published: 2009/02/04, Modified: 2025/07/14

Plugin Output

tcp/22/ssh

```
Port 22/tcp was found to be open
```

11219 - Nessus SYN scanner

Synopsis

It is possible to determine which TCP ports are open.

Description

This plugin is a SYN 'half-open' port scanner. It shall be reasonably quick even against a firewalled target.

Note that SYN scans are less intrusive than TCP (full connect) scans against broken services, but they might cause problems for less robust firewalls and also leave unclosed connections on the remote target, if the network is loaded.

Solution

Protect your target with an IP filter.

Risk Factor

None

Plugin Information

Published: 2009/02/04, Modified: 2025/07/14

Plugin Output

tcp/80/www

```
Port 80/tcp was found to be open
```

11219 - Nessus SYN scanner

Synopsis

It is possible to determine which TCP ports are open.

Description

This plugin is a SYN 'half-open' port scanner. It shall be reasonably quick even against a firewalled target.

Note that SYN scans are less intrusive than TCP (full connect) scans against broken services, but they might cause problems for less robust firewalls and also leave unclosed connections on the remote target, if the network is loaded.

Solution

Protect your target with an IP filter.

Risk Factor

None

Plugin Information

Published: 2009/02/04, Modified: 2025/07/14

Plugin Output

tcp/445/cifs

```
Port 445/tcp was found to be open
```

11219 - Nessus SYN scanner

Synopsis

It is possible to determine which TCP ports are open.

Description

This plugin is a SYN 'half-open' port scanner. It shall be reasonably quick even against a firewalled target.

Note that SYN scans are less intrusive than TCP (full connect) scans against broken services, but they might cause problems for less robust firewalls and also leave unclosed connections on the remote target, if the network is loaded.

Solution

Protect your target with an IP filter.

Risk Factor

None

Plugin Information

Published: 2009/02/04, Modified: 2025/07/14

Plugin Output

tcp/3306/mysql

```
Port 3306/tcp was found to be open
```

11219 - Nessus SYN scanner

Synopsis

It is possible to determine which TCP ports are open.

Description

This plugin is a SYN 'half-open' port scanner. It shall be reasonably quick even against a firewalled target.

Note that SYN scans are less intrusive than TCP (full connect) scans against broken services, but they might cause problems for less robust firewalls and also leave unclosed connections on the remote target, if the network is loaded.

Solution

Protect your target with an IP filter.

Risk Factor

None

Plugin Information

Published: 2009/02/04, Modified: 2025/07/14

Plugin Output

tcp/3500/www

```
Port 3500/tcp was found to be open
```

11219 - Nessus SYN scanner

Synopsis

It is possible to determine which TCP ports are open.

Description

This plugin is a SYN 'half-open' port scanner. It shall be reasonably quick even against a firewalled target.

Note that SYN scans are less intrusive than TCP (full connect) scans against broken services, but they might cause problems for less robust firewalls and also leave unclosed connections on the remote target, if the network is loaded.

Solution

Protect your target with an IP filter.

Risk Factor

None

Plugin Information

Published: 2009/02/04, Modified: 2025/07/14

Plugin Output

tcp/6697/irc

```
Port 6697/tcp was found to be open
```

11219 - Nessus SYN scanner

Synopsis

It is possible to determine which TCP ports are open.

Description

This plugin is a SYN 'half-open' port scanner. It shall be reasonably quick even against a firewalled target.

Note that SYN scans are less intrusive than TCP (full connect) scans against broken services, but they might cause problems for less robust firewalls and also leave unclosed connections on the remote target, if the network is loaded.

Solution

Protect your target with an IP filter.

Risk Factor

None

Plugin Information

Published: 2009/02/04, Modified: 2025/07/14

Plugin Output

tcp/8080/www

```
Port 8080/tcp was found to be open
```

19506 - Nessus Scan Information

Synopsis

This plugin displays information about the Nessus scan.

Description

This plugin displays, for each tested host, information about the scan itself :

- The version of the plugin set.
- The type of scanner (Nessus or Nessus Home).
- The version of the Nessus Engine.
- The port scanner(s) used.
- The port range scanned.
- The ping round trip time
- Whether credentialed or third-party patch management checks are possible.
- Whether the display of superseded patches is enabled
- The date of the scan.
- The duration of the scan.
- The number of hosts scanned in parallel.
- The number of checks done in parallel.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2005/08/26, Modified: 2026/03/04

Plugin Output

tcp/0

```
Information about this scan :

Nessus version : 10.12.0
Nessus build : 20184
Plugin feed version : 202605050546
Scanner edition used : Nessus
Scanner OS : LINUX
Scanner distribution : ubuntu1804-aarch64
Scan type : Normal
Scan name : pentest exam
```

```
Scan policy used : Basic Network Scan
Scanner IP : 10.10.10.174
Port scanner(s) : nessus_syn_scanner
Port range : 1-65535
Ping RTT : 126.314 ms
Thorough tests : no
Experimental tests : no
Scan for Unpatched Vulnerabilities : no
Plugin debugging enabled : no
Paranoia level : 1
Report verbosity : 1
Safe checks : yes
Optimize the test : yes
Credentialed checks : no
Patch management checks : None
Display superseded patches : yes (supersedence plugin did not launch)
CGI scanning : disabled
Web application tests : disabled
Max hosts : 30
Max checks : 4
Recv timeout : 5
Backports : Detected
Allow post-scan editing : Yes
Nessus Plugin Signature Checking : Enabled
Audit File Signature Checking : Disabled
Scan Start Date : 2026/5/5 14:53 IST (UTC +01:00)
Scan duration : 1130 sec
Scan for malware : no
Fully Scan Operational Technology devices : yes
Safely Scan Operational Technology devices with OT Discovery : no
```

209654 - OS Fingerprints Detected

Synopsis

Multiple OS fingerprints were detected.

Description

Using a combination of remote probes (TCP/IP, SMB, HTTP, NTP, SNMP, etc), it was possible to gather one or more fingerprints from the remote system. While the highest-confidence result was reported in plugin 11936, “OS Identification”, the complete set of fingerprints detected are reported here.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2025/02/26, Modified: 2025/03/03

Plugin Output

tcp/0

```
Following OS Fingerprints were found

Remote operating system : F5 Networks BIG-IP
Confidence level : 56
Method : MLSinFP
Type : unknown
Fingerprint : unknown

Remote operating system : Linux Kernel 3.13 on Ubuntu 14.04 (trusty)
Confidence level : 95
Method : SSH
Type : general-purpose
Fingerprint : SSH:SSH-2.0-OpenSSH_6.6.1p1 Ubuntu-2ubuntu2.13

Remote operating system : Linux Kernel 3.13 on Ubuntu 14.04 (trusty)
Confidence level : 95
Method : HTTP
Type : general-purpose
Fingerprint : unknown

Remote operating system : Linux
Confidence level : 59
Method : SinFP
Type : general-purpose
Fingerprint : SinFP:
   P1:B10113:F0x12:W29200:O0204ffff:M1460:
   P2:B10113:F0x12:W28960:O0204ffff0402080affffffff4445414401030307:M1460:
   P3:B00000:F0x00:W0:O0:M0
```

```
    P4:191800_7_p=22
```

11936 - OS Identification

Synopsis

It is possible to guess the remote operating system.

Description

Using a combination of remote probes (e.g., TCP/IP, SMB, HTTP, NTP, SNMP, etc.), it is possible to guess the name of the remote operating system in use. It is also possible sometimes to guess the version of the operating system.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2003/12/09, Modified: 2025/06/03

Plugin Output

tcp/0

```
Remote operating system : Linux Kernel 3.13 on Ubuntu 14.04 (trusty)
Confidence level : 95
Method : HTTP


The remote host is running Linux Kernel 3.13 on Ubuntu 14.04 (trusty)
```

117886 - OS Security Patch Assessment Not Available

Synopsis

OS Security Patch Assessment is not available.

Description

OS Security Patch Assessment is not available on the remote host.

This does not necessarily indicate a problem with the scan.

Credentials may not have been provided, OS security patch assessment may not be supported for the target, the target may not have been identified, or another issue may have occurred that prevented OS security patch assessment from being available. See plugin output for details.

This plugin reports non-failure information impacting the availability of OS Security Patch Assessment. Failure information is reported by plugin 21745 : 'OS Security Patch Assessment failed'. If a target host is not supported for OS Security Patch Assessment, plugin 110695 : 'OS Security Patch Assessment Checks Not Supported' will report concurrently with this plugin.

Solution

n/a

Risk Factor

None

References

XREF IAVB:0001-B-0515

Plugin Information

Published: 2018/10/02, Modified: 2021/07/12

Plugin Output

tcp/0

```
The following issues were reported :

  - Plugin      : no_local_checks_credentials.nasl
    Plugin ID   : 110723
    Plugin Name : Target Credential Status by Authentication Protocol - No Credentials Provided
    Message     :
Credentials were not provided for detected SSH service.
```

181418 - OpenSSH Detection

Synopsis

An OpenSSH-based SSH server was detected on the remote host.

Description

An OpenSSH-based SSH server was detected on the remote host.

See Also

https://www.openssh.com/

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2023/09/14, Modified: 2026/04/28

Plugin Output

tcp/22/ssh

```
Service    : ssh
Version    : 6.6.1p1
Banner     : SSH-2.0-OpenSSH_6.6.1p1 Ubuntu-2ubuntu2.13
backported : 1
```

66334 - Patch Report

Synopsis

The remote host is missing several patches.

Description

The remote host is missing one or more security patches. This plugin lists the newest version of each patch to install to make sure the remote host is up-to-date.

Note: Because the 'Show missing patches that have been superseded' setting in your scan policy depends on this plugin, it will always run and cannot be disabled.

Solution

Install the patches listed below.

Risk Factor

None

Plugin Information

Published: 2013/07/08, Modified: 2026/04/28

Plugin Output

tcp/0

```
. You need to take the following 2 actions :

[ ProFTPD mod_copy Information Disclosure (84215) ]

+ Action to take : Upgrade to ProFTPD 1.3.5a / 1.3.6rc1 or later.


[ SSH Terrapin Prefix Truncation Weakness (CVE-2023-48795) (187315) ]

+ Action to take : Contact the vendor for an update with the strict key exchange countermeasures or
 disable the affected algorithms.
```

277650 - Remote Services Not Using Post-Quantum Ciphers

Synopsis

Reports remote services that do not offer post-quantum ciphers.

Description

This plugin reports network services that do not offer post-quantum ciphers. Tenable makes no attempt to determine whether the remote service would be vulnerable to a post-quantum attack.

However, cryptography that depends on the classic difficulty of solving the discrete logarithm problem or on the classic difficulty of large prime factorization is broken by Shor's algorithm. Examples of this are RSA asymmetric encryption and Diffie-Hellman key exchange.

See Also

http://www.nessus.org/u?7a390f87

http://www.nessus.org/u?ad7d6b3b

http://www.nessus.org/u?1c0c61e0

http://www.nessus.org/u?5eec4b28

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2025/12/08, Modified: 2025/12/08

Plugin Output

tcp/22/ssh

```
The target SSH server offers no post-quantum ciphers.
```

10860 - SMB Use Host SID to Enumerate Local Users

Synopsis

Nessus was able to enumerate local users.

Description

Using the host security identifier (SID), Nessus was able to enumerate local users on the remote Windows system.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2002/02/13, Modified: 2023/02/28

Plugin Output

tcp/445/cifs

```
  - nobody (id 501, Guest account)
  - chewbacca (id 1000)

Note that, in addition to the Administrator, Guest, and Kerberos
accounts, Nessus has enumerated local users with IDs between
1000 and 1200. To use a different range, edit the scan policy
and change the 'Enumerate Local Users: Start UID' and/or 'End UID'
preferences under 'Assessment->Windows' and re-run the scan. Only
UIDs between 1 and 2147483647 are allowed for this range.
```

70657 - SSH Algorithms and Languages Supported

Synopsis

An SSH server is listening on this port.

Description

This script detects which algorithms and languages are supported by the remote service for encrypting communications.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2013/10/28, Modified: 2026/01/12

Plugin Output

tcp/22/ssh

```
Nessus negotiated the following encryption algorithm(s) with the server :

  Client to Server: aes256-ctr
  Server to Client: aes256-ctr

The server supports the following options for compression_algorithms_server_to_client :

  none
  zlib@openssh.com

The server supports the following options for mac_algorithms_client_to_server :

  hmac-md5
  hmac-md5-96
  hmac-md5-96-etm@openssh.com
  hmac-md5-etm@openssh.com
  hmac-ripemd160
  hmac-ripemd160-etm@openssh.com
  hmac-ripemd160@openssh.com
  hmac-sha1
  hmac-sha1-96
  hmac-sha1-96-etm@openssh.com
  hmac-sha1-etm@openssh.com
  hmac-sha2-256
  hmac-sha2-256-etm@openssh.com
  hmac-sha2-512
  hmac-sha2-512-etm@openssh.com
  umac-128-etm@openssh.com
  umac-128@openssh.com
```

```
  umac-64-etm@openssh.com
  umac-64@openssh.com

The server supports the following options for server_host_key_algorithms :

  ecdsa-sha2-nistp256
  ssh-dss
  ssh-ed25519
  ssh-rsa

The server supports the following options for encryption_algorithms_client_to_server :

  3des-cbc
  aes128-cbc
  aes128-ctr
  aes128-gcm@openssh.com
  aes192-cbc
  aes192-ctr
  aes256-cbc
  aes256-ctr
  aes256-gcm@openssh.com
  arcfour
  arcfour128
  arcfour256
  blowfish-cbc
  cast128-cbc
  chacha20-poly1305@openssh.com
  rijndael-cbc@lysator.liu.se

The server supports the following options for mac_algorithms_server_to_client :

  hmac-md5
  hmac-md5-96
  hmac-md5-96-etm@openssh.com
  hmac-md5-etm@openssh.com
  hmac-ripemd160
  hmac-ripemd160-etm@openssh.com
  hmac-ripemd160@openssh.com
  hmac-sha1
  hmac-sha1-96
  hmac-sha1-96-etm@openssh.com
  hmac-sha1-etm@openssh.com
  hmac-sha2-256
  hmac-sha2-256-etm@openssh.com
  hmac-sha2-512
  hmac-sha2-512-etm@openssh.com
  umac-128-etm@openssh.com
  umac-128@openssh.com
  umac-64-etm@openssh.com
  umac-64@openssh.com

The server supports the following options for kex_algorithms :

  curve25519-sha256@libssh.org
  diffie-hellman-group-exchange-sha1
  diffie-hellman-group-exchange-sha256
  diffie-hellman-group1-sha1
  diffie-hellman-group14-sha1
  ecdh-sha2-nistp256
   [...]
```

149334 - SSH Password Authentication Accepted

Synopsis

The SSH server on the remote host accepts password authentication.

Description

The SSH server on the remote host accepts password authentication.

See Also

https://tools.ietf.org/html/rfc4252#section-8

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2021/05/07, Modified: 2021/05/07

Plugin Output

tcp/22/ssh

10881 - SSH Protocol Versions Supported

Synopsis

A SSH server is running on the remote host.

Description

This plugin determines the versions of the SSH protocol supported by the remote SSH daemon.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2002/03/06, Modified: 2026/01/12

Plugin Output

tcp/22/ssh

```
The remote SSH daemon supports the following versions of the
SSH protocol :

  - 1.99
  - 2.0
```

153588 - SSH SHA-1 HMAC Algorithms Enabled

Synopsis

The remote SSH server is configured to enable SHA-1 HMAC algorithms.

Description

The remote SSH server is configured to enable SHA-1 HMAC algorithms.

Although NIST has formally deprecated use of SHA-1 for digital signatures, SHA-1 is still considered secure for HMAC as the security of HMAC does not rely on the underlying hash function being resistant to collisions.

Note that this plugin only checks for the options of the remote SSH server.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2021/09/23, Modified: 2022/04/05

Plugin Output

tcp/22/ssh

```
The following client-to-server SHA-1 Hash-based Message Authentication Code (HMAC) algorithms are
 supported :

  hmac-md5-etm@openssh.com,hmac-sha1-etm@openssh.com,umac-64-etm@openssh.com,umac-128-
etm@openssh.com,hmac-sha2-256-etm@openssh.com,hmac-sha2-512-etm@openssh.com,hmac-ripemd160-
etm@openssh.com,hmac-sha1-96-etm@openssh.com,hmac-md5-96-etm@openssh.com,hmac-md5,hmac-
sha1,umac-64@openssh.com,umac-128@openssh.com,hmac-sha2-256,hmac-sha2-512,hmac-ripemd160,hmac-
ripemd160@openssh.com,hmac-sha1-96,hmac-md5-96

The following server-to-client SHA-1 Hash-based Message Authentication Code (HMAC) algorithms are
 supported :

  hmac-md5-etm@openssh.com,hmac-sha1-etm@openssh.com,umac-64-etm@openssh.com,umac-128-
etm@openssh.com,hmac-sha2-256-etm@openssh.com,hmac-sha2-512-etm@openssh.com,hmac-ripemd160-
etm@openssh.com,hmac-sha1-96-etm@openssh.com,hmac-md5-96-etm@openssh.com,hmac-md5,hmac-
sha1,umac-64@openssh.com,umac-128@openssh.com,hmac-sha2-256,hmac-sha2-512,hmac-ripemd160,hmac-
ripemd160@openssh.com,hmac-sha1-96,hmac-md5-96
```

10267 - SSH Server Type and Version Information

Synopsis

An SSH server is listening on this port.

Description

It is possible to obtain information about the remote SSH server by sending an empty authentication request.

Solution

n/a

Risk Factor

None

References

XREF IAVT:0001-T-0933

Plugin Information

Published: 1999/10/12, Modified: 2024/07/24

Plugin Output

tcp/22/ssh

```
SSH version : SSH-2.0-OpenSSH_6.6.1p1 Ubuntu-2ubuntu2.13
SSH supported authentication : publickey,password
```

25240 - Samba Server Detection

Synopsis

An SMB server is running on the remote host.

Description

The remote host is running Samba, a CIFS/SMB server for Linux and Unix.

See Also

https://www.samba.org/

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/05/16, Modified: 2022/10/12

Plugin Output

tcp/445/cifs

```
The remote host tries to hide its SMB server type by changing the MAC
address and the LAN manager name.

However by sending several valid and invalid RPC requests it was
possible to fingerprint the remote SMB server as Samba.
```

104887 - Samba Version

Synopsis

It was possible to obtain the samba version from the remote operating system.

Description

Nessus was able to obtain the samba version from the remote operating by sending an authentication request to port 139 or 445. Note that this plugin requires SMB1 to be enabled on the host.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2017/11/30, Modified: 2019/11/22

Plugin Output

tcp/445/cifs

```
The remote Samba Version is : Samba 4.3.11-Ubuntu
```

96982 - Server Message Block (SMB) Protocol Version 1 Enabled (uncredentialed check)

Synopsis

The remote host supports the SMBv1 protocol.

Description

The remote host (Windows and/or Samba server) supports Server Message Block Protocol version 1 (SMBv1). Microsoft recommends that users discontinue the use of SMBv1 due to the lack of security features that were included in later SMB versions. Additionally, most security and compliance agencies recommend that users disable SMBv1 per SMB best practices.

See Also

http://www.nessus.org/u?59bfc3ef

http://www.nessus.org/u?b9d9ebf9

http://www.nessus.org/u?8dcab5e4

http://www.nessus.org/u?234f8ef8

http://www.nessus.org/u?4c7e0cf3

Solution

Disable SMBv1 according to the vendor instructions in Microsoft KB2696547. Additionally, block SMB directly by blocking TCP port 445 on all network boundary devices. For SMB over the NetBIOS API, block TCP ports 137 / 139 and UDP ports 137 / 138 on all network boundary devices.

Risk Factor

None

References

XREF IAVT:0001-T-0710

Plugin Information

Published: 2017/02/03, Modified: 2025/08/13

Plugin Output

tcp/445/cifs

```
The remote host supports SMBv1.
```

22964 - Service Detection

Synopsis

The remote service could be identified.

Description

Nessus was able to identify the remote service by its banner or by looking at the error message it sends when it receives an HTTP request.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/08/19, Modified: 2026/03/23

Plugin Output

tcp/21/ftp

```
An FTP server is running on this port.
```

22964 - Service Detection

Synopsis

The remote service could be identified.

Description

Nessus was able to identify the remote service by its banner or by looking at the error message it sends when it receives an HTTP request.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/08/19, Modified: 2026/03/23

Plugin Output

tcp/22/ssh

```
An SSH server is running on this port.
```

22964 - Service Detection

Synopsis

The remote service could be identified.

Description

Nessus was able to identify the remote service by its banner or by looking at the error message it sends when it receives an HTTP request.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/08/19, Modified: 2026/03/23

Plugin Output

tcp/80/www

```
A web server is running on this port.
```

22964 - Service Detection

Synopsis

The remote service could be identified.

Description

Nessus was able to identify the remote service by its banner or by looking at the error message it sends when it receives an HTTP request.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/08/19, Modified: 2026/03/23

Plugin Output

tcp/3306/mysql

```
A MySQL server is running on this port.
```

22964 - Service Detection

Synopsis

The remote service could be identified.

Description

Nessus was able to identify the remote service by its banner or by looking at the error message it sends when it receives an HTTP request.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/08/19, Modified: 2026/03/23

Plugin Output

tcp/3500/www

```
A web server is running on this port.
```

22964 - Service Detection

Synopsis

The remote service could be identified.

Description

Nessus was able to identify the remote service by its banner or by looking at the error message it sends when it receives an HTTP request.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/08/19, Modified: 2026/03/23

Plugin Output

tcp/8080/www

```
A web server is running on this port.
```

17975 - Service Detection (GET request)

Synopsis

The remote service could be identified.

Description

It was possible to identify the remote service by its banner or by looking at the error message it sends when it receives an HTTP request.

Solution

n/a

Risk Factor

None

References

XREF IAVT:0001-T-0935

Plugin Information

Published: 2005/04/06, Modified: 2021/10/27

Plugin Output

tcp/6697/irc

```
An IRC daemon is listening on this port.
```

298387 - Shor's Harvest Now Decrypt Later

Synopsis

Reports remote services potentially vulnerable to Shor's Algorithm.

Description

This plugin reports network services that may be vulnerable now to a future attack by adversaries using a cryptographically relevant quantum computer (CRQC). Shor's is a theoretical algorithm that leverages the unique ability of quantum computation to do massively parallel calculations developed by Peter Shor in 1994.

This algorithm easily computes two classically difficult mathematical problems used in modern cryptography; discrete logarithms, and factoring numbers formed by multiplying large primes. Shor's reduces both of these problems from taking exponential time in chosen cases to being solvable in polynomial time.

Asymmetric encryption algorithms such as RSA, Diffie-Hellman and Elliptic Curve Diffie-Hellman are impacted by Shor's Algorithm. The most common uses of these algorithms are in symmetric key establishment and authentication. These uses render Shor's Algorithm particularly dangerous because it may give an adversary the ability to harvest network communications now, and in the future, when a CRQC becomes available, extract the symmetric key and decrypt the communication.

See Also

http://www.nessus.org/u?54fba2c1

Solution

Replace affected ciphers with algorithms chosen to resist CRQC attack.

Risk Factor

None

Plugin Information

Published: 2026/02/09, Modified: 2026/04/13

Plugin Output

tcp/0

```
The SSH service on port 22 offers these ciphers vulnerable to Shor's:
diffie-hellman-group-exchange-sha256
ecdh-sha2-nistp256
ecdh-sha2-nistp521
curve25519-sha256@libssh.org
ecdh-sha2-nistp384
diffie-hellman-group-exchange-sha1
diffie-hellman-group1-sha1
```

```
diffie-hellman-group14-sha1
```

25220 - TCP/IP Timestamps Supported

Synopsis

The remote service implements TCP timestamps.

Description

The remote host implements TCP timestamps, as defined by RFC1323. A side effect of this feature is that the uptime of the remote host can sometimes be computed.

See Also

http://www.ietf.org/rfc/rfc1323.txt

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/05/16, Modified: 2023/10/17

Plugin Output

tcp/0

110723 - Target Credential Status by Authentication Protocol - No Credentials Provided

Synopsis

Nessus was able to find common ports used for local checks, however, no credentials were provided in the scan policy.

Description

Nessus was not able to successfully authenticate directly to the remote target on an available authentication protocol. Nessus was able to connect to the remote port and identify that the service running on the port supports an authentication protocol, but Nessus failed to authenticate to the remote service using the provided credentials. There may have been a protocol failure that prevented authentication from being attempted or all of the provided credentials for the authentication protocol may be invalid. See plugin output for error details.

Please note the following :

- This plugin reports per protocol, so it is possible for valid credentials to be provided for one protocol and not another. For example, authentication may succeed via SSH but fail via SMB, while no credentials were provided for an available SNMP service.

- Providing valid credentials for all available authentication protocols may improve scan coverage, but the value of successful authentication for a given protocol may vary from target to target depending upon what data (if any) is gathered from the target via that protocol. For example, successful authentication via SSH is more valuable for Linux targets than for Windows targets, and likewise successful authentication via SMB is more valuable for Windows targets than for Linux targets.

Solution

n/a

Risk Factor

None

References

XREF IAVB:0001-B-0504

Plugin Information

Published: 2018/06/27, Modified: 2024/04/19

Plugin Output

tcp/0

```
SSH was detected on port 22 but no credentials were provided.
SSH local checks were not enabled.
```

10287 - Traceroute Information

Synopsis

It was possible to obtain traceroute information.

Description

Makes a traceroute to the remote host.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 1999/11/27, Modified: 2026/04/27

Plugin Output

udp/0

```
For your information, here is the traceroute from 10.10.10.174 to 10.10.10.101 :
10.10.10.174
10.10.10.101

Hop Count: 1
```

20108 - Web Server / Application favicon.ico Vendor Fingerprinting

Synopsis

The remote web server contains a graphic image that is prone to information disclosure.

Description

The 'favicon.ico' file found on the remote web server belongs to a popular web server. This may be used to fingerprint the web server.

Solution

Remove the 'favicon.ico' file or create a custom one for your site.

Risk Factor

None

Plugin Information

Published: 2005/10/28, Modified: 2020/06/12

Plugin Output

tcp/8080/www

```
MD5 fingerprint : ed7d5c39c69262f4ba95418d4f909b10
Web server      : jetty 5.1.14
```

10302 - Web Server robots.txt Information Disclosure

Synopsis

The remote web server contains a 'robots.txt' file.

Description

The remote host contains a file named 'robots.txt' that is intended to prevent web 'robots' from visiting certain directories in a website for maintenance or indexing purposes. A malicious user may also be able to use the contents of this file to learn of sensitive documents or directories on the affected site and either retrieve them directly or target them for other attacks.

See Also

http://www.robotstxt.org/orig.html

Solution

Review the contents of the site's robots.txt file, use Robots META tags instead of entries in the robots.txt file, and/or adjust the web server's access controls to limit access to sensitive material.

Risk Factor

None

Plugin Information

Published: 1999/10/12, Modified: 2026/03/10

Plugin Output

tcp/3500/www

```
Contents of robots.txt :

# See http://www.robotstxt.org/robotstxt.html for documentation on how to use the robots.txt file
#
# To ban all spiders from the entire site uncomment the next two lines:
# User-agent: *
# Disallow: /
```

10150 - Windows NetBIOS / SMB Remote Host Information Disclosure

Synopsis

It was possible to obtain the network name of the remote host.

Description

The remote host is listening on UDP port 137 or TCP port 445, and replies to NetBIOS nbtscan or SMB requests.

Note that this plugin gathers information to be used in other plugins, but does not itself generate a report.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 1999/10/12, Modified: 2021/02/10

Plugin Output

tcp/445/cifs

```
The following 2 NetBIOS names have been gathered :

 METASPLOITABLE3-UB1404 = Computer name
 METASPLOITABLE3-UB1404 = Workgroup / Domain name
```

10.10.10.102

CRITICAL	HIGH	MEDIUM	LOW	INFO
1	0	1	1	33

Scan Information

Start time: Tue May 5 14:52:58 2026
End time: Tue May 5 15:01:12 2026

Host Information

IP: 10.10.10.102
MAC Address: 08:00:27:E8:01:5C
OS: Linux Kernel 4.4 on Ubuntu 16.04 (xenial)

Vulnerabilities

201351 - Canonical Ubuntu Linux SEoL (16.04.x)

Synopsis

An unsupported version of Canonical Ubuntu Linux is installed on the remote host.

Description

According to its version, Canonical Ubuntu Linux is 16.04.x. It is, therefore, no longer maintained by its vendor or provider.

Lack of support implies that no new security patches for the product will be released by the vendor. As a result, it may contain security vulnerabilities.

See Also

http://www.nessus.org/u?cdd15280

Solution

Upgrade to a version of Canonical Ubuntu Linux that is currently supported.

Risk Factor

Critical

CVSS v3.0 Base Score

10.0 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:C/C:H/I:H/A:H)

CVSS v2.0 Base Score

10.0 (CVSS2#AV:N/AC:L/Au:N/C:C/I:C/A:C)

Plugin Information

Published: 2024/07/03, Modified: 2025/03/26

Plugin Output

tcp/22/ssh

```
OS                                    : Ubuntu Linux 16.04
Security End of Life                  : April 30, 2021
Time since Security End of Life (Est.) : >= 5 years
```

187315 - SSH Terrapin Prefix Truncation Weakness (CVE-2023-48795)

Synopsis

The remote SSH server is vulnerable to a mitm prefix truncation attack.

Description

The remote SSH server is vulnerable to a man-in-the-middle prefix truncation weakness known as Terrapin. This can allow a remote, man-in-the-middle attacker to bypass integrity checks and downgrade the connection's security.

Note that this plugin only checks for remote SSH servers that support either ChaCha20-Poly1305 or CBC with Encrypt-then-MAC and do not support the strict key exchange countermeasures. It does not check for vulnerable software versions.

See Also

https://terrapin-attack.com/

Solution

Contact the vendor for an update with the strict key exchange countermeasures or disable the affected algorithms.

Risk Factor

Medium

CVSS v3.0 Base Score

5.9 (CVSS:3.0/AV:N/AC:H/PR:N/UI:N/S:U/C:N/I:H/A:N)

CVSS v3.0 Temporal Score

5.3 (CVSS:3.0/E:P/RL:O/RC:C)

VPR Score

6.1

EPSS Score

0.586

CVSS v2.0 Base Score

5.4 (CVSS2#AV:N/AC:H/Au:N/C:N/I:C/A:N)

CVSS v2.0 Temporal Score

4.2 (CVSS2#E:POC/RL:OF/RC:C)

References

CVE CVE-2023-48795

Plugin Information

Published: 2023/12/27, Modified: 2026/01/12

Plugin Output

tcp/22/ssh

```
Supports following ChaCha20-Poly1305 Client to Server algorithm : chacha20-
poly1305@openssh.com,aes128-ctr,aes192-ctr,aes256-ctr,aes128-gcm@openssh.com,aes256-gcm@openssh.com
Supports following Encrypt-then-MAC Client to Server algorithm  : umac-64-etm@openssh.com,umac-128-
etm@openssh.com,hmac-sha2-256-etm@openssh.com,hmac-sha2-512-etm@openssh.com,hmac-sha1-
etm@openssh.com,umac-64@openssh.com,umac-128@openssh.com,hmac-sha2-256,hmac-sha2-512,hmac-sha1
Supports following ChaCha20-Poly1305 Server to Client algorithm : chacha20-
poly1305@openssh.com,aes128-ctr,aes192-ctr,aes256-ctr,aes128-gcm@openssh.com,aes256-gcm@openssh.com
Supports following Encrypt-then-MAC Server to Client algorithm  : umac-64-etm@openssh.com,umac-128-
etm@openssh.com,hmac-sha2-256-etm@openssh.com,hmac-sha2-512-etm@openssh.com,hmac-sha1-
etm@openssh.com,umac-64@openssh.com,umac-128@openssh.com,hmac-sha2-256,hmac-sha2-512,hmac-sha1
```

10114 - ICMP Timestamp Request Remote Date Disclosure

Synopsis

It is possible to determine the exact time set on the remote host.

Description

The remote host answers to an ICMP timestamp request. This allows an attacker to know the date that is set on the targeted machine, which may assist an unauthenticated, remote attacker in defeating time-based authentication protocols.

Timestamps returned from machines running Windows Vista / 7 / 2008 / 2008 R2 are deliberately incorrect, but usually within 1000 seconds of the actual system time.

Solution

Filter out the ICMP timestamp requests (13), and the outgoing ICMP timestamp replies (14).

Risk Factor

Low

VPR Score

2.2

EPSS Score

0.0037

CVSS v2.0 Base Score

2.1 (CVSS2#AV:L/AC:L/Au:N/C:P/I:N/A:N)

References

CVE	CVE-1999-0524
XREF	CWE:200

Plugin Information

Published: 1999/08/01, Modified: 2024/10/07

Plugin Output

icmp/0

```
The difference between the local and remote clocks is -1 seconds.
```

18261 - Apache Banner Linux Distribution Disclosure

Synopsis

The name of the Linux distribution running on the remote host was found in the banner of the web server.

Description

Nessus was able to extract the banner of the Apache web server and determine which Linux distribution the remote host is running.

Solution

If you do not wish to display this information, edit 'httpd.conf' and set the directive 'ServerTokens Prod' and restart Apache.

Risk Factor

None

Plugin Information

Published: 2005/05/15, Modified: 2025/03/31

Plugin Output

tcp/0

```
The Linux distribution detected was :
 - Ubuntu 16.04 (xenial)
 - Ubuntu 16.10 (yakkety)
```

48204 - Apache HTTP Server Version

Synopsis

It is possible to obtain the version number of the remote Apache HTTP server.

Description

The remote host is running the Apache HTTP Server, an open source web server. It was possible to read the version number from the banner.

See Also

https://httpd.apache.org/

Solution

n/a

Risk Factor

None

References

XREF	IAVT:0001-T-0030
XREF	IAVT:0001-T-0530

Plugin Information

Published: 2010/07/30, Modified: 2026/01/22

Plugin Output

tcp/80/www

```
URL        : http://10.10.10.102/
Version    : 2.4.18
Source     : Server: Apache/2.4.18 (Ubuntu)
backported : 1
os         : Ubuntu
```

39520 - Backported Security Patch Detection (SSH)

Synopsis

Security patches are backported.

Description

Security patches may have been 'backported' to the remote SSH server without changing its version number.

Banner-based checks have been disabled to avoid false positives.

Note that this test is informational only and does not denote any security problem.

See Also

https://access.redhat.com/security/updates/backporting/?sc_cid=3093

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2009/06/25, Modified: 2026/01/22

Plugin Output

tcp/22/ssh

```
Give Nessus credentials to perform local checks.
```

39521 - Backported Security Patch Detection (WWW)

Synopsis

Security patches are backported.

Description

Security patches may have been 'backported' to the remote HTTP server without changing its version number.

Banner-based checks have been disabled to avoid false positives.

Note that this test is informational only and does not denote any security problem.

See Also

https://access.redhat.com/security/updates/backporting/?sc_cid=3093

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2009/06/25, Modified: 2026/01/22

Plugin Output

tcp/80/www

```
Give Nessus credentials to perform local checks.
```

45590 - Common Platform Enumeration (CPE)

Synopsis

It was possible to enumerate CPE names that matched on the remote system.

Description

By using information obtained from a Nessus scan, this plugin reports CPE (Common Platform Enumeration) matches for various hardware and software products found on a host.

Note that if an official CPE is not available for the product, this plugin computes the best possible CPE based on the information available from the scan.

See Also

http://cpe.mitre.org/

https://nvd.nist.gov/products/cpe

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2010/04/21, Modified: 2026/01/05

Plugin Output

tcp/0

```
Following application CPE's matched on the remote system :

  cpe:/a:apache:http_server:2.4.18 -> Apache Software Foundation Apache HTTP Server
  cpe:/a:openbsd:openssh:7.2 -> OpenBSD OpenSSH
  cpe:/a:openbsd:openssh:7.2p2 -> OpenBSD OpenSSH
```

54615 - Device Type

Synopsis

It is possible to guess the remote device type.

Description

Based on the remote operating system, it is possible to determine what the remote system type is (eg: a printer, router, general-purpose computer, etc).

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2011/05/23, Modified: 2025/03/12

Plugin Output

tcp/0

```
Remote device type : general-purpose
Confidence level : 95
```

35716 - Ethernet Card Manufacturer Detection

Synopsis

The manufacturer can be identified from the Ethernet OUI.

Description

Each ethernet MAC address starts with a 24-bit Organizationally Unique Identifier (OUI). These OUIs are registered by IEEE.

See Also

https://standards.ieee.org/faqs/regauth.html

http://www.nessus.org/u?794673b4

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2009/02/19, Modified: 2020/05/13

Plugin Output

tcp/0

```
The following card manufacturers were identified :

08:00:27:E8:01:5C : PCS Systemtechnik GmbH
```

86420 - Ethernet MAC Addresses

Synopsis

This plugin gathers MAC addresses from various sources and consolidates them into a list.

Description

This plugin gathers MAC addresses discovered from both remote probing of the host (e.g. SNMP and Netbios) and from running local checks (e.g. ifconfig). It then consolidates the MAC addresses into a single, unique, and uniform list.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2015/10/16, Modified: 2025/06/10

Plugin Output

tcp/0

```
The following is a consolidated list of detected MAC addresses:
  - 08:00:27:E8:01:5C
```

43111 - HTTP Methods Allowed (per directory)

Synopsis

This plugin determines which HTTP methods are allowed on various CGI directories.

Description

By calling the OPTIONS method, it is possible to determine which HTTP methods are allowed on each directory.

The following HTTP methods are considered insecure:

PUT, DELETE, CONNECT, TRACE, HEAD

Many frameworks and languages treat 'HEAD' as a 'GET' request, albeit one without any body in the response. If a security constraint was set on 'GET' requests such that only 'authenticatedUsers' could access GET requests for a particular servlet or resource, it would be bypassed for the 'HEAD' version. This allowed unauthorized blind submission of any privileged GET request.

As this list may be incomplete, the plugin also tests - if 'Thorough tests' are enabled or 'Enable web applications tests' is set to 'yes'

in the scan policy - various known HTTP methods on each directory and considers them as unsupported if it receives a response code of 400, 403, 405, or 501.

Note that the plugin output is only informational and does not necessarily indicate the presence of any security vulnerabilities.

See Also

http://www.nessus.org/u?d9c03a9a

http://www.nessus.org/u?b019cbdb

https://www.owasp.org/index.php/Test_HTTP_Methods_(OTG-CONFIG-006)

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2009/12/10, Modified: 2022/04/11

Plugin Output

tcp/80/www

```
Based on the response to an OPTIONS request :

  - HTTP methods GET HEAD OPTIONS POST are allowed on :

    /
```

10107 - HTTP Server Type and Version

Synopsis

A web server is running on the remote host.

Description

This plugin attempts to determine the type and the version of the remote web server.

Solution

n/a

Risk Factor

None

References

XREF IAVT:0001-T-0931

Plugin Information

Published: 2000/01/04, Modified: 2020/10/30

Plugin Output

tcp/80/www

```
The remote web server type is :

Apache/2.4.18 (Ubuntu)
```

24260 - HyperText Transfer Protocol (HTTP) Information

Synopsis

Some information about the remote HTTP configuration can be extracted.

Description

This test gives some information about the remote HTTP protocol - the version used, whether HTTP Keep-Alive is enabled, etc...

This test is informational only and does not denote any security problem.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/01/30, Modified: 2024/02/26

Plugin Output

tcp/80/www

```
Response Code : HTTP/1.1 200 OK

Protocol version : HTTP/1.1
HTTP/2 TLS Support: No
HTTP/2 Cleartext Support: No
SSL : no
Keep-Alive : yes
Options allowed : (Not implemented)
Headers :

  Date: Tue, 05 May 2026 13:55:25 GMT
  Server: Apache/2.4.18 (Ubuntu)
  Last-Modified: Thu, 16 Nov 2017 16:53:57 GMT
  ETag: "b1-55e1c7758dcdb"
  Accept-Ranges: bytes
  Content-Length: 177
  Vary: Accept-Encoding
  Keep-Alive: timeout=5, max=98
  Connection: Keep-Alive
  Content-Type: text/html

Response Body :

<html><body><h1>It works!</h1>
<p>This is the default web page for this server.</p>
<p>The web server software is running but no content has been added, yet.</p>
```

```
</body></html>
```

11219 - Nessus SYN scanner

Synopsis

It is possible to determine which TCP ports are open.

Description

This plugin is a SYN 'half-open' port scanner. It shall be reasonably quick even against a firewalled target.

Note that SYN scans are less intrusive than TCP (full connect) scans against broken services, but they might cause problems for less robust firewalls and also leave unclosed connections on the remote target, if the network is loaded.

Solution

Protect your target with an IP filter.

Risk Factor

None

Plugin Information

Published: 2009/02/04, Modified: 2025/07/14

Plugin Output

tcp/21

```
Port 21/tcp was found to be open
```

11219 - Nessus SYN scanner

Synopsis

It is possible to determine which TCP ports are open.

Description

This plugin is a SYN 'half-open' port scanner. It shall be reasonably quick even against a firewalled target.

Note that SYN scans are less intrusive than TCP (full connect) scans against broken services, but they might cause problems for less robust firewalls and also leave unclosed connections on the remote target, if the network is loaded.

Solution

Protect your target with an IP filter.

Risk Factor

None

Plugin Information

Published: 2009/02/04, Modified: 2025/07/14

Plugin Output

tcp/22/ssh

```
Port 22/tcp was found to be open
```

11219 - Nessus SYN scanner

Synopsis

It is possible to determine which TCP ports are open.

Description

This plugin is a SYN 'half-open' port scanner. It shall be reasonably quick even against a firewalled target.

Note that SYN scans are less intrusive than TCP (full connect) scans against broken services, but they might cause problems for less robust firewalls and also leave unclosed connections on the remote target, if the network is loaded.

Solution

Protect your target with an IP filter.

Risk Factor

None

Plugin Information

Published: 2009/02/04, Modified: 2025/07/14

Plugin Output

tcp/80/www

```
Port 80/tcp was found to be open
```

19506 - Nessus Scan Information

Synopsis

This plugin displays information about the Nessus scan.

Description

This plugin displays, for each tested host, information about the scan itself :

- The version of the plugin set.
- The type of scanner (Nessus or Nessus Home).
- The version of the Nessus Engine.
- The port scanner(s) used.
- The port range scanned.
- The ping round trip time
- Whether credentialed or third-party patch management checks are possible.
- Whether the display of superseded patches is enabled
- The date of the scan.
- The duration of the scan.
- The number of hosts scanned in parallel.
- The number of checks done in parallel.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2005/08/26, Modified: 2026/03/04

Plugin Output

tcp/0

```
Information about this scan :

Nessus version : 10.12.0
Nessus build : 20184
Plugin feed version : 202605050546
Scanner edition used : Nessus
Scanner OS : LINUX
Scanner distribution : ubuntu1804-aarch64
Scan type : Normal
Scan name : pentest exam
```

```
Scan policy used : Basic Network Scan
Scanner IP : 10.10.10.174
Port scanner(s) : nessus_syn_scanner
Port range : 1-65535
Ping RTT : 135.008 ms
Thorough tests : no
Experimental tests : no
Scan for Unpatched Vulnerabilities : no
Plugin debugging enabled : no
Paranoia level : 1
Report verbosity : 1
Safe checks : yes
Optimize the test : yes
Credentialed checks : no
Patch management checks : None
Display superseded patches : yes (supersedence plugin did not launch)
CGI scanning : disabled
Web application tests : disabled
Max hosts : 30
Max checks : 4
Recv timeout : 5
Backports : Detected
Allow post-scan editing : Yes
Nessus Plugin Signature Checking : Enabled
Audit File Signature Checking : Disabled
Scan Start Date : 2026/5/5 14:53 IST (UTC +01:00)
Scan duration : 489 sec
Scan for malware : no
Fully Scan Operational Technology devices : yes
Safely Scan Operational Technology devices with OT Discovery : no
```

209654 - OS Fingerprints Detected

Synopsis

Multiple OS fingerprints were detected.

Description

Using a combination of remote probes (TCP/IP, SMB, HTTP, NTP, SNMP, etc), it was possible to gather one or more fingerprints from the remote system. While the highest-confidence result was reported in plugin 11936, “OS Identification”, the complete set of fingerprints detected are reported here.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2025/02/26, Modified: 2025/03/03

Plugin Output

tcp/0

```
Following OS Fingerprints were found

Remote operating system : F5 Networks BIG-IP
Confidence level : 56
Method : MLSinFP
Type : unknown
Fingerprint : unknown

Remote operating system : Linux Kernel 4.4 on Ubuntu 16.04 (xenial)
Confidence level : 95
Method : SSH
Type : general-purpose
Fingerprint : SSH:SSH-2.0-OpenSSH_7.2p2 Ubuntu-4ubuntu2.2

Remote operating system : Ubuntu 16.x
Confidence level : 85
Method : HTTP
Type : general-purpose
Fingerprint : unknown

Remote operating system : Linux
Confidence level : 59
Method : SinFP
Type : general-purpose
Fingerprint : SinFP:
   P1:B10113:F0x12:W29200:O0204ffff:M1460:
   P2:B10113:F0x12:W28960:O0204ffff0402080affffffff4445414401030307:M1460:
   P3:B00000:F0x00:W0:O0:M0
```

```
    P4:191800_7_p=22
```

11936 - OS Identification

Synopsis

It is possible to guess the remote operating system.

Description

Using a combination of remote probes (e.g., TCP/IP, SMB, HTTP, NTP, SNMP, etc.), it is possible to guess the name of the remote operating system in use. It is also possible sometimes to guess the version of the operating system.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2003/12/09, Modified: 2025/06/03

Plugin Output

tcp/0

```
Remote operating system : Linux Kernel 4.4 on Ubuntu 16.04 (xenial)
Confidence level : 95
Method : SSH


The remote host is running Linux Kernel 4.4 on Ubuntu 16.04 (xenial)
```

117886 - OS Security Patch Assessment Not Available

Synopsis

OS Security Patch Assessment is not available.

Description

OS Security Patch Assessment is not available on the remote host.

This does not necessarily indicate a problem with the scan.

Credentials may not have been provided, OS security patch assessment may not be supported for the target, the target may not have been identified, or another issue may have occurred that prevented OS security patch assessment from being available. See plugin output for details.

This plugin reports non-failure information impacting the availability of OS Security Patch Assessment. Failure information is reported by plugin 21745 : 'OS Security Patch Assessment failed'. If a target host is not supported for OS Security Patch Assessment, plugin 110695 : 'OS Security Patch Assessment Checks Not Supported' will report concurrently with this plugin.

Solution

n/a

Risk Factor

None

References

XREF IAVB:0001-B-0515

Plugin Information

Published: 2018/10/02, Modified: 2021/07/12

Plugin Output

tcp/0

```
The following issues were reported :

  - Plugin      : no_local_checks_credentials.nasl
    Plugin ID   : 110723
    Plugin Name : Target Credential Status by Authentication Protocol - No Credentials Provided
    Message     :
Credentials were not provided for detected SSH service.
```

181418 - OpenSSH Detection

Synopsis

An OpenSSH-based SSH server was detected on the remote host.

Description

An OpenSSH-based SSH server was detected on the remote host.

See Also

https://www.openssh.com/

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2023/09/14, Modified: 2026/04/28

Plugin Output

tcp/22/ssh

```
Service    : ssh
Version    : 7.2p2
Banner     : SSH-2.0-OpenSSH_7.2p2 Ubuntu-4ubuntu2.2
backported : 1
```

66334 - Patch Report

Synopsis

The remote host is missing several patches.

Description

The remote host is missing one or more security patches. This plugin lists the newest version of each patch to install to make sure the remote host is up-to-date.

Note: Because the 'Show missing patches that have been superseded' setting in your scan policy depends on this plugin, it will always run and cannot be disabled.

Solution

Install the patches listed below.

Risk Factor

None

Plugin Information

Published: 2013/07/08, Modified: 2026/04/28

Plugin Output

tcp/0

```
. You need to take the following action :

[ SSH Terrapin Prefix Truncation Weakness (CVE-2023-48795) (187315) ]

+ Action to take : Contact the vendor for an update with the strict key exchange countermeasures or
 disable the affected algorithms.
```

277650 - Remote Services Not Using Post-Quantum Ciphers

Synopsis

Reports remote services that do not offer post-quantum ciphers.

Description

This plugin reports network services that do not offer post-quantum ciphers. Tenable makes no attempt to determine whether the remote service would be vulnerable to a post-quantum attack.

However, cryptography that depends on the classic difficulty of solving the discrete logarithm problem or on the classic difficulty of large prime factorization is broken by Shor's algorithm. Examples of this are RSA asymmetric encryption and Diffie-Hellman key exchange.

See Also

http://www.nessus.org/u?7a390f87

http://www.nessus.org/u?ad7d6b3b

http://www.nessus.org/u?1c0c61e0

http://www.nessus.org/u?5eec4b28

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2025/12/08, Modified: 2025/12/08

Plugin Output

tcp/22/ssh

```
The target SSH server offers no post-quantum ciphers.
```

70657 - SSH Algorithms and Languages Supported

Synopsis

An SSH server is listening on this port.

Description

This script detects which algorithms and languages are supported by the remote service for encrypting communications.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2013/10/28, Modified: 2026/01/12

Plugin Output

tcp/22/ssh

```
Nessus negotiated the following encryption algorithm(s) with the server :

  Client to Server: aes256-ctr
  Server to Client: aes256-ctr

The server supports the following options for compression_algorithms_server_to_client :

  none
  zlib@openssh.com

The server supports the following options for mac_algorithms_client_to_server :

  hmac-sha1
  hmac-sha1-etm@openssh.com
  hmac-sha2-256
  hmac-sha2-256-etm@openssh.com
  hmac-sha2-512
  hmac-sha2-512-etm@openssh.com
  umac-128-etm@openssh.com
  umac-128@openssh.com
  umac-64-etm@openssh.com
  umac-64@openssh.com

The server supports the following options for server_host_key_algorithms :

  ecdsa-sha2-nistp256
  rsa-sha2-256
  rsa-sha2-512
  ssh-ed25519
```

```
  ssh-rsa

The server supports the following options for encryption_algorithms_client_to_server :

  aes128-ctr
  aes128-gcm@openssh.com
  aes192-ctr
  aes256-ctr
  aes256-gcm@openssh.com
  chacha20-poly1305@openssh.com

The server supports the following options for mac_algorithms_server_to_client :

  hmac-sha1
  hmac-sha1-etm@openssh.com
  hmac-sha2-256
  hmac-sha2-256-etm@openssh.com
  hmac-sha2-512
  hmac-sha2-512-etm@openssh.com
  umac-128-etm@openssh.com
  umac-128@openssh.com
  umac-64-etm@openssh.com
  umac-64@openssh.com

The server supports the following options for kex_algorithms :

  curve25519-sha256@libssh.org
  diffie-hellman-group-exchange-sha256
  diffie-hellman-group14-sha1
  ecdh-sha2-nistp256
  ecdh-sha2-nistp384
  ecdh-sha2-nistp521

The server supports the following options for compression_algorithms_client_to_server :

  none
  zlib@openssh.com

The server supports the following options for encryption_algorithms_server_to_client :

  aes128-ctr
  aes128-gcm@openssh.com
  aes192-ctr
  aes256-ctr
  aes256-gcm@openssh.com
  chacha20-poly1305@openssh.com
```

149334 - SSH Password Authentication Accepted

Synopsis

The SSH server on the remote host accepts password authentication.

Description

The SSH server on the remote host accepts password authentication.

See Also

https://tools.ietf.org/html/rfc4252#section-8

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2021/05/07, Modified: 2021/05/07

Plugin Output

tcp/22/ssh

10881 - SSH Protocol Versions Supported

Synopsis

A SSH server is running on the remote host.

Description

This plugin determines the versions of the SSH protocol supported by the remote SSH daemon.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2002/03/06, Modified: 2026/01/12

Plugin Output

tcp/22/ssh

```
The remote SSH daemon supports the following versions of the
SSH protocol :

  - 1.99
  - 2.0
```

153588 - SSH SHA-1 HMAC Algorithms Enabled

Synopsis

The remote SSH server is configured to enable SHA-1 HMAC algorithms.

Description

The remote SSH server is configured to enable SHA-1 HMAC algorithms.

Although NIST has formally deprecated use of SHA-1 for digital signatures, SHA-1 is still considered secure for HMAC as the security of HMAC does not rely on the underlying hash function being resistant to collisions.

Note that this plugin only checks for the options of the remote SSH server.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2021/09/23, Modified: 2022/04/05

Plugin Output

tcp/22/ssh

```
The following client-to-server SHA-1 Hash-based Message Authentication Code (HMAC) algorithms are
 supported :

  umac-64-etm@openssh.com,umac-128-etm@openssh.com,hmac-sha2-256-etm@openssh.com,hmac-sha2-512-
etm@openssh.com,hmac-sha1-etm@openssh.com,umac-64@openssh.com,umac-128@openssh.com,hmac-
sha2-256,hmac-sha2-512,hmac-sha1

The following server-to-client SHA-1 Hash-based Message Authentication Code (HMAC) algorithms are
 supported :

  umac-64-etm@openssh.com,umac-128-etm@openssh.com,hmac-sha2-256-etm@openssh.com,hmac-sha2-512-
etm@openssh.com,hmac-sha1-etm@openssh.com,umac-64@openssh.com,umac-128@openssh.com,hmac-
sha2-256,hmac-sha2-512,hmac-sha1
```

10267 - SSH Server Type and Version Information

Synopsis

An SSH server is listening on this port.

Description

It is possible to obtain information about the remote SSH server by sending an empty authentication request.

Solution

n/a

Risk Factor

None

References

XREF IAVT:0001-T-0933

Plugin Information

Published: 1999/10/12, Modified: 2024/07/24

Plugin Output

tcp/22/ssh

```
SSH version : SSH-2.0-OpenSSH_7.2p2 Ubuntu-4ubuntu2.2
SSH supported authentication : publickey,password
```

22964 - Service Detection

Synopsis

The remote service could be identified.

Description

Nessus was able to identify the remote service by its banner or by looking at the error message it sends when it receives an HTTP request.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/08/19, Modified: 2026/03/23

Plugin Output

tcp/22/ssh

```
An SSH server is running on this port.
```

22964 - Service Detection

Synopsis

The remote service could be identified.

Description

Nessus was able to identify the remote service by its banner or by looking at the error message it sends when it receives an HTTP request.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/08/19, Modified: 2026/03/23

Plugin Output

tcp/80/www

```
A web server is running on this port.
```

298387 - Shor's Harvest Now Decrypt Later

Synopsis

Reports remote services potentially vulnerable to Shor's Algorithm.

Description

This plugin reports network services that may be vulnerable now to a future attack by adversaries using a cryptographically relevant quantum computer (CRQC). Shor's is a theoretical algorithm that leverages the unique ability of quantum computation to do massively parallel calculations developed by Peter Shor in 1994.

This algorithm easily computes two classically difficult mathematical problems used in modern cryptography; discrete logarithms, and factoring numbers formed by multiplying large primes. Shor's reduces both of these problems from taking exponential time in chosen cases to being solvable in polynomial time.

Asymmetric encryption algorithms such as RSA, Diffie-Hellman and Elliptic Curve Diffie-Hellman are impacted by Shor's Algorithm. The most common uses of these algorithms are in symmetric key establishment and authentication. These uses render Shor's Algorithm particularly dangerous because it may give an adversary the ability to harvest network communications now, and in the future, when a CRQC becomes available, extract the symmetric key and decrypt the communication.

See Also

http://www.nessus.org/u?54fba2c1

Solution

Replace affected ciphers with algorithms chosen to resist CRQC attack.

Risk Factor

None

Plugin Information

Published: 2026/02/09, Modified: 2026/04/13

Plugin Output

tcp/0

```
The SSH service on port 22 offers these ciphers vulnerable to Shor's:
diffie-hellman-group-exchange-sha256
ecdh-sha2-nistp256
ecdh-sha2-nistp521
curve25519-sha256@libssh.org
ecdh-sha2-nistp384
diffie-hellman-group14-sha1
```

25220 - TCP/IP Timestamps Supported

Synopsis

The remote service implements TCP timestamps.

Description

The remote host implements TCP timestamps, as defined by RFC1323. A side effect of this feature is that the uptime of the remote host can sometimes be computed.

See Also

http://www.ietf.org/rfc/rfc1323.txt

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/05/16, Modified: 2023/10/17

Plugin Output

tcp/0

110723 - Target Credential Status by Authentication Protocol - No Credentials Provided

Synopsis

Nessus was able to find common ports used for local checks, however, no credentials were provided in the scan policy.

Description

Nessus was not able to successfully authenticate directly to the remote target on an available authentication protocol. Nessus was able to connect to the remote port and identify that the service running on the port supports an authentication protocol, but Nessus failed to authenticate to the remote service using the provided credentials. There may have been a protocol failure that prevented authentication from being attempted or all of the provided credentials for the authentication protocol may be invalid. See plugin output for error details.

Please note the following :

- This plugin reports per protocol, so it is possible for valid credentials to be provided for one protocol and not another. For example, authentication may succeed via SSH but fail via SMB, while no credentials were provided for an available SNMP service.

- Providing valid credentials for all available authentication protocols may improve scan coverage, but the value of successful authentication for a given protocol may vary from target to target depending upon what data (if any) is gathered from the target via that protocol. For example, successful authentication via SSH is more valuable for Linux targets than for Windows targets, and likewise successful authentication via SMB is more valuable for Windows targets than for Linux targets.

Solution

n/a

Risk Factor

None

References

XREF IAVB:0001-B-0504

Plugin Information

Published: 2018/06/27, Modified: 2024/04/19

Plugin Output

tcp/0

```
SSH was detected on port 22 but no credentials were provided.
SSH local checks were not enabled.
```

10287 - Traceroute Information

Synopsis

It was possible to obtain traceroute information.

Description

Makes a traceroute to the remote host.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 1999/11/27, Modified: 2026/04/27

Plugin Output

udp/0

```
For your information, here is the traceroute from 10.10.10.174 to 10.10.10.102 :
10.10.10.174
10.10.10.102

Hop Count: 1
```

66717 - mDNS Detection (Local Network)

Synopsis

It is possible to obtain information about the remote host.

Description

The remote service understands the Bonjour (also known as ZeroConf or mDNS) protocol, which allows anyone to uncover information from the remote host such as its operating system type and exact version, its hostname, and the list of services it is running.

This plugin attempts to discover mDNS used by hosts residing on the same network segment as Nessus.

Solution

Filter incoming traffic to UDP port 5353, if desired.

Risk Factor

None

Plugin Information

Published: 2013/05/31, Modified: 2013/05/31

Plugin Output

udp/5353/mdns

```
Nessus was able to extract the following information :

  - mDNS hostname       : vtcsec.local.
```

10.10.10.109

12	5	2	1	33
CRITICAL	HIGH	MEDIUM	LOW	INFO

Scan Information

Start time: Tue May 5 14:52:58 2026
End time: Tue May 5 14:56:46 2026

Host Information

Netbios Name: BOX
IP: 10.10.10.109
MAC Address: 08:00:27:2B:B2:C9
OS: Microsoft Windows XP\nMicrosoft Windows XP Service Pack 1

Vulnerabilities

11808 - MS03-026: Microsoft RPC Interface Buffer Overrun (823980) (uncredentialed check)

Synopsis

Arbitrary code can be executed on the remote host.

Description

The remote version of Windows contains a flaw in the function RemoteActivation() in its RPC interface that could allow an attacker to execute arbitrary code on the remote host with the SYSTEM privileges.

A series of worms (Blaster) are known to exploit this vulnerability in the wild.

See Also

https://docs.microsoft.com/en-us/security-updates/SecurityBulletins/2003/ms03-026

Solution

Microsoft has released patches for Windows NT, 2000, XP, and 2003.

Risk Factor

Critical

VPR Score

7.3

EPSS Score

0.9057

CVSS v2.0 Base Score

10.0 (CVSS2#AV:N/AC:L/Au:N/C:C/I:C/A:C)

CVSS v2.0 Temporal Score

8.3 (CVSS2#E:F/RL:OF/RC:C)

References

BID	8205
CVE	CVE-2003-0352
MSKB	823980
XREF	MSFT:MS03-026

Exploitable With

CANVAS (true) Core Impact (true) Metasploit (true)

Plugin Information

Published: 2003/07/28, Modified: 2018/11/15

Plugin Output

tcp/445/cifs

11835 - MS03-039: Microsoft RPC Interface Buffer Overrun (824146) (uncredentialed check)

Synopsis

Arbitrary code can be executed on the remote host.

Description

The remote host is running a version of Windows that has a flaw in its RPC interface, which may allow an attacker to execute arbitrary code and gain SYSTEM privileges.

An attacker or a worm could use it to gain the control of this host.

Note that this is NOT the same bug as the one described in MS03-026, which fixes the flaw exploited by the 'MSBlast' (or LoveSan) worm.

See Also

https://docs.microsoft.com/en-us/security-updates/SecurityBulletins/2003/ms03-039

Solution

Microsoft has released patches for Windows NT, 2000, XP, and 2003.

Risk Factor

Critical

VPR Score

6.5

EPSS Score

0.6064

CVSS v2.0 Base Score

10.0 (CVSS2#AV:N/AC:L/Au:N/C:C/I:C/A:C)

CVSS v2.0 Temporal Score

7.8 (CVSS2#E:POC/RL:OF/RC:C)

References

BID	8458
BID	8460
CVE	CVE-2003-0715

CVE	CVE-2003-0528
CVE	CVE-2003-0605
MSKB	824146
XREF	MSFT:MS03-039

Plugin Information

Published: 2003/09/10, Modified: 2018/11/15

Plugin Output

tcp/445/cifs

11890 - MS03-043: Buffer Overrun in Messenger Service (828035) (uncredentialed check)

Synopsis

Arbitrary code can be executed on the remote host.

Description

A security vulnerability exists in the Messenger Service that could allow arbitrary code execution on an affected system. An attacker who successfully exploited this vulnerability could be able to run code with Local System privileges on an affected system or could cause the Messenger Service to fail.

Disabling the Messenger Service will prevent the possibility of attack.

This plugin actually tests for the presence of this flaw.

See Also

https://docs.microsoft.com/en-us/security-updates/SecurityBulletins/2003/ms03-043

Solution

Microsoft has released a set of patches for Windows NT, 2000, XP and 2003.

Risk Factor

Critical

VPR Score

8.9

EPSS Score

0.8576

CVSS v2.0 Base Score

10.0 (CVSS2#AV:N/AC:L/Au:N/C:C/I:C/A:C)

CVSS v2.0 Temporal Score

8.7 (CVSS2#E:H/RL:OF/RC:C)

References

BID	8826
CVE	CVE-2003-0717
MSKB	828035

XREF MSFT:MS03-043

Plugin Information

Published: 2003/10/16, Modified: 2019/03/06

Plugin Output

udp/135

12054 - MS04-007: ASN.1 Vulnerability Could Allow Code Execution (828028) (uncredentialed check) (NTLM)

Synopsis

Arbitrary code can be executed on the remote host.

Description

The remote Windows host has an ASN.1 library that could allow an attacker to execute arbitrary code on this host.

To exploit this flaw, an attacker would need to send a specially crafted ASN.1 encoded packet with improperly advertised lengths.

This particular check sent a malformed NTLM packet and determined that the remote host is not patched.

See Also

https://docs.microsoft.com/en-us/security-updates/SecurityBulletins/2004/ms04-007

Solution

Microsoft has released patches for Windows NT, 2000, XP, and 2003.

Risk Factor

Critical

CVSS v3.0 Base Score

9.8 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H)

CVSS v3.0 Temporal Score

9.1 (CVSS:3.0/E:F/RL:O/RC:C)

VPR Score

7.4

EPSS Score

0.8965

CVSS v2.0 Base Score

10.0 (CVSS2#AV:N/AC:L/Au:N/C:C/I:C/A:C)

CVSS v2.0 Temporal Score

8.3 (CVSS2#E:F/RL:OF/RC:C)

References

BID	9633
BID	9635
BID	9743
BID	13300
CVE	CVE-2003-0818
MSKB	828028
XREF	MSFT:MS04-007

Exploitable With

CANVAS (true) Core Impact (true) Metasploit (true)

Plugin Information

Published: 2004/02/13, Modified: 2018/11/15

Plugin Output

tcp/445/cifs

12209 - MS04-011: Security Update for Microsoft Windows (835732) (uncredentialed check)

Synopsis

Arbitrary code can be executed on the remote host due to a flaw in the LSASS service.

Description

The remote version of Windows contains a flaw in the function 'DsRolerUpgradeDownlevelServer' of the Local Security Authority Server Service (LSASS) that allows an attacker to execute arbitrary code on the remote host with SYSTEM privileges.

A series of worms (Sasser) are known to exploit this vulnerability in the wild.

See Also

https://docs.microsoft.com/en-us/security-updates/SecurityBulletins/2004/ms04-011

Solution

Microsoft has released a set of patches for Windows NT, 2000, XP and 2003.

Risk Factor

Critical

CVSS v3.0 Base Score

9.8 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H)

CVSS v3.0 Temporal Score

9.4 (CVSS:3.0/E:H/RL:O/RC:C)

VPR Score

8.9

EPSS Score

0.89

CVSS v2.0 Base Score

10.0 (CVSS2#AV:N/AC:L/Au:N/C:C/I:C/A:C)

CVSS v2.0 Temporal Score

8.7 (CVSS2#E:H/RL:OF/RC:C)

References

BID	10108
CVE	CVE-2003-0533
MSKB	835732
XREF	MSFT:MS04-011

Exploitable With

CANVAS (true) Core Impact (true) Metasploit (true)

Plugin Information

Published: 2004/04/15, Modified: 2018/11/15

Plugin Output

tcp/445/cifs

21655 - MS04-012: Cumulative Update for Microsoft RPC/DCOM (828741) (uncredentialed check)

Synopsis

Arbitrary code can be executed on the remote host.

Description

The remote host has multiple bugs in its RPC/DCOM implementation (828741).

An attacker may exploit one of these flaws to execute arbitrary code on the remote system.

See Also

https://docs.microsoft.com/en-us/security-updates/SecurityBulletins/2004/ms04-012

Solution

Microsoft has released a set of patches for Windows NT, 2000, XP and 2003.

Risk Factor

Critical

VPR Score

5.2

EPSS Score

0.5423

CVSS v2.0 Base Score

10.0 (CVSS2#AV:N/AC:L/Au:N/C:C/I:C/A:C)

CVSS v2.0 Temporal Score

7.4 (CVSS2#E:U/RL:OF/RC:C)

References

BID	10121
BID	10123
BID	10127
BID	8811
CVE	CVE-2003-0813
CVE	CVE-2004-0116

CVE	CVE-2003-0807
CVE	CVE-2004-0124
MSKB	828741
XREF	MSFT:MS04-012

Plugin Information

Published: 2007/03/16, Modified: 2018/11/15

Plugin Output

tcp/135/epmap

18502 - MS05-027: Vulnerability in SMB Could Allow Remote Code Execution (896422) (uncredentialed check)

Synopsis

Arbitrary code can be executed on the remote host due to a flaw in the SMB implementation.

Description

The remote version of Windows contains a flaw in the Server Message Block (SMB) implementation that may allow an attacker to execute arbitrary code on the remote host.

An attacker does not need to be authenticated to exploit this flaw.

See Also

https://docs.microsoft.com/en-us/security-updates/SecurityBulletins/2005/ms05-027

Solution

Microsoft has released a set of patches for Windows 2000, XP and 2003.

Risk Factor

Critical

VPR Score

6.8

EPSS Score

0.4652

CVSS v2.0 Base Score

10.0 (CVSS2#AV:N/AC:L/Au:N/C:C/I:C/A:C)

CVSS v2.0 Temporal Score

8.3 (CVSS2#E:F/RL:OF/RC:C)

References

BID	13942
CVE	CVE-2005-1206
MSKB	896422
XREF	MSFT:MS05-027

Exploitable With

Core Impact (true)

Plugin Information

Published: 2005/06/16, Modified: 2018/11/15

Plugin Output

tcp/445/cifs

22194 - MS06-040: Vulnerability in Server Service Could Allow Remote Code Execution (921883) (uncredentialed check)

Synopsis

Arbitrary code can be executed on the remote host due to a flaw in the 'Server' service.

Description

The remote host is vulnerable to a buffer overrun in the 'Server'
service that may allow an attacker to execute arbitrary code on the remote host with 'SYSTEM' privileges.

See Also

https://docs.microsoft.com/en-us/security-updates/SecurityBulletins/2006/ms06-040

Solution

Microsoft has released a set of patches for Windows 2000, XP and 2003.

Risk Factor

Critical

VPR Score

7.4

EPSS Score

0.8896

CVSS v2.0 Base Score

10.0 (CVSS2#AV:N/AC:L/Au:N/C:C/I:C/A:C)

CVSS v2.0 Temporal Score

8.3 (CVSS2#E:F/RL:OF/RC:C)

References

BID	19409
CVE	CVE-2006-3439
MSKB	921883
XREF	MSFT:MS06-040

Exploitable With

CANVAS (true) Core Impact (true) Metasploit (true)

Plugin Information

Published: 2006/08/08, Modified: 2018/11/15

Plugin Output

tcp/445/cifs

34477 - MS08-067: Microsoft Windows Server Service Crafted RPC Request Handling Remote Code Execution (958644) (ECLIPSEDWING) (uncredentialed check)

Synopsis

The remote Windows host is affected by a remote code execution vulnerability.

Description

The remote Windows host is affected by a remote code execution vulnerability in the 'Server' service due to improper handling of RPC requests. An unauthenticated, remote attacker can exploit this, via a specially crafted RPC request, to execute arbitrary code with 'System'

privileges.

ECLIPSEDWING is one of multiple Equation Group vulnerabilities and exploits disclosed on 2017/04/14 by a group known as the Shadow Brokers.

See Also

https://www.nessus.org/u?adf86aac

Solution

Microsoft has released a set of patches for Windows 2000, XP, 2003, Vista and 2008.

Risk Factor

Critical

CVSS v3.0 Base Score

9.8 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H)

CVSS v3.0 Temporal Score

9.4 (CVSS:3.0/E:H/RL:O/RC:C)

VPR Score

8.9

EPSS Score

0.9348

CVSS v2.0 Base Score

10.0 (CVSS2#AV:N/AC:L/Au:N/C:C/I:C/A:C)

CVSS v2.0 Temporal Score

8.7 (CVSS2#E:H/RL:OF/RC:C)

STIG Severity

I

References

BID	31874
CVE	CVE-2008-4250
MSKB	958644
XREF	MSFT:MS08-067
XREF	CERT:827267
XREF	IAVA:2008-A-0081-S
XREF	EDB-ID:6824
XREF	EDB-ID:7104
XREF	EDB-ID:7132
XREF	CWE:94

Exploitable With

CANVAS (true) Core Impact (true) Metasploit (true)

Plugin Information

Published: 2008/10/23, Modified: 2020/08/05

Plugin Output

tcp/445/cifs

35362 - MS09-001: Microsoft Windows SMB Vulnerabilities Remote Code Execution (958687) (uncredentialed check)

Synopsis

It is possible to crash the remote host due to a flaw in SMB.

Description

The remote host is affected by a memory corruption vulnerability in SMB that may allow an attacker to execute arbitrary code or perform a denial of service against the remote host.

See Also

http://www.microsoft.com/technet/security/bulletin/ms09-001.mspx

Solution

Microsoft has released a set of patches for Windows 2000, XP, 2003, Vista and 2008.

Risk Factor

Critical

VPR Score

7.4

EPSS Score

0.7395

CVSS v2.0 Base Score

10.0 (CVSS2#AV:N/AC:L/Au:N/C:C/I:C/A:C)

CVSS v2.0 Temporal Score

7.8 (CVSS2#E:POC/RL:OF/RC:C)

References

BID	31179
BID	33121
BID	33122
CVE	CVE-2008-4834
CVE	CVE-2008-4835
CVE	CVE-2008-4114

MSKB	958687
XREF	MSFT:MS09-001
XREF	CWE:399

Exploitable With

Core Impact (true) Metasploit (true)

Plugin Information

Published: 2009/01/13, Modified: 2026/04/08

Plugin Output

tcp/445/cifs

73182 - Microsoft Windows XP Unsupported Installation Detection

Synopsis

The remote operating system is no longer supported.

Description

The remote host is running Microsoft Windows XP. Support for this operating system by Microsoft ended April 8th, 2014.

Lack of support implies that no new security patches for the product will be released by the vendor. As a result, it is likely to contain security vulnerabilities. Furthermore, Microsoft is unlikely to investigate or acknowledge reports of vulnerabilities.

See Also

http://www.nessus.org/u?2f80aef2

http://www.nessus.org/u?321523eb

https://blogs.technet.microsoft.com/filecab/2016/09/16/stop-using-smb1/

http://www.nessus.org/u?8dcab5e4

Solution

Upgrade to a version of Windows that is currently supported.

Risk Factor

Critical

CVSS v3.0 Base Score

10.0 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:C/C:H/I:H/A:H)

CVSS v3.0 Temporal Score

9.0 (CVSS:3.0/E:P/RL:O/RC:C)

CVSS v2.0 Base Score

10.0 (CVSS2#AV:N/AC:L/Au:N/C:C/I:C/A:C)

CVSS v2.0 Temporal Score

7.8 (CVSS2#E:POC/RL:OF/RC:C)

References

XREF	EDB-ID:41929
XREF	IAVA:0001-A-0023

Plugin Information

Published: 2014/03/25, Modified: 2020/09/22

Plugin Output

tcp/0

108797 - Unsupported Windows OS (remote)

Synopsis

The remote OS or service pack is no longer supported.

Description

The remote version of Microsoft Windows is either missing a service pack or is no longer supported. As a result, it is likely to contain security vulnerabilities.

See Also

https://support.microsoft.com/en-us/lifecycle

Solution

Upgrade to a supported service pack or operating system

Risk Factor

Critical

CVSS v3.0 Base Score

10.0 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:C/C:H/I:H/A:H)

CVSS v2.0 Base Score

10.0 (CVSS2#AV:N/AC:L/Au:N/C:C/I:C/A:C)

References

XREF IAVA:0001-A-0501

Plugin Information

Published: 2018/04/03, Modified: 2025/10/21

Plugin Output

tcp/0

```
The following Windows version is installed and not supported:

Microsoft Windows XP\nMicrosoft Windows XP Service Pack 1
```

13852 - MS04-022: Microsoft Windows Task Scheduler Remote Overflow (841873) (uncredentialed check)

Synopsis

Arbitrary code can be executed on the remote host.

Description

There is a flaw in the Task Scheduler application which could allow a remote attacker to execute code remotely. There are many attack vectors for this flaw. An attacker, exploiting this flaw, would need to either have the ability to connect to the target machine or be able to coerce a local user to either install a .job file or browse to a malicious website.

See Also

http://www.nessus.org/u?e22930a6

Solution

Microsoft has released a set of patches for Windows 2000, XP and 2003.

Risk Factor

Critical

CVSS v3.0 Base Score

8.8 (CVSS:3.0/AV:N/AC:L/PR:N/UI:R/S:U/C:H/I:H/A:H)

CVSS v3.0 Temporal Score

8.2 (CVSS:3.0/E:F/RL:O/RC:C)

VPR Score

8.9

EPSS Score

0.8136

CVSS v2.0 Base Score

10.0 (CVSS2#AV:N/AC:L/Au:N/C:C/I:C/A:C)

CVSS v2.0 Temporal Score

8.7 (CVSS2#E:H/RL:OF/RC:C)

References

BID	10708
CVE	CVE-2004-0212
MSKB	841873
XREF	MSFT:MS04-022

Plugin Information

Published: 2004/07/29, Modified: 2022/10/05

Plugin Output

tcp/1025/dce-rpc

19407 - MS05-043: Vulnerability in Printer Spooler Service Could Allow Remote Code Execution (896423) (uncredentialed check)

Synopsis

Arbitrary code can be executed on the remote host due to a flaw in the Spooler service.

Description

The remote host contains a version of the Print Spooler service that may allow an attacker to execute code on the remote host or crash the spooler service.

An attacker can execute code on the remote host with a NULL session against :

- Windows 2000

An attacker can crash the remote service with a NULL session against :

- Windows 2000
- Windows XP SP1

An attacker needs valid credentials to crash the service against :

- Windows 2003
- Windows XP SP2

See Also

http://www.nessus.org/u?3f514685

Solution

Microsoft has released a set of patches for Windows 2000, XP and 2003.

Risk Factor

High

CVSS v3.0 Base Score

7.3 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:L/I:L/A:L)

CVSS v3.0 Temporal Score

6.8 (CVSS:3.0/E:F/RL:O/RC:C)

VPR Score

4.9

EPSS Score

0.2788

CVSS v2.0 Base Score

7.5 (CVSS2#AV:N/AC:L/Au:N/C:P/I:P/A:P)

CVSS v2.0 Temporal Score

6.2 (CVSS2#E:F/RL:OF/RC:C)

References

BID	14514
CVE	CVE-2005-1984
MSKB	896423
XREF	MSFT:MS05-043

Exploitable With

CANVAS (true) Core Impact (true)

Plugin Information

Published: 2005/08/09, Modified: 2022/10/05

Plugin Output

tcp/445/cifs

22034 - MS06-035: Vulnerability in Server Service Could Allow Remote Code Execution (917159) (uncredentialed check)

Synopsis

Arbitrary code can be executed on the remote host due to a flaw in the 'Server' service.

Description

The remote host is vulnerable to heap overflow in the 'Server' service that may allow an attacker to execute arbitrary code on the remote host with 'SYSTEM' privileges.

In addition to this, the remote host is also affected by an information disclosure vulnerability in SMB that may allow an attacker to obtain portions of the memory of the remote host.

See Also

https://docs.microsoft.com/en-us/security-updates/SecurityBulletins/2006/ms06-035

https://www.tenable.com/security/research/tra-2006-01

Solution

Microsoft has released a set of patches for Windows 2000, XP and 2003.

Risk Factor

High

VPR Score

6.8

EPSS Score

0.7584

CVSS v2.0 Base Score

7.5 (CVSS2#AV:N/AC:L/Au:N/C:P/I:P/A:P)

CVSS v2.0 Temporal Score

6.2 (CVSS2#E:F/RL:OF/RC:C)

References

BID	18863
BID	18891

CVE	CVE-2006-1314
CVE	CVE-2006-1315
MSKB	917159
XREF	TRA:TRA-2006-01
XREF	MSFT:MS06-035

Exploitable With

Core Impact (true)

Plugin Information

Published: 2006/07/12, Modified: 2018/11/15

Plugin Output

tcp/445/cifs

97833 - MS17-010: Security Update for Microsoft Windows SMB Server (4013389) (ETERNALBLUE) (ETERNALCHAMPION) (ETERNALROMANCE) (ETERNALSYNERGY) (WannaCry) (EternalRocks) (Petya) (uncredentialed check)

Synopsis

The remote Windows host is affected by multiple vulnerabilities.

Description

The remote Windows host is affected by the following vulnerabilities :

- Multiple remote code execution vulnerabilities exist in Microsoft Server Message Block 1.0 (SMBv1) due to improper handling of certain requests. An unauthenticated, remote attacker can exploit these vulnerabilities, via a specially crafted packet, to execute arbitrary code. (CVE-2017-0143, CVE-2017-0144, CVE-2017-0145, CVE-2017-0146, CVE-2017-0148)

- An information disclosure vulnerability exists in Microsoft Server Message Block 1.0 (SMBv1) due to improper handling of certain requests. An unauthenticated, remote attacker can exploit this, via a specially crafted packet, to disclose sensitive information. (CVE-2017-0147)

ETERNALBLUE, ETERNALCHAMPION, ETERNALROMANCE, and ETERNALSYNERGY are four of multiple Equation Group vulnerabilities and exploits disclosed on 2017/04/14 by a group known as the Shadow Brokers. WannaCry / WannaCrypt is a ransomware program utilizing the ETERNALBLUE exploit, and EternalRocks is a worm that utilizes seven Equation Group vulnerabilities. Petya is a ransomware program that first utilizes CVE-2017-0199, a vulnerability in Microsoft Office, and then spreads via ETERNALBLUE.

See Also

http://www.nessus.org/u?68fc8eff

http://www.nessus.org/u?321523eb

http://www.nessus.org/u?065561d0

http://www.nessus.org/u?d9f569cf

https://blogs.technet.microsoft.com/filecab/2016/09/16/stop-using-smb1/

http://www.nessus.org/u?b9d9ebf9

http://www.nessus.org/u?8dcab5e4

http://www.nessus.org/u?234f8ef8

http://www.nessus.org/u?4c7e0cf3

https://github.com/stamparm/EternalRocks/

http://www.nessus.org/u?59db5b5b

Solution

Microsoft has released a set of patches for Windows Vista, 2008, 7, 2008 R2, 2012, 8.1, RT 8.1, 2012 R2, 10, and 2016. Microsoft has also released emergency patches for Windows operating systems that are no longer supported, including Windows XP, 2003, and 8.

For unsupported Windows operating systems, e.g. Windows XP, Microsoft recommends that users discontinue the use of SMBv1. SMBv1 lacks security features that were included in later SMB versions.

SMBv1 can be disabled by following the vendor instructions provided in Microsoft KB2696547. Additionally, US-CERT recommends that users block SMB directly by blocking TCP port 445 on all network boundary devices. For SMB over the NetBIOS API, block TCP ports 137 / 139 and UDP ports 137 / 138 on all network boundary devices.

Risk Factor

High

CVSS v3.0 Base Score

8.8 (CVSS:3.0/AV:N/AC:L/PR:L/UI:N/S:U/C:H/I:H/A:H)

CVSS v3.0 Temporal Score

8.4 (CVSS:3.0/E:H/RL:O/RC:C)

VPR Score

9.8

EPSS Score

0.9432

CVSS v2.0 Base Score

9.3 (CVSS2#AV:N/AC:M/Au:N/C:C/I:C/A:C)

CVSS v2.0 Temporal Score

8.1 (CVSS2#E:H/RL:OF/RC:C)

STIG Severity

I

References

BID	96703
BID	96704
BID	96705
BID	96706
BID	96707
BID	96709
CVE	CVE-2017-0143
CVE	CVE-2017-0144
CVE	CVE-2017-0145

CVE	CVE-2017-0146
CVE	CVE-2017-0147
CVE	CVE-2017-0148
MSKB	4012212
MSKB	4012213
MSKB	4012214
MSKB	4012215
MSKB	4012216
MSKB	4012217
MSKB	4012606
MSKB	4013198
MSKB	4013429
MSKB	4012598
XREF	EDB-ID:41891
XREF	EDB-ID:41987
XREF	MSFT:MS17-010
XREF	IAVA:2017-A-0065
XREF	CISA-KNOWN-EXPLOITED:2022/05/03
XREF	CISA-KNOWN-EXPLOITED:2022/08/10
XREF	CISA-KNOWN-EXPLOITED:2022/04/15
XREF	CISA-KNOWN-EXPLOITED:2022/04/27
XREF	CISA-KNOWN-EXPLOITED:2022/06/14

Exploitable With

CANVAS (true) Core Impact (true) Metasploit (true)

Plugin Information

Published: 2017/03/20, Modified: 2025/12/29

Plugin Output

tcp/445/cifs

```
Sent:
00000054ff534d4225000000001803c800000000000000000000000000810d10008000110000000
00ffffffff0000000000000000000000005400000054000200230000001100005c00500049005000
45005c0000000000

Received:
ff534d4225050200c09803c8000000000000000000000000000810d100080001000000
```

26920 - SMB NULL Session Authentication

Synopsis

It is possible to log into the remote host with a NULL session.

Description

The remote host is running and SMB protocol. It is possible to log into the browser or spoolss pipes using a NULL session (i.e., with no login or password).

Depending on the configuration, it may be possible for an unauthenticated, remote attacker to leverage this issue to get information about the remote host.

See Also

http://www.nessus.org/u?e32d594f

http://www.nessus.org/u?9182e66b

http://www.nessus.org/u?a33fe205

Solution

Please contact the product vendor for recommended solutions.

Risk Factor

High

CVSS v3.0 Base Score

7.3 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:L/I:L/A:L)

CVSS v3.0 Temporal Score

7.0 (CVSS:3.0/E:H/RL:O/RC:C)

VPR Score

6.6

EPSS Score

0.0866

CVSS v2.0 Base Score

7.5 (CVSS2#AV:N/AC:L/Au:N/C:P/I:P/A:P)

CVSS v2.0 Temporal Score

6.5 (CVSS2#E:H/RL:OF/RC:C)

References

BID	494
CVE	CVE-1999-0519
CVE	CVE-1999-0520
CVE	CVE-2002-1117

Plugin Information

Published: 2007/10/04, Modified: 2022/10/07

Plugin Output

tcp/445/cifs

```
It was possible to bind to the following pipes:
  - browser
```

16337 - MS05-007: Vulnerability in Windows Could Allow Information Disclosure (888302) (uncredentialed check)

Synopsis

System information about the remote host can be obtained by an anonymous user.

Description

The remote version of Windows contains a flaw that may allow an attacker to cause it to disclose information over the use of a named pipe through a NULL session.

An attacker may exploit this flaw to gain more knowledge about the remote host.

See Also

https://docs.microsoft.com/en-us/security-updates/SecurityBulletins/2005/ms05-007

Solution

Microsoft has released a set of patches for Windows XP.

Risk Factor

Medium

VPR Score

4.7

EPSS Score

0.4719

CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:P/I:N/A:N)

CVSS v2.0 Temporal Score

3.7 (CVSS2#E:U/RL:OF/RC:C)

References

BID	12486
CVE	CVE-2005-0051
MSKB	888302
XREF	MSFT:MS05-007

Plugin Information

Published: 2005/02/10, Modified: 2018/11/15

Plugin Output

tcp/445/cifs

57608 - SMB Signing not required

Synopsis

Signing is not required on the remote SMB server.

Description

Signing is not required on the remote SMB server. An unauthenticated, remote attacker can exploit this to conduct man-in-the-middle attacks against the SMB server.

See Also

http://www.nessus.org/u?df39b8b3

http://technet.microsoft.com/en-us/library/cc731957.aspx

http://www.nessus.org/u?74b80723

https://www.samba.org/samba/docs/current/man-html/smb.conf.5.html

http://www.nessus.org/u?a3cac4ea

Solution

Enforce message signing in the host's configuration. On Windows, this is found in the policy setting 'Microsoft network server: Digitally sign communications (always)'. On Samba, the setting is called 'server signing'. See the 'see also' links for further details.

Risk Factor

Medium

CVSS v3.0 Base Score

5.3 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:N/I:L/A:N)

CVSS v3.0 Temporal Score

4.6 (CVSS:3.0/E:U/RL:O/RC:C)

CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:N/I:P/A:N)

CVSS v2.0 Temporal Score

3.7 (CVSS2#E:U/RL:OF/RC:C)

Plugin Information

Published: 2012/01/19, Modified: 2022/10/05

Plugin Output

tcp/445/cifs

10114 - ICMP Timestamp Request Remote Date Disclosure

Synopsis

It is possible to determine the exact time set on the remote host.

Description

The remote host answers to an ICMP timestamp request. This allows an attacker to know the date that is set on the targeted machine, which may assist an unauthenticated, remote attacker in defeating time-based authentication protocols.

Timestamps returned from machines running Windows Vista / 7 / 2008 / 2008 R2 are deliberately incorrect, but usually within 1000 seconds of the actual system time.

Solution

Filter out the ICMP timestamp requests (13), and the outgoing ICMP timestamp replies (14).

Risk Factor

Low

VPR Score

2.2

EPSS Score

0.0037

CVSS v2.0 Base Score

2.1 (CVSS2#AV:L/AC:L/Au:N/C:P/I:N/A:N)

References

CVE	CVE-1999-0524
XREF	CWE:200

Plugin Information

Published: 1999/08/01, Modified: 2024/10/07

Plugin Output

icmp/0

```
This host returns non-standard timestamps (high bit is set)
```

```
The ICMP timestamps might be in little endian format (not in network format)
The difference between the local and remote clocks is -1 seconds.
```

45590 - Common Platform Enumeration (CPE)

Synopsis

It was possible to enumerate CPE names that matched on the remote system.

Description

By using information obtained from a Nessus scan, this plugin reports CPE (Common Platform Enumeration) matches for various hardware and software products found on a host.

Note that if an official CPE is not available for the product, this plugin computes the best possible CPE based on the information available from the scan.

See Also

http://cpe.mitre.org/

https://nvd.nist.gov/products/cpe

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2010/04/21, Modified: 2026/01/05

Plugin Output

tcp/0

```
The remote operating system matched the following CPE :

  cpe:/o:microsoft:windows_xp::sp1 -> Microsoft Windows XP
```

10736 - DCE Services Enumeration

Synopsis

A DCE/RPC service is running on the remote host.

Description

By sending a Lookup request to the portmapper (TCP 135 or epmapper PIPE) it was possible to enumerate the Distributed Computing Environment (DCE) services running on the remote port. Using this information it is possible to connect and bind to each service by sending an RPC request to the remote port/pipe.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2001/08/26, Modified: 2021/10/04

Plugin Output

tcp/135/epmap

```
The following DCERPC services are available locally :

Object UUID : 00000000-0000-0000-0000-000000000000
UUID : 4b112204-0e19-11d3-b42b-0000f81feb9f, version 1.0
Description : SSDP service
Windows process : unknow
Type : Local RPC service
Named pipe : LRPC00000478.00000001

Object UUID : 00000000-0000-0000-0000-000000000000
UUID : 5a7b91f8-ff00-11d0-a9b2-00c04fb6e6fc, version 1.0
Description : Messenger Service
Windows process : svchost.exe
Annotation : Messenger Service
Type : Local RPC service
Named pipe : srrpc

Object UUID : 00000000-0000-0000-0000-000000000000
UUID : 5a7b91f8-ff00-11d0-a9b2-00c04fb6e6fc, version 1.0
Description : Messenger Service
Windows process : svchost.exe
Annotation : Messenger Service
Type : Local RPC service
Named pipe : senssvc

Object UUID : 00000000-0000-0000-0000-000000000000
UUID : 5a7b91f8-ff00-11d0-a9b2-00c04fb6e6fc, version 1.0
Description : Messenger Service
```

```
Windows process : svchost.exe
Annotation : Messenger Service
Type : Local RPC service
Named pipe : trkwks

Object UUID : 00000000-0000-0000-0000-000000000000
UUID : 1ff70682-0a51-30e8-076d-740be8cee98b, version 1.0
Description : Scheduler Service
Windows process : svchost.exe
Type : Local RPC service
Named pipe : wzcsvc

Object UUID : 00000000-0000-0000-0000-000000000000
UUID : 1ff70682-0a51-30e8-076d-740be8cee98b, version 1.0
Description : Scheduler Service
Windows process : svchost.exe
Type : Local RPC service
Named pipe : OLE3

Object UUID : 00000000-0000-0000-0000-000000000000
UUID : 378e52b0-c0a9-11cf-822d-00aa0051e40f, version 1.0
Description : Scheduler Service
Windows process : svchost.exe
Type : Local RPC service
Named pipe : wzcsvc

Object UUID : 00000000-0000-0000-0000-000000000000
UUID : 378e52b0-c0a9-11cf-822d-00aa0051e40f, version 1.0
Description : Scheduler Service
Windows process : svchost.exe
Type : Local RPC service
Named pipe : OLE3

Object UUID : 00000000-0000-0000-0000-000000000000
UUID : 0a74ef1c-41a4-4e06-83ae-dc74fb1cdd53, version 1.0
Description : Scheduler Service
Windows process : svchost.exe
T [...]
```

10736 - DCE Services Enumeration

Synopsis

A DCE/RPC service is running on the remote host.

Description

By sending a Lookup request to the portmapper (TCP 135 or epmapper PIPE) it was possible to enumerate the Distributed Computing Environment (DCE) services running on the remote port. Using this information it is possible to connect and bind to each service by sending an RPC request to the remote port/pipe.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2001/08/26, Modified: 2021/10/04

Plugin Output

tcp/445/cifs

```
The following DCERPC services are available remotely :

Object UUID : 00000000-0000-0000-0000-000000000000
UUID : 4b112204-0e19-11d3-b42b-0000f81feb9f, version 1.0
Description : SSDP service
Windows process : unknow
Type : Remote RPC service
Named pipe : \PIPE\DAV RPC SERVICE
Netbios name : \\BOX

Object UUID : 00000000-0000-0000-0000-000000000000
UUID : 5a7b91f8-ff00-11d0-a9b2-00c04fb6e6fc, version 1.0
Description : Messenger Service
Windows process : svchost.exe
Annotation : Messenger Service
Type : Remote RPC service
Named pipe : \PIPE\msgsvc
Netbios name : \\BOX

Object UUID : 00000000-0000-0000-0000-000000000000
UUID : 5a7b91f8-ff00-11d0-a9b2-00c04fb6e6fc, version 1.0
Description : Messenger Service
Windows process : svchost.exe
Annotation : Messenger Service
Type : Remote RPC service
Named pipe : \PIPE\srvsvc
Netbios name : \\BOX
```

```
Object UUID : 00000000-0000-0000-0000-000000000000
UUID : 5a7b91f8-ff00-11d0-a9b2-00c04fb6e6fc, version 1.0
Description : Messenger Service
Windows process : svchost.exe
Annotation : Messenger Service
Type : Remote RPC service
Named pipe : \pipe\trkwks
Netbios name : \\BOX

Object UUID : 00000000-0000-0000-0000-000000000000
UUID : 5a7b91f8-ff00-11d0-a9b2-00c04fb6e6fc, version 1.0
Description : Messenger Service
Windows process : svchost.exe
Annotation : Messenger Service
Type : Remote RPC service
Named pipe : \PIPE\W32TIME
Netbios name : \\BOX

Object UUID : 00000000-0000-0000-0000-000000000000
UUID : 1ff70682-0a51-30e8-076d-740be8cee98b, version 1.0
Description : Scheduler Service
Windows process : svchost.exe
Type : Remote RPC service
Named pipe : \PIPE\atsvc
Netbios name : \\BOX

Object UUID : 00000000-0000-0000-0000-000000000000
UUID : 378e52b0-c0a9-11cf-822d-00aa0051e40f, version 1.0
Description : Scheduler Service
Windows process : svchost.exe
Type : Remote RPC service
Named pipe : \PIPE\atsvc
Netbios name : \\BOX

Object UUID : 00000000-0000-0000-0000-000000000000
UUID : 0a74ef1c-41a4-4e06-83ae-dc74fb1cdd53, version 1.0
Description : Scheduler Service
Windows process : svch [...]
```

10736 - DCE Services Enumeration

Synopsis

A DCE/RPC service is running on the remote host.

Description

By sending a Lookup request to the portmapper (TCP 135 or epmapper PIPE) it was possible to enumerate the Distributed Computing Environment (DCE) services running on the remote port. Using this information it is possible to connect and bind to each service by sending an RPC request to the remote port/pipe.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2001/08/26, Modified: 2021/10/04

Plugin Output

tcp/1025/dce-rpc

```
The following DCERPC services are available on TCP port 1025 :

Object UUID : 00000000-0000-0000-0000-000000000000
UUID : 1ff70682-0a51-30e8-076d-740be8cee98b, version 1.0
Description : Scheduler Service
Windows process : svchost.exe
Type : Remote RPC service
TCP Port : 1025
IP : 10.10.10.109

Object UUID : 00000000-0000-0000-0000-000000000000
UUID : 378e52b0-c0a9-11cf-822d-00aa0051e40f, version 1.0
Description : Scheduler Service
Windows process : svchost.exe
Type : Remote RPC service
TCP Port : 1025
IP : 10.10.10.109

Object UUID : 00000000-0000-0000-0000-000000000000
UUID : 0a74ef1c-41a4-4e06-83ae-dc74fb1cdd53, version 1.0
Description : Scheduler Service
Windows process : svchost.exe
Type : Remote RPC service
TCP Port : 1025
IP : 10.10.10.109

Object UUID : 00000000-0000-0000-0000-000000000000
UUID : 5a7b91f8-ff00-11d0-a9b2-00c04fb6e6fc, version 1.0
```

```
Description : Messenger Service
Windows process : svchost.exe
Annotation : Messenger Service
Type : Remote RPC service
TCP Port : 1025
IP : 10.10.10.109
```

10736 - DCE Services Enumeration

Synopsis

A DCE/RPC service is running on the remote host.

Description

By sending a Lookup request to the portmapper (TCP 135 or epmapper PIPE) it was possible to enumerate the Distributed Computing Environment (DCE) services running on the remote port. Using this information it is possible to connect and bind to each service by sending an RPC request to the remote port/pipe.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2001/08/26, Modified: 2021/10/04

Plugin Output

udp/1026/dce-rpc

```
The following DCERPC services are available on UDP port 1026 :

Object UUID : 00000000-0000-0000-0000-000000000000
UUID : 5a7b91f8-ff00-11d0-a9b2-00c04fb6e6fc, version 1.0
Description : Messenger Service
Windows process : svchost.exe
Annotation : Messenger Service
Type : Remote RPC service
UDP Port : 1026
IP : 10.10.10.109
```

54615 - Device Type

Synopsis

It is possible to guess the remote device type.

Description

Based on the remote operating system, it is possible to determine what the remote system type is (eg: a printer, router, general-purpose computer, etc).

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2011/05/23, Modified: 2025/03/12

Plugin Output

tcp/0

```
Remote device type : general-purpose
Confidence level : 99
```

35716 - Ethernet Card Manufacturer Detection

Synopsis

The manufacturer can be identified from the Ethernet OUI.

Description

Each ethernet MAC address starts with a 24-bit Organizationally Unique Identifier (OUI). These OUIs are registered by IEEE.

See Also

https://standards.ieee.org/faqs/regauth.html

http://www.nessus.org/u?794673b4

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2009/02/19, Modified: 2020/05/13

Plugin Output

tcp/0

```
The following card manufacturers were identified :

08:00:27:2B:B2:C9 : PCS Systemtechnik GmbH
```

86420 - Ethernet MAC Addresses

Synopsis

This plugin gathers MAC addresses from various sources and consolidates them into a list.

Description

This plugin gathers MAC addresses discovered from both remote probing of the host (e.g. SNMP and Netbios) and from running local checks (e.g. ifconfig). It then consolidates the MAC addresses into a single, unique, and uniform list.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2015/10/16, Modified: 2025/06/10

Plugin Output

tcp/0

```
The following is a consolidated list of detected MAC addresses:
  - 08:00:27:2B:B2:C9
```

10785 - Microsoft Windows SMB NativeLanManager Remote System Information Disclosure

Synopsis

It was possible to obtain information about the remote operating system.

Description

Nessus was able to obtain the remote operating system name and version (Windows and/or Samba) by sending an authentication request to port 139 or 445. Note that this plugin requires SMB to be enabled on the host.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2001/10/17, Modified: 2021/09/20

Plugin Output

tcp/445/cifs

```
The remote Operating System is : Windows 5.1
The remote native LAN manager is : Windows 2000 LAN Manager
The remote SMB Domain Name is : BOX
```

11011 - Microsoft Windows SMB Service Detection

Synopsis

A file / print sharing service is listening on the remote host.

Description

The remote service understands the CIFS (Common Internet File System) or Server Message Block (SMB) protocol, used to provide shared access to files, printers, etc between nodes on a network.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2002/06/05, Modified: 2021/02/11

Plugin Output

tcp/139/smb

```
An SMB server is running on this port.
```

11011 - Microsoft Windows SMB Service Detection

Synopsis

A file / print sharing service is listening on the remote host.

Description

The remote service understands the CIFS (Common Internet File System) or Server Message Block (SMB) protocol, used to provide shared access to files, printers, etc between nodes on a network.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2002/06/05, Modified: 2021/02/11

Plugin Output

tcp/445/cifs

```
A CIFS server is running on this port.
```

10395 - Microsoft Windows SMB Shares Enumeration

Synopsis

It is possible to enumerate remote network shares.

Description

By connecting to the remote host, Nessus was able to enumerate the network share names.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2000/05/09, Modified: 2022/02/01

Plugin Output

tcp/445/cifs

```
Here are the SMB shares available on the remote host :

  - IPC$
```

100871 - Microsoft Windows SMB Versions Supported (remote check)

Synopsis

It was possible to obtain information about the version of SMB running on the remote host.

Description

Nessus was able to obtain the version of SMB running on the remote host by sending an authentication request to port 139 or 445.

Note that this plugin is a remote check and does not work on agents.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2017/06/19, Modified: 2019/11/22

Plugin Output

tcp/445/cifs

```
The remote host supports the following versions of SMB :
  SMBv1
```

106716 - Microsoft Windows SMB2 and SMB3 Dialects Supported (remote check)

Synopsis

It was possible to obtain information about the dialects of SMB2 and SMB3 available on the remote host.

Description

Nessus was able to obtain the set of SMB2 and SMB3 dialects running on the remote host by sending an authentication request to port 139 or 445.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2018/02/09, Modified: 2020/03/11

Plugin Output

tcp/445/cifs

```
The remote host does NOT support the following SMB dialects :
_version_  _introduced in windows version_
2.0.2      Windows 2008
2.1        Windows 7
2.2.2      Windows 8 Beta
2.2.4      Windows 8 Beta
3.0        Windows 8
3.0.2      Windows 8.1
3.1        Windows 10
3.1.1      Windows 10
```

11219 - Nessus SYN scanner

Synopsis

It is possible to determine which TCP ports are open.

Description

This plugin is a SYN 'half-open' port scanner. It shall be reasonably quick even against a firewalled target.

Note that SYN scans are less intrusive than TCP (full connect) scans against broken services, but they might cause problems for less robust firewalls and also leave unclosed connections on the remote target, if the network is loaded.

Solution

Protect your target with an IP filter.

Risk Factor

None

Plugin Information

Published: 2009/02/04, Modified: 2025/07/14

Plugin Output

tcp/135/epmap

```
Port 135/tcp was found to be open
```

11219 - Nessus SYN scanner

Synopsis

It is possible to determine which TCP ports are open.

Description

This plugin is a SYN 'half-open' port scanner. It shall be reasonably quick even against a firewalled target.

Note that SYN scans are less intrusive than TCP (full connect) scans against broken services, but they might cause problems for less robust firewalls and also leave unclosed connections on the remote target, if the network is loaded.

Solution

Protect your target with an IP filter.

Risk Factor

None

Plugin Information

Published: 2009/02/04, Modified: 2025/07/14

Plugin Output

tcp/139/smb

```
Port 139/tcp was found to be open
```

11219 - Nessus SYN scanner

Synopsis

It is possible to determine which TCP ports are open.

Description

This plugin is a SYN 'half-open' port scanner. It shall be reasonably quick even against a firewalled target.

Note that SYN scans are less intrusive than TCP (full connect) scans against broken services, but they might cause problems for less robust firewalls and also leave unclosed connections on the remote target, if the network is loaded.

Solution

Protect your target with an IP filter.

Risk Factor

None

Plugin Information

Published: 2009/02/04, Modified: 2025/07/14

Plugin Output

tcp/445/cifs

```
Port 445/tcp was found to be open
```

11219 - Nessus SYN scanner

Synopsis

It is possible to determine which TCP ports are open.

Description

This plugin is a SYN 'half-open' port scanner. It shall be reasonably quick even against a firewalled target.

Note that SYN scans are less intrusive than TCP (full connect) scans against broken services, but they might cause problems for less robust firewalls and also leave unclosed connections on the remote target, if the network is loaded.

Solution

Protect your target with an IP filter.

Risk Factor

None

Plugin Information

Published: 2009/02/04, Modified: 2025/07/14

Plugin Output

tcp/1025/dce-rpc

```
Port 1025/tcp was found to be open
```

11219 - Nessus SYN scanner

Synopsis

It is possible to determine which TCP ports are open.

Description

This plugin is a SYN 'half-open' port scanner. It shall be reasonably quick even against a firewalled target.

Note that SYN scans are less intrusive than TCP (full connect) scans against broken services, but they might cause problems for less robust firewalls and also leave unclosed connections on the remote target, if the network is loaded.

Solution

Protect your target with an IP filter.

Risk Factor

None

Plugin Information

Published: 2009/02/04, Modified: 2025/07/14

Plugin Output

tcp/5000/www

```
Port 5000/tcp was found to be open
```

19506 - Nessus Scan Information

Synopsis

This plugin displays information about the Nessus scan.

Description

This plugin displays, for each tested host, information about the scan itself :

- The version of the plugin set.
- The type of scanner (Nessus or Nessus Home).
- The version of the Nessus Engine.
- The port scanner(s) used.
- The port range scanned.
- The ping round trip time
- Whether credentialed or third-party patch management checks are possible.
- Whether the display of superseded patches is enabled
- The date of the scan.
- The duration of the scan.
- The number of hosts scanned in parallel.
- The number of checks done in parallel.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2005/08/26, Modified: 2026/03/04

Plugin Output

tcp/0

```
Information about this scan :

Nessus version : 10.12.0
Nessus build : 20184
Plugin feed version : 202605050546
Scanner edition used : Nessus
Scanner OS : LINUX
Scanner distribution : ubuntu1804-aarch64
Scan type : Normal
Scan name : pentest exam
```

```
Scan policy used : Basic Network Scan
Scanner IP : 10.10.10.174
Port scanner(s) : nessus_syn_scanner
Port range : 1-65535
Ping RTT : 129.203 ms
Thorough tests : no
Experimental tests : no
Scan for Unpatched Vulnerabilities : no
Plugin debugging enabled : no
Paranoia level : 1
Report verbosity : 1
Safe checks : yes
Optimize the test : yes
Credentialed checks : no
Patch management checks : None
Display superseded patches : yes (supersedence plugin did not launch)
CGI scanning : disabled
Web application tests : disabled
Max hosts : 30
Max checks : 4
Recv timeout : 5
Backports : None
Allow post-scan editing : Yes
Nessus Plugin Signature Checking : Enabled
Audit File Signature Checking : Disabled
Scan Start Date : 2026/5/5 14:53 IST (UTC +01:00)
Scan duration : 223 sec
Scan for malware : no
Fully Scan Operational Technology devices : yes
Safely Scan Operational Technology devices with OT Discovery : no
```

10884 - Network Time Protocol (NTP) Server Detection

Synopsis

An NTP server is listening on the remote host.

Description

An NTP server is listening on port 123. If not securely configured, it may provide information about its version, current date, current time, and possibly system information.

See Also

http://www.ntp.org

Solution

n/a

Risk Factor

None

References

XREF IAVT:0001-T-0934

Plugin Information

Published: 2015/03/20, Modified: 2021/02/24

Plugin Output

udp/123/ntp

```
An NTP service has been discovered, listening on port 123.

No sensitive information has been disclosed.

Version : unknown
```

209654 - OS Fingerprints Detected

Synopsis

Multiple OS fingerprints were detected.

Description

Using a combination of remote probes (TCP/IP, SMB, HTTP, NTP, SNMP, etc), it was possible to gather one or more fingerprints from the remote system. While the highest-confidence result was reported in plugin 11936, “OS Identification”, the complete set of fingerprints detected are reported here.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2025/02/26, Modified: 2025/03/03

Plugin Output

tcp/0

```
Following OS Fingerprints were found

Remote operating system : Microsoft Windows XP
Confidence level : 56
Method : MLSinFP
Type : unknown
Fingerprint : unknown

Remote operating system : Microsoft Windows XP
Microsoft Windows XP for Embedded Systems
Confidence level : 70
Method : Misc
Type : general-purpose
Fingerprint : unknown

Remote operating system : Windows 5.1
Confidence level : 70
Method : smb
Type : general-purpose
Fingerprint : unknown

Remote operating system : Microsoft Windows XP\nMicrosoft Windows XP Service Pack 1
Confidence level : 99
Method : MSRPC
Type : general-purpose
Fingerprint : unknown

Remote operating system : EMC CLARiiON AX150SCi SAN Disk Array
```

```
EMC CLARiiON CX3-10 SAN Disk Array
Microsoft Windows 2000
Microsoft Windows XP
Confidence level : 59
Method : SinFP
Type :
Fingerprint : SinFP:
   P1:B11113:F0x12:W64240:O0204ffff:M1460:
   P2:B11113:F0x12:W64240:O0204ffff010303000101080a00000000000000000001010402:M1460:
   P3:B00000:F0x00:W0:O0:M0
   P4:191800_7_p=139

Following fingerprints could not be used to determine OS :
 NTP:!:unknown
```

11936 - OS Identification

Synopsis

It is possible to guess the remote operating system.

Description

Using a combination of remote probes (e.g., TCP/IP, SMB, HTTP, NTP, SNMP, etc.), it is possible to guess the name of the remote operating system in use. It is also possible sometimes to guess the version of the operating system.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2003/12/09, Modified: 2025/06/03

Plugin Output

tcp/0

```
Remote operating system : Microsoft Windows XP\nMicrosoft Windows XP Service Pack 1
Confidence level : 99
Method : MSRPC

Not all fingerprints could give a match. If you think that these
signatures would help us improve OS fingerprinting, please submit
them by visiting https://www.tenable.com/research/submitsignatures.

NTP:!:unknown
SinFP:
   P1:B11113:F0x12:W64240:O0204ffff:M1460:
   P2:B11113:F0x12:W64240:O0204ffff010303000101080a0000000000000000000001010402:M1460:
   P3:B00000:F0x00:W0:O0:M0
   P4:191800_7_p=139


The remote host is running Microsoft Windows XP\nMicrosoft Windows XP Service Pack 1
```

117886 - OS Security Patch Assessment Not Available

Synopsis

OS Security Patch Assessment is not available.

Description

OS Security Patch Assessment is not available on the remote host.

This does not necessarily indicate a problem with the scan.

Credentials may not have been provided, OS security patch assessment may not be supported for the target, the target may not have been identified, or another issue may have occurred that prevented OS security patch assessment from being available. See plugin output for details.

This plugin reports non-failure information impacting the availability of OS Security Patch Assessment. Failure information is reported by plugin 21745 : 'OS Security Patch Assessment failed'. If a target host is not supported for OS Security Patch Assessment, plugin 110695 : 'OS Security Patch Assessment Checks Not Supported' will report concurrently with this plugin.

Solution

n/a

Risk Factor

None

References

XREF IAVB:0001-B-0515

Plugin Information

Published: 2018/10/02, Modified: 2021/07/12

Plugin Output

tcp/0

```
The following issues were reported :

  - Plugin      : no_local_checks_credentials.nasl
    Plugin ID   : 110723
    Plugin Name : Target Credential Status by Authentication Protocol - No Credentials Provided
    Message     :
Credentials were not provided for detected SMB service.
```

66334 - Patch Report

Synopsis

The remote host is missing several patches.

Description

The remote host is missing one or more security patches. This plugin lists the newest version of each patch to install to make sure the remote host is up-to-date.

Note: Because the 'Show missing patches that have been superseded' setting in your scan policy depends on this plugin, it will always run and cannot be disabled.

Solution

Install the patches listed below.

Risk Factor

None

Plugin Information

Published: 2013/07/08, Modified: 2026/04/28

Plugin Output

tcp/0

```
. You need to take the following 2 actions :


[ MS04-022: Microsoft Windows Task Scheduler Remote Overflow (841873) (uncredentialed check)
 (13852) ]

+ Action to take : Microsoft has released a set of patches for Windows 2000, XP and 2003.


[ MS05-027: Vulnerability in SMB Could Allow Remote Code Execution (896422) (uncredentialed check)
 (18502) ]

+ Action to take : Microsoft has released a set of patches for Windows 2000, XP and 2003.
```

162529 - SMB NULL Session Authentication (Domain Controller)

Synopsis

It is possible to log into the remote Windows host with a NULL session.

Description

The remote host is running an SMB protocol. It is possible to log into the netlogon, lsarpc, or samr pipes using a NULL session (i.e., with no login or password).

Depending on the configuration, it may be possible for an unauthenticated, remote attacker to leverage this issue to get information about the remote host.

See Also

http://www.nessus.org/u?e32d594f

http://www.nessus.org/u?9182e66b

http://www.nessus.org/u?a33fe205

Solution

Please contact the product vendor for recommended solutions.

Risk Factor

None

Plugin Information

Published: 2022/06/24, Modified: 2022/06/24

Plugin Output

tcp/445/cifs

```
It was possible to bind to the following pipes:
  - netlogon
  - lsarpc
  - samr
```

96982 - Server Message Block (SMB) Protocol Version 1 Enabled (uncredentialed check)

Synopsis

The remote host supports the SMBv1 protocol.

Description

The remote host (Windows and/or Samba server) supports Server Message Block Protocol version 1 (SMBv1). Microsoft recommends that users discontinue the use of SMBv1 due to the lack of security features that were included in later SMB versions. Additionally, most security and compliance agencies recommend that users disable SMBv1 per SMB best practices.

See Also

http://www.nessus.org/u?59bfc3ef

http://www.nessus.org/u?b9d9ebf9

http://www.nessus.org/u?8dcab5e4

http://www.nessus.org/u?234f8ef8

http://www.nessus.org/u?4c7e0cf3

Solution

Disable SMBv1 according to the vendor instructions in Microsoft KB2696547. Additionally, block SMB directly by blocking TCP port 445 on all network boundary devices. For SMB over the NetBIOS API, block TCP ports 137 / 139 and UDP ports 137 / 138 on all network boundary devices.

Risk Factor

None

References

XREF IAVT:0001-T-0710

Plugin Information

Published: 2017/02/03, Modified: 2025/08/13

Plugin Output

tcp/445/cifs

```
The remote host supports SMBv1.
```

22964 - Service Detection

Synopsis

The remote service could be identified.

Description

Nessus was able to identify the remote service by its banner or by looking at the error message it sends when it receives an HTTP request.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/08/19, Modified: 2026/03/23

Plugin Output

tcp/5000/www

```
A web server is running on this port.
```

25220 - TCP/IP Timestamps Supported

Synopsis

The remote service implements TCP timestamps.

Description

The remote host implements TCP timestamps, as defined by RFC1323. A side effect of this feature is that the uptime of the remote host can sometimes be computed.

See Also

http://www.ietf.org/rfc/rfc1323.txt

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/05/16, Modified: 2023/10/17

Plugin Output

tcp/0

110723 - Target Credential Status by Authentication Protocol - No Credentials Provided

Synopsis

Nessus was able to find common ports used for local checks, however, no credentials were provided in the scan policy.

Description

Nessus was not able to successfully authenticate directly to the remote target on an available authentication protocol. Nessus was able to connect to the remote port and identify that the service running on the port supports an authentication protocol, but Nessus failed to authenticate to the remote service using the provided credentials. There may have been a protocol failure that prevented authentication from being attempted or all of the provided credentials for the authentication protocol may be invalid. See plugin output for error details.

Please note the following :

- This plugin reports per protocol, so it is possible for valid credentials to be provided for one protocol and not another. For example, authentication may succeed via SSH but fail via SMB, while no credentials were provided for an available SNMP service.

- Providing valid credentials for all available authentication protocols may improve scan coverage, but the value of successful authentication for a given protocol may vary from target to target depending upon what data (if any) is gathered from the target via that protocol. For example, successful authentication via SSH is more valuable for Linux targets than for Windows targets, and likewise successful authentication via SMB is more valuable for Windows targets than for Linux targets.

Solution

n/a

Risk Factor

None

References

XREF IAVB:0001-B-0504

Plugin Information

Published: 2018/06/27, Modified: 2024/04/19

Plugin Output

tcp/0

```
SMB was detected on port 445 but no credentials were provided.
SMB local checks were not enabled.
```

10287 - Traceroute Information

Synopsis

It was possible to obtain traceroute information.

Description

Makes a traceroute to the remote host.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 1999/11/27, Modified: 2026/04/27

Plugin Output

udp/0

```
For your information, here is the traceroute from 10.10.10.174 to 10.10.10.109 :
10.10.10.174
10.10.10.109

Hop Count: 1
```

11765 - UPnP TCP Helper Detection

Synopsis

The remote host appears to be running Microsoft UPnP TCP helper.

Description

The remote host is running Microsoft UPnP TCP helper.

If the tested network is not a home network, you should disable this service.

Solution

Set the following registry key :
Location : HKLM\SYSTEM\CurrentControlSet\Services\SSDPSRV Key : Start Value : 0x04

Risk Factor

None

Plugin Information

Published: 2003/06/19, Modified: 2019/11/22

Plugin Output

tcp/5000/www

10150 - Windows NetBIOS / SMB Remote Host Information Disclosure

Synopsis

It was possible to obtain the network name of the remote host.

Description

The remote host is listening on UDP port 137 or TCP port 445, and replies to NetBIOS nbtscan or SMB requests.

Note that this plugin gathers information to be used in other plugins, but does not itself generate a report.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 1999/10/12, Modified: 2021/02/10

Plugin Output

udp/137/netbios-ns

```
The following 5 NetBIOS names have been gathered :

 BOX              = Computer name
 WORKGROUP        = Workgroup / Domain name
 BOX              = Messenger Service
 BOX              = File Server Service
 WORKGROUP        = Browser Service Elections

The remote host has the following MAC address on its adapter :

   08:00:27:2b:b2:c9
```