Scan Report

May 15, 2026

Summary

This document reports on the results of an automatic security scan. All dates are displayed using the timezone "Coordinated Universal Time", which is abbreviated "UTC". The task was "pentest exam". The scan started at Tue May 5 13:37:55 2026 UTC and ended at Tue May 5 14:19:17 2026 UTC. The report first summarises the results found. Then, for each host, the report describes every issue found. Please consider the advice given in each description, in order to rectify the issue.

Contents

1 Result Overview **2**
1.1 Host Authentications . . . 2

2 Results per Host **2**
2.1 10.10.10.101 . . . 2
2.1.1 Critical 22/tcp . . . 3
2.1.2 Critical 80/tcp . . . 5
2.1.3 Critical 21/tcp . . . 6
2.1.4 High 80/tcp . . . 7
2.1.5 High 21/tcp . . . 8
2.1.6 Medium 22/tcp . . . 10
2.1.7 Medium 80/tcp . . . 14
2.1.8 Medium 21/tcp . . . 22
2.1.9 Low 22/tcp . . . 23
2.1.10 Low general/tcp . . . 25
2.1.11 Low general/icmp . . . 26
2.2 10.10.10.102 . . . 27
2.2.1 Critical 21/tcp . . . 27
2.2.2 Medium 21/tcp . . . 29
2.2.3 Medium 80/tcp . . . 29
2.2.4 Low 22/tcp . . . 31
2.2.5 Low general/tcp . . . 32

2.2.6 Low general/icmp 33
2.3 10.10.10.109 34
2.3.1 Critical 445/tcp 34
2.3.2 Critical general/tcp 38
2.3.3 High 445/tcp 39
2.3.4 Medium 135/tcp 40
2.3.5 Low general/icmp 42

1 Result Overview

Host	Critical	High	Medium	Low	Log	False P.
10.10.10.101	3	3	12	3	0	0
10.10.10.102	1	0	2	3	0	0
10.10.10.109	4	1	1	1	0	0
Total: 3	8	4	15	7	0	0

Vendor security updates are not trusted.
Overrides are off. Even when a result has an override, this report uses the actual threat of the result.
Information on overrides is excluded from the report.
Notes are excluded from the report.
This report might not show details of all issues that were found.
Issues with the threat level "Log" are not shown.
Issues with the threat level "Debug" are not shown.
Issues with the threat level "False Positive" are not shown.
Only results with a minimum QoD of 70 are shown.

This report contains all 34 results selected by the filtering described above. Before filtering there were 572 results.

1.1 Host Authentications

Host	Protocol	Result	Port/User
10.10.10.101	SMB	Success	Protocol SMB, Port 445, User

2 Results per Host

2.1 10.10.10.101

Host scan start Tue May 5 13:39:03 2026 UTC
Host scan end Tue May 5 14:19:15 2026 UTC

Service (Port)	Threat Level
22/tcp	Critical
80/tcp	Critical
21/tcp	Critical
80/tcp	High
21/tcp	High
22/tcp	Medium
80/tcp	Medium

... (continues) ...

... (continued) ...

Service (Port)	Threat Level
21/tcp	Medium
22/tcp	Low
general/tcp	Low
general/icmp	Low

2.1.1 Critical 22/tcp

Critical (CVSS: 9.8)

NVT: SSH Brute Force Logins With Default Credentials Reporting

Summary
It was possible to login into the remote SSH server using default credentials.

Quality of Detection (QoD): 95%

Vulnerability Detection Result
`It was possible to login with the following credentials <User>:<Password>`
`vagrant:vagrant`

Impact
This issue may be exploited by a remote attacker to e.g. gain access to sensitive information or modify system configuration.

Solution:
Solution type: Mitigation
Change the password as soon as possible.

Affected Software/OS
The following products are known to use the default credentials checked by the VT 'SSH Brute Force Logins With Default Credentials' (OID: 1.3.6.1.4.1.25623.1.0.108013) used for this reporting:
- CVE-2017-16523: MitraStar GPT-2541GNAC (HGU) 1.00(VNJ0)b1 and DSL-100HN-T1 ES_113WJY0b16 devices
- CVE-2017-20214: FLIR Thermal Camera F/FC/PT/D
- CVE-2018-25138: FLIR AX8 Thermal Camera
- CVE-2018-25147: Microhard Systems IPn4G
- CVE-2019-25241: FaceSentry Access Control System
- CVE-2019-25291: INIM Electronics Smartliving SmartLAN/G/SI
- CVE-2020-29583: Zyxel Firewall / AP Controller
- CVE-2020-36915: Adtec Digital SignEdje Digital Signage Player
- CVE-2020-37092: Netis E1+ devices
- CVE-2020-9473: S. Siedle & Soehne SG 150-0 Smart Gateway before 1.2.4

... continues on next page ...

... continued from previous page ...

- CVE-2021-27797: Brocade Fabric OS
- CVE-2021-47744: Cypress Solutions CTM-200/CTM-ONE
- CVE-2023-1944: minikube 1.29.0 and probably prior
- CVE-2023-53983: Anevia Flamingo XL/XS
- CVE-2024-22902: Vinchin Backup & Recovery
- CVE-2024-31970: AdTran SRG 834-5 HDC17600021F1 devices (with SmartOS 11.1.1.1) during a window of time when the device is being set up
- CVE-2024-46328: VONETS VAP11G-300 v3.3.23.6.9
- CVE-2025-12592: Legacy Vivotek devices
- CVE-2025-68718: KAYSUS KS-WR1200
- Various additional products like e.g. Ubiquiti EdgeMax / EdgeRouter, Crestron AM-100 and similar for which no CVE was assigned (See 'default_credentials.inc' file on the file system for a full list)

Other products might be affected as well.

Vulnerability Insight

As the VT 'SSH Brute Force Logins With Default Credentials' (OID: 1.3.6.1.4.1.25623.1.0.108013) might run into a timeout the actual reporting of this vulnerability takes place in this VT instead.

Vulnerability Detection Method

Reports default credentials detected by the VT 'SSH Brute Force Logins With Default Credentials' (OID: 1.3.6.1.4.1.25623.1.0.108013).

Details: `SSH Brute Force Logins With Default Credentials Reporting`

OID:1.3.6.1.4.1.25623.1.0.103239

Version used: `2026-02-05T05:56:23Z`

References

`cve: CVE-1999-0501`
`cve: CVE-1999-0502`
`cve: CVE-1999-0507`
`cve: CVE-1999-0508`
`cve: CVE-2005-1379`
`cve: CVE-2006-5288`
`cve: CVE-2009-3710`
`cve: CVE-2012-4577`
`cve: CVE-2016-1000245`
`cve: CVE-2017-16523`
`cve: CVE-2017-20214`
`cve: CVE-2018-25138`
`cve: CVE-2018-25147`
`cve: CVE-2019-25241`
`cve: CVE-2019-25291`
`cve: CVE-2020-29583`
`cve: CVE-2020-36915`
`cve: CVE-2020-37092`
`cve: CVE-2020-9473`

... continues on next page ...

... continued from previous page ...

```
cve: CVE-2021-27797
cve: CVE-2021-47744
cve: CVE-2023-1944
cve: CVE-2023-53983
cve: CVE-2024-22902
cve: CVE-2024-31970
cve: CVE-2024-46328
cve: CVE-2025-12592
cve: CVE-2025-41696
cve: CVE-2025-68718
url: https://www.cisa.gov/known-exploited-vulnerabilities-catalog
cisa: Known Exploited Vulnerability (KEV) catalog
cert-bund: WID-SEC-2025-2760
```

[return to 10.10.10.101]

2.1.2 Critical 80/tcp

Critical (CVSS: 10.0)

NVT: Drupal Coder RCE Vulnerability (SA-CONTRIB-2016-039) - Active Check

Summary
Drupal is prone to a remote code execution (RCE) vulnerability.

Quality of Detection (QoD): 95%

Vulnerability Detection Result
`Vulnerable URL: http://10.10.10.101/drupal/sites/all/modules/coder/coder_upgrade`
`↪/scripts/coder_upgrade.run.php`

Solution:
Solution type: VendorFix
Install the latest version.

Vulnerability Insight
The Coder module checks your Drupal code against coding standards and other best practices. It can also fix coding standard violations and perform basic upgrades on modules. The module doesn't sufficiently validate user inputs in a script file that has the php extension. A malicious unauthenticated user can make requests directly to this file to execute arbitrary php code.

Vulnerability Detection Method
Checks for known error message from affected modules.
Details: `Drupal Coder RCE Vulnerability (SA-CONTRIB-2016-039) - Active Check`

... continues on next page ...

... continued from previous page ...

OID:1.3.6.1.4.1.25623.1.0.105818
Version used: 2023-07-21T05:05:22Z

References
url: https://www.drupal.org/node/2765575

[return to 10.10.10.101]

2.1.3 Critical 21/tcp

Critical (CVSS: 10.0)

NVT: ProFTPD 'mod_copy' Unauthenticated Copying Of Files Via SITE CPFR/CPTO Vulnerability (Apr 2015) - Active Check

Summary
ProFTPD is prone to an unauthenticated copying of files vulnerability.

Quality of Detection (QoD): 99%

Vulnerability Detection Result
The target was found to be vulnerable

Impact
Under some circumstances this could result in remote code execution.

Solution:
Solution type: VendorFix
Ask the vendor for an update.

Vulnerability Detection Method
Tries to copy /etc/passwd to /tmp/passwd.copy with SITE CPFR/CPTO command.
Details: ProFTPD 'mod_copy' Unauthenticated Copying Of Files Via SITE CPFR/CPTO Vulnerab.
↪..
OID:1.3.6.1.4.1.25623.1.0.105254
Version used: 2026-03-17T05:57:28Z

References
cve: CVE-2015-3306
url: http://bugs.proftpd.org/show_bug.cgi?id=4169
cert-bund: CB-K15/0791
cert-bund: CB-K15/0553
dfn-cert: DFN-CERT-2015-0839
dfn-cert: DFN-CERT-2015-0576

[return to 10.10.10.101]

2.1.4 High 80/tcp

High (CVSS: 7.5)

NVT: Drupal Core SQLi Vulnerability (SA-CORE-2014-005) - Active Check

Summary
Drupal is prone to an SQL injection (SQLi) vulnerability.

Quality of Detection (QoD): 98%

Vulnerability Detection Result
`Vulnerable URL: http://10.10.10.101/drupal/?q=node&destination=node`

Impact
Exploiting this issue could allow an attacker to execute arbitrary code, to gain elevated privileges and to compromise the application, access or modify data, or exploit latent vulnerabilities in the underlying database.

Solution:
Solution type: VendorFix
Updates are available. Please see the references for more information.

Affected Software/OS
Drupal 7.x versions prior to 7.32 are vulnerable.

Vulnerability Insight
Drupal fails to sufficiently sanitize user-supplied data before using it in an SQL query.

Vulnerability Detection Method
Sends a special crafted HTTP POST request and checks the response.
Details: `Drupal Core SQLi Vulnerability (SA-CORE-2014-005) - Active Check`
OID:1.3.6.1.4.1.25623.1.0.105101
Version used: `2023-07-26T05:05:09Z`

References
`cve: CVE-2014-3704`
`url: https://www.drupal.org/forum/newsletters/security-advisories-for-drupal-cor`
`↪e/2014-10-15/sa-core-2014-005-drupal-core-sql`
`url: http://www.securityfocus.com/bid/70595`
`cert-bund: CB-K14/1301`
`cert-bund: CB-K14/0920`
`dfn-cert: DFN-CERT-2014-1369`
`dfn-cert: DFN-CERT-2014-0958`

High (CVSS: 7.5)

NVT: Test HTTP dangerous methods

Summary
Misconfigured web servers allows remote clients to perform dangerous HTTP methods such as PUT and DELETE.

Quality of Detection (QoD): 99%

Vulnerability Detection Result
`We could upload the following files via the PUT method at this web server:`
`http://10.10.10.101/uploads/puttest1129640649.html`
`We could delete the following files via the DELETE method at this web server:`
`http://10.10.10.101/uploads/puttest1129640649.html`

Impact
- Enabled PUT method: This might allow an attacker to upload and run arbitrary code on this web server.
- Enabled DELETE method: This might allow an attacker to delete additional files on this web server.

Solution:
Solution type: Mitigation
Use access restrictions to these dangerous HTTP methods or disable them completely.

Affected Software/OS
Web servers with enabled PUT and/or DELETE methods.

Vulnerability Detection Method
Checks if dangerous HTTP methods such as PUT and DELETE are enabled and can be misused to upload or delete files.
Details: `Test HTTP dangerous methods`
OID:1.3.6.1.4.1.25623.1.0.10498
Version used: `2023-08-01T13:29:10Z`

References
`url: http://www.securityfocus.com/bid/12141`
`owasp: OWASP-CM-001`

[return to 10.10.10.101]

2.1.5 High 21/tcp

High (CVSS: 7.5)

NVT: FTP Brute Force Logins With Default Credentials Reporting

Summary
It was possible to login into the remote FTP server using weak/known credentials.

Quality of Detection (QoD): 95%

Vulnerability Detection Result
`It was possible to login with the following credentials <User>:<Password>`
`vagrant:vagrant`

Impact
This issue may be exploited by a remote attacker to e.g. gain access to sensitive information or modify system configuration.

Solution:
Solution type: Mitigation
Change the password as soon as possible.

Vulnerability Insight
The following devices are / software is known to be affected:
- CVE-2001-1594: Codonics printer FTP service as used in GE Healthcare eNTEGRA P&R
- CVE-2013-7404: GE Healthcare Discovery NM 750b
- CVE-2014-9198: Schneider Electric ETG3000 FactoryCast HMI gateways
- CVE-2015-7261: QNAP iArtist Lite distributed with QNAP Signage Station
- CVE-2016-8731: Foscam C1 devices
- CVE-2017-8218: vsftpd on TP-Link C2 and C20i devices
- CVE-2018-9068: IMM2 for IBM and Lenovo System x
- CVE-2018-17771: Ingenico Telium 2 PoS terminals
- CVE-2018-19063, CVE-2018-19064: Foscam C2 and Opticam i5 devices
- CVE-2018-25147: Microhard Systems IPn4G
- CVE-2020-36915: Adtec Digital SignEdje Digital Signage Player

Note: As the VT 'FTP Brute Force Logins With Default Credentials' (OID: 1.3.6.1.4.1.25623.1.0.108717) might run into a timeout the actual reporting of this vulnerability takes place in this VT instead.

Vulnerability Detection Method
Reports weak/known credentials detected by the VT 'FTP Brute Force Logins With Default Credentials' (OID: 1.3.6.1.4.1.25623.1.0.108717).
Details: `FTP Brute Force Logins With Default Credentials Reporting`
OID:1.3.6.1.4.1.25623.1.0.108718
Version used: `2026-01-16T15:42:49Z`

References

. . . continues on next page . . .

... continued from previous page ...

```
cve: CVE-1999-0501
cve: CVE-1999-0502
cve: CVE-1999-0507
cve: CVE-1999-0508
cve: CVE-2001-1594
cve: CVE-2013-7404
cve: CVE-2014-9198
cve: CVE-2015-7261
cve: CVE-2016-8731
cve: CVE-2017-8218
cve: CVE-2018-9068
cve: CVE-2018-17771
cve: CVE-2018-19063
cve: CVE-2018-19064
cve: CVE-2018-25147
cve: CVE-2020-36915
```

[return to 10.10.10.101]

2.1.6 Medium 22/tcp

Medium (CVSS: 5.3)

NVT: Weak Host Key Algorithm(s) (SSH)

Product detection result

```
cpe:/a:ietf:secure_shell_protocol
Detected by SSH Protocol Algorithms Supported (OID: 1.3.6.1.4.1.25623.1.0.105565
↪)
```

Summary

The remote SSH server is configured to allow / support weak host key algorithm(s).

Quality of Detection (QoD): 80%

Vulnerability Detection Result

```
The remote SSH server supports the following weak host key algorithm(s):
host key algorithm | Description
----------------------------------------------------------------------------------
↪---------
ssh-dss            | Digital Signature Algorithm (DSA) / Digital Signature Stand
↪ard (DSS)
```

Solution:

... continues on next page ...

... continued from previous page ...

Solution type: Mitigation
Disable the reported weak host key algorithm(s).

Vulnerability Detection Method
Checks the supported host key algorithms of the remote SSH server.
Currently weak host key algorithms are defined as the following:
- ssh-dss: Digital Signature Algorithm (DSA) / Digital Signature Standard (DSS)
Details: `Weak Host Key Algorithm(s) (SSH)`
OID:1.3.6.1.4.1.25623.1.0.117687
Version used: `2024-06-14T05:05:48Z`

Product Detection Result
Product: `cpe:/a:ietf:secure_shell_protocol`
Method: `SSH Protocol Algorithms Supported`
OID: 1.3.6.1.4.1.25623.1.0.105565)

References
`url: https://www.rfc-editor.org/rfc/rfc8332`
`url: https://www.rfc-editor.org/rfc/rfc8709`
`url: https://www.rfc-editor.org/rfc/rfc4253#section-6.6`

Medium (CVSS: 5.3)

NVT: Weak Key Exchange (KEX) Algorithm(s) Supported (SSH)

Product detection result
`cpe:/a:ietf:secure_shell_protocol`
`Detected by SSH Protocol Algorithms Supported (OID: 1.3.6.1.4.1.25623.1.0.105565`
`↪)`

Summary
The remote SSH server is configured to allow / support weak key exchange (KEX) algorithm(s).

Quality of Detection (QoD): 80%

Vulnerability Detection Result

```
The remote SSH server supports the following weak KEX algorithm(s):
KEX algorithm                      | Reason
-----------------------------------------------------------------------------
↪-----------
diffie-hellman-group-exchange-sha1 | Using SHA-1
diffie-hellman-group1-sha1         | Using Oakley Group 2 (a 1024-bit MODP group
```

... continues on next page ...

... continued from previous page ...

↪) and SHA-1

Impact
An attacker can quickly break individual connections.

Solution:
Solution type: Mitigation
Disable the reported weak KEX algorithm(s)
- 1024-bit MODP group / prime KEX algorithms:
Alternatively use elliptic-curve Diffie-Hellmann in general, e.g. Curve 25519.

Vulnerability Insight
- 1024-bit MODP group / prime KEX algorithms:
Millions of HTTPS, SSH, and VPN servers all use the same prime numbers for Diffie-Hellman key exchange. Practitioners believed this was safe as long as new key exchange messages were generated for every connection. However, the first step in the number field sieve-the most efficient algorithm for breaking a Diffie-Hellman connection-is dependent only on this prime.
A nation-state can break a 1024-bit prime.

Vulnerability Detection Method
Checks the supported KEX algorithms of the remote SSH server.
Currently weak KEX algorithms are defined as the following:
- non-elliptic-curve Diffie-Hellmann (DH) KEX algorithms with 1024-bit MODP group / prime
- ephemerally generated key exchange groups uses SHA-1
- using RSA 1024-bit modulus key
Details: Weak Key Exchange (KEX) Algorithm(s) Supported (SSH)
OID:1.3.6.1.4.1.25623.1.0.150713
Version used: 2024-06-14T05:05:48Z

Product Detection Result
Product: cpe:/a:ietf:secure_shell_protocol
Method: SSH Protocol Algorithms Supported
OID: 1.3.6.1.4.1.25623.1.0.105565)

References
url: https://weakdh.org/sysadmin.html
url: https://www.rfc-editor.org/rfc/rfc9142
url: https://www.rfc-editor.org/rfc/rfc9142#name-summary-guidance-for-implem
url: https://www.rfc-editor.org/rfc/rfc6194
url: https://www.rfc-editor.org/rfc/rfc4253#section-6.5

Medium (CVSS: 4.3)

NVT: Weak Encryption Algorithm(s) Supported (SSH)

Product detection result
cpe:/a:ietf:secure_shell_protocol
Detected by SSH Protocol Algorithms Supported (OID: 1.3.6.1.4.1.25623.1.0.105565
↪)

Summary
The remote SSH server is configured to allow / support weak encryption algorithm(s).

Quality of Detection (QoD): 80%

Vulnerability Detection Result
The remote SSH server supports the following weak client-to-server encryption al
↪gorithm(s):
3des-cbc
aes128-cbc
aes192-cbc
aes256-cbc
arcfour
arcfour128
arcfour256
blowfish-cbc
cast128-cbc
rijndael-cbc@lysator.liu.se
The remote SSH server supports the following weak server-to-client encryption al
↪gorithm(s):
3des-cbc
aes128-cbc
aes192-cbc
aes256-cbc
arcfour
arcfour128
arcfour256
blowfish-cbc
cast128-cbc
rijndael-cbc@lysator.liu.se

Solution:
Solution type: Mitigation
Disable the reported weak encryption algorithm(s).

Vulnerability Insight

. . . continues on next page . . .

... continued from previous page ...

- The 'arcfour' cipher is the Arcfour stream cipher with 128-bit keys. The Arcfour cipher is believed to be compatible with the RC4 cipher [SCHNEIER]. Arcfour (and RC4) has problems with weak keys, and should not be used anymore.
- The 'none' algorithm specifies that no encryption is to be done. Note that this method provides no confidentiality protection, and it is NOT RECOMMENDED to use it.
- A vulnerability exists in SSH messages that employ CBC mode that may allow an attacker to recover plaintext from a block of ciphertext.

Vulnerability Detection Method
Checks the supported encryption algorithms (client-to-server and server-to-client) of the remote SSH server.
Currently weak encryption algorithms are defined as the following:
- Arcfour (RC4) cipher based algorithms
- 'none' algorithm
- CBC mode cipher based algorithms
Details: `Weak Encryption Algorithm(s) Supported (SSH)`
OID:1.3.6.1.4.1.25623.1.0.105611
Version used: `2024-06-14T05:05:48Z`

Product Detection Result
Product: `cpe:/a:ietf:secure_shell_protocol`
Method: `SSH Protocol Algorithms Supported`
OID: 1.3.6.1.4.1.25623.1.0.105565)

References
`url: https://www.rfc-editor.org/rfc/rfc8758`
`url: https://www.kb.cert.org/vuls/id/958563`
`url: https://www.rfc-editor.org/rfc/rfc4253#section-6.3`

[return to 10.10.10.101]

2.1.7 Medium 80/tcp

Medium (CVSS: 6.1)

NVT: jQuery < 1.9.0 XSS Vulnerability

Summary
jQuery is prone to a cross-site scripting (XSS) vulnerability.

Quality of Detection (QoD): 80%

Vulnerability Detection Result
`Installed version: 1.6.2`

... continues on next page ...

... continued from previous page ...

```
Fixed version:     1.9.0
Installation
path / port:       /phpmyadmin/js/jquery/jquery-1.6.2.js
Detection info (see OID: 1.3.6.1.4.1.25623.1.0.150658 for more info):
- Identified file: http://10.10.10.101/phpmyadmin/js/jquery/jquery-1.6.2.js
- Referenced at:   http://10.10.10.101/phpmyadmin/
```

Solution:
Solution type: VendorFix
Update to version 1.9.0 or later.

Affected Software/OS
jQuery prior to version 1.9.0.

Vulnerability Insight
The jQuery(strInput) function does not differentiate selectors from HTML in a reliable fashion. In vulnerable versions, jQuery determined whether the input was HTML by looking for the '<' character anywhere in the string, giving attackers more flexibility when attempting to construct a malicious payload. In fixed versions, jQuery only deems the input to be HTML if it explicitly starts with the '<' character, limiting exploitability only to attackers who can control the beginning of a string, which is far less common.

Vulnerability Detection Method
Checks if a vulnerable version is present on the target host.
Details: `jQuery < 1.9.0 XSS Vulnerability`
OID:1.3.6.1.4.1.25623.1.0.141636
Version used: `2023-07-14T05:06:08Z`

References
`cve: CVE-2012-6708`
`url: https://bugs.jquery.com/ticket/11290`
`cert-bund: WID-SEC-2022-0673`
`cert-bund: CB-K22/0045`
`cert-bund: CB-K18/1131`
`dfn-cert: DFN-CERT-2025-1803`
`dfn-cert: DFN-CERT-2023-1197`
`dfn-cert: DFN-CERT-2020-0590`

Medium (CVSS: 6.1)

NVT: jQuery < 1.9.0 XSS Vulnerability

Summary
jQuery is prone to a cross-site scripting (XSS) vulnerability.

... continues on next page ...

... continued from previous page ...

Quality of Detection (QoD): 80%

Vulnerability Detection Result

```
Installed version: 1.6.2
Fixed version:     1.9.0
Installation
path / port:       /phpmyadmin/setup/../js/jquery/jquery-1.6.2.js
Detection info (see OID: 1.3.6.1.4.1.25623.1.0.150658 for more info):
- Identified file: http://10.10.10.101/phpmyadmin/setup/../js/jquery/jquery-1.6.
↪2.js
- Referenced at:   http://10.10.10.101/phpmyadmin/setup/
```

Solution:
Solution type: VendorFix
Update to version 1.9.0 or later.

Affected Software/OS
jQuery prior to version 1.9.0.

Vulnerability Insight
The jQuery(strInput) function does not differentiate selectors from HTML in a reliable fashion. In vulnerable versions, jQuery determined whether the input was HTML by looking for the '<' character anywhere in the string, giving attackers more flexibility when attempting to construct a malicious payload. In fixed versions, jQuery only deems the input to be HTML if it explicitly starts with the '<' character, limiting exploitability only to attackers who can control the beginning of a string, which is far less common.

Vulnerability Detection Method
Checks if a vulnerable version is present on the target host.
Details: `jQuery < 1.9.0 XSS Vulnerability`
OID:1.3.6.1.4.1.25623.1.0.141636
Version used: `2023-07-14T05:06:08Z`

References

```
cve: CVE-2012-6708
url: https://bugs.jquery.com/ticket/11290
cert-bund: WID-SEC-2022-0673
cert-bund: CB-K22/0045
cert-bund: CB-K18/1131
dfn-cert: DFN-CERT-2025-1803
dfn-cert: DFN-CERT-2023-1197
dfn-cert: DFN-CERT-2020-0590
```

Medium (CVSS: 5.0)

NVT: Unprotected Web App / Device Installers (HTTP)

Summary
The script attempts to identify installation/setup pages of various web apps/devices that are publicly accessible and not protected by e.g. account restrictions or having their setup finished.

Quality of Detection (QoD): 80%

Vulnerability Detection Result
```
The following web app/device installers are unprotected/have not finished their
↪setup and are publicly accessible (URL:Description):
http://10.10.10.101/phpmyadmin/setup/index.php - CubeCart / phpMyAdmin installer
```

Impact
It is possible to install or reconfigure the software. In doing so, the attacker could overwrite existing configurations. It could be possible for the attacker to gain access to the base system

Solution:
Solution type: Mitigation
Setup and/or installation pages for Web Apps should not be publicly accessible via a web server. Restrict access to it, remove it completely or finish the setup of the application / device.

Vulnerability Detection Method
Enumerate the remote web server and check if unprotected web apps/devices are accessible for installation.
Details: `Unprotected Web App / Device Installers (HTTP)`
OID:1.3.6.1.4.1.25623.1.0.107307
Version used: `2025-12-18T05:46:55Z`

Medium (CVSS: 5.0)

NVT: Drupal 7.0 Information Disclosure Vulnerability - Active Check

Summary
Drupal is prone to an information disclosure vulnerability.

Quality of Detection (QoD): 95%

Vulnerability Detection Result
```
Vulnerable URL: http://10.10.10.101/drupal/modules/simpletest/tests/upgrade/drup
↪al-6.upload.database.php
```

Impact

. . . continues on next page . . .

... continued from previous page ...

Successful exploitation will allow attacker to obtain sensitive information that could aid in further attacks.

Solution:
Solution type: WillNotFix
No known solution was made available for at least one year since the disclosure of this vulnerability. Likely none will be provided anymore. General solution options are to upgrade to a newer release, disable respective features, remove the product or replace the product by another one.

Affected Software/OS
Drupal version 7.0 is known to be affected.

Vulnerability Insight
The flaw is due to insufficient error checking, allows remote attackers to obtain sensitive information via a direct request to a .php file, which reveals the installation path in an error message.

Vulnerability Detection Method
Details: `Drupal 7.0 Information Disclosure Vulnerability - Active Check`
OID:1.3.6.1.4.1.25623.1.0.902574
Version used: `2021-12-01T11:10:56Z`

References
`cve: CVE-2011-3730`
`url: http://code.google.com/p/inspathx/source/browse/trunk/paths_vuln/!_README`
`url: http://code.google.com/p/inspathx/source/browse/trunk/paths_vuln/drupal-7.0`

Medium (CVSS: 5.0)

NVT: Sensitive File Disclosure (HTTP)

Summary
The script attempts to identify files containing sensitive data at the remote web server.

Quality of Detection (QoD): 70%

Vulnerability Detection Result

```
The following files containing sensitive information were identified:
Description:   Microsoft IIS / ASP.NET Core Module web.config file accessible. T
↪his could contain sensitive information about the structure of the application
↪ / web server and shouldn't be accessible.
Match:         <configuration>
  <system.webServer>
Used regex:    ^\s*<(configuration|system\.web(Server)?)>
Extra match 1:   </system.webServer>
</configuration>
```

... continues on next page ...

... continued from previous page ...

Used regex: ^\s*</(configuration|system\.web(Server)?)>
URL: http://10.10.10.101/drupal/web.config

Impact
Based on the information provided in these files an attacker might be able to gather additional info and/or sensitive data like usernames and passwords.

Solution:
Solution type: Mitigation
The sensitive files shouldn't be accessible via a web server. Restrict access to it or remove it completely.

Vulnerability Insight
Currently the script is checking for files like e.g.:
- Software (Blog, CMS) configuration or log files
- Web / application server configuration / password files (e.g. .htaccess, .htpasswd, web.config, web.xml, ...)
- Cloud (e.g. AWS) configuration files
- Files containing API keys for services / providers
- Database backup files (e.g. .sql, ...)
- Editor / history files (e.g. .lesshst, .dbshell, ...)
- SSH or SSL/TLS Private Keys
- Generic environment files (e.g. .env including the ones from Codeigniter, ...)
- CVE-2017-16894: Laravel framework specific environment/.env files

Vulnerability Detection Method
Enumerate the remote web server and check if sensitive files are accessible.
Details: Sensitive File Disclosure (HTTP)
OID:1.3.6.1.4.1.25623.1.0.107305
Version used: 2025-10-29T05:40:29Z

References
cve: CVE-2017-16894

Medium (CVSS: 4.8)

NVT: Cleartext Transmission of Sensitive Information via HTTP

Summary
The host / application transmits sensitive information (username, passwords) in cleartext via HTTP.

Quality of Detection (QoD): 80%

Vulnerability Detection Result

... continues on next page ...

... continued from previous page ...

The following input fields were identified (URL:input name):
http://10.10.10.101/drupal/:pass
http://10.10.10.101/drupal/?D=A:pass
http://10.10.10.101/payroll_app.php:password
http://10.10.10.101/phpmyadmin/:pma_password
http://10.10.10.101/phpmyadmin/?D=A:pma_password
http://10.10.10.101/phpmyadmin/changelog.php:pma_password
http://10.10.10.101/phpmyadmin/index.php:pma_password
http://10.10.10.101/phpmyadmin/license.php:pma_password
http://10.10.10.101/phpmyadmin/url.php:pma_password

Impact
An attacker could use this situation to compromise or eavesdrop on the HTTP communication between the client and the server using a man-in-the-middle attack to get access to sensitive data like usernames or passwords.

Solution:
Solution type: Workaround
Enforce the transmission of sensitive data via an encrypted SSL/TLS connection. Additionally make sure the host / application is redirecting all users to the secured SSL/TLS connection before allowing to input sensitive data into the mentioned functions.

Affected Software/OS
Hosts / applications which doesn't enforce the transmission of sensitive data via an encrypted SSL/TLS connection.

Vulnerability Detection Method
Evaluate previous collected information and check if the host / application is not enforcing the transmission of sensitive data via an encrypted SSL/TLS connection.
The script is currently checking the following:
- HTTP Basic Authentication (Basic Auth)
- HTTP Forms (e.g. Login) with input field of type 'password'
Details: Cleartext Transmission of Sensitive Information via HTTP
OID:1.3.6.1.4.1.25623.1.0.108440
Version used: 2023-09-07T05:05:21Z

References
url: https://www.owasp.org/index.php/Top_10_2013-A2-Broken_Authentication_and_Se
↪ssion_Management
url: https://www.owasp.org/index.php/Top_10_2013-A6-Sensitive_Data_Exposure
url: https://cwe.mitre.org/data/definitions/319.html

Medium (CVSS: 4.3)

NVT: jQuery < 1.6.3 XSS Vulnerability

Summary
jQuery is prone to a cross-site scripting (XSS) vulnerability.

Quality of Detection (QoD): 80%

Vulnerability Detection Result
```
Installed version: 1.6.2
Fixed version:     1.6.3
Installation
path / port:       /phpmyadmin/js/jquery/jquery-1.6.2.js
Detection info (see OID: 1.3.6.1.4.1.25623.1.0.150658 for more info):
- Identified file: http://10.10.10.101/phpmyadmin/js/jquery/jquery-1.6.2.js
- Referenced at:   http://10.10.10.101/phpmyadmin/
```

Solution:
Solution type: VendorFix
Update to version 1.6.3 or later.

Affected Software/OS
jQuery prior to version 1.6.3.

Vulnerability Insight
Cross-site scripting (XSS) vulnerability in jQuery before 1.6.3, when using location.hash to select elements, allows remote attackers to inject arbitrary web script or HTML via a crafted tag.

Vulnerability Detection Method
Checks if a vulnerable version is present on the target host.
Details: `jQuery < 1.6.3 XSS Vulnerability`
OID:1.3.6.1.4.1.25623.1.0.141637
Version used: `2023-07-14T05:06:08Z`

References
```
cve: CVE-2011-4969
url: https://blog.jquery.com/2011/09/01/jquery-1-6-3-released/
cert-bund: CB-K17/0195
dfn-cert: DFN-CERT-2017-0199
dfn-cert: DFN-CERT-2016-0890
```

Medium (CVSS: 4.3)

NVT: jQuery < 1.6.3 XSS Vulnerability

Summary
jQuery is prone to a cross-site scripting (XSS) vulnerability.

Quality of Detection (QoD): 80%

Vulnerability Detection Result
```
Installed version: 1.6.2
Fixed version:     1.6.3
Installation
path / port:       /phpmyadmin/setup/../js/jquery/jquery-1.6.2.js
Detection info (see OID: 1.3.6.1.4.1.25623.1.0.150658 for more info):
- Identified file: http://10.10.10.101/phpmyadmin/setup/../js/jquery/jquery-1.6.
↪2.js
- Referenced at:   http://10.10.10.101/phpmyadmin/setup/
```

Solution:
Solution type: VendorFix
Update to version 1.6.3 or later.

Affected Software/OS
jQuery prior to version 1.6.3.

Vulnerability Insight
Cross-site scripting (XSS) vulnerability in jQuery before 1.6.3, when using location.hash to select elements, allows remote attackers to inject arbitrary web script or HTML via a crafted tag.

Vulnerability Detection Method
Checks if a vulnerable version is present on the target host.
Details: `jQuery < 1.6.3 XSS Vulnerability`
OID:1.3.6.1.4.1.25623.1.0.141637
Version used: 2023-07-14T05:06:08Z

References
```
cve: CVE-2011-4969
url: https://blog.jquery.com/2011/09/01/jquery-1-6-3-released/
cert-bund: CB-K17/0195
dfn-cert: DFN-CERT-2017-0199
dfn-cert: DFN-CERT-2016-0890
```

[return to 10.10.10.101]

2.1.8 Medium 21/tcp

Medium (CVSS: 4.8)

NVT: FTP Unencrypted Cleartext Login

Summary
The remote host is running a FTP service that allows cleartext logins over unencrypted connections.

Quality of Detection (QoD): 70%

Vulnerability Detection Result
```
The remote FTP service accepts logins without a previous sent 'AUTH TLS' command
↪. Response(s):
Non-anonymous sessions: 331 Password required for openvasvt
Anonymous sessions:     331 Anonymous login ok, send your complete email address
↪ as your password
```

Impact
An attacker can uncover login names and passwords by sniffing traffic to the FTP service.

Solution:
Solution type: Mitigation
Enable FTPS or enforce the connection via the 'AUTH TLS' command. Please see the manual of the FTP service for more information.

Vulnerability Detection Method
Tries to login to a non FTPS enabled FTP service without sending a 'AUTH TLS' command first and checks if the service is accepting the login without enforcing the use of the 'AUTH TLS' command.
Details: `FTP Unencrypted Cleartext Login`
OID:1.3.6.1.4.1.25623.1.0.108528
Version used: `2023-12-20T05:05:58Z`

[return to 10.10.10.101]

2.1.9 Low 22/tcp

Low (CVSS: 2.6)

NVT: Weak MAC Algorithm(s) Supported (SSH)

Product detection result
```
cpe:/a:ietf:secure_shell_protocol
Detected by SSH Protocol Algorithms Supported (OID: 1.3.6.1.4.1.25623.1.0.105565
```

... continues on next page ...

... continued from previous page ...

↪)

Summary
The remote SSH server is configured to allow / support weak MAC algorithm(s).

Quality of Detection (QoD): 80%

Vulnerability Detection Result

```
The remote SSH server supports the following weak client-to-server MAC algorithm
↪(s):
hmac-md5
hmac-md5-96
hmac-md5-96-etm@openssh.com
hmac-md5-etm@openssh.com
hmac-sha1-96
hmac-sha1-96-etm@openssh.com
umac-64-etm@openssh.com
umac-64@openssh.com
The remote SSH server supports the following weak server-to-client MAC algorithm
↪(s):
hmac-md5
hmac-md5-96
hmac-md5-96-etm@openssh.com
hmac-md5-etm@openssh.com
hmac-sha1-96
hmac-sha1-96-etm@openssh.com
umac-64-etm@openssh.com
umac-64@openssh.com
```

Solution:
Solution type: Mitigation
Disable the reported weak MAC algorithm(s).

Vulnerability Detection Method
Checks the supported MAC algorithms (client-to-server and server-to-client) of the remote SSH server.
Currently weak MAC algorithms are defined as the following:
- MD5 based algorithms
- 96-bit based algorithms
- 64-bit based algorithms
- 'none' algorithm
Details: `Weak MAC Algorithm(s) Supported (SSH)`
OID:1.3.6.1.4.1.25623.1.0.105610
Version used: `2024-06-14T05:05:48Z`

... continues on next page ...

... continued from previous page ...

Product Detection Result
Product: cpe:/a:ietf:secure_shell_protocol
Method: SSH Protocol Algorithms Supported
OID: 1.3.6.1.4.1.25623.1.0.105565)

References
url: https://www.rfc-editor.org/rfc/rfc6668
url: https://www.rfc-editor.org/rfc/rfc4253#section-6.4

[return to 10.10.10.101]

2.1.10 Low general/tcp

Low (CVSS: 2.6)

NVT: TCP Timestamps Information Disclosure

Summary
The remote host implements TCP timestamps and therefore allows to compute the uptime.

Quality of Detection (QoD): 80%

Vulnerability Detection Result
It was detected that the host implements RFC1323/RFC7323.
The following timestamps were retrieved with a delay of 1 seconds in-between:
Packet 1: 4327591
Packet 2: 4327855

Impact
A side effect of this feature is that the uptime of the remote host can sometimes be computed.

Solution:
Solution type: Mitigation
To disable TCP timestamps on linux add the line 'net.ipv4.tcp_timestamps = 0' to /etc/sysctl.conf. Execute 'sysctl -p' to apply the settings at runtime.
To disable TCP timestamps on Windows execute 'netsh int tcp set global timestamps=disabled'
Starting with Windows Server 2008 and Vista, the timestamp can not be completely disabled.
The default behavior of the TCP/IP stack on this Systems is to not use the Timestamp options when initiating TCP connections, but use them if the TCP peer that is initiating communication includes them in their synchronize (SYN) segment.
See the references for more information.

Affected Software/OS

... continues on next page ...

... continued from previous page ...

TCP implementations that implement RFC1323/RFC7323.

Vulnerability Insight
The remote host implements TCP timestamps, as defined by RFC1323/RFC7323.

Vulnerability Detection Method
Special IP packets are forged and sent with a little delay in between to the target IP. The responses are searched for a timestamps. If found, the timestamps are reported.
Details: `TCP Timestamps Information Disclosure`
OID:1.3.6.1.4.1.25623.1.0.80091
Version used: `2023-12-15T16:10:08Z`

References
`url: https://datatracker.ietf.org/doc/html/rfc1323`
`url: https://datatracker.ietf.org/doc/html/rfc7323`
`url: https://web.archive.org/web/20151213072445/http://www.microsoft.com/en-us/d`
`↪ownload/details.aspx?id=9152`
`url: https://www.fortiguard.com/psirt/FG-IR-16-090`

[return to 10.10.10.101]

2.1.11 Low general/icmp

Low (CVSS: 2.1)

NVT: ICMP Timestamp Reply Information Disclosure

Summary
The remote host responded to an ICMP timestamp request.

Quality of Detection (QoD): 80%

Vulnerability Detection Result
`The following response / ICMP packet has been received:`
`- ICMP Type: 14`
`- ICMP Code: 0`

Impact
This information could theoretically be used to exploit weak time-based random number generators in other services.

Solution:
Solution type: Mitigation
Various mitigations are possible:
- Disable the support for ICMP timestamp on the remote host completely

... continues on next page ...

... continued from previous page ...

- Protect the remote host by a firewall, and block ICMP packets passing through the firewall in either direction (either completely or only for untrusted networks)

Vulnerability Insight
The Timestamp Reply is an ICMP message which replies to a Timestamp message. It consists of the originating timestamp sent by the sender of the Timestamp as well as a receive timestamp and a transmit timestamp.

Vulnerability Detection Method
Sends an ICMP Timestamp (Type 13) request and checks if a Timestamp Reply (Type 14) is received.
Details: `ICMP Timestamp Reply Information Disclosure`
OID:1.3.6.1.4.1.25623.1.0.103190
Version used: `2025-01-21T05:37:33Z`

References
`cve: CVE-1999-0524`
`url: https://datatracker.ietf.org/doc/html/rfc792`
`url: https://datatracker.ietf.org/doc/html/rfc2780`
`cert-bund: CB-K15/1514`
`cert-bund: CB-K14/0632`
`dfn-cert: DFN-CERT-2014-0658`

[return to 10.10.10.101]

2.2 10.10.10.102

Host scan start	Tue May 5 13:39:03 2026 UTC
Host scan end	Tue May 5 13:55:05 2026 UTC

Service (Port)	Threat Level
21/tcp	Critical
21/tcp	Medium
80/tcp	Medium
22/tcp	Low
general/tcp	Low
general/icmp	Low

2.2.1 Critical 21/tcp

Critical (CVSS: 9.8)

NVT: ProFTPD Backdoor Unauthorized Access Vulnerability (Dec 2010) - Active Check

Summary
ProFTPD is prone to an unauthorized access vulnerability due to a backdoor in certain versions of the application.

Quality of Detection (QoD): 99%

Vulnerability Detection Result
```
It was possible to execute the command "id" on the remote host, which produces t
↪he following output:
uid=0(root) gid=0(root) groups=0(root),65534(nogroup)
```

Impact
Exploiting this issue allows remote attackers to execute arbitrary system commands with superuser privileges.

Solution:
Solution type: VendorFix
The vendor released an advisory to address the issue. Please see the references for more information.

Affected Software/OS
The issue affects the ProFTPD 1.3.3c package downloaded between November 28 and December 2, 2010.
The MD5 sums of the unaffected ProFTPD 1.3.3c source packages are as follows:
8571bd78874b557e98480ed48e2df1d2 proftpd-1.3.3c.tar.bz2
4f2c554d6273b8145095837913ba9e5d proftpd-1.3.3c.tar.gz
Files with MD5 sums other than those listed above should be considered affected.

Vulnerability Detection Method
Sends multiple crafted FTP commands and checks the responses.
Details: `ProFTPD Backdoor Unauthorized Access Vulnerability (Dec 2010) - Active Check`
OID:1.3.6.1.4.1.25623.1.0.100933
Version used: `2025-09-25T05:39:09Z`

References
```
cve: CVE-2010-20103
url: https://web.archive.org/web/20110917012335/http://www.securityfocus.com/bid
↪/45150
url: http://sourceforge.net/mailarchive/message.php?msg_name=alpine.DEB.2.00.101
↪2011542220.12930%40familiar.castaglia.org
url: https://www.exploit-db.com/exploits/15662
url: https://www.exploit-db.com/exploits/16921
```

... continues on next page ...

... continued from previous page ...

cert-bund: WID-SEC-2025-1879

[return to 10.10.10.102]

2.2.2 Medium 21/tcp

Medium (CVSS: 4.8)

NVT: FTP Unencrypted Cleartext Login

Summary
The remote host is running a FTP service that allows cleartext logins over unencrypted connections.

Quality of Detection (QoD): 70%

Vulnerability Detection Result
The remote FTP service accepts logins without a previous sent 'AUTH TLS' command ↪. Response(s):
Non-anonymous sessions: 331 Password required for openvasvt

Impact
An attacker can uncover login names and passwords by sniffing traffic to the FTP service.

Solution:
Solution type: Mitigation
Enable FTPS or enforce the connection via the 'AUTH TLS' command. Please see the manual of the FTP service for more information.

Vulnerability Detection Method
Tries to login to a non FTPS enabled FTP service without sending a 'AUTH TLS' command first and checks if the service is accepting the login without enforcing the use of the 'AUTH TLS' command.
Details: FTP Unencrypted Cleartext Login
OID:1.3.6.1.4.1.25623.1.0.108528
Version used: 2023-12-20T05:05:58Z

[return to 10.10.10.102]

2.2.3 Medium 80/tcp

Medium (CVSS: 5.3)

NVT: WordPress < 6.5 Private Information Exposure Vulnerability

Summary
WordPress is prone to a private information exposure via 'redirect_guess_404_permalink()'.

Quality of Detection (QoD): 80%

Vulnerability Detection Result
```
Installed version: 4.9
Fixed version:     6.5
Installation
path / port:       /secret
```

Impact
This can allow unauthenticated attackers to expose the slug of a custom post whose 'publicly_queryable' post status has been set to 'false'.

Solution:
Solution type: VendorFix
Update to version 6.5 or later.
Note: As of 04/2024 the security fix is only available in version 6.5 and haven't been 'backported' to older versions yet.

Affected Software/OS
WordPress versions prior to 6.5.

Vulnerability Insight
When guessing the proper URL to redirect a 404, WordPress only considers the post statuses and not the proper post type privacy settings, leading to potential information disclosure.

Vulnerability Detection Method
Checks if a vulnerable version is present on the target host.
Details: `WordPress < 6.5 Private Information Exposure Vulnerability`
OID:1.3.6.1.4.1.25623.1.0.114477
Version used: `2025-01-13T08:32:03Z`

References
```
cve: CVE-2023-5692
url: https://core.trac.wordpress.org/ticket/59795
url: https://core.trac.wordpress.org/changeset/57645
url: https://bugzilla.redhat.com/show_bug.cgi?id=2273662
url: https://www.wordfence.com/threat-intel/vulnerabilities/id/6e6f993b-ce09-405
↪0-84a1-cbe9953f36b1
url: https://patchstack.com/database/vulnerability/wordpress/wordpress-wordpress
```
... continues on next page ...

... continued from previous page ...

```
↪-core-plugin-6-4-3-sensitive-information-exposure-via-redirect-guess-404-perma
↪link-vulnerability
cert-bund: WID-SEC-2024-0808
```

[return to 10.10.10.102]

2.2.4 Low 22/tcp

Low (CVSS: 2.6)

NVT: Weak MAC Algorithm(s) Supported (SSH)

Product detection result

```
cpe:/a:ietf:secure_shell_protocol
Detected by SSH Protocol Algorithms Supported (OID: 1.3.6.1.4.1.25623.1.0.105565
↪)
```

Summary

The remote SSH server is configured to allow / support weak MAC algorithm(s).

Quality of Detection (QoD): 80%

Vulnerability Detection Result

```
The remote SSH server supports the following weak client-to-server MAC algorithm
↪(s):
umac-64-etm@openssh.com
umac-64@openssh.com
The remote SSH server supports the following weak server-to-client MAC algorithm
↪(s):
umac-64-etm@openssh.com
umac-64@openssh.com
```

Solution:

Solution type: Mitigation

Disable the reported weak MAC algorithm(s).

Vulnerability Detection Method

Checks the supported MAC algorithms (client-to-server and server-to-client) of the remote SSH server.

Currently weak MAC algorithms are defined as the following:

- MD5 based algorithms
- 96-bit based algorithms
- 64-bit based algorithms

... continues on next page ...

... continued from previous page ...

- 'none' algorithm
Details: Weak MAC Algorithm(s) Supported (SSH)
OID:1.3.6.1.4.1.25623.1.0.105610
Version used: 2024-06-14T05:05:48Z

Product Detection Result
Product: cpe:/a:ietf:secure_shell_protocol
Method: SSH Protocol Algorithms Supported
OID: 1.3.6.1.4.1.25623.1.0.105565)

References
url: https://www.rfc-editor.org/rfc/rfc6668
url: https://www.rfc-editor.org/rfc/rfc4253#section-6.4

[return to 10.10.10.102]

2.2.5 Low general/tcp

Low (CVSS: 2.6)

NVT: TCP Timestamps Information Disclosure

Summary
The remote host implements TCP timestamps and therefore allows to compute the uptime.

Quality of Detection (QoD): 80%

Vulnerability Detection Result
It was detected that the host implements RFC1323/RFC7323.
The following timestamps were retrieved with a delay of 1 seconds in-between:
Packet 1: 404684266
Packet 2: 404684545

Impact
A side effect of this feature is that the uptime of the remote host can sometimes be computed.

Solution:
Solution type: Mitigation
To disable TCP timestamps on linux add the line 'net.ipv4.tcp_timestamps = 0' to /etc/sysctl.conf. Execute 'sysctl -p' to apply the settings at runtime.
To disable TCP timestamps on Windows execute 'netsh int tcp set global timestamps=disabled' Starting with Windows Server 2008 and Vista, the timestamp can not be completely disabled.

... continues on next page ...

... continued from previous page ...

The default behavior of the TCP/IP stack on this Systems is to not use the Timestamp options when initiating TCP connections, but use them if the TCP peer that is initiating communication includes them in their synchronize (SYN) segment.
See the references for more information.

Affected Software/OS
TCP implementations that implement RFC1323/RFC7323.

Vulnerability Insight
The remote host implements TCP timestamps, as defined by RFC1323/RFC7323.

Vulnerability Detection Method
Special IP packets are forged and sent with a little delay in between to the target IP. The responses are searched for a timestamps. If found, the timestamps are reported.
Details: `TCP Timestamps Information Disclosure`
OID:1.3.6.1.4.1.25623.1.0.80091
Version used: `2023-12-15T16:10:08Z`

References
```
url: https://datatracker.ietf.org/doc/html/rfc1323
url: https://datatracker.ietf.org/doc/html/rfc7323
url: https://web.archive.org/web/20151213072445/http://www.microsoft.com/en-us/d
↪ownload/details.aspx?id=9152
url: https://www.fortiguard.com/psirt/FG-IR-16-090
```

[return to 10.10.10.102]

2.2.6 Low general/icmp

Low (CVSS: 2.1)

NVT: ICMP Timestamp Reply Information Disclosure

Summary
The remote host responded to an ICMP timestamp request.

Quality of Detection (QoD): 80%

Vulnerability Detection Result
```
The following response / ICMP packet has been received:
- ICMP Type: 14
- ICMP Code: 0
```

Impact

... continues on next page ...

... continued from previous page ...

This information could theoretically be used to exploit weak time-based random number generators in other services.

Solution:
Solution type: Mitigation
Various mitigations are possible:
- Disable the support for ICMP timestamp on the remote host completely
- Protect the remote host by a firewall, and block ICMP packets passing through the firewall in either direction (either completely or only for untrusted networks)

Vulnerability Insight
The Timestamp Reply is an ICMP message which replies to a Timestamp message. It consists of the originating timestamp sent by the sender of the Timestamp as well as a receive timestamp and a transmit timestamp.

Vulnerability Detection Method
Sends an ICMP Timestamp (Type 13) request and checks if a Timestamp Reply (Type 14) is received.
Details: `ICMP Timestamp Reply Information Disclosure`
OID:1.3.6.1.4.1.25623.1.0.103190
Version used: `2025-01-21T05:37:33Z`

References
`cve: CVE-1999-0524`
`url: https://datatracker.ietf.org/doc/html/rfc792`
`url: https://datatracker.ietf.org/doc/html/rfc2780`
`cert-bund: CB-K15/1514`
`cert-bund: CB-K14/0632`
`dfn-cert: DFN-CERT-2014-0658`

[return to 10.10.10.102]

2.3 10.10.10.109

Host scan start	Tue May 5 13:39:03 2026 UTC
Host scan end	Tue May 5 13:47:18 2026 UTC

Service (Port)	Threat Level
445/tcp	Critical
general/tcp	Critical
445/tcp	High
135/tcp	Medium
general/icmp	Low

2.3.1 Critical 445/tcp

Critical (CVSS: 10.0)

NVT: Microsoft Windows SMB Server NTLM Multiple Vulnerabilities (971468)

Summary
This host is missing a critical security update according to Microsoft Bulletin MS10-012.

Quality of Detection (QoD): 98%

Vulnerability Detection Result
Vulnerability was detected according to the Vulnerability Detection Method.

Impact
Successful exploitation will allow remote attackers to execute arbitrary code or cause a denial of service or bypass the authentication mechanism via brute force technique.

Solution:
Solution type: VendorFix
The vendor has released updates. Please see the references for more information.

Affected Software/OS
- Microsoft Windows 7
- Microsoft Windows 2000 Service Pack and prior
- Microsoft Windows XP Service Pack 3 and prior
- Microsoft Windows Vista Service Pack 2 and prior
- Microsoft Windows Server 2003 Service Pack 2 and prior
- Microsoft Windows Server 2008 Service Pack 2 and prior

Vulnerability Insight
- An input validation error exists while processing SMB requests and can be exploited to cause a buffer overflow via a specially crafted SMB packet.
- An error exists in the SMB implementation while parsing SMB packets during the Negotiate phase causing memory corruption via a specially crafted SMB packet.
- NULL pointer dereference error exists in SMB while verifying the 'share' and 'servername' fields in SMB packets causing denial of service.
- A lack of cryptographic entropy when the SMB server generates challenges during SMB NTLM authentication and can be exploited to bypass the authentication mechanism.

Vulnerability Detection Method
Details: `Microsoft Windows SMB Server NTLM Multiple Vulnerabilities (971468)`
OID:1.3.6.1.4.1.25623.1.0.902269
Version used: `2025-03-05T05:38:52Z`

References
`cve: CVE-2010-0020`
`cve: CVE-2010-0021`

. . . continues on next page . . .

... continued from previous page ...

cve: CVE-2010-0022
cve: CVE-2010-0231
url: http://support.microsoft.com/kb/971468
url: http://www.vupen.com/english/advisories/2010/0345
url: https://docs.microsoft.com/en-us/security-updates/securitybulletins/2010/ms
↪10-012
dfn-cert: DFN-CERT-2010-0192

Critical (CVSS: 10.0)

NVT: Microsoft SMB Multiple RCE Vulnerabilities (958687) - Active Check

Summary
This host is missing a critical security update according to Microsoft Bulletin MS09-001.

Quality of Detection (QoD): 98%

Vulnerability Detection Result
Vulnerability was detected according to the Vulnerability Detection Method.

Impact
Successful exploitation could allow remote unauthenticated attackers to cause denying the service by sending a specially crafted network message to a system running the server service.

Solution:
Solution type: VendorFix
The vendor has released updates. Please see the references for more information.

Affected Software/OS
- Microsoft Windows 2K Service Pack 4 and prior
- Microsoft Windows XP Service Pack 3 and prior
- Microsoft Windows 2003 Service Pack 2 and prior

Vulnerability Insight
The issue is due to the way Server Message Block (SMB) Protocol software handles specially crafted SMB packets.

Vulnerability Detection Method
Details: Microsoft SMB Multiple RCE Vulnerabilities (958687) - Active Check
OID:1.3.6.1.4.1.25623.1.0.900233
Version used: 2025-04-16T05:39:43Z

References
cve: CVE-2008-4114
cve: CVE-2008-4834

... continues on next page ...

... continued from previous page ...

cve: CVE-2008-4835
url: http://www.milw0rm.com/exploits/6463
url: http://www.securityfocus.com/bid/31179
url: https://docs.microsoft.com/en-us/security-updates/securitybulletins/2009/ms
↪09-001

Critical (CVSS: 10.0)

NVT: Microsoft Windows Server Service Remote Code Execution Vulnerability (921883)

Summary
This host is missing important security update according to Microsoft Bulletin MS06-040.

Quality of Detection (QoD): 98%

Vulnerability Detection Result
Vulnerability was detected according to the Vulnerability Detection Method.

Impact
Successful exploitation could allow remote code execution by sending a specially crafted RPC request and can take complete control of an affected system.

Solution:
Solution type: VendorFix
The vendor has released updates. Please see the references for more information.

Affected Software/OS
- Microsoft Windows XP Service Pack 2 and prior
- Microsoft Windows 2K3 Service Pack 1 and prior
- Microsoft Windows 2000 Service Pack 4 and prior

Vulnerability Insight
The flaw is due to a boundary error in the 'CanonicalizePathName()' function in netapi32.dll and can be exploited to cause a stack-based buffer overflow via a malicious NetrpPathCanonicalize RPC request with an overly long path name to the Server Service.

Vulnerability Detection Method
Details: Microsoft Windows Server Service Remote Code Execution Vulnerability (921883)
OID:1.3.6.1.4.1.25623.1.0.902782
Version used: 2025-03-05T05:38:52Z

References
cve: CVE-2006-3439
url: http://securitytracker.com/id?1016667
url: http://www.securityfocus.com/bid/19409

... continues on next page ...

... continued from previous page ...

```
url: https://docs.microsoft.com/en-us/security-updates/securitybulletins/2006/ms
↪06-040
```

[return to 10.10.10.109]

2.3.2 Critical general/tcp

Critical (CVSS: 10.0)

NVT: Operating System (OS) End of Life (EOL) Detection

Product detection result

```
cpe:/o:microsoft:windows_xp
Detected by OS Detection Consolidation and Reporting (OID: 1.3.6.1.4.1.25623.1.0
↪.105937)
```

Summary

The Operating System (OS) on the remote host has reached the end of life (EOL) and should not be used anymore.

Quality of Detection (QoD): 80%

Vulnerability Detection Result

```
The "Windows XP" Operating System on the remote host has reached the end of life
↪.
CPE:                cpe:/o:microsoft:windows_xp
EOL date:           2014-04-08
EOL info:           https://support.microsoft.com/en-us/lifecycle/search?sort=PN&
↪alpha=Microsoft%20Windows%20XP&Filter=FilterNO
```

Impact

An EOL version of an OS is not receiving any security updates from the vendor. Unfixed security vulnerabilities might be leveraged by an attacker to compromise the security of this host.

Solution:

Solution type: Mitigation

Update the OS on the remote host to a version which is still supported and receiving security updates by the vendor.

Note / Important: Please create an override for this result if the target host is a:

- Windows system with Extended Security Updates (ESU)
- System with additional 3rd-party / non-vendor security updates like e.g. from 'TuxCare', 'Freexian Extended LTS' or similar

... continues on next page ...

... continued from previous page ...

Vulnerability Detection Method
Checks if an EOL version of an OS is present on the target host.
Details: `Operating System (OS) End of Life (EOL) Detection`
OID:1.3.6.1.4.1.25623.1.0.103674
Version used: `2025-05-21T05:40:19Z`

Product Detection Result
Product: `cpe:/o:microsoft:windows_xp`
Method: `OS Detection Consolidation and Reporting`
OID: 1.3.6.1.4.1.25623.1.0.105937)

[return to 10.10.10.109]

2.3.3 High 445/tcp

High (CVSS: 8.8)

NVT: Microsoft Windows SMB Server Multiple Vulnerabilities-Remote (4013389)

Summary
This host is missing a critical security update according to Microsoft Bulletin MS17-010.

Quality of Detection (QoD): 95%

Vulnerability Detection Result
Vulnerability was detected according to the Vulnerability Detection Method.

Impact
Successful exploitation will allow remote attackers to gain the ability to execute code on the target server, also could lead to information disclosure from the server.

Solution:
Solution type: VendorFix
The vendor has released updates. Please see the references for more information.

Affected Software/OS
- Microsoft Windows 10 x32/x64
- Microsoft Windows Server 2012
- Microsoft Windows Server 2016
- Microsoft Windows 8.1 x32/x64
- Microsoft Windows Server 2012 R2
- Microsoft Windows 7 x32/x64 Service Pack 1
- Microsoft Windows Vista x32/x64 Service Pack 2
- Microsoft Windows Server 2008 R2 x64 Service Pack 1

... continues on next page ...

... continued from previous page ...

- Microsoft Windows Server 2008 x32/x64 Service Pack 2

Vulnerability Insight
Multiple flaws exist due to the way that the Microsoft Server Message Block 1.0 (SMBv1) server handles certain requests.

Vulnerability Detection Method
Send the crafted SMB transaction request with fid = 0 and check the response to confirm the vulnerability.
Details: `Microsoft Windows SMB Server Multiple Vulnerabilities-Remote (4013389)`
OID:1.3.6.1.4.1.25623.1.0.810676
Version used: `2024-07-17T05:05:38Z`

References
`cve: CVE-2017-0143`
`cve: CVE-2017-0144`
`cve: CVE-2017-0145`
`cve: CVE-2017-0146`
`cve: CVE-2017-0147`
`cve: CVE-2017-0148`
`cisa: Known Exploited Vulnerability (KEV) catalog`
`url: https://www.cisa.gov/known-exploited-vulnerabilities-catalog`
`url: https://support.microsoft.com/en-us/kb/4013078`
`url: http://www.securityfocus.com/bid/96703`
`url: http://www.securityfocus.com/bid/96704`
`url: http://www.securityfocus.com/bid/96705`
`url: http://www.securityfocus.com/bid/96707`
`url: http://www.securityfocus.com/bid/96709`
`url: http://www.securityfocus.com/bid/96706`
`url: https://technet.microsoft.com/library/security/MS17-010`
`url: https://github.com/rapid7/metasploit-framework/pull/8167/files`
`cert-bund: CB-K17/0435`
`dfn-cert: DFN-CERT-2017-0448`

[return to 10.10.10.109]

2.3.4 Medium 135/tcp

Medium (CVSS: 5.0)

NVT: DCE/RPC and MSRPC Services Enumeration Reporting

Summary
Distributed Computing Environment / Remote Procedure Calls (DCE/RPC) or MSRPC based service enumeration reporting.

... continues on next page ...

... continued from previous page ...

Quality of Detection (QoD): 80%

Vulnerability Detection Result

```
Here is the list of DCE/RPC or MSRPC services running on this host via the TCP p
↪rotocol:
Port: 1025/tcp
     UUID: 0a74ef1c-41a4-4e06-83ae-dc74fb1cdd53, version 1
     Endpoint: ncacn_ip_tcp:10.10.10.109[1025]
     UUID: 1ff70682-0a51-30e8-076d-740be8cee98b, version 1
     Endpoint: ncacn_ip_tcp:10.10.10.109[1025]
     Named pipe : atsvc
     Win32 service or process : mstask.exe
     Description : Scheduler service
     UUID: 378e52b0-c0a9-11cf-822d-00aa0051e40f, version 1
     Endpoint: ncacn_ip_tcp:10.10.10.109[1025]
     UUID: 5a7b91f8-ff00-11d0-a9b2-00c04fb6e6fc, version 1
     Endpoint: ncacn_ip_tcp:10.10.10.109[1025]
     Annotation: Messenger Service
     Named pipe : ntsvcs
     Win32 service or process : messenger
     Description : Messenger service
Here is the list of DCE/RPC or MSRPC services running on this host via the UDP p
↪rotocol:
Note: DCE/RPC or MSRPC services running on this host locally were identified. Re
↪porting this list is not enabled by default due to the possible large size of
↪this list. See the script preferences to enable this reporting.
```

Impact

An attacker may use this information to gain more knowledge about the remote host and to conduct further attacks based on it.

Solution:

Solution type: Mitigation

Filter incoming traffic to this ports.

Affected Software/OS

All systems exposing / disclosing information via DCE/RPC or MSRPC services.

Vulnerability Insight

DCE/RPC or MSRPC services running on the remote host can be enumerated by connecting on port 135 and doing the appropriate queries.

Vulnerability Detection Method

Reports previously collected (via 'DCE/RPC and MSRPC Services Enumeration' OID: 1.3.6.1.4.1.25623.1.0.108044) DCE/RPC or MSRPC services.

... continues on next page ...

... continued from previous page ...

This VT is reporting a severity by default. If the scanned network is e.g. a private LAN / private WAN which contains systems not accessible to the public (access restricted) and it is accepted that the service is disclosing information to this network please set the 'Network type' configuration of the following VT to e.g. 'Private LAN' or 'Private WAN':
Global variable settings (OID: 1.3.6.1.4.1.25623.1.0.12288)
In this case a 'Log' level result is used instead.
Details: `DCE/RPC and MSRPC Services Enumeration Reporting`
OID:1.3.6.1.4.1.25623.1.0.10736
Version used: `2025-11-26T05:40:08Z`

[return to 10.10.10.109]

2.3.5 Low general/icmp

Low (CVSS: 2.1)

NVT: ICMP Timestamp Reply Information Disclosure

Summary
The remote host responded to an ICMP timestamp request.

Quality of Detection (QoD): 80%

Vulnerability Detection Result
```
The following response / ICMP packet has been received:
- ICMP Type: 14
- ICMP Code: 0
```

Impact
This information could theoretically be used to exploit weak time-based random number generators in other services.

Solution:
Solution type: Mitigation
Various mitigations are possible:
- Disable the support for ICMP timestamp on the remote host completely
- Protect the remote host by a firewall, and block ICMP packets passing through the firewall in either direction (either completely or only for untrusted networks)

Vulnerability Insight
The Timestamp Reply is an ICMP message which replies to a Timestamp message. It consists of the originating timestamp sent by the sender of the Timestamp as well as a receive timestamp and a transmit timestamp.

... continues on next page ...

... continued from previous page ...

Vulnerability Detection Method
Sends an ICMP Timestamp (Type 13) request and checks if a Timestamp Reply (Type 14) is received.
Details: `ICMP Timestamp Reply Information Disclosure`
OID:1.3.6.1.4.1.25623.1.0.103190
Version used: `2025-01-21T05:37:33Z`

References
`cve: CVE-1999-0524`
`url: https://datatracker.ietf.org/doc/html/rfc792`
`url: https://datatracker.ietf.org/doc/html/rfc2780`
`cert-bund: CB-K15/1514`
`cert-bund: CB-K14/0632`
`dfn-cert: DFN-CERT-2014-0658`

[return to 10.10.10.109]