

Elementary Data Structures

Doan Nhat Quang

doan-nhat.quang@usth.edu.vn
University of Science and Technology of Hanoi
ICTLab


Today Objectives

- ▶ Introduce the fundamental definitions in C/C++.
- ▶ Review elementary data types in programming such as array, pointer, structure, enumeration, etc.
- ▶ Study the C/C++ examples.

Definitions

Data

Data refers to the fact that some existing information or knowledge. Data is a set of values of qualitative or quantitative **variables**.



Everything can be considered as data:

- ▶ name, age, adresse of a person
- ▶ number, series of number
- ▶ pixels or images in RGB color model or in grayscale
- ▶ linear functions, polynomial functions, exponential functions
- ▶ trees, graphs, maps, documents

Variables

Being used to store data, **variables** are simply names used to refer to some location in memory, a location that we can use to write, retrieve, and manipulate throughout the course of program.

Variables

Being used to store data, **variables** are simply names used to refer to some location in memory, a location that we can use to write, retrieve, and manipulate throughout the course of program.

Variable declaration

Variable declaration shows **a specific type**, which determines **the size** used in the memory; the range of values that can be stored within that memory; and **the set of operations** that can be applied to the variable.

Variables

Variable name is an identifier for that variable call-by-name; reference-by-name. The name can be composed of letters, digits, and the underscore character. Upper and lowercase letters are distinct.

```
1 <Type> <Variable>;  
2 float F;  
3 // declaration of a real number F  
4 int id;  
5 // declaration of an integer as an id  
6 char *address;  
7 // declaration of a string of characters
```

Variables

A variable **MUST be initialized** with a value before it is used.

Code C/C++

```
1 int student_number=1254;
2 double scholarship=1132.50;
3 unsigned char gender=1;
4 string *home_address=" Hanoi" ;
5 char class_type='A' ;
```


Integer Types

There are few ways to declare an integer:

- 1 `char` `short int` `unsigned short int`
- 2 `signed char` `int` `unsigned int`
- 3 `unsigned char` `long int` `unsigned long int`

Type	Size	Description
<code>char</code>	8 bits	an integer type $[-127; 127]$
<code>(signed) int</code>	32 bits	the most natural size of integer for a computer $[-2^{31} - 1; 2^{31} + 1]$
<code>unsigned</code>	32 bits	non-negative integer number
<code>short</code>	16 bits	a half of normal integer size
<code>long</code>	64 bits	a double of normal integer size

Real Types

Represent real values, such as 3.14 or 0.01, with different levels of precision, depending on which of the three floating-point types is used.

Type	Size	Description
float	32 bits	a single-precision floating point value
double	64 bits	a double-precision floating point value
long double	≥ 64 bits	often more precise than double precision

Character Type

Beside the use as an integer, char also can be declared for a character. The value is determined at the character code in the ASCII table.

```
1 char ch = 65;    // an integer
2 char ch = 'A';   // a character
```


Examples

```
1  int a, b;   float c;   char d = 'A';
2  b = 1;
3  a = b + 4.5;
4  c = a / 4;
5  d = c + d;
6  printf("%d, %d, %f, %d", a, b, c, d);
```

```
1  int a, b;   float c;   char d = 'A';
2  b = 1;
3  a = b + 4.5;
4  c = a / 4.0;
5  d = c + d;
6  printf("%d, %d, %f, %c", a, b, c, d);
```

Computer program

A computer program is a collection of instructions that performs a specific task when executed by a computer. A program always consists of a main including with many functions and procedures.



Function

A named section of a computer program that performs a specific task and returns value.

Function

Function

A named section of a computer program that performs a specific task and returns value.

```
1  int sum(int n){  
2      int s = 0;  
3      for (int i = 1; i <= n; i++)  
4          s += i;  
5      return s;  
6  }
```

Function

A named section of a computer program that performs a specific task and returns value.

```
1  int sum(int n){  
2      int s = 0;  
3      for (int i = 1; i <= n; i++)  
4          s += i;  
5      return s;  
6  }
```



Attention

return has to be used to return the value and complete the function.

Function

A function can be called or used in other functions.

Function

A function can be called or used in other functions.

```
1  int doublesum(int n){
2      int sum2 = sum(n) + sum(n);
3      return sum2;
4  }
5  int main(){
6      int n = 10;
7      int sum1 = sum(10);
8      int sum2 = doublesum(10*sum(n));
9      return 0;
10 }
```

Void

Void means nothing to be used in C, C++

Void

Void means nothing to be used in C, C++

```
1  int myFunction(void) {  
2      return 10; // function parameters are absent  
3  }  
4  void myFunction(){  
5      statement; // the return value is absent  
6  }
```

Void

Void means nothing to be used in C, C++

```
1  int myFunction(void) {  
2      return 10; // function parameters are absent  
3  }  
4  void myFunction(){  
5      statement; // the return value is absent  
6  }
```



Attention

return in a void function is not necessary; however, it can be used to exit void functions.

Void

Void functions can be called and used like normal functions.

Void

Void functions can be called and used like normal functions.

```
1 void myPrint() {  
2     printf(" Hello World!" );  
3     return;  
4 }  
5 void myPrint2(int n){  
6     printf(" Number is %d" , n);  
7 }  
8 int main(){  
9     myPrint();  
10    myPrint2(100);  
11    return 0;  
12 }
```

Global variable vs local variable

Global variable

A global variable is a variable that it is visible (hence accessible) throughout the program. Its value can be changed anywhere in the code.

Global variable vs local variable

Global variable

A global variable is a variable that it is visible (hence accessible) throughout the program. Its value can be changed anywhere in the code.

Local variable

A local variable is a variable which is either a variable declared within the function or is an argument passed to a function. This type of variable can be only used within a function, after the execution, local variables are removed from the computer memory.

Global variable vs local variable

Code C/C++

```
1  int main(){
2      int result = sum(10); // local variable
3  }
4  int sum(int n){
5      int s = 0; // local variable
6      for (int i = 1; i<=n; i++){
7          s += i;
8      }
9      return s;
10 }
```

Global variable vs local variable

Code C/C++

```
1 #include <stdio.h>
2 int add_numbers( void );
3 int value1, value2, value3;
4 int add_numbers( void ){
5     int result = value1 + value2 + value3;
6     return result;
7 }
8 int main(){
9     int result;
10    value1 = 10; value2 = 20; value3 = 30;
11    result = add_numbers();
12    printf("The sum of %d + %d + %d is %d\n",
13    value1, value2, value3, result);
14    return 0;
15 }
```

Definition

- ▶ An array is a predefined-size sequential collection of N elements of the same type.
- ▶ The objects are called elements of the array and they are indexed by their order in the sequence.
- ▶ The element indices are from 0 to $N - 1$.

```
1 <type> <name>[<number of elements>];  
2 int age[100]; /* declaration of an array  
3 consisted of 100 integer variables */  
4 float series[50]; /* declaration of an array  
5 consisted of 50 float variables */
```

To access an element in an array, **an index** is available for use such as $a[0]$, $b[1]$, $a[i]$, $b[i + j]$ with $i, j \in \mathbb{N}$. A basic loop permits to process every elements of the array.

```
1  for (i = 0; i < n; i++){  
2      <processing the ith element of the array>;  
3  }
```

Multi-Dimensional Arrays

The simplest form of the multi-dimensional array is the two-dimensional array (a table or a matrix). It can be extended to more general multi-dimensional cases. It's preferable to avoid arrays of dimension more than 3.

```
1 <type> <name> [<nb>][<nb>]...;  
2 int a[3][4][5];  
3 double b[10][10];  
4 char str[17][5];
```

Multi-Dimensional Arrays

The table indicates the structure of an two dimensional array with an element denoted by $a[i][j]$ where i is the i^{th} row and j is the j^{th} column.

	Column 0	Column 1	Column 2	Column 3
Row 0	$a[0][0]$	$a[0][1]$	$a[0][2]$	$a[0][3]$
Row 1	$a[1][0]$	$a[1][1]$	$a[1][2]$	$a[1][3]$
Row 2	$a[2][0]$	$a[2][1]$	$a[2][2]$	$a[2][3]$

Multi-dimensional arrays may be initialized by specifying bracketed values for each row.

```
1  int a[2][3] = { {1, 5, 8}, {2, 4, 7} };
2  for (int i = 0; i < 2; i++)
3      for (int j = 0; j < 3; j++)
4          statement;
```

Definition

A **pointer** is a variable whose value is the address of another variable, i.e., direct address of the memory location. Like any variable or constant, a pointer must be declared before its use to store any variable address.

```
1 int count;  
2 int *countPtr = &count;  
3 int *undecided = NULL;  
4 int &countAlias = count;    // In C++
```


Definition

Reference of a pointer must be initialized when being declared.
Pointer could be initialized with **NULL**.

- ▶ **&** or ampersand indicate a reference of a variable.
- ▶ ***** allows to get the value of the variables being pointed by pointers.

Creating references

- ▶ Consider a variable name as a label attached to the variable's location in memory.
- ▶ A reference is considered as a second label attached to that memory location. overloading

Example

We can declare reference variables for i as follows.

```
1  int    i = 17;  
2  int&    r = i;
```

Read the & in these declarations as reference: "r is an integer reference initialized to i".

Example

```
1  #include <iostream>
2  using namespace std;
3  int main () {
4      int    i;
5      double d;
6      // declare reference variables
7      int&    r = i;
8      double& s = d;
9      i = 5;
10     cout << "Value_of_i:_" << i << endl;
11     cout << "Value_of_i_reference:_" << r << endl;
12     d = 11.7;
13     cout << "Value_of_d:_" << d << endl;
14     cout << "Value_of_d_reference:_" << s << endl;
15     return 0;
16 }
```

What is the result?

References are often confused with pointers but

- ▶ There is no NULL references. A reference is connected to a legitimate piece of memory.
- ▶ Once a reference is initialized to an object, it cannot be changed to refer to another object. Pointers can be pointed to another object at any time.
- ▶ A reference must be initialized when it is created. Pointers can be initialized at any time.



Note

The variables in the formal parameter list are always local variables of a function

- ▶ With Pass By Value, function parameters receive copies of the data sent in.
- ▶ The original variables passed into a function from another function are not affected by the function call.

Pass By Value

Example

```
1  #include <iostream>
2  using namespace std;
3  void twice1(int x){
4      x = x*2; // LOCAL value of x will change
5  }
6  int twice2(int x){
7      return x*2; // return value of x gets changed
8  }
9  int main () {
10     int i = 10;
11     twice1(i);
12     cout << "value:_" << i << endl;
13     i = twice2(i);
14     cout << "value:_" << i << endl;
15     return 0;
16 }
```

What is the result?

Pass By Value

Example

```
1  #include <iostream>
2  using namespace std;
3  void twice(int x, int y){
4      x = x*2;    // LOCAL value of x will change
5      y = y*2;    // LOCAL value of y will change
6  }
7  int main () {
8      int    a = 10;
9      int    b = 5;
10     twice(a,b);
11     cout << "value_1:" << a << endl;
12     cout << "value_2:" << b << endl;
13     return 0;
14 }
```

What is the result?

Pass By Reference

- ▶ The parameters are still local to the function, but they are reference variables.
- ▶ The variables passed into a function DO get changed by the function call.

Example

```
1 void twice(int &x, int &y){  
2     x = x*2;    // these WILL affect the original arguments  
3     y = y*2;    // these WILL affect the original arguments  
4 }
```


Pass By Reference

Example

```
1  #include <iostream>
2  using namespace std;
3  void twice(int &x, int &y){
4      x = x*2;    // these WILL affect the original arguments
5      y = y*2;    // these WILL affect the original arguments
6  }
7  int main () {
8      int    a = 10;
9      int    b = 5;
10     twice(a,b);
11     cout << "value_1:" << a << endl;
12     cout << "value_2:" << b << endl;
13     return 0;
14 }
```

What is the result?



Note

When a function expects strict reference types in the parameter list, a value (i.e. a variable, or storage location) must be passed in.

Example

```
1 void twice(int &x, int &y){
2     x = x*2; // these WILL affect the original arguments
3     y = y*2; // these WILL affect the original arguments
4 }
5 int main(){
6     int a = 6, b = 10;
7     twice(a, b); // it is legal
8     twice(4, b); // it is NOT legal
9     twice(num + 6, avg - 10.6); // it is NOT legal
10 }
```

Pass By Value

- ▶ The local parameters are copies of the original arguments passed in.
- ▶ Changes made in the function to these variables do not affect originals.

Pass By Reference

- ▶ The local parameters are references to the storage locations of the original arguments passed in.
- ▶ Changes to these variables in the function will affect the originals.
- ▶ No copy is made, so overhead of copying (time, storage) is saved.

Arrays vs Pointers

- ▶ A variable declared as an array of some type acts as a pointer to that type.
- ▶ A pointer can be indexed to access to an array.

```
1  int a[10], *intPtr;  
2  intPtr = a; //intPtr pointing to a[0]  
3  *(intPtr+5) = 4; //a[5]=4  
4  intPtr = &a[7]; //intPtr pointing to the 7th element  
5  intPtr++; //intPtr pointing to the 8th element
```

Arrays vs Pointers

Pointers can also be assigned to reference dynamically allocated memory. The **malloc()** and **calloc()** functions are often used to do this.

```
1  int *intPtr;  
2  int size;  
3  scanf("%d", &size);  
4  intPtr = (int *)malloc(sizeof(int)*(size+10));  
5  *(intPtr + 3) = 5;  
6  intPtr[3] = 5;  
7  free(intPtr);
```

Arrays vs Pointers

An array of pointers can be used to point to a data array with each element of the pointer array pointing to an element of the data array.

```
1 int *Ptr [5];  
2 char *Ptr = " Hello , _World" ;  
3 char *Ptr [4]={ " Spring" , "Summer" , " Autumn" , " Winter" };
```

Since an array could be replaced by a pointer. An array of pointer is equivalent to pointer to pointer.

```
1 int **Ptr;  
2 char **Ptr;
```

String

String is an one-dimensional array of characters which is terminated by a NULL character `'\0'`. Built-in functions for C-string is in `<string.h>`.

```
1  char str1[5]; //maximal 4 characters
2  char str3[]="HANOI";
3  char *str4;
4  char *str4= (char *)calloc(6, sizeof(char));
5  char *str4="HANOI";
```

- ▶ One possible way to read in a string is by using **scanf()**. This function finishes reading when it reaches a space, or the string would get cut off.
- ▶ The function **gets()** can overcome this issue.

```
1 scanf("%s", str);  
2 // finish when it reaches space or enter  
3  
4 gets(str)  
5 /* finish when it reaches EOL or EOF replace  
6  it with 0 they do not do the bound checking  
7  of the string! */
```


Structures

Structure is user defined data type available in C programming, which allows to combine one or more variables, possibly of different types, grouped together under a single name for convenient handling.

```
1 struct [structure tag]{  
2     member definition;  
3     member definition;  
4     ...  
5     member definition;  
6 } [structure name];
```

Structures

```
1 typedef struct Student{
2     int age;
3     char name[50];
4     unsigned char gender;
5 } ;
6 struct Student s1, s2;
```

```
1 struct StudentUSTH{
2     int age;
3     char name[50];
4     unsigned char gender;
5 };
6 typedef struct StudentUSTH STH;
7 STH s1, s2;
```

To access and process structure fields, dot '.' operator can be used

```
1 s1.age = 20;  
2 s2.name = 'Nguyen Van An';
```

Or using this symbol '→' when it involves in pointers

```
1 s1→age = 20;  
2 s2→name = 'Nguyen Van An';
```

Structures and Pointers

Pointer can be used for a single structure variable, but it is mostly used with array of structure variables.

```
1 #include <stdio.h>
2 struct Book{
3     char name[1000];
4     int price;
5 };
6 int main(){
7     struct Book a;           // Single structure variable
8     struct Book* ptr;        // Pointer of Structure type
9     ptr = &a;
10    struct Book b[10];        // Array of structure variables
11    struct Book* p;           // Pointer of Structure type
12    p = &b;
13 }
```

Enumeration

Enumerated types are types that are defined with finite number of values, known as enumerators, as possible values. The key word for an enumerated type is `enum`. Here is the syntax:

```
1 enum <type_name> {  
2     enum_val1 ,  
3     enum_val2 ,  
4     enum_val3 ,  
5     ... };
```

```
1 enum Season {Spring , Fall , Summer, Winter};  
2 Season s1, s2;  
3 s1 = Summer;  
4 s2 = Fall;  
5 if (s1 == Summer)  
6     printf( "Summer is coming" );
```