

Practice 8: Simulating and fitting ARMA models

The goal of this practice is to identify a possible ARMA model to a given data, to fit it and to validate it as a good model.

The outline is the following:

1. Simulation of a model.
2. Heuristic identification of a model. Auto-correlation and partial auto-correlation functions.
3. Fitting a model.
4. Validation.

1. Simulation of a model.

Do

```
SIM1<-arima.sim(list(order=c(1,0,0), ar=0.7),n=1000)
```

```
SIM2<-arima.sim(list(order=c(0,0,2), ma=c(1.5,0.75)),n=1000)
```

```
SIM3<-arima.sim(list(order=c(2,0,1), ar=c(0.3,0.2), ma=0.3), n=1000)
```

We have simulated an AR(1) model with parameter 0.7, an MA(2) model with parameters -1.5 and -0.75 , and an ARMA(2,1) model with parameters AR 0.3 and 0.2 and parameter MA -0.3 .

Make the charts of SIM1, SIM2 and SIM3.

2. Heuristic identification of the model. Auto-correlation and partial auto-correlation functions.

Here we want to compute and represent graphically functions acf and pacf of our series. If x represents any of our series, we have to write

```
acf(x,k)
pacf(x,k)
```

where k represents the number of represented lags. Recall that k has to be at most one third of n , the number of simulated data. Some authors recommend at most $k=\ln(n)$.

Recall that an $AR(p)$ model has an exponentially decreasing acf and a pacf that is null after p lags. An $MA(q)$ model has an exponentially decreasing pacf and an acf that is null after q lags.

3. Fitting a model.

Observe the graphics of acf and pacf of the three series and deduce heuristically a good model. Afterwards fit the proposed model using the instruction

```
S1<-arima(SIM3, order=c(1,0,0), method="ML")
S1
```

And similarly, for the other two. Check if the estimations are good.

4. Validation.

We can apply the following instructions to S3:

```
x<-SIM3
h<-log(n)
Box.test(x, lag = h, type = c("Ljung-Box"))
```

Here we reject the null hypothesis; SIM3 is not an IID noise!

But we can compute

```
y<-resid (S3)
Box.test (y, lag =h, type = c("Ljung-Box"))
```

and now the p-value is greater than 0.05 and so we can accept the series of residuals is an IID noise. Thus, we validate our ARMA(2,0,1) model.

A faster way to do it is using the instruction

```
tsdiag(S3, gof.lag=20)
```

See the graphics. The third one shows clearly that data are well fitted; the p-values for all the lags are high. Option gof.lag indicates until what order we compute the statistics of Ljung-Box test.

5. A complete example:

Do:

```
n<-10000
h<-log(n)
s3<-arima.sim(list(order=c(2,0,1),ar=c(0.3,0.2),ma=0.3), n)
plot(s3, type="l")
acf(s3)
pacf(s3)
p3<-arima(s3,order=c(2,0,1),method="ML")
p3
Box.test(p3,lag=h,type=c("Ljung-Box"))
y<-resid(p3)
Box.test(y,lag=h,type=c("Ljung-Box"))
```

6. Roots of a polynomial:

Given a polynomial $1+a_1 x+a_2 x^2+\cdots+a_n x^n$ we can obtain its roots using the R instruction

`Polyroot (c(1,a_1,...,a_n))`