```
100001111100
110110101101
110010110000
111101010011
101101010110
000010101110
110110010001
011101010111
000101101011
010110011010
101110110000
111110101011
010001111110
010011111110
101010111001
110010010111
110001100101
```

Wij en onze partners slaan informatie, zoals unieke identificatoren in cookies, op apparaten op en/of gebruiken deze om persoonsgegevens te verwerken. U kunt uw keuzes te kennen geven of beheren door hieronder te klikken. U kunt ze ook op elk moment wijzigen op de pagina met onze privacyverklaring. Uw keuzes worden aan onze partners doorgegeven en hebben geen effect op browsegegevens.

```
public static String concatStringsWSep(Iterable<String> strings, String
separator) {
    StringBuilder sb = new StringBuilder();
    String sep = "";
    for(String s: strings) {
        sb.append(sep).append(s);
        sep = separator;
    }
    return sb.toString();
}
```

<u>Guava</u> is a pretty neat library from Google:

Joiner joiner = Joiner.on(", "); joiner.join(sList);

hist.stream().collect(Collectors.joining(delimiter));

I really like this answer b/c you can use a foreach and it is very simple, but it is also more inefficient. How can you make it a tighter loop? If you are developing for Android, there is TextUtils.join provided by the SDK.

Have you seen this Coding Horror blog entry?

The Sad Tragedy of Micro-Optimization Theater

I am not shure
whether or not it is
"neater", but from a
performancestandpoint it probably
won't matter much.

Your approach is dependent on Java's ArrayList#toString() implementation.

While the implementation is documented in the Java API and very unlikely to change, there's a chance it could. It's far more reliable to implement this yourself (loops, StringBuilders, recursion whatever you like better).

Sure this approach may seem "neater" or more "too sweet" or "money" but it is, in my opinion, a worse approach.