

Clean Room Instruments

Differential Pressure Transmitter

Three Parameters Display

Temperature & Humidity
Transmitter

Clocks

Dredger Monitoring Unit

Pressure Production Calculator



Three Parameters Display

 [Download PDF](#)

The Clean Room Smart Process Scanner Is A 3 Line Smart Process Scanner Which Accepts 3 Analog Inputs From Sensors/Transmitters & Displays The 3 Parameters Directly Onto The Display. Especially Suited To Display The Clean Room Parameters Of Temperature, Humidity & Differential Pressure In A Single Instrument. Also Suited To Display The Various Parameters Of Air Velocity, Oxygen, Particle Count Or Any Other Analog Input.

The Clean Room Smart Process Scanner Accepts 3 Analog Inputs Of 4-20Ma Or 0-10 V.D.C. & Displays All 3 Parameters Simultaneously On The Large 1 Inch High Red LED 7 Segment Display. The Instrument Works On 24 V.D.C. & Has An Integrated RS485 Modbus Ommunication For Integration To BMS/SCADA/PLC. The Enclosure Is Only 30 Mm. Deep & Has A Front Stainless Steel Flush Plate Mounting , Suitable For Both Modular Walls/Brick Walls.

Products

Clean Room Instruments

Wireless Products

Defence

Data Convertors

Automation

PLC

HMI

SCADA

Special Machies Automation

Follow us on



Enquiry

Home

About

Career

Contact

Enquiry Form



Full name

Email Id

Enquiry for

☒ **Product** ☐ **Career**

Description

SUBMIT

Differential Pressure Transmitter

Three Parameters Display

Temperature & Humidity Transmitter

Clocks

Dredger Monitoring Unit

Pressure Production Calculator

Three Parameters Display



Download PDF

Three Parameters Smart Process Scanner Is A 3 Line Smart Process Scanner. It Accepts 3 Analog Inputs From Sensors/Transmitters & Displays All 3 Parameters Directly Onto The Display. Especially Suited For Clean Room Parameters Of Temperature, Humidity & Pressure. Can Be Used In A Single Instrument. Also Suited To Display The Parameters Of Air Velocity, Oxygen, Particle Count Or Any Other Parameters.

Three Parameters Smart Process Scanner Accepts 3 Analog Inputs (0-5V.D.C. & Displays All 3 Parameters Simultaneously On The Large 1 Inch High Red LED 7 Segment Display. The Instrument Works On 24 V.D.C. & Has An Integrated RS485 Modbus Ommunication For Integration To BMS/SCADA/PLC. The Enclosure Is Only 30 Mm. Deep & Has A Front Stainless Steel Flush Plate Mounting , Suitable For Both Modular Walls/Brick Walls.

Home

About

Career

Contact

Products

Clean Room Instruments

Wireless Products

Defence

Data Convertors

Automation

PLC

HMI

SCADA

Special Machies Automation

Follow us on



Enquiry

Enquiry Form



Full name

Email Id

Enquiry for

☐ Product ☒ Career

Upload Resume

Choose file

No file chosen

SUBMIT

Differential Pressure Transmitter

Three Parameters Display

Temperature & Humidity Transmitter

Clocks

Dredger Monitoring Unit

Pressure Production Calculator

Three Parameters Display



Download PDF

Three Parameters Smart Process Scanner Is A 3 Line Smart Process Scanner. It Accepts 3 Analog Inputs From Sensors/Transmitters & Displays All 3 Parameters Directly Onto The Display. Especially Suited For Clean Room Parameters Of Temperature, Humidity & Pressure. It Can Be Used In A Single Instrument. Also Suited To Display The Parameters Of Air Velocity, Oxygen, Particle Count Or Any Other Parameters.

Three Parameters Smart Process Scanner Accepts 3 Analog Inputs (0-5V.D.C. & Displays All 3 Parameters Simultaneously On The Large 1 Inch High Red LED 7 Segment Display. The Instrument Works On 24 V.D.C. & Has An Integrated RS485 Modbus Ommunication For Integration To BMS/SCADA/PLC. The Enclosure Is Only 30 Mm. Deep & Has A Front Stainless Steel Flush Plate Mounting , Suitable For Both Modular Walls/Brick Walls.

Home

About

Career

Contact

Products

Clean Room Instruments

Wireless Products

Defence

Data Convertors

Automation

PLC

HMI

SCADA

Special Machies Automation

Follow us on



Enquiry