

```
import cv2
import numpy as np
import matplotlib.pyplot as plt

# -----
# INPUT IMAGE CREATED INSIDE CODE
# -----
img = np.zeros((300, 400), dtype=np.uint8)

# Create sample objects
cv2.rectangle(img, (50, 50), (200, 200), 160, -1)
cv2.circle(img, (300, 150), 70, 220, -1)

# Add text
cv2.putText(img, "IMAGE", (90, 270),
            cv2.FONT_HERSHEY_SIMPLEX, 1, 255, 2)

# -----
# GRADIENT MASKS
# -----

# X-direction mask
mask_x = np.array([
    [-1, 0, 1],
    [-2, 0, 2],
    [-1, 0, 1]
], dtype=np.float32)

# Y-direction mask
mask_y = np.array([
    [-1, -2, -1],
    [0, 0, 0],
    [1, 2, 1]
], dtype=np.float32)

# -----
# ADDING GRADIENT MASKS
```

```
# APPLY GRADIENT MASKS
# -----

gradient_x = cv2.filter2D(img, cv2.CV_64F, mask_x)
gradient_y = cv2.filter2D(img, cv2.CV_64F, mask_y)

# Calculate gradient magnitude
gradient = np.sqrt(gradient_x**2 + gradient_y**2)

# Convert gradient to 8-bit
gradient = cv2.convertScaleAbs(gradient)

# -----
# SHARPENING
# -----

sharpened = cv2.add(img, gradient)

# -----
# DISPLAY RESULTS
# -----

plt.figure(figsize=(12, 4))

plt.subplot(1, 3, 1)
plt.imshow(img, cmap='gray')
plt.title("Original Image")
plt.axis("off")

plt.subplot(1, 3, 2)
plt.imshow(gradient, cmap='gray')
plt.title("Gradient Image")
plt.axis("off")


plt.subplot(1, 3, 3)
plt.imshow(sharpened, cmap='gray')
plt.title("Sharpened Image")
plt.axis("off")
```

```
plt.show()


# Print masks
print("X-direction Gradient Mask:")
print(mask_x)

print("\nY-direction Gradient Mask:")
print(mask_y)
```


Original Image



Gradient Image



Sharpened Image



X-direction Gradient Mask:

```
[[ -1.  0.  1.]
 [ -2.  0.  2.]
 [ -1.  0.  1.]]
```

Y-direction Gradient Mask:

```
[[ -1. -2. -1.]
 [  0.  0.  0.]
 [  1.  2.  1.]]
```