



---

# Design and Analysis of Algorithms

## Lecture # 9



---

# STRING MATCHING

# String Matching

- Introduction
- The Naive String Matching Algorithm
- The Rabin-Karp Algorithm
- String Matching with Finite Automata
- The Knuth-Morris-Pratt Algorithm

# Introduction

- ▶ Text-editing programs frequently need to find all occurrences of a pattern in the text.
- ▶ Efficient algorithms for this problem is called String-Matching Algorithms.
- ▶ Among its many applications, “String-Matching” is highly used in Searching for patterns in DNA and Internet search engines.
- ▶ Assume that the text is represented in the form of an array  $T[1..n]$  and the pattern is an array  $P[1..m]$ .

Text  $T[1..13]$

a	b	c	a	b	a	a	b	c	a	b	a	c
---	---	---	---	---	---	---	---	---	---	---	---	---

Pattern  $P[1..4]$

a	b	a	a
---	---	---	---




---

# **NAIVE STRING MATCHING ALGORITHM**

# Naive String Matching - Example

- ▶ The naive algorithm finds all valid shifts using a loop that checks the condition  $P[1..m] = T[s+1..s+m]$




# Naive String Matching - Algorithm

## NAIVE-STRING MATCHER (T,P)

1.  $n = T.length$
2.  $m = P.length$
3. for  $s = 0$  to  $n-m$
4.     if  $p[1..m] == T[s+1..s+m]$
5.         print "Pattern occurs with shift"  $s$

Naive String Matcher takes time  $O((n-m+1)m)$



$s = 3$

Pattern occurs with shift 2



---

# **RABIN-KARP ALGORITHM**



# Introduction

Text T

3 1 4 1 5 9 2 6 5 3 5

Pattern P

2 6

Choose a random prime number  $q = 11$

Let,  $p = P \bmod q$   
 $= 26 \bmod 11 = 4$

Let  $t_s$  denotes modulo  $q$  for text of length  $m$


3 1 4 1 5 9 2 6 5 3 5


# Rabin-Karp Algorithm

Pattern P    

2	6
---	---

 $p = P \bmod q = 26 \bmod 11 = 4$



```
if  $t_s == p$ 
    if  $P[1..m] == T[s+1..s+m]$ 
        print "pattern occurs with shift" s
```

# Rabin-Karp Algorithm

► We can compute  $t_s$  using following formula

$$t_{s+1} = 10(t_s - 10^{m-1}T[s+1]) + T[s + m + 1]$$

3	1	4	1	5	9	2	6	5	3	5
---	---	---	---	---	---	---	---	---	---	---

For  $m=2$  and  $s=0$   $t_s = 31$

We wish to remove higher order digit  $T[s+1]=3$  and bring the new lower order digit  $T[s+m+1]=4$

$$\begin{aligned} t_{s+1} &= 10(31 - 10 \cdot 3) + 4 \\ &= 10(1) + 4 = \mathbf{14} \end{aligned}$$

$$\begin{aligned} t_{s+2} &= 10(14 - 10 \cdot 1) + 1 \\ &= 10(4) + 1 = \mathbf{41} \end{aligned}$$

# Rabin-Karp-Matcher

RABIN-KARP-MATCHER(T, P, d, q)

$n \leftarrow \text{length}[T];$

$m \leftarrow \text{length}[P];$

$h \leftarrow d^{m-1} \bmod q;$

$p \leftarrow 0;$

$t_0 \leftarrow 0;$

for  $i \leftarrow 1$  to  $m$  do

$p \leftarrow (d_p + P[i]) \bmod q$

$t_0 \leftarrow (dt_0 + T[i]) \bmod q$

for  $s \leftarrow 0$  to  $n - m$  do

    if  $p == t_s$  then

        if  $P[1..m] == T[s+1..s+m]$  then

            print "pattern occurs with shift"  $s$

    if  $s < n-m$  then

$t_{s+1} \leftarrow (d(t_s - T[s+1]h) + T[s+m+1]) \bmod q$

T	3	1	4	1	5	9	2	6	5	3	5
P	2	6									
			d	10				q	11		
n	11				m	2				h	10
p	0							t <sub>0</sub>	0		



---

# **STRING MATCHING WITH FINITE AUTOMATA**

# Introduction to Finite Automata

---

- ▶ Finite automaton (FA) is a simple machine, used to recognize patterns. It has a set of states and rules for moving from one state to another.
- ▶ It takes the string of symbol as input and changes its state accordingly. When the desired symbol is found, then the transition occurs.
- ▶ At the time of transition, the automata can either move to the next state or stay in the same state.
- ▶ When the input string is processed successfully, and the automata reached its final state, then it will accept the input string.
- ▶ The string-matching automaton is very efficient: it examines each character in the text exactly once and reports all the valid shifts.

# Introduction to Finite Automata


- ▶ A finite automaton  $M$  is a 5-tuple, which consists of,

$$(Q, q_0, A, \Sigma, \delta)$$

- ▶  $Q$  is a finite set of **states**,
- ▶  $q_0 \in Q$  is a **start state**,
- ▶  $A \subseteq Q$  set of **accepting states**,
- ▶  $\Sigma$  is a finite **input alphabet**,
- ▶  $\delta$  is a **transition function** of  $M$ .

Input		
State	a	b
0	1	0
1	0	0

Transition  
Table



Finite  
Automaton

# Suffix of String

- ▶ Suffix of a string is any number of trailing symbols of that string. If a string  $\omega$  is a suffix of a string  $x$  then it is denoted by  $\omega \sqsupset x$ .

$P = ababa$	
<input type="text"/>	<input type="text"/>
<input type="text"/>	<input type="text"/>
<input type="text"/>	<input type="text"/>
<input type="text"/>	<input type="text"/>
<input type="text"/>	<input type="text"/>



# Compute Transition Function

COMPUTE-TRANSITION-FUNCTION( $P, \Sigma$ )

$m \leftarrow \text{length}[P]$

for  $q \leftarrow 0$  to  $m$  do

  for each character  $\alpha \in \Sigma$  do

$k \leftarrow \min(m + 1, q + 2)$

    repeat  $k \leftarrow k - 1$  until  $P_k \supseteq P_q \alpha$

$\delta(q, \alpha) \leftarrow k$

return  $\delta$

	1	2	3	4	5	6	7
Pattern	a	b	a	b	a	c	a
	1	2	3	4	5	6	7

$\Sigma = \{a, b, c\}$

$m = 7$

	input		
State	a	b	c
0			
1			
2			
3			
4			
5			
6			
7			

for  $q \leftarrow 0$  to  $m$  do

for each character  $\omega \in \Sigma$  do

$k \leftarrow \min(m + 1, q + 2)$

repeat  $k \leftarrow k - 1$  until  $P_k \supset P_q \omega$

$\delta(q, \omega) \leftarrow k$

return  $\delta$

$q=\emptyset$	$w=a$	$k=2$	$P_2 \supset P_\emptyset w$	$ab \supset \epsilon a$
		$k=1$	$P_1 \supset P_\emptyset w$	$a \supset \epsilon a$
	$w=b$	$k=2$	$P_2 \supset P_\emptyset w$	$ab \supset \epsilon b$
		$k=1$	$P_1 \supset P_\emptyset w$	$a \supset \epsilon b$
		$k=\emptyset$	$P_\emptyset \supset P_\emptyset w$	$\epsilon \supset \epsilon b$
	$w=c$	$k=2$	$P_2 \supset P_\emptyset w$	$ab \supset \epsilon c$
		$k=1$	$P_1 \supset P_\emptyset w$	$a \supset \epsilon c$
		$k=\emptyset$	$P_\emptyset \supset P_\emptyset w$	$\epsilon \supset \epsilon c$

	1	2	3	4	5	6	7
Pattern	a	b	a	b	a	c	a
	1	2	3	4	5	6	7

$\Sigma = \{a, b, c\}$

$m = 7$

	input		
State	a	b	c
0	1	0	0
1			
2			
3			
4			
5			
6			
7			

for  $q \leftarrow 0$  to  $m$  do

for each character  $\omega \in \Sigma$  do

$k \leftarrow \min(m + 1, q + 2)$

repeat  $k \leftarrow k - 1$  until  $P_k \supset P_q \omega$

$\delta(q, \omega) \leftarrow k$

return  $\delta$

q=1	$\omega=a$	k=3	$P_3 \supset P_1 \omega$	$aba \supset aa$
		k=2	$P_2 \supset P_1 \omega$	$ab \supset aa$
		k=1	$P_1 \supset P_1 \omega$	$a \supset aa$
$\omega=b$		k=3	$P_3 \supset P_1 \omega$	$aba \supset ab$
		k=2	$P_2 \supset P_1 \omega$	$ab \supset ab$
$\omega=c$		k=3	$P_3 \supset P_1 \omega$	$aba \supset ac$
		k=2	$P_2 \supset P_1 \omega$	$ab \supset ac$
		k=1	$P_1 \supset P_1 \omega$	$a \supset ac$
		k=0	$P_0 \supset P_1 \omega$	$\epsilon \supset ac$

	1	2	3	4	5	6	7
Pattern	a	b	a	b	a	c	a
	1	2	3	4	5	6	7

$\Sigma = \{a, b, c\}$

$m = 7$

	input		
State	a	b	c
0	1	0	0
1	1	2	0
2			
3			
4			
5			
6			
7			

for  $q \leftarrow 0$  to  $m$  do

for each character  $\omega \in \Sigma$  do

$k \leftarrow \min(m + 1, q + 2)$

repeat  $k \leftarrow k - 1$  until  $P_k \supset P_q \omega$

$\delta(q, \omega) \leftarrow k$

return  $\delta$

$q=2$	$\omega=a$	$k=4$	$P_4 \supset P_2 \omega$	$abab \supset aba$
-------	------------	-------	--------------------------	--------------------

$k=3$	$P_3 \supset P_2 \omega$	$aba \supset aba$
-------	--------------------------	-------------------

$\omega=b$	$k=0$	$P_0 \supset P_2 \omega$	$\epsilon \supset abb$
------------	-------	--------------------------	------------------------

$\omega=c$	$k=0$	$P_0 \supset P_2 \omega$	$\epsilon \supset abc$
------------	-------	--------------------------	------------------------

$q=3$	$\omega=a$	$k=1$	$P_1 \supset P_3 \omega$	$a \supset abaa$
-------	------------	-------	--------------------------	------------------

$\omega=b$	$k=4$	$P_4 \supset P_3 \omega$	$abab \supset abab$
------------	-------	--------------------------	---------------------

$\omega=c$	$k=0$	$P_0 \supset P_3 \omega$	$\epsilon \supset abac$
------------	-------	--------------------------	-------------------------

# Finite Automata Matcher

**FINITE-AUTOMATON MATCHER( $T, \delta, m$ )**

$n \leftarrow \text{length}[T]$

$q \leftarrow 0$

**for**  $i \leftarrow 1$  **to**  $n$  **do**

$q \leftarrow \delta(q, T[i])$

**if**  $q == m$  **then**

**print** "Pattern occurs with shift"  $i - m$

	1	2	3	4	5	6	7
Pattern	a	b	a	b	a	c	a

	1	2	3	4	5	6	7	8	9	10	11
Text	a	b	a	b	a	b	a	c	a	b	a

$i = 7$

$q = 5$

$q = \delta(0, a) = 1$

$q = \delta(1, b) = 2$

$q = \delta(2, a) = 3$

$q = \delta(3, b) = 4$

$q = \delta(4, a) = 5$

$q = \delta(5, b) = 4$

$q = \delta(4, a) = 5$

	input		
State	a	b	c
0	1	0	0
1	1	2	0
2	3	0	0
3	1	4	0
4	5	0	0
5	1	4	6
6	7	0	0
7	1	2	0

# Finite Automata Matcher

FINITE-AUTOMATON MATCHER( $T, \delta, m$ )

$n \leftarrow \text{length}[T]$

$q \leftarrow 0$

for  $i \leftarrow 1$  to  $n$  do

$q \leftarrow \delta(q, T[i])$

    if  $q == m$  then

        print "Pattern occurs with shift"  $i - m$

	1	2	3	4	5	6	7
Pattern	a	b	a	b	a	c	a

	1	2	3	4	5	6	7	8	9	10	11
Text	a	b	a	b	a	b	a	c	a	b	a

$i = 9$

$q = 7$

$q = \delta(0, a) = 1$

$q = \delta(1, b) = 2$

$q = \delta(2, a) = 3$

$q = \delta(3, b) = 4$

$q = \delta(4, a) = 5$

$q = \delta(5, b) = 4$

$q = \delta(4, a) = 5$

$q = \delta(5, c) = 6$

$q = \delta(6, a) = 7$

	input		
State	a	b	c
0	1	0	0
1	1	2	0
2	3	0	0
3	1	4	0
4	5	0	0
5	1	4	6
6	7	0	0
7	1	2	0

# Suffix & Prefix of a String

## Suffix of a string

$P = \text{string}$

$P_1 = g$	$P_1 \sqsupset P$
$P_2 = ng$	$P_2 \sqsupset P$
$P_3 = ing$	$P_3 \sqsupset P$
$P_4 = ring$	$P_4 \sqsupset P$
$P_5 = tring$	$P_5 \sqsupset P$

## Prefix of a string

$P = \text{string}$

$P_1 = s$	$P_1 \sqsubset P$
$P_2 = st$	$P_2 \sqsubset P$
$P_3 = str$	$P_3 \sqsubset P$
$P_4 = stri$	$P_4 \sqsubset P$
$P_5 = strin$	$P_5 \sqsubset P$



---








# **STRING MATCHING WITH KNUTH-MORRIS-PRATT ALGORITHM**



# Introduction

- ▶ The KMP algorithm relies on **prefix function ( $\pi$ )**.
- ▶ **Proper prefix:** All the characters in a string, with one or more cut off the end. “S”, “Sn”, “Sna”, and “Snap” are all the proper prefixes of “Snape”.
- ▶ **Proper suffix:** All the characters in a string, with one or more cut off the beginning. “agrid”, “grid”, “rid”, “id”, and “d” are all proper suffixes of “Hagrid”.
- ▶ KMP algorithm works as follows:
  - Step-1: **Calculate** Prefix Function
  - Step-2: **Match** Pattern with Text

# Longest Common Prefix and Suffix











							
	1	2	3	4	5	6	7
Pattern	a	b	a	b	a	c	a
Prefix( $\pi$ )							

ababa

Possible prefix = a, ab, aba, abab

Possible suffix = a, ba, aba, baba

# Calculate Prefix Function - Example

	<b>k+</b>	<b>q</b>					<b>q</b>
	<b>1</b>						
							
	1	2	3	4	5	6	7
<b>P</b>	a	c	a	c	a	g	t
<b>π</b>							


$k = 0$

$q = 7$

Initially set  $\pi[1] = 0$

$k$  is the longest prefix found

$q$  is the current index of pattern



# KMP- Compute Prefix Function

## COMPUTE-PREFIX-FUNCTION(P)

```
m ← length[P]
 $\pi[1] \leftarrow 0$ 
k ← 0
for q ← 2 to m
    while k > 0 and P[k + 1] ≠ P[q]
        k ←  $\pi[k]$ 
    end while
    if P[k + 1] == P[q] then
        k ← k + 1
    end if
     $\pi[q] \leftarrow k$ 
return  $\pi$ 
```

# KMP String Matching

	1	2	3	4	5	6	7
Pattern	a	c	a	c	a	g	t
Prefix( $\pi$ )	0	0	1	2	3	0	0

T a c a t a c g a c a c a g t

a c a c a g t

✗

a c a c a g t

Mismatch ?

Check value in prefix table

We can skip 2 shifts

(Skip unnecessary shifts)

T a c a t a c g a c a c a g t

a c a c a g t

Mismatch ?

Check value in prefix table


T a c a t a c g a c a c a g t

a c a c a g t

Mismatch ?

Check value in prefix table

# KMP String Matching



# KMP-MATCHER

## KMP-MATCHER(T, P)

```
n ← length[T]
m ← length[P]
 $\pi$  ← COMPUTE-PREFIX-FUNCTION(P)
q ← 0           //Number of characters matched.
for i ← 1 to n   //Scan the text from left to right.
    while q > 0 and P[q + 1] ≠ T[i]
        q ←  $\pi$ [q] //Next character does not match.
    if P[q + 1] == T[i] then
        then q ← q + 1 //Next character matches.
    if q == m then //Is all of P matched?
        print "Pattern occurs with shift" i - m
        q ←  $\pi$ [q] //Look for the next match.
```