

(Empowered Autonomous Institute Affiliated to University of Mumbai)

[Knowledge is Nectar]

Department of Computer Engineering


Course - System Programming and Compiler Construction (SPCC)

UID	2021300101
Name	Adwait Purao
Class and Batch	TE Computer Engineering - Batch B
Date	15-02-2024
Lab #	3
Aim	Design syntax analyser for various grammars and implement using different parsing techniques* (Top-down and Bottom-up).
Objective	To implement syntax analysis using various parsing techniques.
Theory	Syntax Analysis: Compiler Top Down & Bottom Up Parsing Types What is Syntax Analysis?[1] Syntax Analysis is a second phase of the compiler design process in which the given input string is checked for the confirmation of rules and structure of the formal grammar. It analyses the syntactical structure and checks if the given input is in the correct syntax of the programming language or not. Syntax Analysis in Compiler Design process comes after the Lexical analysis phase. It is also known as the Parse Tree or Syntax Tree. The Parse Tree is developed with the help of pre-defined grammar of the language. The syntax analyser also checks whether a given program fulfills the rules implied by a context-free grammar. If it satisfies, the parser then creates the parse tree of that source program. Otherwise, it will display error messages.[1]



(Empowered Autonomous Institute Affiliated to University of Mumbai)
[Knowledge is Nectar]

Department of Computer Engineering



Why do you need Syntax Analyser?

- Check if the code is valid grammatically
- The syntactical analyser helps you to apply rules to the code
- Helps you to make sure that each opening brace has a corresponding closing balance
- Each declaration has a type and that the type must be exists

Important Syntax Analyser Terminology

Important terminologies used in syntax analysis process:

Sentence: A sentence is a group of character over some alphabet.

Lexeme: A lexeme is the lowest level syntactic unit of a language (e.g., total, start).

Token: A token is just a category of lexemes.

Keywords and reserved words – It is an identifier which is used as a fixed part of the syntax of a statement. It is a reserved word which you can't use as a variable name or identifier.

Noise words – Noise words are optional which are inserted in a statement to enhance the readability of the sentence.

Comments – It is a very important part of the documentation. It mostly display by, /* */, or//Blank (spaces)

Delimiters – It is a syntactic element which marks the start or end of some syntactic unit. Like a statement or expression, "begin"..."end", or {}.

Character set - ASCII, Unicode

Identifiers – It is a restrictions on the length which helps you to reduce the readability of the sentence.


Operator symbols – + and – performs two basic arithmetic operations.

Syntactic elements of the Language

Why do we need Parsing?




(Empowered Autonomous Institute Affiliated to University of Mumbai)
[Knowledge is Nectar]





(Empowered Autonomous Institute Affiliated to University of Mumbai) [Knowledge is Nectar]

Department of Computer Engineering



Helps you to detect all types of Syntax errors

- Find the position at which error has occurred
- Clear & accurate description of the error.
- Recovery from an error to continue and find further errors in the code.
- Should not affect compilation of "correct" programs.
- The parse must reject invalid texts by reporting syntax errors

Construction of LL(1) Parsing Table[2]

LL(1) Parsing: Here the 1st L represents that the scanning of the Input will be done from the Left to Right manner and the second L shows that in this parsing technique, we are



(Empowered Autonomous Institute Affiliated to University of Mumbai)
[Knowledge is Nectar]

Department of Computer Engineering

going to use the Left most Derivation Tree. And finally, the 1 represents the number of look-ahead, which means how many symbols are you going to see when you want to make a decision.

Essential conditions to check first are as follows:

- The grammar is free from left recursion.
- The grammar should not be ambiguous.
- The grammar has to be left factored in so that the grammar is deterministic grammar.

These conditions are necessary but not sufficient for proving a LL(1) parser.

Algorithm to construct LL(1) Parsing Table:

- Step 1: First check all the essential conditions mentioned above and go to step 2.
- Step 2: Calculate First() and Follow() for all non-terminals.
 - First(): If there is a variable, and from that variable, if we try to drive all the strings then the beginning Terminal Symbol is called the First.
 - Follow(): What is the Terminal Symbol which follows a variable in the process of derivation.
- Step 3: For each production A -> α. (A tends to alpha)

Find First(α) and for each terminal in First(α), make entry A \rightarrow α in the table.

If First(α) contains ϵ (epsilon) as terminal, then find the Follow(A) and for each terminal in Follow(A), make entry A \rightarrow ϵ in the table.

If the First(α) contains ϵ and Follow(A) contains \$ as terminal, then make entry A \rightarrow ϵ in the table for the \$.

To construct the parsing table, we have two functions:

In the table, rows will contain the Non-Terminals and the column will contain the Terminal Symbols. All the Null Productions of the Grammars will go under the Follow elements and the remaining productions will lie under the elements of the First set.

Implementation / Code

Code 1 (LL(1) Parser)

```
#include <stdio.h>
#include <ctype.h>
#include <string.h>

void followfirst(char, int, int);
void findfirst(char, int, int);
```



(Empowered Autonomous Institute Affiliated to University of Mumbai)
[Knowledge is Nectar]

```
void follow(char c);
int count, n = 0;
char calc first[10][100];
char calc follow[10][100];
int m = 0;
char production[10][10], first[10];
char f[10];
int k;
char ck;
int e;
int main(int argc, char **argv)
   int jm = 0;
   int km = 0;
   int i, choice;
   char c, ch;
   printf("How many productions ? :");
   scanf("%d", &count);
   printf("\nEnter %d productions in form A=B where A and B are
grammar symbols :\n\n", count);
    for (i = 0; i < count; i++)
        scanf("%s%c", production[i], &ch);
   int kay;
   char done[count];
   int ptr = -1;
   for (k = 0; k < count; k++)
        for (kay = 0; kay < 100; kay++)
            calc first[k][kay] = '!';
```



(Empowered Autonomous Institute Affiliated to University of Mumbai)
[Knowledge is Nectar]

```
int point1 = 0, point2, xxx;
for (k = 0; k < count; k++)
   c = production[k][0];
   point2 = 0;
   xxx = 0;
    for (kay = 0; kay \le ptr; kay++)
        if (c == done[kay])
            xxx = 1;
    if (xxx == 1)
        continue;
    findfirst(c, 0, 0);
   ptr += 1;
   done[ptr] = c;
   printf("\n First(%c) = { ", c);
    calc first[point1][point2++] = c;
    for (i = 0 + jm; i < n; i++)
        int lark = 0, chk = 0;
        for (lark = 0; lark < point2; lark++)</pre>
            if (first[i] == calc_first[point1][lark])
                chk = 1;
                break;
        if (chk == 0)
            printf("%c, ", first[i]);
            calc first[point1][point2++] = first[i];
    printf("}\n");
    jm = n;
    point1++;
```



(Empowered Autonomous Institute Affiliated to University of Mumbai)
[Knowledge is Nectar]

```
printf("\n");
printf("----
char donee[count];
ptr = -1;
for (k = 0; k < count; k++)
    for (kay = 0; kay < 100; kay++)
        calc follow[k][kay] = '!';
point1 = 0;
int land = 0;
for (e = 0; e < count; e++)
    ck = production[e][0];
    point2 = 0;
    xxx = 0;
    for (kay = 0; kay \le ptr; kay++)
        if (ck == donee[kay])
            xxx = 1;
    if (xxx == 1)
        continue;
    land += 1;
    follow(ck);
    ptr += 1;
    donee[ptr] = ck;
    printf(" Follow(%c) = { ", ck);
    calc follow[point1][point2++] = ck;
    for (i = 0 + km; i < \overline{m}; i++)
        int lark = 0, chk = 0;
        for (lark = 0; lark < point2; lark++)</pre>
            if (f[i] == calc follow[point1][lark])
```



(Empowered Autonomous Institute Affiliated to University of Mumbai)
[Knowledge is Nectar]

```
chk = 1;
           if (chk == 0)
               printf("%c, ", f[i]);
               calc follow[point1][point2++] = f[i];
       printf(" }\n\n");
       km = m;
       point1++;
   char ter[10];
   for (k = 0; k < 10; k++)
       ter[k] = '!';
   int ap, vp, sid = 0;
   for (k = 0; k < count; k++)
       for (kay = 0; kay < count; kay++)
           if (!isupper(production[k][kay]) && production[k][kay] !=
'#' && production[k][kay] != '=' && production[k][kay] != '\0')
               vp = 0;
               for (ap = 0; ap < sid; ap++)
                   if (production[k][kay] == ter[ap])
                        vp = 1;
```



(Empowered Autonomous Institute Affiliated to University of Mumbai)
[Knowledge is Nectar]

```
if (vp == 0)
               ter[sid] = production[k][kay];
               sid++;
  ter[sid] = '$';
   sid++;
  printf("\n\t\t\t\t The LL(1) Parsing Table for the above
grammer :-");
printf("\n\t\t\t\t\t\t\t\+^^^^^^
^^^^\n");
printf("\t\t\t\t|\t");
  for (ap = 0; ap < sid; ap++)
      printf("%c\t\t", ter[ap]);
   -----\n");
  char first prod[count][sid];
  for (ap = 0; ap < count; ap++)
      int destiny = 0;
      k = 2;
      int ct = 0;
      char tem[100];
      while (production[ap][k] != '\0')
```



(Empowered Autonomous Institute Affiliated to University of Mumbai)
[Knowledge is Nectar]

```
if (!isupper(production[ap][k]))
        tem[ct++] = production[ap][k];
        tem[ct++] = ' ';
        tem[ct++] = ' \setminus 0';
        k++;
        break;
    else
        int zap = 0;
        int tuna = 0;
        for (zap = 0; zap < count; zap++)
             if (calc first[zap][0] == production[ap][k])
                 for (tuna = 1; tuna < 100; tuna++)</pre>
                     if (calc first[zap][tuna] != '!')
                          tem[ct++] = calc first[zap][tuna];
                     else
                         break;
                 break;
        tem[ct++] = ' ';
    k++;
int zap = 0, tuna;
for (tuna = 0; tuna < ct; tuna++)</pre>
    if (tem[tuna] == '#')
```



(Empowered Autonomous Institute Affiliated to University of Mumbai)
[Knowledge is Nectar]

```
zap = 1;
        else if (tem[tuna] == ' ')
            if (zap == 1)
                zap = 0;
            else
                break;
        else
            first prod[ap][destiny++] = tem[tuna];
char table[land][sid + 1];
ptr = -1;
for (ap = 0; ap < land; ap++)
    for (kay = 0; kay < (sid + 1); kay++)
        table[ap][kay] = '!';
for (ap = 0; ap < count; ap++)
    ck = production[ap][0];
    xxx = 0;
    for (kay = 0; kay \le ptr; kay++)
        if (ck == table[kay][0])
            xxx = 1;
    if (xxx == 1)
        continue;
```



(Empowered Autonomous Institute Affiliated to University of Mumbai)
[Knowledge is Nectar]

```
else
       ptr = ptr + 1;
        table[ptr][0] = ck;
for (ap = 0; ap < count; ap++)
   int tuna = 0;
   while (first prod[ap][tuna] != '\0')
        int to, ni = 0;
        for (to = 0; to < sid; to++)
            if (first prod[ap][tuna] == ter[to])
                ni = 1;
        if (ni == 1)
            char xz = production[ap][0];
            int cz = 0;
            while (table[cz][0] != xz)
                cz = cz + 1;
            int vz = 0;
            while (ter[vz] != first prod[ap][tuna])
                vz = vz + 1;
            table[cz][vz + 1] = (char)(ap + 65);
        tuna++;
```



(Empowered Autonomous Institute Affiliated to University of Mumbai)
[Knowledge is Nectar]

```
for (k = 0; k < sid; k++)
    for (kay = 0; kay < 100; kay++)
        if (calc first[k][kay] == '!')
            break;
        else if (calc first[k][kay] == '#')
            int fz = 1;
            while (calc follow[k][fz] != '!')
                char xz = production[k][0];
                int cz = 0;
                while (table[cz][0] != xz)
                    cz = cz + 1;
                int vz = 0;
                while (ter[vz] != calc_follow[k][fz])
                    vz = vz + 1;
                table[k][vz + 1] = '#';
                fz++;
            break;
for (ap = 0; ap < land; ap++)
   printf("\t\t\ \c\t|\t", table[ap][0]);
    for (kay = 1; kay < (sid + 1); kay++)
```



(Empowered Autonomous Institute Affiliated to University of Mumbai)
[Knowledge is Nectar]

```
if (table[ap][kay] == '!')
            printf("\t\t");
         else if (table[ap][kay] == '#')
            printf("%c=#\t\t", table[ap][0]);
         else
            int mum = (int)(table[ap][kay]);
            mum -= 65;
            printf("%s\t\t", production[mum]);
      printf("\n");
printf("\t\t\t-----
     printf("\n");
  int j;
  printf("\n\nPlease enter the desired INPUT STRING = ");
  char input[100];
   scanf("%s%c", input, &ch);
printf("\t\t\t\t\t\tStack\t\tInput\t\tAction");
int i ptr = 0, s ptr = 1;
  char stack[100];
  stack[0] = '$';
   stack[1] = table[0][0];
  while (s ptr !=-1)
      printf("\t\t\t\t\t\t");
```



(Empowered Autonomous Institute Affiliated to University of Mumbai)
[Knowledge is Nectar]

```
int vamp = 0;
for (vamp = 0; vamp <= s ptr; vamp++)</pre>
    printf("%c", stack[vamp]);
printf("\t\t\t");
vamp = i_ptr;
while (input[vamp] != '\0')
    printf("%c", input[vamp]);
    vamp++;
printf("\t\t\t");
char her = input[i ptr];
char him = stack[s ptr];
s ptr--;
if (!isupper(him))
    if (her == him)
        i ptr++;
        printf("POP ACTION\n");
else
    for (i = 0; i < sid; i++)
        if (ter[i] == her)
            break;
    char produ[100];
    for (j = 0; j < land; j++)
        if (him == table[j][0])
```



(Empowered Autonomous Institute Affiliated to University of Mumbai)
[Knowledge is Nectar]

```
if (table[j][i + 1] == '#')
                        printf("%c=#\n", table[j][0]);
                        produ[0] = '#';
                        produ[1] = ' \setminus 0';
                    else if (table[j][i + 1] != '!')
                        int mum = (int) (table[j][i + 1]);
                        mum -= 65;
                        strcpy(produ, production[mum]);
                        printf("%s\n", produ);
                    else
                        printf("\nString Not Accepted by LL(1) Parser
!!\n");
            int le = strlen(produ);
            le = le - 1;
            if (le == 0)
                continue;
            for (j = le; j >= 2; j--)
                s ptr++;
                stack[s ptr] = produ[j];
```



(Empowered Autonomous Institute Affiliated to University of Mumbai)
[Knowledge is Nectar]

```
if (input[i ptr] == '\0')
        printf("\t\t\t\t\t\t\t\tYOUR STRING HAS BEEN ACCEPTED !!\n");
   else
        printf("\n\t\t\t\t\t\t\t\t\tYOUR STRING HAS BEEN REJECTED
!!\n");
    return 0;
void follow(char c)
    int i, j;
    if (production[0][0] == c)
        f[m++] = '$';
    for (i = 0; i < 10; i++)
        for (j = 2; j < 10; j++)
            if (production[i][j] == c)
                 if (production[i][j + 1] != ' \setminus 0')
                     followfirst(production[i][j + 1], i, (j + 2));
                 if (production[i][j + 1] == ' \setminus 0' \&\& c !=
production[i][0])
                     follow(production[i][0]);
```



(Empowered Autonomous Institute Affiliated to University of Mumbai)
[Knowledge is Nectar]

```
void findfirst(char c, int q1, int q2)
   int j;
   if (!(isupper(c)))
       first[n++] = c;
   for (j = 0; j < count; j++)
       if (production[j][0] == c)
            if (production[j][2] == '#')
                if (production[q1][q2] = ' \setminus 0')
                    first[n++] = '#';
                else if (production[q1][q2] != '\0' && (q1 != 0 || q2
! = 0))
                    findfirst(production[q1][q2], q1, (q2 + 1));
                else
                    first[n++] = '#';
            else if (!isupper(production[j][2]))
                first[n++] = production[j][2];
            else
                findfirst(production[j][2], j, 3);
```



(Empowered Autonomous Institute Affiliated to University of Mumbai)
[Knowledge is Nectar]

```
void followfirst(char c, int c1, int c2)
   int k;
   if (!(isupper(c)))
       f[m++] = c;
   else
       int i = 0, j = 1;
       for (i = 0; i < count; i++)
           if (calc first[i][0] == c)
               break;
       while (calc first[i][j] != '!')
           if (calc_first[i][j] != '#')
               f[m++] = calc_first[i][j];
           else
               if (production[c1][c2] == '\0')
                   follow(production[c1][0]);
               else
                    followfirst(production[c1][c2], c1, c2 + 1);
           j++;
```



(Empowered Autonomous Institute Affiliated to University of Mumbai)
[Knowledge is Nectar]

```
Code 2( SLR Parser)
import java.util.*;
import java.io.*;
class LR parser
  HashMap<String,ArrayList<ArrayList<String>>> rules;
  HashSet<String> terminals;
  HashSet<String> nonTerminals;
  ArrayList<String> allSymbols;
  ArrayList<String> table[][];
  String startSymbol;
  DFA dfa;
  int minId;
  static class Pair
       String rule;
       int dot;
       Pair(String c,int d)
           rule=c;
           dot=d;
       @Override
       public String toString()
           int l=rule.indexOf("->"),i;
           String left=rule.substring(0,1).trim();
           String right=rule.substring(1+2).trim();
           StringBuilder sb=new StringBuilder();
           sb.append(left+" -> ");
           String tokens[]=right.split(" ");
           for(i=0;i<tokens.length;i++)</pre>
```



(Empowered Autonomous Institute Affiliated to University of Mumbai)
[Knowledge is Nectar]

```
if(i==dot)
            sb.append(". ");
        sb.append(tokens[i]+" ");
    if(i==dot)
        sb.append(". ");
    return sb.toString();
@Override
public int hashCode() {
    final int prime = 31;
    int result = 1;
    result = prime * result + rule.hashCode();
    result = prime * result + dot;
    return result;
@Override
public boolean equals(Object obj) {
    if (this == obj)
    if (obj == null)
    if (getClass() != obj.getClass())
    Pair other = (Pair) obj;
    if (dot!= other.dot)
        return false;
    if (!rule.equals(other.rule))
        return false;
HashSet<Pair> rules;
```



(Empowered Autonomous Institute Affiliated to University of Mumbai)
[Knowledge is Nectar]

```
int id;
      HashMap<String, DFA> transitions;
      DFA()
          rules=new HashSet<>();
          id=-1;
          transitions=new HashMap<>();
      @Override
      public String toString()
          return "Id: "+id+" , Rules: "+rules+"\n";//Mapping:
'+transitions+"\n\n";
  LR parser()
      rules=new HashMap<>();
      startSymbol="";
      terminals=new HashSet<>();
      terminals.add("(");
      terminals.add("+");
      terminals.add("*");
      terminals.add(")");
      terminals.add("id");
      //terminals.add("=");
      terminals.add("/");
      terminals.add("-");
      nonTerminals=new HashSet<>();
      nonTerminals.add("E");
      nonTerminals.add("T");
      nonTerminals.add("F");
      allSymbols=new ArrayList<>();
      allSymbols.addAll(nonTerminals);
      allSymbols.addAll(terminals);
      minId=-1;
```



(Empowered Autonomous Institute Affiliated to University of Mumbai)
[Knowledge is Nectar]

```
dfa=new DFA();
  private int getId()
      return ++minId;
  static void modify(AugmentedFirstAndFollow utils,LR parser obj)
      utils.ntCount.clear();
      utils.ntCount.addAll(obj.nonTerminals);
      utils.tCount.clear();
      utils.tCount.addAll(obj.terminals);
      utils.tCount.add("$");
      utils.ntCount.add(obj.startSymbol+"'");
  public static void main(String args[])throws IOException
      LR parser obj=new LR parser();
      obj.read grammar("Grammar.txt");
      AugmentedFirstAndFollow utils=new AugmentedFirstAndFollow();
      obj.augment();
      modify(utils,obj);
      utils.module1("Grammar.txt");
      obj.unAugment();
      HashSet<Pair> hs=new HashSet<>();
      HashSet<Pair> closure=new HashSet<>();
      BufferedReader br=new BufferedReader (new
InputStreamReader(System.in));
      HashSet<Pair> goTo=new HashSet<>();
      /*goTo.add(new Pair("E -> T",0));
      System.out.println(obj.getGoto(goTo,"T"));
      System.out.println(obj.getGoto(goTo,"("));
      goTo.clear();
```



(Empowered Autonomous Institute Affiliated to University of Mumbai)
[Knowledge is Nectar]

```
goTo.add(new Pair("F -> ( E )",0));
       System.out.println(obj.getGoto(goTo,"id"));*/
       ArrayList<DFA> states=obj.buildDFA();
       obj.getParsingTable(states,utils);
       obj.parse("id $");
          String str=br.readLine();
           if(str.equals("1"))
               break;
           closure.add(new Pair(str,k));
          obj.getClosure(closure);
  public void read grammar(String filePath)
      String str="";
      int line=0;
          BufferedReader br=new BufferedReader (new
FileReader(filePath));
           while((str=br.readLine())!=null)//Read the string, put in
               int l=str.indexOf("->"),i,j;
               String left=str.substring(0,1).trim();
               String right=str.substring(1+2).trim();
               l=right.length();
               String tokens[]=right.split("[|]");
"+Arrays.toString(tokens));
               if(line==0)
```



(Empowered Autonomous Institute Affiliated to University of Mumbai)
[Knowledge is Nectar]

```
startSymbol=left;
            line++;
            ArrayList<ArrayList<String>> al=new ArrayList<>();
            for(i=0;i<tokens.length;i++)</pre>
                String s[]=tokens[i].trim().split(" ");
                ArrayList<String> temp=new ArrayList<>();
                for(j=0;j<s.length;j++)</pre>
                     temp.add(s[j]);
                al.add(temp);
            rules.put(left,al);//Put all the rules in the map
            line++;
        br.close();
    }catch(Exception e)
        System.out.println("Parse failure: "+e.getMessage());
        System.exit(0);
String join(ArrayList<String> v, String delim)
    StringBuilder ss=new StringBuilder();
    for (int i = 0; i < v.size(); ++i)
        if(i != 0)
            ss.append(delim);
        ss.append(v.get(i));
    return ss.toString();
public void getClosure(HashSet<Pair> closure)
```



(Empowered Autonomous Institute Affiliated to University of Mumbai)
[Knowledge is Nectar]

```
boolean done=false;
       while(!done)
           done=true;
           Iterator iterator=closure.iterator();
           HashSet<Pair> addAble=new HashSet<>();
           while(iterator.hasNext())
               Pair pair=(Pair)iterator.next();
               int l=pair.rule.indexOf("->"),i;
               //System.out.println(l);
               String left=pair.rule.substring(0,1).trim();
               String right=pair.rule.substring(1+2).trim();
               String tokens[]=right.split(" ");
               if(pair.dot>=tokens.length||pair.dot<0)</pre>
                   continue;
               else if(nonTerminals.contains(tokens[pair.dot]))
                   ArrayList<ArrayList<String>>
al=rules.get(tokens[pair.dot]);
                   for(i=0;i<al.size();i++)</pre>
                       String str=join(al.get(i)," ");
                       Pair p=new Pair(tokens[pair.dot]+" -> "+str,0);
                       //System.out.println(p);
                       if(!closure.contains(p))
                           done=false;
                           addAble.add(new Pair(tokens[pair.dot]+" ->
"+str.trim(),0));
```



(Empowered Autonomous Institute Affiliated to University of Mumbai)
[Knowledge is Nectar]

```
/*System.out.println(closure+"\n"+addAble);
               Thread.sleep(5000);
           }catch(Exception e)
           closure.addAll(addAble);
  public HashSet<Pair> getGoto(HashSet<Pair> X, String I)
       HashSet<Pair> goTo=new HashSet<>();
       HashSet<Pair> add=new HashSet<>();
       for(Pair p: X)
str[]=p.rule.substring(p.rule.indexOf("->")+2).trim().split(" ");
           //System.out.println(Arrays.toString(str));
           if (p.dot>=str.length||p.dot<0)</pre>
           if(str[p.dot].equals(I))
               goTo.add(new Pair(p.rule,p.dot+1));
       for(Pair p:goTo)
           HashSet<Pair> temp=new HashSet<>();
           temp.add(p);
           getClosure(temp);
           add.addAll(temp);
       goTo.addAll(add);
       return goTo;
  public void augment()
```



(Empowered Autonomous Institute Affiliated to University of Mumbai)
[Knowledge is Nectar]

```
ArrayList<ArrayList<String>> al=new ArrayList<>();
      ArrayList<String> al2=new ArrayList<>();
      al2.add(startSymbol);
      al.add(a12);
       rules.put(startSymbol+"'",al);
  public void unAugment()
       rules.remove(startSymbol+"'");
  public ArrayList<DFA> buildDFA()
      augment();
      dfa.id=getId();
       for (Map.Entry<String, ArrayList<ArrayList<String>>> mp:
rules.entrySet())
           for(ArrayList<String> al: mp.getValue())
               dfa.rules.add(new Pair(mp.getKey()+" -> "+join(al,"
"),0));
      ArrayList<DFA> states=new ArrayList<>();
      states.add(dfa);
       int i=0;
      boolean done=false;
      while(!done)
          done=true;
           for(i=0;i<states.size();i++)</pre>
               DFA current=states.get(i);
               for(String str: allSymbols)//All symbol iteration
```



(Empowered Autonomous Institute Affiliated to University of Mumbai)
[Knowledge is Nectar]

```
HashSet<Pair> Goto=getGoto(current.rules,str);
                   int index=getIndex(Goto, states);
                   if(index>=0)
                       //System.out.println("Old");
                       current.transitions.put(str, states.get(index));
                   else
                       DFA new DFA=new DFA();
                       new DFA.id=getId();
                       new DFA.rules=Goto;
                       states.add(new DFA);
                       current.transitions.put(str,new DFA);
                       done=false;
           //break;
       System.out.println(states);
       print transitions(states);
       unAugment();
       return states;
  public void getParsingTable(ArrayList<DFA>
states, AugmentedFirstAndFollow utils)
       terminals.add("$");
       table=new
ArrayList[states.size()][terminals.size()+nonTerminals.size()];
       int i,j;
       for(i=0;i<states.size();i++)</pre>
           for(j=0;j<terminals.size()+nonTerminals.size();j++)</pre>
               table[i][j]=new ArrayList<>();
```



(Empowered Autonomous Institute Affiliated to University of Mumbai)
[Knowledge is Nectar]

```
ArrayList<String> colMap=new ArrayList<>();
      colMap.addAll(terminals);
      colMap.addAll(nonTerminals);
      allSymbols.clear();
      allSymbols.addAll(colMap);
      System.out.println(colMap);
      System.out.println(allSymbols);
      int row=0;
      boolean isLR=true;
      for(DFA dfa: states)
           for(Pair p:dfa.rules)
               String
str[]=p.rule.substring(p.rule.indexOf("->")+2).trim().split(" ");
left=p.rule.substring(0,p.rule.indexOf("->")).trim();
               if(p.dot<0||p.dot>str.length)
               if(left.equals(startSymbol+"'")&&p.dot==str.length)
                   table[row][colMap.indexOf("$")].add("Accept :)");
               else if(p.dot==str.length)
                   ArrayList<String> al=utils. follow.get(left);
                   for(String s:al)
                       table[row][colMap.indexOf(s)].add("Reduce
+p.rule);
               else if(terminals.contains(str[p.dot]))
                   HashSet<Pair> hs=getGoto(dfa.rules,str[p.dot]);
                   int index=getIndex(hs, states);
```



(Empowered Autonomous Institute Affiliated to University of Mumbai)
[Knowledge is Nectar]

```
if(index>=0)
table[row][colMap.indexOf(str[p.dot].trim())].add("Shift "+index);
           for(String ss:nonTerminals)
               HashSet<Pair> hs=getGoto(dfa.rules,ss);
               int index=getIndex(hs, states);
               if(index>=0&&states.get(index).rules.size()!=0)
                   table[row] [colMap.indexOf(ss)].add(index+"");
           row++;
       ArrayList<String> pretty[][]=new
ArrayList[table.length+1][table[0].length+1];
       for (i=0;iitty.length;i++)
           for(j=0;jjtty[0].length;j++)
               pretty[i][j]=new ArrayList<>();
               /*if(i==0)
       pretty[0][0].add("State");
       for(i=1;iitty[0].length;i++)
          pretty[0][i].add(colMap.get(i-1)+"");
       for(i=1;i<pretty.length;i++)</pre>
```



(Empowered Autonomous Institute Affiliated to University of Mumbai)
[Knowledge is Nectar]

```
pretty[i][0].add((i-1)+"");
      for(i=1;i<pretty.length;i++)</pre>
          for(j=1;j<pretty[0].length;j++)</pre>
              if(table[i-1][j-1].size()>1)
                  isLR=false;
              pretty[i][j].addAll(table[i-1][j-1]);
      PrettyPrinter printer = new PrettyPrinter(System.out);
      printer.convert(pretty);
      terminals.remove("$");
      if(isLR)
          System.out.println("Grammar is LR :)");
      else
          System.out.println("Grammar isn't LR :(");
 public void parse(String toParse)
      Stack<String> stack=new Stack<>();
      ArrayList<ArrayList<>tring>> al=new ArrayList<>();
      ArrayList<String> a=new ArrayList<>();
      a.add("Step");
      a.add("Stack");
      a.add("Action");
      a.add("Input");
      al.add(a);
      stack.push("$");
      stack.push("0");
      int pointer=0,i,step=0;
      String toParse[] = toParse.split(" ");
/System.out.println("Step:\t\tStack\t\t\t\tAction\t\tInput");
      while(!stack.empty()&&pointer<toParse.length)</pre>
```



(Empowered Autonomous Institute Affiliated to University of Mumbai)
[Knowledge is Nectar]

```
a=new ArrayList<>();
int row=Integer.parseInt(stack.peek());
int col=allSymbols.indexOf(toParse[pointer]);
a.add(step+"");
a.add(stack+"");
//System.out.print(step+"\t\t"+stack+"\t\t\t\t\t");
if(table[row][col].size()==0)
    a.add("Parse error");
    al.add(a);
    pretty it(al);
    System.exit(0);
    break;
String action=table[row][col].get(0);
a.add(action);
//System.out.print(action+"\t\t");
String str[]=action.split(" ");
String left=str[0].trim();
String right="";
for(i=1;i<str.length;i++)</pre>
    right+=str[i]+" ";
right=right.trim();
if(left.equals("Shift"))
    //stack.pop();
    stack.push(toParse[pointer]);
    stack.push(right);
    pointer++;
else if(left.equals("Reduce"))
    left=right.substring(0,right.indexOf("->")).trim();
    right=right.substring(right.indexOf("->")+2).trim();
    for (i=0; i<2*(str.length-3); i++)
```



(Empowered Autonomous Institute Affiliated to University of Mumbai)
[Knowledge is Nectar]

```
if(stack.size()!=0)
                       stack.pop();
                   else
                       a.add("Parse error");
                       al.add(a);
                       pretty it(al);
                       //System.out.println("Parse error");
                       System.exit(0);
               int top=Integer.parseInt(stack.peek());
               stack.push(left);
stack.push(table[top][allSymbols.indexOf(left)].get(0));
           else if(left.equals("Accept")&&pointer==toParse.length-1)
               String ppp="";
               for(i=pointer;i<toParse.length;i++)</pre>
                   ppp+=toParse[i]+" ";
               a.add(ppp);
               al.add(a);
               pretty it(al);
               System.out.println("Woohoo, accepted :) ");
               System.exit(0);
           String pp="";
           for(i=pointer;i<toParse.length;i++)</pre>
               pp+=toParse[i]+" ";
           //System.out.println(pp+"\t\t");
           a.add(pp);
           al.add(a);
           step++;
```



(Empowered Autonomous Institute Affiliated to University of Mumbai)
[Knowledge is Nectar]

```
private void pretty_it(ArrayList<ArrayList<String>> al)
      int n=al.size(),i,j;
      String t[][]=new String[n][4];
      for(i=0;i<n;i++)
          for (j=0; j<4; j++)
               if(al.get(i).size() == 3&&j == 3)
                   t[i][j]="Parse Error";
              else
                   t[i][j]=al.get(i).get(j);
      PrettyPrinter printer = new PrettyPrinter(System.out);
      printer.print(t);
  private int getIndex(HashSet<Pair> Goto,ArrayList<DFA> states)
      int i=0;
      for(DFA dfa: states)
if(dfa.rules.containsAll(Goto)&&Goto.containsAll(dfa.rules))
               return i;
          i++;
      return -1;
  private void print transitions(ArrayList<DFA> states)
      for(DFA dfa: states)
          System.out.println("Map for state: "+dfa);
```



(Empowered Autonomous Institute Affiliated to University of Mumbai)
[Knowledge is Nectar]

```
Department of Computer Engineering

System.out.println("Transitions: ");
for(Map.Entry<String, DFA> mp:dfa.transitions.entrySet())

{

System.out.println(mp.getKey()+"->"+mp.getValue().rules+" (

S"+getIndex(mp.getValue().rules, states)+" )");
}
System.out.println();
}

}

Output

Output 1: LL1 Parser

Output


Output

First printle (s. b.)
FirstDe (s. b.)
FirstDe
```

The LL(1) Parsing Table for the above grammer :-



(Empowered Autonomous Institute Affiliated to University of Mumbai)
[Knowledge is Nectar]





(Empowered Autonomous Institute Affiliated to University of Mumbai)

[Knowledge is Nectar]

```
T*F, E->. E-T]
Id: 5, Rules: []
Id: 6, Rules: [F-> id.]
Id: 6, Rules: [F-> (E), T-> T*. F, F->. id]
Id: 7, Rules: [F->. (E), F->. id, T-> T/. F]
Id: 8, Rules: [F->. (E), F->. id, T-> T/. F]
Id: 9, Rules: [T->. F, F->. (E), T->. T/F, E-> E+. T, F->. id, T->. T*F]
Id: 10, Rules: [E-> E-. T, T->. F, F->. (E), T->. T/F, F->. id, T->. T*F]
Id: 11, Rules: [E-> E.- T, F-> (E.), E-> E.+ T]
Id: 12, Rules: [T-> T/F.]
Id: 13, Rules: [T-> T/F.]
Id: 14, Rules: [E-> E+T., T-> T./F, T-> T.*F]
Id: 15, Rules: [E-> E-T., T-> T./F, T-> T.*F]
Id: 16, Rules: [F-> (E).]
  ,
Map for state: Id: 0 , Rules: [T -> . F , F -> . ( E ) , E' -> . E , T -> . T / F , F -> . id , T -> . T * F , E -> .
E + T , E -> . T , E -> . E - T ]
 Transitions:
T->[T -> T . / F , E -> T . , T -> T . * F ] ( S1 )
E->[E -> E . - T , E' -> E . , E -> E . + T ] ( S2 )
F->[T -> F . ] ( S3 )
(->[F -> ( . E ) , T -> . F , F -> . (E ) , T -> . T / F , F -> . id , E -> . E + T , E -> . T , T -> . T * F , E -> . E - T ] ( S4 )
)->[] ( S5 )
*->[] ( S5 )
+->[] ( S5 )
id->[F -> id . ] ( S6 )
-->[] ( S5 )
/->[] ( S5 )
  Transitions:
  Map for state: Id: 1 , Rules: [T -> T . / F , E -> T . , T -> T . * F ]
  Transitions
  T->[] ( S5 )
E->[] ( S5 )
F->[] ( S5 )
(->[] ( S5 )
)->[] ( S5 )
Transitions:

T->[] ( S5 )

E->[] ( S5 )

F->[] ( S5 )

(->[] ( S5 )

)->[] ( S5 )

+->[] ( S5 )

id->[] ( S5 )

-->[] ( S5 )

-->[] ( S5 )

/->[F -> . ( E ) , F -> . id , T -> T / . F ] ( S8 )
 Map for state: Id: 2 , Rules: [E -> E . - T , E' -> E . , E -> E . + T ]
Transitions:
T->[] ( S5 )
E->[] ( S5 )
F->[] ( S5 )
 -->[E -> E -
/->[] ( S5 )
                              . T , T -> . F , F -> . (E) , T -> . T / F , F -> . id , T -> . T * F ] (S10)
 Map for state: Id: 3 , Rules: [T -> F . ]
 Transitions:
Transitions:

T->[] ( S5 )

E->[] ( S5 )

F->[] ( S5 )

(->[] ( S5 )

*->[] ( S5 )

*->[] ( S5 )
```



(Empowered Autonomous Institute Affiliated to University of Mumbai)
[Knowledge is Nectar]

```
for state: Id: 4 , Rules: [F -> ( . E ) , T -> . F , F -> . ( E ) , T -> . T / F , F -> . id , E -> . E + T , E 「, T -> . T * F , E -> . E - T ]
Transitions:
T->[T -> T . / F , E -> T . , T -> T . * F ] (S1)
E->[E -> E . - T , F -> (E .) , E -> E . + T ] (S11)
F->[T -> F . ] (S3)
(->[F -> ( . E ) , T -> . F , F -> . (E ) , T -> . T / F .
E - T ] (S4)
)->[] (S5)
*->[] (S5)
*->[] (S5)
id->[F -> id .] (S6)
-->[] (S5)
/->[] (S5)
                                                                -> . ( E ) , T -> . T / F , F -> . id , E -> . E + T , E -> . T , T -> . T * F , E ->
 Map for state: Id: 5 , Rules: []
| Transitions:
| T->|| ( 55 )
| E->|| ( 55 )
| F->|| ( 55 )
| ( ->|| ( 55 )
| ->|| ( 55 )
| +->|| ( 55 )
| -->|| ( 55 )
| -->|| ( 55 )
 Map for state: Id: 6 , Rules: [F -> id . ]
Transitions:
T->[] ( S5 )
E->[] ( S5 )
   Map for state: Id: 6 , Rules: [F -> id . ]
 Transitions:
T->[] ( S5 )
E->[] ( S5 )
F->[] ( S5 )
)->[] ( S5 )
*->[] ( S5 )
*->[] ( S5 )
d->[] ( S5 )
-->[] ( S5 )
/->[] ( S5 )
  Transitions:
  Map for state: Id: 7 , Rules: [F -> . ( E ) , T -> T * . F , F -> . id ]
 Transitions:

T->[] ( S5 )

E->[] ( S5 )

F->[T -> T * F . ] ( S12 )

(->[F -> ( . E ) , T -> . F , F -> . ( E )

. E - T ] ( S4 )

)->[] ( S5 )

*->[] ( S5 )

*->[] ( S5 )

id->[F -> id . ] ( S6 )

-->[] ( S5 )

/->[] ( S5 )
                                                                                          T -> . T / F , F -> . id , E -> . E + T , E -> . T , T -> . T * F , E ->
  Map for state: Id: 8 , Rules: [F -> . ( E ) , F -> . id , T -> T / . F ]
  Transitions:
T->[] ( S5 )
E->[] ( S5 )
F->[T -> T / F .
(->[F -> ( . E )
. E - T ] ( S4 )
                                   ] ( S13 )
                                                          , F -> . ( E ) , T -> . T / F , F -> . id , E -> . E + T , E -> . T , T -> . T * F , E ->
```



(Empowered Autonomous Institute Affiliated to University of Mumbai)
[Knowledge is Nectar]

```
Transitions:
T->[] ( S5 )
E->[] ( S5 )
T -> . T / F , F -> . id , E -> . E + T , E -> . T , T -> . T * F , E ->
 Map for state: Id: 9 , Rules: [T -> . F , F -> . ( E ) , T -> . T / F , E -> E + . T , F -> . id , T -> . T * F ]
                        , T -> T . / F , T -> T . * F ] ( S14 )
                                       , F -> . ( E ) , T -> . T / F , F -> . id , E -> . E + T , E -> . T , T -> . T * F , E ->
 id->[F -> id . ] ( S6 )
-->[] ( S5 )
/->[] ( S5 )
 Map for state: Id: 10 , Rules: [E -> E - . T , T -> . F , F -> . (E) , T -> . T / F , F -> . id , T -> . T * F]
 T->[E -> E - T . , T ·
E->[] (S5 )
F->[T -> F . ] (S3 )
(->[F -> ( . E ) , T ·
. E - T ] (S4 )
)->[] (S5 )
                                             -> . (E) , T -> . T / F , F -> . id , E -> . E + T , E -> . T , T -> . T * F , E ->
  Transitions:
. > ( F .

. E - T ] ( S4 )

)->[] ( S5 )

*->[] ( S5 )

+->[] ( S5 )

id->[F -> id-]
                                                                  -> . T / F . F -> . id . E -> . E + T . E -> . T . T -> . T * F . E ->
 id->[F -> id . ] ( S6 )
-->[] ( S5 )
/->[] ( S5 )
 Map for state: Id: 9 , Rules: [T -> . F , F -> . ( E ) , T -> . T / F , E -> E + . T , F -> . id , T -> . T * F ]
F->[T -> F . ] ( S3 )
(->[F -> ( . E ) , T ->
. E - T ] ( S4 )
)->[] ( S5 )
*->[] ( S5 )
+->[] ( S5 )
id->[F -> id . ] ( S6 )
-->[] ( S5 )
/->[] ( S5 )
                                                               T -> . T / F , F -> . id , E -> . E + T , E -> . T , T -> . T * F , E ->
 Map for state: Id: 10 , Rules: [E -> E - . T , T -> . F , F -> . ( E ) , T -> . T / F , F -> . id , T -> . T * F ]
 T-s[E -> E - T . , T . E->[] ( S5 )
F->[T -> F . ] ( S3 )
(->[F -> ( . E ) , T . . E - T ] ( S4 )
```



(Empowered Autonomous Institute Affiliated to University of Mumbai)
[Knowledge is Nectar]

```
Transitions:
T>[] (SS)
E>[] (SS)
F>[T > T / F .] (SI3)
(>[F < (.E) , T > . F , F > . (E) , T > . T / F , F > . id , E > . E + T , E > . T , T > . T * F , E > . E - T ] (SA)
(>[F < (.E) , T > . F , F > . (E) , T > . T / F , F > . id , E > . E + T , E > . T , T > . T * F , E > . E - T ] (SA)
(>[F < (.E) , T > . T / F , F > . (E) , T > . T / F , E > . E + T , F > . id , T > . T * F ]

**Tansitions:
T=[E > E + T . , T > T . / F , T > T . * F ] (SI4)
E>[] (SS)
F>[T > F .] (S3)
(>[F > (.E) , T > . F , F > . (E) , T > . T / F , F > . id , E > . E + T , E > . T , T > . T * F , E > . E - T ] (SA)
)>[] (SS)
**O[] (SS)
```



(Empowered Autonomous Institute Affiliated to University of Mumbai)
[Knowledge is Nectar]

```
Transitions:
T->[] ( S5 )
E->[] ( S5
F->[] ( S5
 ·>[] ( S5
 ->[] ( S5 )
  ·>[F -> . ( E ) , T -> T * . F , F -> . id ] ( S7 )
+->[] ( S5
id->[] ( S5 )
-->[](S5)
/->[F -> .(E),F -> . id,T -> T / . F](S8)
Map for state: Id: 15 , Rules: [E -> E - T . , T -> T . / F , T -> T . * F ]
Transitions:
T->[] ( S5
        S5
F->[] ( S5
        S5
 ->[] ( S5
*->[F -> . ( E ) , T -> T * . F , F -> . id ] ( S7 )
+->[] ( S5 )
id->[] ( S5 )
-->[] ( S5 )
/->[F -> . ( E ) , F -> . id , T -> T / . F ] ( S8 )
Map for state: Id: 16 , Rules: [F -> ( E ) . ]
Transitions:
T->[] ( S5 )
        S5
      ( S5
      ( S5
      ( S5
        S5
    [] ( S5
id->[] ( S5 )
```



(Empowered Autonomous Institute Affiliated to University of Mumbai)
[Knowledge is Nectar]

>[] (S5) /->[] (S5)					•
[\$, (,), *, +, id, -, / [\$, (,), *, +, id, -, /	', T, E, F] ', T, E, F] +		-+	+	+
State \$ T E F	[()	*	+	id -	1/
	Shift 4			Shift 6	
1 Reduce E -> T 8		Shift 7	Reduce E -> T	Reduce E -> T	Shift
2 Accept :)	I I	1	Shift 9	Shift 10	
3 Reduce T -> F e T -> F	Reduce T -> F	F Reduce T -> F	Reduce T -> F	Reduce T -> F	Reduc
4	Shift 4			Shift 6	
5 		l		1 1	
6 Reduce F -> id e F -> id	Reduce F -> i	id Reduce F -> id	Reduce F -> id	Reduce F -> id	Reduc
			•		
			Shift 9		1
2	 	 + 		Shift 10 	 + Reduc
		 		+	 + Reduc
	-+	 		Reduce T -> F	 + Reduc
	Shift 4 	1	Reduce T -> F	Reduce T -> F	
	Shift 4 	1	Reduce T -> F	Reduce T -> F	
	Shift 4 	1	Reduce T -> F	Reduce T -> F	
	Shift 4 	1	Reduce T -> F		
	Shift 4	1	Reduce T -> F		



(Empowered Autonomous Institute Affiliated to University of Mumbai)
[Knowledge is Nectar]

		+	+	+	+	+	+
4 1 11 3	Shift 4		l •	l *	Shift 6	5	
5							
6		Reduce F -> id	Reduce F -> id	Reduce F -> id	 	Reduce F -> id	Reduc
	Shift 4		 	 	Shift 6	5 -+	
8	Shift 4		 	 	Shift 6	5	1
9	Shift 4	- 	· 	 	Shift 6	5 -+	
10	Shift 4	- 	· 	 	Shift 6	5 -+	
11		Shift 16	 -	Shift 9	 	Shift 10	
12 Reduce T -> T * F e T -> T * F		Reduce T -> T * F	Reduce T -> T * F	Reduce T -> T * F	 	Reduce T -> T * F	Reduc
++	-+	-+	-+	-+	+	-+	+
12 Reduce T -> T * F e T -> T * F	F	Reduce T -> T *	FIReduce T -> T *	ElDadusa T . T * I	-1	Inches T. T. T.	
++	+	-+	-+	-+	-+	Reduce T -> T * F	Reduc
13 Reduce T -> T / F e T -> T / F	-+ F -+	Reduce T -> T /	+	-+	+	-+	
+++++++	-+	-+	F Reduce T -> T /	-+	-+ F -+	-+	Reduc
13	-+ τι -+	Reduce E -> E +	F Reduce T -> T /	F Reduce T -> T /	-+ FI -+ TI	Reduce T -> T / F	F Reduc
13	-+ T -+ T -+	Reduce E -> E +	F Reduce T -> T / -+	F Reduce T -> T /	TI	Reduce T -> T / F	Reduc Shift
13	TI -+ TI -+ TI -+	Reduce E -> E +	F Reduce T -> T / -+	Reduce E -> E + Reduce E -> E -	TI	Reduce T -> T / F	Reduc Shift
13	T -+ T -+ T -+)	Reduce E -> E +	F Reduce T -> T / -+	Reduce E -> E + Reduce E -> E -	TI	Reduce T -> T / F	Reduc Shift
13	T -+ T -+) -+	Reduce E -> E +	F Reduce T -> T / -+	Reduce E -> E + Reduce E -> E -	TI	Reduce T -> T / F	Reduc Shift
13	T -+ T -+) -+ ion ft 6	Reduce E -> E + Reduce E -> E - Reduce F -> (E Input	F Reduce T -> T / -+	Reduce E -> E + Reduce E -> E -	TI	Reduce T -> T / F	Reduc Shift
13	T -+ T -+ ion ft 6 uce F ->	Reduce E -> E + Reduce E -> E - Reduce F -> (E	F Reduce T -> T / -+	Reduce E -> E + Reduce E -> E -	TI	Reduce T -> T / F	Reduc Shift
13	T -+	Reduce E -> E + Reduce E -> E - Reduce F -> (E	F Reduce T -> T / -+	Reduce E -> E + Reduce E -> E -	TI	Reduce T -> T / F	Reduc Shift
13	T -+ T -+ ion ft 6 uce F -> uce E ->	Reduce E -> E + Reduce E -> E - Reduce F -> (E + Input \$ id \$ T \$ \$	F Reduce T -> T / -+	Reduce T -> T /	TI	Reduce T -> T / F	Reduc Shift



(Empowered Autonomous Institute Affiliated to University of Mumbai)
[Knowledge is Nectar]

Conclusion	Through this experiment, I gained hands-on experience in understanding and implementing the functionality of an LL(1) parser and SLR Parser. I successfully applied the concepts of computing the First and Follow sets for a given production, subsequently constructing a parse tree. Additionally, I successfully parsed a string to validate its correctness, and I created a corresponding stack during the parsing process.
References	[1] Syntax Analysis: Compiler Top Down & Bottom Up Parsing Types from https://www.guru99.com/syntax-analysis-parsing-types.html [2] Construction of LL(1) Parsing Table from https://www.geeksforgeeks.org/construction-of-ll1-parsing-table/